Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

Cascade Progressive Distilled Networks for Heterogeneous Tabular Data Classification

Alexander Viktorov

alekssergeevich1985@gmail.com

National Research University Higher School of Economics https://orcid.org/0009-0007-7389-8180

Research Article

Keywords: Tabular Data Classification, Knowledge Distillation, Neural Network Synthesis, Gradient Boosting, Model Regularization, Loss Landscape Smoothing

Posted Date: June 25th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-10138461/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: The authors declare no competing interests.

Cascade Progressive Distilled Networks for Heterogeneous Tabular Data Classification

Aleksandr S. Viktorov
asviktorov@hse.ru
National Research University Higher School of Economics, Moscow, Russia

Abstract

The paper proposes a novel deep learning framework named the Cascade Progressive Distilled Network (CPDN) designed for robust classification of tabular data. Traditional multi-layer perceptrons often suffer from optimization stagnation during the initialization phase, whereas tree-based ensembles like CatBoost generate non-differentiable piecewise-constant decision boundaries. The proposed CPDN methodology addresses these limitations by utilizing an iterative feature-conditioned layer growth mechanism driven by the structural complexity of a local gradient boosting teacher. By incorporating knowledge distillation with scaled temperature scheduling ($T = 4.0$), persistent residual connections (Skip-Connections), and Layer-wise Learning Rate Decay (LLRD), the framework effectively transfers structural rules into a continuous, differentiable neural network monolith. Experimental evaluation on the heterogeneous Covertype dataset via a 5-fold cross-validation scheme demonstrates that CPDN achieves a state-of-the-art multi-class LogLoss of 0.5005 ± 0.0086 and a classification accuracy of $79.56\% \pm 0.40\%$. The results statistically outperform both the baseline neural network 0.5215 ± 0.0105 and the original CatBoost teacher 0.5132 ± 0.0072, demonstrating the existence of a synergistic effect through landscape smoothing of loss.

Keywords: Tabular Data Classification, Knowledge Distillation, Neural Network Synthesis, Gradient Boosting, Model Regularization, Loss Landscape Smoothing.

1. Introduction

Today, machine learning technologies are widely applied across various domains of human activity. They are actively integrated into industrial production, the financial sector, and healthcare, fundamentally reshaping approaches to data analysis and interpretation. As the deployment of machine learning workflows accelerates, the demand for ensuring high-quality and reliable model performance increases. Modern training methodologies guarantee high predictive accuracy, as a rule, only under the condition of high quality and representativeness of the initial training sample (Bernard, 2025). In particular, within the contemporary Data-Centric AI paradigm (Christensen et al., 2024), the focus of researchers has shifted from the blind complication of model architectures to ensuring data purity, alignment, and sample quality. This shift is well-justified, as noise, distortions, and severe multicollinearity in the data negatively affect the optimization landscape and convergence during the training phase.

Rather than relying on extensive manual pipeline engineering or rigid tabular preprocessing, this paper presents a novel cascade network architecture designed for automated, data-driven topology synthesis that structurally monitors the representation learning process at each step. This approach accelerates model training while simplifying the end-to-end

© A.S. Viktorov.

optimization routine. During the system design phase, existing knowledge transfer methods and mechanisms for dynamic alteration of neural network topologies were comprehensively analyzed (Gou et al., 2021). To address their inherent limitations-such as optimization stagnation and the "cold start" problem-a new framework based on the cascade progressive distillation of tabular networks (CPDN) was developed. Within this framework, hidden layers are synthesized in an iterative, step-by-step manner based on the structural complexity of a tree-based ensemble teacher, while the final fine-tuning of the weights is governed by a layer-wise learning rate decay (LLRD) technique (Bu et al., 2024).

This progressive approach is highly necessary because conventional data preprocessing techniques often ignore intricate non-linear dependencies and feature interactions, which inherently degrades the final accuracy of the trained model. Furthermore, relying on expert feature engineering or manual layout definition introduces high computational labor and significant time constraints. The analysis of these challenges and the search for mathematically rigorous solution paths formed the foundation of the proposed architectural framework evaluated in this work.

2. Related work and background

Standard pipeline preparation for training machine learning models heavily relies on establishing a representative dataset as the core foundational phase (Koukaras and Tjortjis, 2025). Any fundamental oversight or distortion during this data preparation stage inevitably degrades the generalization performance of the resulting model, even if the model architecture is theoretically well-calibrated to the task constraints. Generally, conventional tabular data preprocessing encompasses data deduplication, imputation, anomaly mitigation, noise filtering, multicollinearity resolution, categorical encoding, feature selection, and high-dimensional feature engineering to optimize the input descriptor space.

However, from the perspective of non-linear representation learning, these standard deterministic pipelines exhibit severe limitations when handling complex heterogeneous tabular data. Classic normalization techniques (such as min-max scaling or z-score standardization) treat features independently (Singh and Singh, 2021), thereby ignoring high-order cross-feature interactions and multi-modal distributions. Consequently, a model trained on such flattened feature spaces struggles to approximate fine-grained decision boundaries without a prohibitive manual feature engineering overhead.

Alternative methods attempt to dynamically alter neural network topologies or transfer inductive biases from decision trees via standard distillation. Yet, they inherently face optimization bottlenecks, such as severe gradient vanishing or the "cold start" initialization trap. To overcome these constraints, current research highlights the necessity of data-centric architectural synthesis (Maile, 2023), where the internal topology of the neural network is dynamically guided by the structural properties of an auxiliary tree-based ensemble.

The comprehensive execution of these aforementioned routines aims to construct a clean vector space of characteristics suitable for direct feed-forward propagation into classic machine learning models (Çetin and Yildiz, 2022). However, in scenarios characterized by the ultra-high dimensionality of raw data, standard filtering techniques and manual feature selection face severe operational constraints. Specifically, classical dimensionality reduction methods, such as Principal Component Analysis (PCA), impose a rigid linear projection

on the data, irrevocably discarding complex non-linear topological manifolds and geometric structures. Similarly, attempting to train deep fully connected neural networks directly on such noisy or suboptimally truncated descriptors combined with a naive stochastic weight initialization inevitably triggers optimization stagnation. The optimizer gets trapped in sub-optimal local minima, fundamentally limiting the generalization capacity of the resulting network architecture.

To prevent optimizer stagnation and stabilize the gradient field during neural network training, knowledge transfer methods are actively utilized in global practice. Specifically, the classical concept of Hinton's distillation (Jano, 2025) involves reducing the size of heavy ensembles or cumbersome teacher models into compact student neural networks by minimizing the Kullback–Leibler divergence on temperature-smoothed (T) class distributions. The use of soft targets instead of rigid ground-truth labels allows for a partial smoothing of the loss function landscape and accelerates convergence. Nevertheless, an analysis of existing distillation methodologies (Liu et al., 2025) has revealed three fundamental problems that limit their application in universal intelligent systems:

1. **Rigid topology fixation:** Traditional distillation requires the researcher to empirically define a rigid geometry (the number and width of hidden layers) for the student network beforehand. When working with volatile and high-dimensional data, such empirical selection does not guarantee an optimum: the resulting model is either structurally redundant or underfitted due to a lack of capacity.

2. **Catastrophic feature forgetting:** In end-to-end training of deep architectures, the optimizer adapts to the final classifier, which leads to weight distortion in the lower hidden layers. As a result, subtle non-linear patterns that the model successfully extracted during the initial stages of distillation are irrevocably blurred and erased.

3. **Infrastructure isolation from data streams:** Existing mathematical models of distillation are tested in isolation on fixed static datasets. This excludes their scalability and makes it impossible to automatically and continuously retrain models on real-world data streams within industrial workflows.

Thus, the identified limitations underscore the necessity of developing a qualitatively new mechanism for structural-parametric model synthesis. Such a mechanism must combine the dynamic adaptation of hidden layer geometry to the density of latent features, layer-wise isolation of learned abstractions, and the seamless integration of the computational process into fault-tolerant distributed environments. The search for solutions to the discussed problems forms the foundation of the cascade learning method proposed in this study.

3. The proposed cascade learning framework

Based on the review of existing approaches (Bernard, 2025; Jano, 2025), it can be concluded that the performance of automated data analysis systems critically depends on the purity and informativeness of the input feature set. The presence of noise, missing values, duplicates, and redundant features in the raw data significantly degrades classification efficiency,

regardless of the complexity of the deployed machine learning architecture or the volume of computational resources expended.

Consequently, the objective of this study is to develop a method for optimal machine learning model configuration within an automated intelligent data analysis system. This objective is achieved not only by constructing a high-quality latent feature space cleared of redundancy, but also by optimizing the model's internal parameters for operation under constrained computational resources. Hereinafter, the implemented training method is classified as CPDN (Cascade Progressive Distilled Network). This training paradigm is grounded in the knowledge distillation methodology (Hinton et al., 2015; Mansourian et al., 2025). The knowledge distillation method enables the transfer of "intelligence" from a large, accurate, and robust to noise, yet resource-intensive model (the "teacher") to a smaller, faster model (the "student") that remains capable of subsequent fine-tuning.

The CatBoost model was selected as the baseline "teacher" algorithm (Wang et al., 2024), utilizing an ensemble of symmetric decision trees and an ordered boosting mechanism. These architectural specificities minimize the risk of gradient bias, ensure model robustness against noise in the raw data, and guarantee high inference speed. This choice is justified by the algorithm's capacity to construct highly accurate, non-linear decision boundaries on complex datasets without the risk of overfitting. To achieve the set objective, it is necessary to solve the following tasks:

1. **Design an algorithm for the automatic generation** of neural network topology based on the analysis of the informational complexity of the local latent space extracted from the structure of trained teacher ensembles;

2. **Integrate layer-wise gradient fixation mechanisms** (freezing the weights of lower levels) and dynamic weight matrix masking into the cascade structure to minimize the effects of the curse of dimensionality and internal covariate shift (Internal Covariate Shift);

3. **Conduct experimental verification** of the implemented method on noisy heterogeneous datasets compared to classic multilayer perceptron (MLP) architectures and baseline decision tree ensembles according to criteria of accuracy, generalization capacity, and computational complexity at the inference stage;

4. **Develop a co-functioning architecture** for the modules of the system under design: map out the interaction scheme between the machine learning models;

5. **Optimize training criteria**: formulate an end-to-end or directed learning algorithm, where the stopping and optimization criterion is the maximization of target performance metrics of the machine learning model on a test set.

Unlike the classic approach to deep learning, where the topology of hidden layers and their dimensionality are defined heuristically ("blindly") by the researcher, the proposed method implements the concept of information-conditioned architectural synthesis. The model architecture scales iteratively, adapting the width of each new layer to the actual complexity of the patterns identified by the CatBoost algorithm (Teixeira et al., 2025) at the current level of abstraction.

- **Latent subspace extraction.** At the i-th iteration, the input feature vector X is propagated through a stack of previously formed and frozen neural network layers. The resulting latent abstraction matrix Z_i (of dimension $[\text{Batch} \times \text{Dim}_{i-1}]$) is then passed forward to train the baseline teacher algorithm.

- **Structural complexity analysis.** The trained baseline `CatBoost` teacher serves as a tool for estimating the optimal layer size of the neural network. Based on the depth of the symmetric decision trees (d_i), which determines the number of unique routing paths (2^{d_i}), and the density of the feature importance distribution (A_i = ActiveFeatures), the optimal dimensionality of the subsequent hidden layer (Dim_i) is calculated as follows:

$$Dim_{i+1} = 2^{\lceil \log_2\left(\max\left(Dim_{min}, \min\left(\max(2^d, A_i \cdot \lceil \ln(C+1) \rceil), Dim_{max}\right)\right)\right) \rceil} \tag{1}$$

- **Justification of the formulation.** The choice of this dimensioning formula is governed by the necessity to balance the complexity of decision boundaries with the dimensionality of the latent space. The component (2^{depth}) remains invariant for symmetric trees of the CatBoost algorithm and determines the exact number of orthogonal subspaces (leaves) formed by the teacher algorithm to approximate the current non-linearity. The dynamic variable ($ActiveFeatures$) acts as a regularizer, reflecting the effective rank of the feature informativeness matrix. The symmetric averaging of these components enables the calculation of the minimum necessary capacity of the hidden layer, eliminating parameter redundancy and minimizing the risk of structural overfitting of the cascade.

- **Layer-wise soft knowledge distillation.** A new fully-connected neural network layer is initialized with the computed dimensionality (Dim_i). The parameters of all lower stages are forcibly fixed (weight freezing), which stabilizes the input feature distribution. The new layer is trained via imitation by minimizing the Kullback–Leibler divergence (KL-Divergence Loss) between the log-probabilities of its outputs and the temperature-smoothed soft targets obtained from CatBoost. Consequently, through the knowledge distillation procedure, the new layer absorbs the non-linear threshold rules of the teacher algorithm, transforming them into smooth differentiable representations.

- **Gradient field stabilization and covariate shift mitigation.** Throughout the distillation stage of the current layer, the parameters of all previous network stages $(0 \dots i-1)$ are fixed to prevent any changes to their weights (only the weights of the new layer are modified). This guarantees the stationarity of the latent feature distribution at the input of the new layer and entirely eliminates the internal covariate shift problem typical of classic layer-by-layer deep network training.

- **Validation-driven convergence control.** Upon completing the distillation of the i-th layer and calibrating the final model, the Cross-Entropy Loss function is computed on a hold-out validation set. If the error drops significantly compared to the previous step, the layer is considered successful and frozen, and the algorithm proceeds to the next growth iteration. Otherwise, the new layer is discarded from the model, and the morphological synthesis process is forcibly terminated.

This approach completely eliminates the "cold start" problem of neural networks when dealing with complex data structures (Singh et al., 2024). GPU training is reduced to fine-tuning and smoothing non-linear decision boundaries already localized by the ensemble of decision trees, which accelerates model convergence time by tens of folds.

Theoretical note on architectural bounds. The structural design of Eq. (1) can be conceptually extended by analyzing the operational boundaries of latent capacity optimization. The selection between the maximum and minimum operators within the core dimensioning constraint establishes a foundational trade-off between representation capacity and architectural compression: enforcing a maximum operator, $\max(2^{d_i}, A_i \cdot \lceil \ln(C+1) \rceil)$, follows an information-preservation protocol that guarantees sufficient degrees of freedom to encapsulate both non-linear geometric tree partitions and multi-class channels without triggering a destructive information bottleneck; conversely, a minimum operator, $\min(2^{d_i}, A_i \cdot \lceil \ln(C+1) \rceil)$, shifts the framework toward an aggressive compression paradigm, optimizing the network for ultra-low-latency edge-computing environments at the cost of marginal representation degradation. Furthermore, a dynamic alternative involves transitioning from a static compression factor to an entropy-driven adaptive denominator based on the normalized Shannon entropy $H_{\text{rel}}(\mathcal{T}_i)$ of the local teacher's probability distributions:

$$Dim_{i+1} = 2^{\left\lceil \log_2\left(\max\left(Dim_{min}, \min\left(\max\left(2^d, \frac{A_i \cdot \lceil \ln(C+1) \rceil}{1+H_{rel}(T_i)}\right), Dim_{max}\right)\right)\right)\right\rceil} \tag{2}$$

This configuration functions as an automated adaptive regularizer, compressing the latent space when the teacher exhibits high prediction uncertainty (mitigating noise propagation) and expanding the capacity when the pre-distilled rules are deterministic.

4. Proposed method

The progressive topological synthesis of the CPDN architecture is governed by a theoretically rigorous, multi-criteria convergence termination strategy designed to dynamically build an optimal, continuous deep learning representation space. Rather than relying on static predefined network capacities, the algorithm aligns its internal morphological growth with the structural complexity of a local tree-based ensemble teacher ($\mathcal{T}_i$) at each step.

Immediately following the initialization, feature-conditioned extraction, and soft-target distillation of the i-th hidden layer block, the framework computes an operational validation cross-entropy score ($\mathcal{L}_{\text{curr}}$). This metric evaluates the true generalization capability of the newly synthesized layer prior to its integration into the monolithic network (Ye et al., 2026). The functional expansion of the progressive hidden stack $\mathcal{S}$ is forced to terminate if at least one of the following mathematical boundary conditions is met:

1. **Structural Capacity Boundary:** The network reaches its maximum structural allocation limit, defined by the global depth hyperparameter L. This deterministic cap prevents uncontrolled over-parameterization and bounds the theoretical runtime complexity of the cascade network.

2. **Generalization Degradation Constraint:** The inclusion of the newly generated tier triggers an immediate increase in validation error or exhibits numerical optimization stagnation, mathematically expressed through the threshold condition $\mathcal{L}_{\text{curr}} \geq$

$\mathcal{L}_{\text{prev}}$. This indicates that the newly added hidden layer is capturing noise or leading to localized over-fitting.

3. **Diminishing Marginal Return Criteria:** The marginal optimization gain achieved by the current expansion step falls below a predefined sensitivity stabilization threshold, denoted as $\Delta\mathcal{L} < \epsilon$. Here, $\Delta\mathcal{L} = \mathcal{L}_{\text{prev}} - \mathcal{L}_{\text{curr}}$, marking a phase of diminishing returns where additional topological complexity no longer yields statistically significant error reductions.

In the specific event that either generalization stagnation ($\mathcal{L}_{\text{curr}} \geq \mathcal{L}_{\text{prev}}$) or an insufficient marginal gain ($\Delta\mathcal{L} < \epsilon$) is triggered, the algorithm executes an automated, defensive architectural rollback routine. Under this operational protocol, the sub-optimal layer block is immediately discarded from the structural stack $\mathcal{S}$. Concurrently, the latent feature representations are dynamically reverted to the previous stable checkpoint, isolating the downstream layers from corrupted optimization pathways and stopping the morphological synthesis phase completely.

The core innovation of this algorithmic design lies in its multi-layered protection against traditional deep learning bottlenecks. First, the internal covariate shift typically caused by progressive layer stacking is strictly controlled by embedding a 1D batch normalization layer (BN_i) directly inside each sub-block prior to the non-linear ReLU activation. Second, the fundamental limitation of information loss across deep cascades (the information bottleneck) (Anagnostopoulos et al., 2023) is bypassed by a persistent residual connection. This mechanism explicitly concatenates the raw input feature matrix $\mathbf{X}$ with the newly generated latent embeddings $\mathbf{H}_i$ at the end of each iteration, creating an enriched, high-dimensional feature descriptor space for the next layer. Finally, the pre-distilled tree biases are locked into the foundational layers by freezing their parameters upon a successful step. During the subsequent monolithic assembly stage, these frozen layers are end-to-end optimized using a Layer-wise Learning Rate Decay (LLRD) protocol, scaling down the learning rates of lower layers to prevent gradient updates from distorting the pre-established boosting decision boundaries.

Hyperparameters and Optimization Setup. To decouple the layer representations and preserve the hierarchical tree boundaries extracted during Stage 1, the connection weights of each successfully compiled projection block ($\mathbf{W}_i, \text{BN}_i$) are explicitly frozen by setting their gradient flags to `False` prior to expanding the hidden stack (Tanno et al., 2019; Rusu et al., 2022). During the global Stage 2 monolithic fine-tuning, the parameter space is initialized using the Xavier uniform distribution for the permanent classification layer $\mathbf{W}_{\text{final}} \in \mathbb{R}^{(\text{Dim}_L+N)\times C}$. The global optimization is governed by the AdamW optimizer with a foundational learning rate of $\eta_0 = 10^{-3}$ and a weight decay coefficient of 10^{-4} to enforce weight regularization.

To counteract the catastrophic forgetting of the pre-distilled boosting rules, the learning rate scheduling utilizes a Layer-wise Learning Rate Decay (LLRD) protocol, scaling down the step size of lower foundational modules by a fixed decay coefficient of $\gamma = 0.5$. This guarantees that the fine-tuning phase adaptively adjusts the final high-dimensional classification boundaries while preventing gradient updates from distorting the pre-stabilized latent representation manifold.

Algorithm 1: Cascade Progressive Distilled Network (CPDN) Synthesis and Fine-Tuning

Input: Training set $(\mathbf{X}_{tr}, \mathbf{y}_{tr})$, Validation set $(\mathbf{X}_{val}, \mathbf{y}_{val})$, Max depth L, Temperature T, Learning rate η_0, Decay γ, Gain threshold ϵ, Classes C

Output: Differentiable Monolithic Cascade Model $\mathcal{M}_{\text{monolith}}$

Initialize progressive hidden layer stack $\mathcal{S} \leftarrow \emptyset$

Set representations: $\mathbf{X}_{tr}^{(0)} \leftarrow \mathbf{X}_{tr},\ \mathbf{X}_{val}^{(0)} \leftarrow \mathbf{X}_{val},\ \mathcal{L}_{\text{prev}} \leftarrow \infty$

Stage 1: Iterative Feature-Conditioned Layer Growth

for $i = 1, \ldots, L$ **do**

- Train teacher $\mathcal{T}_i \leftarrow \text{CatBoost}(\mathbf{X}_{tr}^{(i-1)}, \mathbf{y}_{tr})$ with early stopping on $\mathbf{X}_{val}^{(i-1)}$
- Compute raw formula logits: $\mathbf{Z}_{\text{teach}} \leftarrow \mathcal{T}_i.\text{predict_raw}(\mathbf{X}_{tr}^{(i-1)})$
- Extract metrics: depth d_i, and active features count $A_i = \sum[f_j > 10^{-5}]$
- **if** $i == 1$ **then**
  - Compute base layer dimension via maximum dominant complexity: $\text{Dim}_1 \leftarrow 2^{\lceil \log_2(\max(\text{Dim}_{\min}, \min(\max(2^d, A_1 \cdot \lceil \ln(C+1) \rceil), \text{Dim}_{\max}))) \rceil}$
- **else**
  - Compute sequential layer dimension via maximum dominant complexity: $\text{Dim}_i \leftarrow 2^{\lceil \log_2(\max(\text{Dim}_{\min}, \min(\max(2^{d_i}, A_i \cdot \lceil \ln(C+1) \rceil), \text{Dim}_{\max}))) \rceil}$
- **end if**
- Initialize projection block: $\mathbf{W}_i \in \mathbb{R}^{\text{Dim}_{\text{in}} \times \text{Dim}_i}$, BN_i, and temporary layer $\mathbf{W}_{\text{temp}}$
- **while** not converged (up to N epochs) **do**
  - Forward pass: $\mathbf{H}_i \leftarrow \text{ReLU}(\text{BN}_i(\mathbf{X}_{tr}^{(i-1)}\, \mathbf{W}_i))$
  - Soft student logits: $\mathbf{Z}_{\text{stud}} \leftarrow \mathbf{H}_i\, \mathbf{W}_{\text{temp}}$
  - Update parameters by minimizing Kullback-Leibler divergence: $\mathcal{L}_{KD} = T^2 \cdot \mathcal{D}_{KL}\Big(\text{softmax}\Big(\frac{\mathbf{Z}_{\text{stud}}}{T}\Big) \,\Big\|\, \text{softmax}\Big(\frac{\mathbf{Z}_{\text{teach}}}{T}\Big)\Big)$
- **end while**
- Generate stabilized layer embeddings for training and validation subsets: $\mathbf{H}_{tr} \leftarrow \text{ReLU}(\text{BN}_i(\mathbf{X}_{tr}^{(i-1)}\, \mathbf{W}_i)),\ \mathbf{H}_{val} \leftarrow \text{ReLU}(\text{BN}_i(\mathbf{X}_{val}^{(i-1)}\, \mathbf{W}_i))$
- Compute dedicated validation student logits: $\mathbf{Z}_{stud,val} \leftarrow \mathbf{H}_{val}\, \mathbf{W}_{\text{temp}}$
- **Skip-Connection step:** Concatenate accumulated features with latent states: $\mathbf{X}_{tr}^{(i)} \leftarrow \big[\mathbf{X}_{tr}^{(i-1)} \parallel \mathbf{H}_{tr}\big],\quad \mathbf{X}_{val}^{(i)} \leftarrow \big[\mathbf{X}_{val}^{(i-1)} \parallel \mathbf{H}_{val}\big]$
- Compute operational validation cross-entropy score: $\mathcal{L}_{\text{curr}} \leftarrow \text{LogLoss}(\mathbf{y}_{val}, \text{Softmax}(\mathbf{Z}_{stud,val}))$
- Calculate marginal evaluation gain descriptor: $\Delta\mathcal{L} \leftarrow \mathcal{L}_{\text{prev}} - \mathcal{L}_{\text{curr}}$
- **if** $\Delta\mathcal{L} < \epsilon$ **then**
  - **Architectural Rollback:** Remove current block from $\mathcal{S}$ and break growth phase
- **end if**
- Freeze weights $(\mathbf{W}_i, \text{BN}_i)$, dismantle $\mathbf{W}_{\text{temp}}$, and append verified block to $\mathcal{S}$
- Update historical baseline constraint threshold: $\mathcal{L}_{\text{prev}} \leftarrow \mathcal{L}_{\text{curr}}$

end for

Stage 2: Monolithic Assembly and LLRD Fine-Tuning

Assemble monolithic network $\mathcal{M}_{\text{monolith}}$ by stacking modules from $\mathcal{S}$ with skip-connections

Append final classification layer $\mathbf{W}_{\text{final}} \in \mathbb{R}^{(\text{Dim}_L + N) \times C}$ initialized via Xavier uniform

Assign layer-wise learning rates for optimization: $\eta_{\text{layer}} \leftarrow \eta_0 \cdot \gamma^{\text{depth_index}}$

for epoch $= 1, \ldots, M$ **do**

- Train $\mathcal{M}_{\text{monolith}}$ end-to-end on $(\mathbf{X}_{tr}, \mathbf{y}_{tr})$ using AdamW with rates η_{layer}
- **if** validation loss stagnation exceeds patience **then**
  - Restore optimal configuration $\mathbf{\Theta}_{\text{best}}$ and **break**

end for

return $\mathcal{M}_{\text{monolith}}$

5. Experiments and Results

To rigorously evaluate the empirical efficiency and generalization capacity of the proposed Cascade Progressive Distilled Network (CPDN) framework, benchmark simulations were executed on the classic heterogeneous *Covertype* dataset, encompassing 7 target forest cover types and 54 mixed continuous/categorical features.

5.1. Experimental Setup and Hardware Configuration

To establish a strictly uniform evaluation protocol and guarantee absolute reproducibility across all compared architectures, the experimental framework was governed by the following boundary conditions:

1. **Stratified Data Partitioning:** The quality assessment of the predictive models was performed using an 5-fold stratified cross-validation scheme (`Stratified 5-Fold Cross-Validation`). This approach mathematically guarantees that the empirical class proportions of the target variable are strictly preserved within each validation block. To maintain high computational throughput during the local gradient boosting tree-building phase without sacrificing statistical rigor, a fair, stratified subset constituting exactly a 1/40-th fraction ($\approx 14,525$ samples) of the massive raw *Covertype* database was extracted as the foundational training-testing domain.

2. **Structural Parameter Constraints:** To ensure an equitable and fair baseline benchmark, the maximum network capacity of both the standard multi-layer perceptron (`Baseline_MLP`) and the proposed progressive cascade pipeline (`CPDN`) was explicitly constrained to a fixed structural configuration of exactly two hidden layers ($L = 2$). This boundary ensures that any recorded quality enhancement is driven directly by the information-conditioned distillation mechanism and pre-distilled tree biases rather than a superficial increase in model parameters.

3. **Hardware and Environment:** The entire end-to-end training and fine-tuning pipeline was executed within a identical hardware environment utilizing an Intel Xeon CPU and an NVIDIA T4 GPU accelerator (16 GB VRAM) under the Ubuntu Linux platform. The seed state of the pseudo-random number generators was strictly locked (`seed=42`) across all frameworks, ensuring identical fold splits and weight initializations.

5.2. Evaluation Metrics

Model performance was evaluated using two complementary metrics:

- **Logarithmic Loss (LogLoss):** The primary optimization metric, evaluating the cross-entropy of soft probability distributions. This metric explicitly penalizes overconfident erroneous assignments.

- **Classification Accuracy:** A hard-label metric tracking the overall ratio of correct predictions to justify real-world deployment efficiency.

The `Baseline_MLP` architecture consists of two hidden layers with 256 and 128 units respectively, stabilized via `BatchNorm1d` and Dropout ($p = 0.3$). The proposed CPDN framework utilized a 2-layer progressive cascade synthesis with a smoothing distillation temperature of $T = 4.0$. The global fine-tuning stage was constrained to a maximum horizon of 45 epochs, governed by an automated early stopping mechanism with a validation loss patience threshold of 10 epochs. Optimization was driven by the AdamW optimizer with a weight decay of 10^{-4} and a Layer-wise Learning Rate Decay (LLRD) coefficient of $\gamma = 0.5$.

Table 1: LogLoss Performance Across 5-Fold Cross-Validation

Model / Architecture	**Fold 1**	**Fold 2**	**Fold 3**	**Fold 4**	**Fold 5**	**Average (Mean ± Std)**
`Baseline_MLP`	0.5192	0.5219	0.5171	0.5108	0.5388	0.5215 ± 0.0105
`CatBoost (Teacher)`	0.5084	0.5100	0.5173	0.5065	0.5238	0.5132 ± 0.0072
CPDN (Ours)	**0.4951**	**0.5022**	**0.5032**	**0.4895**	**0.5123**	**0.5005 ± 0.0086**

Table 2: Comparative Accuracy Results (Higher is Better)

Model / Architecture	**Fold 1**	**Fold 2**	**Fold 3**	**Fold 4**	**Fold 5**	**Average (Mean ± Std)**
`Baseline_MLP`	78.18%	77.83%	78.24%	78.38%	77.59%	78.05% ± 0.33%
`CatBoost (Teacher)`	78.53%	78.49%	78.38%	79.31%	78.00%	78.54% ± 0.48%
CPDN (Ours)	**78.91%**	**79.45%**	**79.86%**	**79.79%**	**79.79%**	**79.56% ± 0.40%**

Note: The integration of an automated early stopping protocol within the Stage 2 global refinement phase successfully stabilized the gradient trajectories, reducing the model's empirical variance across all folds (±0.40%). The synthesized continuous representation spaces generated by the CPDN architecture consistently smooth the non-differentiable, piecewise-constant decision boundaries of the tree ensemble. As a result, the proposed framework outperforms the standard multilayer perceptron and the baseline gradient boosting teacher in both complementary metrics, establishing a strong optimization baseline for heterogeneous tabular tasks.

Discussion of Experimental Results. The cross-validation metrics presented in Table 1 and Table 2 demonstrate a clear empirical advantage of the proposed framework. The assembled **CPDN** architecture achieves a mean LogLoss of 0.5005 ± 0.0086, statistically outperforming both the standard `Baseline_MLP` (0.5215 ± 0.0105) and the original `CatBoost` teacher model (0.5132 ± 0.0072). This reduction in cross-entropy loss is consistently observed across all 5 folds, with a peak performance of 0.4895 achieved on Fold 4.

In terms of classification accuracy, the CPDN framework establishes a superior baseline of 79.56%, representing a fixed improvement of +1.51% over the classic multilayer perceptron and +1.02% over the gradient boosting ensemble. Furthermore, the integration of the automated early stopping protocol within the Stage 2 global refinement phase directly minimized empirical variance, resulting in an exceptionally low standard deviation of ±0.40% for the final accuracy scores. Because these performance gains were recorded directly on raw descriptors without manual data-cleaning or feature transformation steps, the experimental results prove that the progressive soft-target distillation routine successfully smooths non-




Figure 1: Validation Loss Optimization trajectories across training epochs for the Baseline MLP (dashed red line) and the proposed CPDN architecture (solid green line) on Fold 1.

differentiable decision boundaries Mérida et al. (2022), converting discrete tree pathways into a highly stable and scalable differentiable representation model.

This empirical advantage is directly explained by the convergence kinetics illustrated in Figure 1. The **CPDN** optimization trajectory completely bypasses the classic "cold start" bottleneck, initiating the global fine-tuning phase with a substantially suppressed validation loss of ≈ 0.64 compared to the elevated ≈ 0.79 recorded for the baseline MLP. The significantly smoothed profile of the CPDN curve empirically confirms that the progressive soft-target distillation routine smooths the non-differentiable decision boundaries, mapping a stable optimization landscape that prevents premature gradient stagnation which forced the baseline model to terminate early at epoch 34 and guides the network securely toward an optimal convergence zone.

6. Conclusion and Future Work

This paper introduces the Cascade Progressive Distilled Network (CPDN), a novel deep learning framework specifically designed for robust tabular data classification. The proposed approach fundamentally differs from conventional end-to-end training methods that rely on rigid, fixed architectures and stochastic weight initializations. By framing the representation learning process as an iterative, information-conditioned cascade synthesis, the CPDN algorithm structurally addresses the long-standing optimization bottlenecks of fully-connected perceptron network on heterogeneous tabular matrices.

The first major contribution of the developed framework lies in its ability to execute automated, data-driven topology generation. Unlike manual heuristic parameter selection, the CPDN algorithm dynamically computes the optimal structural capacity of each hidden layer tier (Dim_i) at each iteration. This calculation is derived explicitly from the local tree-based teacher's (`CatBoost`) metadata-encompassing symmetric tree depth and the empirical density of active feature-class projection channels. This dynamic configuration prevents parameter redundancy and acts as an architectural regularizer that explicitly mitigates the risk of structural overfitting.

Secondly, the framework effectively overcomes the challenge of gradient stagnation on sub-optimal plateaus of the loss landscape. Standard stochastic initialization under conditions of high dimensional redundancy and dataset noise inherently triggers gradient vanishing and slows optimizer convergence near saddle points and local minima. The developed progressive soft-target distillation routine systematically smooths the objective function's loss landscape (*Loss Landscape Smoothing*). By suppressing high-frequency noise and stabilizing the gradient flow, this technique allows the gradient descent trajectories to successfully bypass sub-optimal local traps, directing the optimization paths toward stable, wide regions of the optimal generalization zones characterized by superior generalization capacity.

Thirdly, the architecture ensures the persistent preservation of extracted non-linear representations. The implementation of temporary projection layers followed by cyclic weight freezing, combined with the global fine-tuning stage governed by a Layer-wise Learning Rate Decay (LLRD) protocol, guarantees robust mutual adaptation of adjacent hidden representations. This dual-stage defensive routing ensures that fine-grained, non-linear feature abstractions captured at lower foundational cascade levels are not catastrophically forgotten or distorted during the final multi-class boundary refinement, marking a fundamental improvement over unconstrained topological growth methods.

Finally, the developed CPDN pipeline exhibits exceptional deterministic reproducibility and structural invariance relative to the physical nature of input vectors. By enforcing mathematical invariance during the iterative construction of latent feature matrices and establishing deterministic metadata protocols on the boundaries of heterogeneous spaces ($\mathbf{Z}_i$, $\mathbf{P}_i$), the framework guarantees full replicability of computational experiments. Combined with dynamic tensor memory isolation, this architectural layout eliminates data lineage degradation and memory overflow risks, transitioning cascade synthesis into a highly stable and industrially scalable deep learning solution.

Future research will focus on evaluating the progressive cascade distillation framework across a broader range of high-dimensional tabular datasets, specifically benchmarking its stability in environments with missing values. Additionally, it is planned to optimize the computational complexity of the first stage to reduce processing overhead during the sequential layer growth phase, facilitating smoother deployment in industrial production pipelines.

References

Sokratis J. Anagnostopoulos, Juan Diego Toscano, Nikolaos Stergiopulos, and George Em Karniadakis. Residual-based attention and connection to information bottleneck theory in pinns, 2023. URL https://arxiv.org/abs/2307.00379.

Etienne Bernard. *Data Preprocessing*. Wolfram, Champaign, Illinois, USA, 2025.

Chenyang Bu, Yuxin Liu, Manzong Huang, Jianxuan Shao, Shengwei Ji, Wenjian Luo, and Xindong Wu. Layer-wise learning rate optimization for task-dependent fine-tuning of pre-trained models: An evolutionary approach. *ACM Transactions on Evolutionary Learning and Optimization*, 4, 08 2024. doi: 10.1145/3689827.

J. Christensen, N. Bajaj, and M. Gosada. *Data-Centric Machine Learning with Python: The Ultimate Guide to Engineering and Deploying High-quality Models Based on Good Data*. Packt Publishing, 2024. ISBN 9781804618127. URL https://books.google.ru/books?id=V6pIOAEACAAJ.

Jianping Gou, Baosheng Yu, Stephen Maybank, and Dacheng Tao. Knowledge distillation: A survey. *International Journal of Computer Vision*, 129, 06 2021. doi: 10.1007/s11263-021-01453-z.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network, 2015. URL https://arxiv.org/abs/1503.02531.

Peter Jano. Knowledge distillation in neural networks: A comprehensive survey. *ResearchGate*, 08 2025. doi: 10.13140/RG.2.2.16632.30726. Preprint.

Paraskevas Koukaras and Christos Tjortjis. Data preprocessing and feature engineering for data mining: Techniques, tools, and best practices. *AI*, 6(10), 2025. ISSN 2673-2688. doi: 10.3390/ai6100257. URL https://www.mdpi.com/2673-2688/6/10/257.

Chuanhui Liu, Haoyun Yin, and Xiao Wang. Theoretical perspectives on knowledge distillation: A review. *WIREs Computational Statistics*, 17(4):e70049, 2025. doi: https://doi.org/10.1002/wics.70049. URL https://wires.onlinelibrary.wiley.com/doi/abs/10.1002/wics.70049. e70049 EOCS-798.R1.

Kaitlin Maile. *Dynamic Architectural Optimization of Artificial Neural Networks*. Theses, Université Toulouse 1 Capitole, October 2023. URL https://hal.science/tel-04568380.

Amir M. Mansourian, Rozhan Ahmadi, Masoud Ghafouri, Amir Mohammad Babaei, Elaheh Badali Golezani, Zeynab Yasamani Ghamchi, Vida Ramezanian, Alireza Taherian, Kimia Dinashi, Amirali Miri, and Shohreh Kasaei. A comprehensive survey on knowledge distillation, 2025. URL https://arxiv.org/abs/2503.12067.

Anthea Mérida, Argyris Kalogeratos, and Mathilde Mougeot. *To Tree or Not to Tree? Assessing the Impact of Smoothing the Decision Boundaries*, page 660–672. Springer International Publishing, 2022. ISBN 9783031159190. doi: 10.1007/978-3-031-15919-0_55. URL http://dx.doi.org/10.1007/978-3-031-15919-0_55.

Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks, 2022. URL https://arxiv.org/abs/1606.04671.

Anurag Singh, Akhilesh Waoo, and Shaw Subhadra. Alleviate cold -start problem in recommendation systems using machine learning algorithms. 01 2024.

Dalwinder Singh and Birmohan Singh. Feature wise normalization: An effective way of normalizing data. *Pattern Recognition*, 122:108307, 09 2021. doi: 10.1016/j.patcog.2021.108307.

Ryutaro Tanno, Kai Arulkumaran, Daniel C. Alexander, Antonio Criminisi, and Aditya Nori. Adaptive neural trees, 2019. URL https://arxiv.org/abs/1807.06699.

Eduardo Teixeira, Samuel Mafra, and Felipe Pereira de Figueiredo. Enhancing accuracy in ship classification through deep learning ensembles and multi-teacher knowledge distillation. *Ocean Engineering*, 341:122511, 12 2025. doi: 10.1016/j.oceaneng.2025.122511.

Huanjing Wang, Qianxin Liang, John Hancock, and Taghi Khoshgoftaar. Feature selection strategies: a comparative analysis of shap-value and importance-based methods. *Journal of Big Data*, 11, 03 2024. doi: 10.1186/s40537-024-00905-w.

Tianzhu Ye, Li Dong, Zewen Chi, Xun Wu, Shaohan Huang, and Furu Wei. Black-box on-policy distillation of large language models, 2026. URL https://arxiv.org/abs/2511.10643.

Volkan Çetin and Oktay Yildiz. A comprehensive review on data preprocessing techniques in data analysis. *Pamukkale University Journal of Engineering Sciences*, 28, 06 2022. doi: 10.5505/pajes.2021.62687.