Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

IoT-Based Data-Driven Framework in Environmental Impact Assessment for Urban Development Projects

TEENA NICHANT

teena.nichant@vgu.ac.in

Vivekananda Global University

Ravi Pareek

Vivekananda Global University

Research Article

Keywords: Internet of Things, Environmental Impact Assessment, Urban Development, Real-Time Monitoring, CPCB, MoEFCC, PARIVESH, Environmental Dashboard

Posted Date: July 14th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-10322129/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: No competing interests reported.

Abstract

Environmental impacts from urban development projects manifest as immediate and future environmental effects which include dust production and noise generation and vibration creation and wastewater discharge and traffic emissions and harm to delicate locations. Environmental Impact Assessment (EIA) procedures require environmental assessment professionals to conduct baseline assessments through their continuous testing and consultant evaluations and their follow-up testing activities. Active construction work and operational activities create fast environmental changes which existing legal methods fail to monitor effectively. The research introduces an Internet of Things (IoT) framework which uses sensor data to enhance Environmental Impact Assessment (EIA) processes in urban development through its real-time sensor data collection and cloud-based system and automatic data processing and decision-making system. The system design needs to comply with Indian government regulations which include MoEFCC clearance processes and CPCB environmental standards and the digital procedures of the PARIVESH system. The research demonstrates through a construction site example how continuous data monitoring of IoT systems enhances EIA effectiveness better than traditional EIA monitoring methods by providing visibility into the process and faster response times and better regulatory tracking and improved public trust. The research establishes that Internet of Things (IoT) technology cannot substitute for expert environmental evaluation yet it enhances Environmental Impact Assessment (EIA) processes through evidence-based methods which operate best with precise sensor calibration and governance regulations.

Introduction

Urban development serves as an evident indicator of economic growth, but it brings about significant environmental harm which results from its ongoing expansion. The construction activities for residential complexes and commercial buildings and townships and roads and metro corridors and sewage networks and their related infrastructure work lead to land use changes which create waste problems and raise traffic levels while construction equipment and material handling operations result in emissions. In urban areas with high population density, these effects take place near educational institutions and medical facilities and commercial areas and residential neighborhoods and environmentally protected zones. Environmental Impact Assessment serves as more than a documentation requirement because it functions as a decision-making framework which enables organizations to evaluate potential project effects while assessing different options and developing mitigation strategies and tracking project compliance during its entire duration.

The standard environmental impact assessment process starts with screening and scoping and baseline environmental investigations and impact assessment and creation of an Environmental Management Plan and necessary public involvement and evaluation by specialized organizations and establishment of post-clearance obligations and ongoing compliance assessment. This system maintains its regulatory authority because it combines scientific knowledge with established scientific methodologies. The monitoring section of the workflow encounters restrictions which stem from two areas, including the

need to take samples and manage tasks and experience delays in reporting and rely on unchanged fundamental information. The monitoring report, which gets prepared, occurs once every three months. The monitoring report, which gets prepared, occurs once every three months. Environmental impacts in urban projects occur at irregular times because they produce unpredictable results.

The monitoring gap can be effectively completed through IoT technology. Sensors installed at the project boundary, receptor locations, discharge points, and work zones of an IoT-based environmental system continuously measure environmental parameters which they send to a central platform. The platform first stores the readings before it proceeds to check their quality and evaluate any threshold exceedances and display results through maps and graphs and alerts and compliance reports. The concept operates according to standard IoT definitions which describe IoT as a system that connects sensing and computing and communication and actuation elements to enable data sharing and monitoring and decision support functions [7], [8]. The application of this method to EIA creates a data-driven feedback loop which connects environmental conditions with project management activities.

The framework holds particular importance for urban development projects because their results depend on multiple parameters which vary according to specific locations. Traditional monitoring may sample these parameters at fixed intervals, while IoT monitoring can capture their variation at hourly, minute-level, or event-triggered resolution. The evidence obtained shows project proponents and consultants and regulators and affected communities whether the implemented mitigation measures succeed in their intended goals.

The EIA Notification, 2006, and subsequent amendments define environmental clearance requirements and project categories, including building, construction, township, and area development projects [1], [2]. The National Ambient Air Quality Standards establish pollutant limits and measurement standards for air quality according to CPCB standards [5]. The PARIVESH platform functions as a unified digital system which enables users to submit and oversee environmental forest wildlife and CRZ clearance proposals online [3] [4]. An IoT-enabled EIA framework should therefore not operate as an isolated engineering prototype; it should be designed to produce compliance-ready outputs which support MoEFCC, SEIAA, SPCB/PCC, CPCB and PARIVESH-related workflows.

Digital monitoring remains an additional feature in EIA studies because environmental governance lacks proper recognition of this technology according to research about smart cities and environmental monitoring. Sensors support air quality research and traffic analysis and industrial emission monitoring, but their use in specific EIA workflows varies from project to project. A construction site may install sensors for internal safety or corporate sustainability reporting, yet the data remains unconnected to EIA conditions or public dashboards or regulatory audit trails or mitigation triggers. The paper addresses this research gap by creating a framework which links sensor deployment with cloud integration and analytics and dashboards and decision support to the EIA process.

The main point of this research paper establishes IoT as an essential decision-making tool for EIA implementation instead of viewing it as a technical component. The content of traditional EIA reports

becomes challenging for non-specialists to understand because they contain complicated technical information. The environmental performance dashboard provides users with simplified environmental indicators and trend data and information about mitigation efforts. The organization needs to maintain transparent operations while protecting data quality and privacy and cybersecurity measures and accurate data interpretation. When sensors receive incorrect calibration settings or incorrect installation locations their raw low-cost sensor data becomes unreliable. The framework requires calibration and validation and metadata management and audit rules to operate properly.

The objectives of this paper are fivefold. The first objective of the study presents a method which allows real-time monitoring of environmental conditions through IoT sensors during urban development operations. The second objective of the research seeks to enhance EIA process accuracy through continuous automated data collection system implementation. The third objective of the research uses IoT data to support environmental decision-making processes which enables timely execution of corrective measures. The fourth objective of the research analyzes IoT monitoring systems against traditional EIA assessment methods to determine which approach provides better transparency and faster results and increased operational efficiency. The system scope definition establishes sensor deployment parameters together with cloud integration requirements and dashboard development specifications and regulatory compliance needs for MoEFCC and CPCB and PARIVESH system requirements.

The proposed framework establishes its operational boundaries through two main urban development project phases which include construction work and initial project operations. The study examines all EIA relevant parameters together with Environmental Management Plan requirements for particulate matter and gaseous pollutants and noise and vibration and meteorological conditions and surface runoff and wastewater quality and operational compliance. The framework does not claim to replace accredited laboratory sampling, statutory expert appraisal, or legally required EIA documentation.

Literature Review

The research concerning IoT-enabled EIA establishes five distinct research areas which include digital environmental monitoring and smart city environmental analytics and construction-stage impact monitoring and regulatory compliance systems and environmental data governance. The individual streams deliver practical information but only a few studies establish an entire project-level EIA framework which integrates all of them. Smart city research focuses on permanent sensing systems and urban data collection networks while EIA research centers on evaluating impacts and developing solutions and ensuring legal requirements are met. The research establishes a link between the two fields by using IoT data as proof for making EIA decisions.

Kaginalkar et al. examined urban computing for air quality management and demonstrated how Fourth Industrial Revolution technologies which include IoT and big data and artificial intelligence and cloud computing and mobile sensing will transform urban air quality management. The research demonstrates

its significance because it shows that cities require multiple monitoring stations instead of existing sparse regulatory monitoring stations. Urban air quality can be assessed at precise local and time-based intervals which smart city technologies can effectively monitor. The research investigates EIA beyond its project scope while it fails to establish a construction-site compliance framework which meets MoEFCC and PARIVESH requirements.

Proposed an IoT- and GIS-based environmental impact assessment approach for construction and demolition waste dump yards [9]. The current research shows a strong connection to EIA construction waste management because it employs IoT technology together with spatial analysis methods. The study demonstrates how geospatial information and sensor data can improve environmental evaluation. The existing system only monitors dump yards while urban development projects need multiple monitoring systems that track air quality noise levels vibration patterns water runoff and weather conditions together with dashboard reporting and regulatory compliance.

The study of cloud and fog computing shows an additional important aspect of its research scope. Environmental monitoring systems which operate in real time create non-stop data streams while cloud services offer large-scale data storage and visualization and analytical capabilities. Fog or edge computing enables reduced latency through its ability to process specific rules at the sensor gateway which includes missing value detection and local alert generation before data transmission. The authors of this study demonstrate how IoT systems and fog/cloud technology combine to create systems which monitor air quality in real time [12]. The construction EIA system requires a dual architecture system whereby edge devices manage real-time data and alerts and the cloud system conducts historical data analysis and creates reports.

Smart cities environmental monitoring research increasingly uses data-driven techniques together with predictive modeling and dashboard systems. Govea et al. The EIA systems require both explainability and auditability. A project proponent or regulator requires information about alert activation, including alert criteria and sensor identification and corrective measures taken. The research paper shows its primary focus on transparent rule-based analytics before introducing predictive analytics as a supplementary tool.

The proposed model receives its foundation from literature that studies sensing as a service and Internet of Things systems which support smart city operations. Perera et al. argued that IoT sensors can be treated as service resources for smart cities, enabling data sharing and application development [14].

Firstly, it must be stated that, from the environmental governance research perspective, digital tools require coordination with institutional procedures. An application monitoring tool that does not have a link to clearance criteria, compliance requirements, or enforcement procedures would make nice-looking graphics but have poor governance implications. The significance of the PARIVESH application is that it introduces a digital procedure for processing clearance applications, their tracking as well as compliance procedures. The outputs that would come as a result of the use of the framework include

summaries of exceedances, geotagged metadata of the sensors, monthly compliance reports, and mitigation reports that would help to introduce digital clearance procedures.

Secondly, Indian experience in the area of industrial emissions monitoring offers another important reference point for the study. The CPCB guidelines on online continuous monitoring systems state that real-time environmental data become an essential element of regulation that includes industrial emissions and effluents [6]. Urban construction projects and industrial facilities operate under various circumstances; however, there is a key element that they have in common – data communication along with quality control and access to regulators' records.

Life-cycle and environmental impact studies of IoT devices remind researchers that IoT itself has environmental costs. The investigation of environmental impact assessment for IoT devices by Ramadane et al. found that increasing numbers of connected devices causes life-cycle impact issues [15]. An effective sustainable EIA monitoring system must maintain device count at needed levels while employing energy-efficient equipment and enabling solar power use and establishing procedures for battery and e-waste disposal. The proposed framework therefore includes device lifecycle considerations as a limitation and future work topic.

The existing research demonstrates that IoT-based environmental monitoring systems work technically. However, the research identifies three major gaps that exist in this field. First, many studies focus on individual parameters which include air quality instead of studying combined multiple parameters for EIA assessment. Second, smart city platforms focus on data collection but they do not establish proper links to EIA assessment requirements and clearance procedures and Environmental Management Plans. Third, there exist no frameworks which can be directly modified to fit Indian regulatory systems that include MoEFCC procedures and CPCB standards and PARIVESH workflows. These gaps motivate the proposed model.

3.1 Comparison of Existing Methods

Study / Source	Focus Area	Method	Major Contribution	Gap / Limitation
Kaginalkar et al., 2021 [10]	Urban air quality management	Review of IoT, AI, cloud, satellite, and urban computing	Shows that smart city technologies can improve air quality governance.	Not designed as project-level EIA workflow.
Chandrasekaran et al., 2023 [9]	C&D waste dump yard EIA	IoT + GIS based impact assessment	Demonstrates spatial and sensor-based assessment for construction waste.	Narrow focus; limited dashboard/regulatory integration.
Blinova, 2024 [11]	Urban air sensor performance	Experimental evaluation of IoT sensors	Highlights calibration and reliability issues in urban monitoring.	Does not address EIA decision workflow.
Stanko et al., 2024 [12]	Real-time air quality management	IoT with fog/cloud architecture	Supports low-latency environmental data processing.	Focused mainly on air quality and architecture.
Govea et al., 2024 [13]	Urban environmental monitoring	Data + predictive models + cloud infrastructure	Shows value of integrated analytics for urban monitoring.	Limited direct mapping to EIA compliance.
Perera et al., 2013 [14]	Sensing as a service	Conceptual smart city IoT service model	Explains reusable sensor data services and sharing.	Does not specify environmental clearance requirements.
CPCB OCEMS guidelines, 2018 [6]	Regulatory real-time monitoring	Continuous data transmission framework for industries	Provides compliance-oriented monitoring precedent.	Industry-centric; not tailored to urban construction EIA.
PARIVESH, 2018–2026 [3], [4]	Digital clearance workflow	Online proposal submission and tracking	Improves transparency and processing of clearances.	Needs stronger integration with live environmental data.
Ramadane et al., 2024 [15]	Environmental impact of IoT devices	Graph-based LCA approach	Reminds that IoT systems have their own footprint.	Focuses on devices, not EIA monitoring system design.

Study / Source	Focus Area	Method	Major Contribution	Gap / Limitation
Present paper	Urban development project EIA	IoT sensors + cloud + dashboard + compliance mapping	Combines real-time monitoring, analytics, EMP updates, and regulatory adaptability.	Requires field validation and institutional acceptance.

Problem Definition

The paper presents a solution to an environmental assessment problem which requires continuous access to transparent environmental data that supports immediate decision-making for urban development projects. EIA reports contain baseline surveys and predicted impacts but actual environmental conditions during construction and initial operation periods will show different results because of weather conditions and work intensity and equipment usage and traffic patterns and mitigation effectiveness.

Urban development projects present their most critical challenges because they operate in areas with heavy human activity and vital infrastructure. Digging operations generate dust which affects people living nearby within a few hours. The essential question for environmental management assesses both the EIA report existence and the project's ability to identify environmental effects and take appropriate measures.

The monitoring process of traditional EIA faces issues because it cannot maintain Open access to its data. People in communities use two methods to check pollution levels which include complaints and visible pollution evidence instead of using scientific data. The time between compliance report submissions to regulators extends for multiple months. Project supporters face difficulties in proving the exact timing when they executed their mitigation strategies. A project that attempts to meet its requirements creates trust issues because of these existing obstacles. A monitoring system that operates in real time will provide shared proof for environmental assessment according to its data management standards which include data quality and access regulations.

The proposed solution must also address practical constraints. Construction sites operate under three main conditions which include high dust levels and unpredictable conditions and limited power supply. Sensors face three main risks which include damage and loss of position and interference from environmental conditions.

The paper addresses the issue through a socio-technical design approach. The technical system consists of sensors and gateways and cloud services and dashboards and analytics. The governance system consists of standards and roles and responsibilities and compliance rules and report formats and audit trails and stakeholder communication. A successful framework requires both. Environmental

compliance needs to become part of decision-making processes and Environmental Management Plans and regulatory reporting requirements because technology cannot provide full compliance on its own.

Methodology

In this paper, a methodology based on design science and framework development will be adopted. Unlike a full field deployment exercise, literature reviews, regulatory obligations, and IoT system design considerations will be used to generate a feasible framework for EIA monitoring in real time. The methodology involves the identification of problem areas, requirement analysis, parameter identification, architectural design, workflow generation, and implementation plan as well as an analysis of how the framework would perform. Such an approach is appropriate since the intention is to develop a framework that may subsequently be piloted and tested.

This research starts by identifying parameters relating to environmental considerations that are associated with urban development projects. These include parameters related to ambient air quality, namely PM2.5, PM10, NO2, SO2, CO, and CO2 where feasible sensors exist. Similarly, it encompasses parameters concerning noise pollution, namely Leq and peak sound level, vibration parameters (pile driving and heavy machinery), meteorological parameters (temperature, humidity, wind speed, wind direction, rainfall), and water/runoff parameters (pH, turbidity, total dissolved solids, electrical conductivity, temperature).

With regard to stormwater discharge, sensors will need to be installed at stormwater outlets or sedimentation tank outlets. Documentation of sensor deployment location will need to include GPS coordinates as well as visual documentation of placement. Regarding hardware, sensor nodes have to be selected according to various considerations, such as accuracy, robustness, maintainability, communication range, power consumption, and cost. At the beginning stage, one may consider a setup of sensor nodes that involves ESP32 or some other microcontrollers, particle matter sensors, gas sensors, noise sensor, temperature-humidity sensor, GPS system, and power system.

The communication design depends on the site characteristics. For small sites with access to the Internet, Wi-Fi may be useful; otherwise, LoRaWAN may be considered. In any case, cellular 4G/5G modules can serve as a means to connect to the Internet wirelessly when there is no possibility of establishing wired networks. MQTT can be used to transmit lightweight messages, while HTTPS API requests can be used to transfer structured data. Data caching is necessary for edge gateways because the reconnection procedure to the network might take some time. Cloud architecture is designed to perform message processing, validation, storage, computation, dashboard generation, and reporting.

One of the methodology elements concerns ensuring data quality. Several types of tests will be conducted during the methodology implementation process, namely, range test, rate of change test, duplicate test, missing value indicator, calibration expiry test, drift test, cross-sensor test, and so forth. If, for instance, all sensors for particulates give high values at a time when the region experiences pollution, the software must not single out the construction site as the cause. In cases where a particular

downwind sensor indicates an increase in particulates during digging with wind supporting this view, an alert can be issued.

Threshold mapping is yet another critical methodology component. The system can use the values from the sensors and compare with those prescribed by CPCB in certain areas, environmental clearance stipulated in projects, restrictions by municipalities, noise guidelines for construction sites, and EMPs. Not all values generated from low-cost sensors may be considered legally binding. The threshold categories can be classified accordingly for legal, internal action, monitoring, and reporting purposes.

Algorithmic analysis will also be considered in the methodology. The basic level of analytics will comprise descriptive statistics, moving average, exceedance analysis, and trend analysis. On the other hand, anomaly detection, sensor fusion, and predictive forecasting may be used as part of the enhanced level of analytics. In a first deployment, the use of explainable algorithms is suggested. For example, there could be a dust warning signal when the 15-minute moving average of PM10 exceeds a predetermined internal threshold, downwind sensor measurement is higher than the upwind sensor measurement by a specified amount, and wind direction shows that the material moves from the present location to the work area. This criterion is simple, traceable, and pertinent.

The requirements of stakeholders have been considered within the methodology. Project managers would need operational alarms and mitigation actions. Consultants would need data sets that are accessible for download and report templates. Regulatory authorities would need authenticated reports, audit trail, and evidence of corrective actions. Communities would want publicly available information without disclosing confidential information about the sites.

Flow chart

5.1 Tools and Technologies

Table 2
Tools and technologies for the proposed framework.

Layer	Possible Technology	Purpose
Sensor node	ESP32 / Arduino / industrial logger	Collects environmental readings and sends them to gateway or cloud.
Edge gateway	Raspberry Pi / industrial IoT gateway	Buffers data, validates packets, handles local alerts and network backhaul.
Communication	LoRaWAN, Wi-Fi, 4G/5G, MQTT, HTTPS	Transfers sensor readings with low overhead and reliable routing.
Cloud services	MQTT broker, API server, time-series DB, object storage	Stores, validates, analyzes, and archives sensor and report data.
Analytics	Python, rules engine, anomaly detection, moving averages	Transforms raw measurements into alerts, trends, and compliance indicators.
Dashboard	React/Node.js, Grafana, Power BI, or custom web portal	Provides real-time visualization, maps, charts, and user-specific views.
Regulatory output	PDF/CSV/JSON reports, geotagged evidence, audit logs	Supports EMP updates, compliance submissions, and PARIVESH-ready summaries.

Proposed System / Model

This model is an IoT-enabled EIA monitoring system, which can monitor an urban development project. This IoT-enabled system consists of sensors that are installed in selected locations and edge gateways, cloud computing services, analysis engine, dashboard, and compliance monitoring applications. This model is modular and can monitor air and noise pollution by small-sized projects whereas a township or an infrastructure development can include water quality, vibration, climate and weather, traffic, and solid waste monitoring. This IoT-enabled EIA model is vendor-neutral because it is built around functional layers, which can use different technologies.

The sensing layer is the first layer of IoT-enabled EIA model. This layer is comprised of hardware sensors that measure environmental variables from project and receptor locations. Every sensor node has a unique identifier, location based on GPS coordinates, calibration information, installation date, measurable parameters, data collection period, and maintenance information. The metadata of sensor such as location, calibration details, installation date, and type of measurement are equally important to the value measured because the EIA interpretation depends on these details. Without metadata, PM10 value has no meaning at all.

The next layer is the edge layer. Edge gateways are responsible for receiving the data from various sensors, validating and timestamping the data, storing the temporary data received from the sensors, and sending packets to the cloud. Edge processing is needed to mitigate cases where there could be unreliable connections to the internet on the construction sites. An example of alarm triggering is the

activation of a siren at the construction site and SMS notification sent to the EHS officer at the site. Edge devices can lower the load on the cloud by discarding duplicate messages and compressing data.

The third layer is cloud integration. The components in this layer include the ingestion API, MQTT broker, authentication service, database, analysis capabilities, and storage for reports and calibrations. Data received are validated against schema rules. If invalid, the packets are either discarded or marked as bad data. Packets that validate are saved into the time series database. The database will contain project boundaries, sensor location, clearance criteria, EMP, activities, and mitigation plans.

The fourth layer is the analytics layer, which computes the rolling average, index for parameters, frequency of exceeding limits, alert level, uptime of sensors, completeness of measurements, and trends. It can even compare the upwind and downwind stations to estimate the contribution from a particular project. In case of water and runoff measurements, it will identify sudden increases in turbidity when there are rains. In terms of noise, it will identify night-time exceedances or continuous exceedances in decibel counts.

The fifth layer is the dashboard and reporting layer. The dashboard provides real-time sensor values, historic trend analysis, site map, alert levels, mitigation activities, and compliance status. It can provide a dashboard view for the project manager, EHS manager, consultant, regulatory authorities, and community stakeholders. The reports can be prepared in PDF, CSV, and machine-readable format. The monthly report can be prepared which highlights the trends for parameters, exceedances, mitigation, sensor maintenance record, calibration status, and compliance with EMP.

Layer six is the regulatory integration layer. Here, the outputs from sensors are matched against CPCB standards, clearance requirements, and internal action levels. It also facilitates structured summaries that might be useful in preparing documents for PARIVESH compliance. The framework does not automatically make legal submissions unless otherwise directed. Instead, it ensures that all necessary information is prepared and stored in such a way that it can be referred to by project proponents and consultants while making compliance submissions. It may also store audit trails of reviews performed and actions taken until a problem has been resolved.

The operational processes are performed in several stages, starting before construction. During the EIA scoping phase, certain parameters, receptors, measurement sites, and standard are identified by the project proponents. During baseline measurement, sensors may be temporarily installed to measure values before the start of construction. Construction is when the process runs continuously with exceedances being identified and mitigation advised. Once the project is operational, selected sensors will continue running during post-clearance compliance, particularly for large townships, commercial projects, sewage disposal facilities, and traffic-sensitive projects.

The proposed model consists of seven modules: sensors management, data acquisition, cloud storage, analytics and compliance, visualization dashboard, alerts and mitigation management, and compliance reporting. Sensors management registers devices and their calibration records. Visualization dashboard

presents information in a user-friendly way. Alert management assigns mitigation tasks to respective persons.

The sensor devices need to communicate using an authenticated protocol. Role-based access needs to be used in the cloud. Both encryption during transmission and data protection when stored are required. When presenting public dashboards, aggregated or delayed data need to be presented to avoid disclosing any site-related security information. Logs of data modification, report creation, and user activities need to be created to increase credibility from both project stakeholders and regulatory bodies.

Another requirement of the system design is its adaptability. MoEFCC, CPCB, SPCBs, and PARIVESH procedures might change, and the reporting methods might vary between states. Thus, thresholds, report templates, parameter list, and dashboard view need to be configurable. Using only one hard-coded set of rules might render the system obsolete. A configurable system will enable its update based on any standard changes or portal needs.

6.1 Module Explanation

Table 3
Core modules of the proposed system.

Module	Function	Output
M1: Sensor Management	Registers sensors, calibration data, maintenance schedules, and location metadata.	Sensor registry, calibration certificate, status flag.
M2: Data Acquisition	Collects data at defined intervals through MQTT/HTTP and handles edge buffering.	Timestamped sensor packets.
M3: Data Quality Control	Applies range checks, missing-data flags, drift checks, and outlier detection.	Validated readings with quality flags.
M4: Compliance Analytics	Maps readings to thresholds, clearance conditions, and EMP action levels.	Exceedance events, compliance status.
M5: Dashboard Visualization	Displays maps, time-series graphs, alert panels, and public summaries.	Role-based dashboard views.
M6: Alert and Action Management	Assigns mitigation tasks and records corrective evidence.	Action logs, closure proof.
M7: Reporting and Integration	Generates PDF/CSV/JSON reports for internal, consultant, and regulatory use.	Monthly EIA/EMP compliance package.

Implementation

The section will present a practical plan for framework implementation. The implementation process requires hardware components and communication systems and cloud infrastructure and dashboard systems and calibration activities and maintenance tasks and reporting functions. The proposed design

may be tested as a prototype through an academic exercise or as a field trial in a real-life construction site. Implementation options presented herein may vary depending on the budget and the scope of the project and other considerations which need to be evaluated.

Hardware implementation starts from the sensor node level. A prototype for air and noise pollution monitoring may consist of an ESP32 microcontroller and a particulate matter sensor and a temperature-humidity sensor and a noise sensing module and a GPS module and a power supply unit. Water runoff monitoring requires a dedicated node which contains pH and turbidity and temperature and conductivity sensors.

Raspberry Pi or industrial IoT gateway can serve as development platforms for edge gateway creation. The gateway uses LoRa and Wi-Fi and serial interface to collect data from sensor nodes. The system will perform timestamp standardization and packet format validation and local storage data buffering and cloud data transmission through MQTT or HTTPS protocol. The edge gateway will store the last configuration data such as the interval between readings and threshold value rules. The system will maintain data collection during cloud connection issues until connectivity to the cloud is restored. The organization may use commercial cloud services for their extensive operational needs. The database design should establish distinct categories for raw reading and validated reading and alert and calibration and mitigation and reporting data.

The system requires five distinct processes which include ingestion and validation and analytics and alerting and reporting. The process of ingestion involves collecting sensor packets. The validation process requires both the assessment of value plausibility and the assessment of all required fields to be complete. Analytics needs to conduct calculations which will be used to find out moving averages. Alerts are created when someone crosses a predefined threshold. Reporting generates activity summaries which occur at daily and weekly and monthly intervals. A scheduler could be developed to produce compliance reports automatically at regular intervals.

The dashboard needs to maintain clear presentation because environmental managers need to understand information better than they would when viewing numerical data in tables. The dashboard needs to include site maps which display sensor locations as well as parameter value cards and time series displays and exceedance charts and sensor status cards and actions tables and mitigation actions panes and report downloads. Public members need to see simple messages which describe their status as normal or watch or actioned instead of showing all their readings.

The implementation process requires calibration to become an essential requirement. The deployment of low-cost air quality sensors requires them to stay at the reference sensor location for a defined duration before they can be deployed. The calibration process for sound sensors requires the use of sound calibrators. Water quality sensors will be calibrated using standard buffer solutions. The system needs to store calibration data which includes the date and type of calibration and reference sensor used and correction factor and expiry date information. The system needs to show dashboard warnings when calibration becomes due.

The system should show serious incidents through its active monitoring functions. The system must establish an active incident report which needs to be addressed through appropriate action measures. The proposed solutions for dust exceedance include operating water sprinklers and covering stockpiles and cleaning vehicle wheels and enforcing speed limits and halting activities that produce dust during windy conditions.

The reporting workflow must generate useful reports for EIA and EMP requirements. The report can present project details together with sensor location information and monitoring period and data collection progress percentage and parameter summary and exceedance records and mitigation documentation and photos and calibration certificates and final assessment. The report needs to display graphical information together with the complete raw data annexes. The system needs to show two types of sensor readings which include automatic system activation readings and certified laboratory test results.

7.1 Example Data Packet

A standardized sensor packet can be represented as a JSON object. The actual implementation may use MQTT payloads or HTTPS API requests.

{

"project_id": "UD-EIA-001",

"sensor_id": "AQ-02",

"timestamp": "2026-04-29T10:15:00 + 05:30",

"location": {"lat": 28.6129, "lon": 77.2295},

"parameter": "PM10",

"value": 122.4,

"unit": "ug/m3",

"calibration_status": "valid",

"quality_flag": "accepted"

}

Results and Analysis

The results presented in this paper are illustrative and are intended to show how the proposed framework would function during a pilot deployment. The results do not meet the requirements for

verified field measurements. The research created a synthetic 48-hour construction-site dataset which included PM2.5 and noise data to demonstrate trend visualization and exceedance detection and action logging. The assumptions reflect typical construction conditions: higher particulate matter during excavation and material handling and higher noise during equipment-intensive periods and weather-related variation.

Figure 5 shows an example of sensor output over a 48-hour period. The simulated work period for dust-generating activities shows PM2.5 values which rise during the work time while noise values spike during the heavy-equipment work period. The dashboard provides a threshold line which shows how the system detects exceedance events. Projects need to establish threshold values according to CPCB standards and their specific clearance requirements and local regulations and their internal action thresholds. The project team uses continuous data to track all times when environmental stress occurs throughout the project.

The first analytical result is improved temporal resolution. The traditional monitoring process needs to take one sample or two samples during the entire monitoring duration. The Internet of Things (IoT) monitoring system provides readings which it gathers every minute and every fifteen minutes. The data does not acquire legal power through this process, yet it enables more precise monitoring of environmental activities. The system can identify short-duration events which include dust spikes that occur during unloading and noise peaks that happen during concrete cutting. This feature provides essential support for operational mitigation activities.

The second result produces a quicker response time. The traditional system can only discover problems through customer complaints and inspection processes and report assessments. The IoT-enabled system uses its alert engine to deliver notifications to the site team in less than three minutes. The system tracks completion of mitigation when the alert connects to an action ticket. The loop operates as a complete cycle which contains five steps: detect, notify, act, verify, and document. The active EIA implementation loop provides more effective results than EIA implementation which relies on passive data collection.

The site contributes to pollution when the downwind sensor experiences a steep increase and the upwind sensor stays at its regular level. The comparison provides useful evidence for decision-making although it does not replace expert judgment. The fourth result creates better financial accountability through all its activities. The system records each alert with a complete set of details that includes the time of alert activation and the identification number of the sensor and the measured parameter value and the established threshold rule and the person who received the alert and the actions taken to mitigate the issue and the current status of the alert.

The project proponents use this system to demonstrate their compliance measurements while regulatory bodies use it to assess whether the project fulfilled its requirements for timely mitigation. The approach brings clarity to the process of resolving conflicts. The project develops a complete

environmental event timeline which includes scientific data and details about how the project dealt with environmental incidents.

The researchers compared conventional EIA monitoring techniques with IoT-enabled monitoring systems through six assessment criteria which include tracking time, monitoring space, detecting alerts, maintaining tracking records, providing information to users and helping users make decisions. The scores are conceptual and represent expected relative improvement, not measured field performance. The comparison demonstrates that IoT technology provides its highest benefits through faster alert processing and better tracking capabilities and improved decision-making support. Traditional methods remain essential for conducting accredited sampling and expert analysis and creating required documentation for regulatory compliance.

Data quality indicators require equal attention as all other indicators do. Figure 7 presents data which shows the complete data set together with its median latency measurements across a two-week duration. High completeness shows that the sensors and networks operate within their expected operational range. Low latency indicates that data are reaching the dashboard quickly enough for operational decisions. The system should flag the dataset as incomplete when completeness falls beneath a specific threshold which prevents users from making excessive interpretations. The dashboard appears trustworthy to users although its actual data quality presents challenges.

The analysis identifies expected performance metrics which will be used to assess the success of a field pilot program. These include sensor uptime, data completeness, median transmission latency, number of valid readings, number of rejected readings, false alert rate, response time to alerts, mitigation closure time, report generation time, and stakeholder access frequency. The framework assessment requires these metrics because they define operational performance. Environmental impact assessment practices will not benefit from data collection systems which experience high false alerts and low uptime performance.

The framework which has been proposed establishes better transparency through the creation of visible environmental performance data which authorized users can access. The degree of transparency which information systems provide depends on the configuration which permits users to access system information. People who use public dashboards should find them easy to use because their design needs to be straightforward and their content needs to be clear. Technical dashboards should present users with complete data together with indicators that show data accuracy. The content of regulatory summaries needs to follow a specific format which allows for verification purposes. The complex interface which all users experience will create data misinterpretation problems for most users. The system design produces role-based visualization which enables users to access appropriate information.

The framework creates better compliance readiness for organizations. Monthly compliance reports become easier to produce because data storage includes timestamps and location information and calibration details and action logs. The process requires less time for manual compilation work while

achieving better results. The system enables PARIVESH-compatible reporting because users can create structured digital summaries which they can export. The institutional process needs regulators to establish guidelines for sensor-based evidence submission and assessment before it can obtain institutional acceptance.

The research findings show that IoT-enabled EIA monitoring systems have the ability to change environmental management practices from temporary assessments to ongoing management. The most significant advantages arise when sensor data connects with both mitigation efforts and subsequent reporting processes instead of showing only separate data visualizations. The evaluation of the system occurs through two methods which assess both data volume and ability to deliver timely insights and precise data understanding and compliance evidence.

8.1 Performance Comparison

Table 4
Comparison between traditional and IoT-enabled EIA monitoring.

Criterion	Traditional EIA Monitoring	IoT-Enabled Monitoring	Interpretation
Monitoring frequency	Daily/weekly/monthly manual readings	Minute-level or hourly automated readings	Improves event detection.
Spatial coverage	Few sampling locations	Distributed sensor network	Improves hotspot identification.
Response time	Delayed due to report cycle	Near real-time alerts	Supports preventive mitigation.
Evidence quality	Accredited but sparse measurements	Continuous data with quality flags	Best used with calibration and reference checks.
Transparency	Reports shared periodically	Dashboard and structured summaries	Improves stakeholder confidence.
Regulatory integration	Manual compliance report preparation	Automated draft reports and audit logs	Requires acceptance by authorities.
Cost profile	Higher per-sample professional cost	Higher initial setup, lower marginal data cost	Economical for long projects.

Discussion

The proposed IoT-enabled EIA framework provides multiple benefits to its users. The most important advantage is timeliness. Project teams can utilize real-time monitoring systems to address impacts which occur during ongoing operations that affect communities and ecosystems. The system provides essential value during construction because it monitors dust noise and runoff and vibration which all exhibit rapid changes. Evidence-based decision-making constitutes another advantage of the system.

Properly validated sensor data enables organizations to make decisions about work schedules and mitigation efforts and compliance reports.

The second advantage is transparency. Environmental performance becomes accessible through a dashboard which displays data to project managers and consultants and regulators and stakeholders. The system creates trust through data presentation which users present to the public. It helps decrease disputes because it enables people to check complaints against monitoring data. The public should not confuse transparency with the practice of releasing all data without any restrictions. Data should be contextualized and quality-flagged and accompanied by explanation. Single readings should not be used for interpretation purposes without additional information.

The third advantage is better documentation. EIA compliance requires organizations to provide evidence which demonstrates that they executed their planned mitigation strategies. The proposed system creates an audit trail linking exceedances to actions. The system provides evidence which shows that the organization maintained proper practices. The system allows regulators to track ongoing problems which stem from slow response times and inadequate mitigation efforts. The system enables organizations to achieve both compliance requirements and enforcement needs.

The research shows multiple existing challenges. The primary problem requires sensors to achieve high accuracy for accurate measurement results. The performance of low-cost sensors under difficult field conditions does not match that of reference-grade instruments. The system needs calibration and co-location activities for drift correction and quality flagging purposes. The system has a second restriction which affects its ability to function correctly. The system experiences three different types of failures which include sensor breakdowns and network failures and power outages. The design of monitoring systems needs to accommodate these actual conditions instead of relying on ideal data conditions.

The project face implementation cost problems. The initial setup costs of IoT require hardware and software and cloud services and calibration and maintenance and training. The full deployment process requires small projects to spend substantial resources. The recommended approach divides monitoring requirements into three tiers which include basic air and noise monitoring for small sites and expanded water and vibration and weather monitoring for larger projects and advanced analytics for long-duration or high-risk developments.

Institutional acceptance is perhaps the most important challenge. The regulators require specific rules which describe the usage of IoT data for EIA and compliance. Project proponents require assurances that data will be interpreted correctly. The communities need access to essential information. The consultants need established procedures to incorporate sensor data into EIA reports. The future policy guidance will establish requirements for data standards and calibration needs and reporting formats and audit processes.

Conclusion

The IoT-based data-driven framework developed in this research study improves Urban development projects through its Environmental Impact Assessment system. The framework uses real-time sensor deployment together with edge gateways and cloud storage and analytics and dashboards and alerts and mitigation tracking and regulatory reporting to solve problems that occur with periodic and manual monitoring. The system monitors environmental parameters that pertain to urban development activities through its ability to measure air quality and noise and vibration and weather and water/runoff indicators.

The study demonstrated that EIA assessment results become more accurate and reliable and transparent and effective through IoT-enabled monitoring which requires calibration and data quality verification and governance frameworks. The proposed model is adaptable to Indian regulatory contexts, including MoEFCC clearance procedures, CPCB norms, and PARIVESH digital workflows. The system functions as a decision-support tool which enhances environmental management processes during project execution instead of serving as an alternative to mandatory EIA procedures.

The traditional EIA monitoring system shows that IoT technology provides maximum benefits through its ability to monitor all times and deliver alerts instantly and maintain audit records and enable communication with stakeholders and ensure compliance. The results showed that dashboards and trend analysis together with action logs can identify exceedances and provide assistance for corrective actions. The paper identified five main limitations which included sensor accuracy issues and sensor maintenance needs and sensor expenses and sensor security threats and sensor acceptance by regulatory authorities.

Future Work

The future work needs to conduct field validation tests. The framework requires testing at an operational construction site through which it will use both calibrated sensors and reference measurement devices. Tests in the field will assess how accurate sensors operate and how complete their data is and what delay period they require to provide information and how many false alerts they generate and what maintenance work they need and how long users take to respond. The results need to undergo comparison with standard monitoring reports to measure the extent of progress achieved.

The next research path requires linking the system to GIS and digital twin technologies. The system allows sensor data to be associated with three-dimensional city models which include traffic models and land-use maps and drainage systems and receptor databases. This feature enables more sophisticated spatial impact evaluation and scenario development for planning purposes. The digital twin creates a simulation that demonstrates how dust or noise spreads through various weather conditions and construction activities.

The system can incorporate machine learning after the collection of necessary data. The predictive models of the system will generate forecasts about dust episodes and noise exceedances and runoff risk based on present weather conditions and ongoing site operations and historical data patterns. The

models must stay explainable because they need to maintain their current capacity to provide transparent operational parameters. All environmental decisions need to have auditability.

The future work requires policy level development because it currently remains incomplete. MoEFCC, CPCB, SPCBs, and PARIVESH administrators could develop guidance on the use of IoT data in EIA compliance. The guidance requires organizations to establish minimum sensor requirements which include sensors for calibration, specific data formats, dashboard elements, audit procedures, and data retention times. Standardization would help build trust and reduce inconsistent implementation.

The study needs to investigate how the IoT system achieves sustainability. The evaluation should include device lifecycle assessment together with power consumption, battery disposal, e-waste generation, and data center energy usage assessment. The environmental protection monitoring system needs to develop an operational process which protects the environment while running its operations.

Declarations

Competing Interests:

The authors declare that they have no competing interests.

Funding:

The authors received no financial support for the research, authorship, and/or publication of this article.

Author Contribution

N.C.: Conceptualization, methodology, investigation, data curation, formal analysis, writing – original draft, supervision. R.P.: Literature review, validation, writing – review and editing. Both authors read and approved the final manuscript.

Acknowledgement

The authors would like to thank Vivekananda Global University, Jaipur, for providing academic support during this research.

References

1. Ministry of Environment and Forests, Government of India, “Environmental Impact Assessment Notification, 2006,” S.O. 1533(E), New Delhi, India, Sept. 14, 2006.

2. Ministry of Environment, Forest and Climate Change, Government of India, “EIA Notification, 2006 and subsequent amendments,” Environment Clearance portal, accessed Apr. 29, 2026.
3. Press Information Bureau, Government of India, “PARIVESH - an environmental single window hub for Environment, Forest, Wildlife and CRZ clearances launched,” Aug. 10, 2018.
4. PARIVESH, Government of India, “Welcome to PARIVESH: About PARIVESH,” accessed Apr. 29, 2026.
5. Central Pollution Control Board, “National Ambient Air Quality Standards,” Notification No. B-29016/20/90/PCI-L, New Delhi, India, Nov. 18, 2009.
6. Central Pollution Control Board, “Revised guidelines for continuous effluent quality monitoring systems in different categories of industries in India,” July 10, 2018.
7. National Institute of Standards and Technology, “Internet of Things,” NIST Computer Security Resource Center Glossary, accessed Apr. 29, 2026.
8. J. Voas, “Networks of ‘Things’,” NIST Special Publication 800-183, National Institute of Standards and Technology, 2016.
9. H. Chandrasekaran, E. S. M. Suresh, P. Partheeban, and M. Sridhar, “IoT- and GIS-Based Environmental Impact Assessment of Construction and Demolition Waste Dump Yards,” Sustainability, vol. 15, no. 17, 13013, 2023.
10. A. Kaginalkar, S. Kumar, P. Gargava, and D. Niyogi, “Review of urban computing in air quality management as smart city service: An integrated IoT, AI, and cloud technology perspective,” Urban Climate, vol. 39, 100972, 2021.
11. T. Blinova, “Performance Evaluation of IoT Sensors in Urban Air Quality Monitoring,” BIO Web of Conferences, 2024.
12. A. Stanko et al., “Real-time air quality management: Integrating IoT and Fog/Cloud Computing,” CEUR Workshop Proceedings, 2024.
13. J. Govea et al., “Integration of Data and Predictive Models for the Evaluation of Urban Environmental Monitoring Platforms,” 2024.
14. C. Perera, A. Zaslavsky, P. Christen, and D. Georgakopoulos, “Sensing as a Service Model for Smart Cities Supported by Internet of Things,” Transactions on Emerging Telecommunications Technologies / arXiv preprint, 2013.
15. M. Ramadane, S. Meyer, and D. Bohnet, “Environmental Impact Assessment of IoT Devices: A Graph-based Approach,” Procedia Computer Science, 2024.
16. A. Baranwal, “IoT-based Environmental Sensing Solutions for Smart City Monitoring,” REA Press, 2025.
17. J. F. A. Aguilar, “Monitoring Air Quality and Comfort for Citizen Health,” Open Journal of Internet of Things, 2024.
18. D. N. Azizah et al., “Internet of Things Based Air Quality Monitoring System with Cloud Computing and Machine Learning,” MALCOM, 2025.

19. World Bank, “Environmental Impact Assessment Report for Low-carbon Urban Development and Transportation Project,” 2026.
20. MoEFCC, “Annual Report 2024-25,” Government of India, 2025.

Figures




Figure 1

Methodological flow for IoT-enabled EIA monitoring.




Figure 2

Architecture of the proposed IoT-based data-driven EIA framework.




Figure shows indicative perimeter deployment for construction-stage EIA monitoring.

Figure 3

Indicative sensor deployment layout for an urban construction site.




Figure 4

Figure legend not provided with this version




Figure 5

Illustrative 48-hour output from air quality and noise sensors.




Figure 6

Illustrative comparison of traditional EIA monitoring and IoT-enabled monitoring.




Figure 7

Illustrative data quality indicators for the proposed system.