

Adapting Witwatersrand Deep Mining Seismic Experience to a 3D Printed Auxetic Resonant Acoustic Metamaterial Framework for Tunnel Shock Wave Mitigation in Peru

Paul Ricardo Prudencio Gálvez

pprudencio@autonoma.edu.pe

Universidad Autónoma del Perú

Research Article

Keywords: Acoustic metamaterials, auxetic structures, additive manufacturing, deep-tunnel lining, seismic shock-wave mitigation, underground mining, applied earth sciences, technology transfer, Peru

Posted Date: September 4th, 2026

DOI: <https://doi.org/10.21203/rs.3.rs-10632809/v1>

License:  This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Additional Declarations: No competing interests reported.

Abstract

Deep underground excavations — whether ultra-deep gold mines in South Africa’s Witwatersrand Basin or seismically active tunnels along Peru’s Andean margin — face recurrent damage from dynamic shock waves generated by mining-induced rockbursts and tectonic subduction earthquakes. Conventional support systems (shotcrete, steel sets, resin-grouted bolts) provide limited broadband energy dissipation. This manuscript presents a documentary and comparative-analytical study that (i) synthesises the DOI-verified literature on 3D-printed acoustic and mechanical metamaterials with auxetic and locally resonant unit cells, (ii) builds a quantitative comparison matrix of the attenuation mechanisms and manufacturing routes reported in that literature, (iii) specifies the materials, additive-manufacturing machinery, underground installation equipment, and human-capital competencies required to fabricate and deploy such liners at industrial scale, and (iv) develops a technology-transfer framework adapting South Africa’s deep-mining seismic experience to Peru’s public-space and mining-tunnel infrastructure, benchmarked against seismic-mitigation solutions already implemented in developed countries. As a documentary synthesis, the study does not report new physical experiments; its contribution is the integration of dispersed engineering evidence into a reproducible design, procurement, and workforce-training roadmap, together with an explicit identification of the low-frequency (< 50 Hz) attenuation gap that future field-scale prototypes must close.

1. Introduction

Peru lies on the convergent margin between the Nazca and South American plates, a setting that generates frequent subduction-zone earthquakes and sustains one of the highest probabilistic seismic hazard levels in South America [5]. Underground public infrastructure (metro tunnels, pedestrian underpasses, ventilation shafts) and the country’s deep and expanding mining sector are both exposed to this hazard, yet neither sector currently specifies dynamic-energy-absorbing liners in its design codes. In parallel, South Africa’s Witwatersrand Basin gold mines, now operating at depths approaching 4,000 m, have accumulated more than a century of engineering experience with mining-induced seismicity and rockburst damage, and remain one of the most heavily instrumented seismic environments in the world [6].

Acoustic and mechanical metamaterials — architected periodic structures whose unit cells produce local resonance or negative effective mass/stiffness — were first demonstrated to open sonic band gaps by Liu et al. [1], and were subsequently shown, at field scale, to reshape seismic surface waves through soil-embedded inclusions [2]. Numerical studies have since extended the concept to large-scale mechanical metamaterials capable of attenuating both bulk and surface seismic waves [3]. Additive manufacturing (AM) is the enabling technology that allows the complex, often auxetic or chiral, lattice geometries required for broadband low-frequency attenuation to be fabricated with the dimensional control that conventional casting or machining cannot achieve [4, 7, 8].

Research gap and contribution. The metamaterials literature is concentrated on laboratory-scale panels and frequencies above the seismic band of engineering concern, and it rarely addresses the logistics of deploying 3D-printed liners in large-scale, remote, or underground civil and mining works – particularly in developing-country contexts where additive-manufacturing capacity, regulatory codes, and specialised workforce are still emerging. This manuscript addresses that gap through three contributions: (i) a DOI-verified comparative matrix that consolidates quantitative and mechanistic evidence from the foundational metamaterials literature; (ii) a materials-, machinery-, and human-capital-explicit implementation protocol for fabricating and installing auxetic-resonant liners in deep-tunnel and mining contexts; and (iii) a transnational technology-transfer roadmap that adapts South Africa’s deep-mining seismic-mitigation experience to Peru’s public-space infrastructure and to its principal underground and open-pit mining operations.

2. Methods

2.1 Documentary synthesis protocol

This study follows a documentary and comparative-analytical design rather than a primary experimental protocol. A structured literature search was carried out across Scopus-indexed sources (Science, Physical Review Letters, New Journal of Physics, Additive Manufacturing, Automation in Construction, Engineering Geology, Geophysical Prospecting) using the terms “acoustic metamaterial”, “auxetic”, “seismic shield”, “phononic band gap”, “3D printing construction”, and “mining-induced seismicity”. Only sources with an active, verifiable Digital Object Identifier (DOI) were retained; entries that could not be independently verified against the publisher record were excluded, consistent with editorial requirements on reference integrity.

2.2 Conceptual unit-cell design

The proposed liner unit cell couples a dense resonant core (a metallic inclusion) suspended in a viscoelastic thermoplastic matrix with chiral, auxetic (negative Poisson’s ratio) struts. Under the governing periodic elastodynamic equation $\nabla \cdot [C(x) : \nabla u(x)] + \rho(x)\omega^2 u(x) = 0$, with Floquet–Bloch periodic boundary conditions $u(x+a\hat{x}) = u(x)e^{jk \cdot a\hat{x}}$, this topology is designed conceptually to open a low-frequency band gap by combining Bragg scattering with local resonance, following the mechanisms demonstrated experimentally and numerically in [1] and [3]. No new finite-element results are reported here; the formulation is presented as the design basis for the field-scale prototype proposed in Section 4.4.

2.3 Materials, additive-manufacturing machinery, and post-processing

Table 1 summarises the material–process combinations documented in the literature and adapted here for tunnel-lining panels.

Material	AM process / machinery	Typical layer	Post-processing
Polycarbonate–carbon-nanotube (CNT) composite	Fused Filament Fabrication (FFF), heated-chamber industrial printers	0.1 mm	Thermal annealing
Photopolymer resin (rigid/flexible)	Stereolithography (SLA/DLP)	0.05 mm	UV post-cure
Thermoplastic polyurethane (TPU) + shape-memory alloy struts	Multi-material Material Extrusion (MEX) + Selective Laser Melting (SLM) for metal struts	0.1–0.2 mm	Stress-relief heat treatment
Metal–matrix / geopolymer composite	Directed Energy Deposition (DED); large-format robotic MEX for cementitious matrices [7,8]	0.03–0.5 mm	Hot isostatic pressing / curing

Table 1 Material–process combinations documented in the literature, adapted for tunnel-lining panels

2.4 Underground installation machinery and procedures (mining context)

Deployment inside an active mine or tunnel requires equipment distinct from the fabrication stage:

- Containerised or skid-mounted DED/MEX printing units, sited at the portal or on intermediate levels, to shorten the logistics chain for panel replenishment.
- Robotic telescopic manipulators / shotcrete robots (e.g., boom-type units already used for fibre-reinforced shotcrete application) retrofitted with vacuum or mechanical grippers for panel placement against the primary support.
- Multi-boom drilling jumbos for anchoring the panel frame to the rock mass.
- 3D laser scanning / LiDAR and ground-penetrating radar (GPR) for as-built verification of panel alignment and detection of voids behind the lining.
- Distributed fibre-optic sensing cable, embedded during installation, for continuous post-installation monitoring of dynamic strain.

2.5 Human capital and training protocol

Table 2 specifies the professional profiles and the competencies each must acquire.

Role	Required background	Core competencies to develop
Geomechanical / geotechnical engineer	Civil or mining engineering, rock mechanics	Stress-field mapping, target-frequency definition, interpretation of microseismic monitoring
Additive-manufacturing technician	Mechanical or materials engineering technology	Parametric CAD/CAM, printer calibration, material rheology, defect (porosity) control
Robotics / installation operator	Technical certification in heavy mobile equipment	Kinematic control of robotic arms, laser-scanning alignment verification, confined-space safety
Structural dynamics specialist	Civil/structural engineering, postgraduate in dynamics	Floquet–Bloch dispersion analysis, finite-element modelling, code-compliance verification

Table 2 Required professional profiles and competencies

Recommended training protocol: an intensive modular programme (approx. 100–120 contact hours) combining classroom instruction in metamaterial theory and seismic risk, hands-on printer operation and maintenance, and supervised on-site installation drills, delivered through a university–industry partnership (e.g., UAP with the Ministerio de Energía y Minas and mine operators), with periodic refresher modules tied to equipment updates.

2.6 Ethical considerations

This is a documentary and comparative-analytical study: it does not involve human participants, animal subjects, or the collection of primary field data, and therefore does not require Institutional Review Board approval. All quantitative claims are attributed to their original, DOI-verified sources; no experimental results are claimed as original findings of this manuscript.

3. Results

3.1 Comparative matrix of the foundational metamaterials literature

Table 3
Comparative matrix of the foundational metamaterials literature

Source	Scale / mechanism	Reported wave-attenuation evidence	Relevance to tunnel lining
Liu et al., 2000 [1]	Laboratory sonic crystal; local resonance	Locally resonant composite breaks the conventional mass-density law of transmission by one or more orders of magnitude near 400 Hz in a 2-cm slab	Establishes the local-resonance mechanism exploited in the resonant core of the proposed unit cell
Brûlé et al., 2014 [2]	Field-scale soil metamaterial; vertical bored inclusions	Full-scale seismic test shows measurable modification of surface-wave energy distribution in the presence of the metamaterial mesh, consistent with numerical plate-model predictions	First field-scale proof that architected media can redirect seismic surface-wave energy, motivating panel-scale application inside tunnels
Miniaci et al., 2016 [3]	Numerical large-scale mechanical metamaterial shield	3D transient simulations show substantial attenuation of both bulk and surface seismic waves using combined phononic-crystal / locally-resonant configurations	Provides the numerical basis for extending panel-scale resonant design to the low-frequency seismic band
Askari et al., 2020 [4]	Systematic review of AM for metamaterials	Comprehensive synthesis confirming that AM uniquely enables the complex, non-machinable lattice/auxetic geometries metamaterial design requires	Justifies the AM process selection (DED, MEX, SLA/SLM) adopted in Section 2.3

3.2 Geomechanical comparison: Witwatersrand Basin vs. Peru's principal mining operations vs. developed-country solutions

Table 4

Geomechanical comparison: Witwatersrand Basin, Peru's principal mining operations, and developed-country urban tunnels

Parameter	Witwatersrand Basin (South Africa)	Peru – principal deep/large-scale mining operations (e.g., Antamina, Cerro Verde, Las Bambas, Toromocho, Quellaveco, Constanca)	Developed-country urban tunnels (Japan, Switzerland)
Typical operating depth	Ultra-deep gold mining, approaching 4,000 m	Predominantly large open-pit and moderate-depth underground block-cave operations; site-specific depth varies by deposit	Civil/metro tunnels, generally shallower but under dense urban loading
Dominant seismic driver	Mining-induced seismicity from stress redistribution and micro-fault reactivation [6]	Regional subduction tectonics superimposed on mining-induced ground vibration [5]	Tectonic (Japan) and Alpine-orogenic (Switzerland) sources plus traffic-induced micro-vibration
Documented mitigation approach	Rockburst monitoring networks, destress blasting, energy-absorbing bolts, seismic source characterisation [6]	Conventional shotcrete and rock-bolt support; national seismic design code (E-030) governs surface structures but has no metamaterial-liner provision	Base isolation, periodic pile barriers, tuned-mass and viscous dampers embedded in tunnel design

The comparison indicates a governance gap rather than a technical one: Peru's principal mining projects and its national seismic code already assume conventional support and isolation strategies, but neither currently references architected metamaterial liners, despite the country's seismic-hazard profile [5] and the scale of its underground and open-pit operations.

3.3 Machinery and workforce implementation matrix

Table 5

Machinery and workforce implementation matrix

Implementation stage	Key machinery	Professional profile leading the stage
Design	CAD/FEA workstations (topology optimisation, dispersion analysis)	Structural dynamics specialist
Fabrication	Containerised DED / MEX / SLA printing units	Additive-manufacturing technician
Installation	Robotic telescopic manipulators, multi-boom drilling jumbos, LiDAR/GPR scanning	Robotics/installation operator, under geomechanical supervision
Monitoring	Distributed fibre-optic sensing, accelerometer arrays	Geomechanical/geotechnical engineer

4. Discussion

4.1 Transferability to Peruvian public-space infrastructure

Lima's underground public-space infrastructure — metro stations (e.g., future extensions of Línea 2), pedestrian underpasses, and parking structures built on deformable alluvial or aeolian soils — is exposed to local seismic-wave amplification. Modular metamaterial panels, bolted to primary support in the same manner as conventional pre-cast linings, could be incorporated as a technical annex to the national seismic-resistant building code without requiring a new construction system, since installation follows the sequencing already used for shotcrete and pre-cast panel linings.

4.2 Application to mining projects in Peru

For Peru's principal mining operations, the highest-value application is in access declines, ventilation raises, and haulage tunnels where dynamic vibration from blasting, heavy equipment, and any locally induced seismicity threatens both structural integrity and personnel safety. Implementation would proceed in four phases: (1) geomechanical characterisation and target-frequency definition using existing mine seismic-monitoring networks; (2) design adaptation of the auxetic-resonant unit cell to the site-specific stress regime; (3) containerised on-site fabrication to avoid the logistics penalty of transporting finished panels to remote or high-altitude sites; and (4) robotic installation integrated into the existing ground-support cycle, followed by fibre-optic monitoring. This sequencing mirrors, and is intended to complement rather than replace, the rock-bolt and shotcrete practices already documented for South African deep mines [6] and for mining-induced seismicity management more broadly.

4.3 How developed countries have addressed the same problem

Japan and Switzerland — both operating extensive underground infrastructure under active seismic or high-vibration conditions — rely predominantly on heavy elastomeric base isolation and periodic buried-pile barriers to protect critical underground assets [3]. These solutions are effective but costly and geometrically invasive for tunnels that are already built, which is precisely the gap that a modular, retrofit-compatible, 3D-printed metamaterial panel is intended to close: it targets the same low-frequency band without requiring excavation of a new isolation gap around the structure.

4.4 Limitations and field-scale validation pathway

As a documentary and comparative-analytical study, this manuscript does not report new experimental transmission-loss measurements, and the quantitative claims in Section 3.1 are drawn strictly from the cited sources. The logical next step — outside the scope of the present synthesis — is a field-scale shake-table and in-situ pilot validation of the proposed unit cell in a representative Peruvian tunnel segment, reporting frequency-resolved transmission loss with statistically robust replication (multiple runs, confidence intervals), before any performance claim specific to this design can be made.

5. Conclusions

- The DOI-verified literature confirms that locally resonant and auxetic metamaterial architectures, fabricated by additive manufacturing, are mechanistically capable of attenuating seismic-relevant frequency bands, but published evidence remains concentrated at laboratory or numerical scale [1, 3, 4].
- A field-implementable liner requires an explicit combination of additive-manufacturing machinery (DED/MEX/SLA), underground installation equipment (robotic manipulators, drilling jumbos, LiDAR/GPR), and a trained multidisciplinary workforce; none of these elements is technically exotic for Peru, but none is currently integrated into a single deployment protocol.
- Peru's principal mining operations and its national seismic design code do not yet reference metamaterial liners, revealing a regulatory and procurement gap rather than a materials-availability gap.
- Technology transfer from South Africa's deep-mining seismic experience to Peru is feasible through a phased roadmap (characterisation → design adaptation → on-site fabrication → robotic installation → monitoring), but requires field-scale pilot validation before performance claims can be generalised beyond the literature synthesised here.

Future work should prioritise an instrumented pilot panel in an operating Peruvian tunnel segment (public-space or mining), coupled with a life-cycle comparison against conventional shotcrete and rock-bolt systems.

Declarations

Funding: The author received no specific funding for this work.

Competing interests: The author declares no competing interests.

Author contributions: P.R.P.G. conceived the study, performed the literature synthesis, designed the comparative matrices and figures, and wrote and approved the final manuscript.

Ethics approval and consent to participate: Not applicable. This study is not a clinical trial and does not require clinical-trial registration. This is a documentary and comparative-analytical study; it involved no human participants, animal subjects, or primary field data collection.

Consent for publication: Not applicable.

Data availability: All data generated or analysed during this study are included in this published article. No new empirical datasets were generated; all quantitative evidence is drawn from the DOI-referenced sources cited in the Reference list.


Acknowledgements: None.

References

1. Liu Z, Zhang X, Mao Y, Zhu YY, Yang Z, Chan CT, Sheng P. Locally resonant sonic materials. *Science*. 2000;289(5485):1734–1736. <https://doi.org/10.1126/science.289.5485.1734>
2. Brûlé S, Javelaud EH, Enoch S, Guenneau S. Experiments on seismic metamaterials: molding surface waves. *Physical Review Letters*. 2014;112:133901. <https://doi.org/10.1103/PhysRevLett.112.133901>
3. Miniaci M, Krushynska A, Bosia F, Pugno NM. Large scale mechanical metamaterials as seismic shields. *New Journal of Physics*. 2016;18:083041. <https://doi.org/10.1088/1367-2630/18/8/083041>
4. Askari M, Hutchins DA, Thomas PJ, Astolfi L, Watson RL, Abdi M, Ricci M, Laureti S, Nie L, Freear S, Wildman R, Tuck C, Clarke M, Woods E, Clare AT. Additive manufacturing of metamaterials: a review. *Additive Manufacturing*. 2020;36:101562. <https://doi.org/10.1016/j.addma.2020.101562>
5. Das R, Gonzalez G, de la Llera JC, Saez E, Salazar P, Gonzalez J, Meneses C. A probabilistic seismic hazard assessment of southern Peru and northern Chile. *Engineering Geology*. 2020;271:105585. <https://doi.org/10.1016/j.enggeo.2020.105585>
6. Masethe RT, Manzi MSD, Durrheim RJ. Using legacy 3D seismic data and source parameters of mining-induced earthquakes to mitigate the risk of rockbursting in Kloof Gold Mine, South Africa. *Geophysical Prospecting*. 2023;71(7):1281–1311. <https://doi.org/10.1111/1365-2478.13319>
7. Buswell RA, Soar RC, Gibb AGF, Thorpe A. Freeform construction: mega-scale rapid manufacturing for construction. *Automation in Construction*. 2007;16(2):224–231. <https://doi.org/10.1016/j.autcon.2006.05.002>
8. Craveiro F, Duarte JP, Bartolo H, Bartolo PJ. Additive manufacturing as an enabling technology for digital construction: A perspective on Construction 4.0. *Automation in Construction*. 2019;103:251–267. <https://doi.org/10.1016/j.autcon.2019.03.011>

Figures

Figure 4. Qualitative synthesis of wave-attenuation mechanisms reported in the foundational literature underlying the proposed hybrid resonator-auxetic design.



Source: compiled by the author from the cited studies (Liu et al., 2000; Brûlé et al., 2014; Miniaci et al., 2016; Askari et al., 2020).

Figure 1

Qualitative synthesis of the wave-attenuation mechanisms reported in the foundational literature underlying the proposed hybrid resonator-auxetic design. Source: compiled by the author from the cited studies




Figure 1. Unit-cell architecture and panel cross-section of the proposed chiral-auxetic acoustic metamaterial liner. Source: original design by the author (Paul Ricardo Prudencio Gálvez, 2026).

Figure 2

Unit-cell architecture and panel cross-section of the proposed chiral-auxetic acoustic metamaterial liner.
Source: original design by the author (Paul Ricardo Prudencio Gálvez, 2026)




Figure 2. Manufacturing and installation workflow for 3D-printed acoustic metamaterial tunnel-lining panels. Source: original diagram by the author (Paul Ricardo Prudencio Gálvez, 2026).

Figure 3

Manufacturing and installation workflow for 3D-printed acoustic metamaterial tunnel-lining panels. Source: original diagram by the author (Paul Ricardo Prudencio Gálvez, 2026)




Figure 5. Technology-transfer roadmap adapting South African deep-mining seismic experience to Peruvian public-space and mining infrastructure. Source: original framework by the author (Paul Ricardo Prudencio Gálvez, 2026).

Figure 4

Technology-transfer roadmap adapting South African deep-mining seismic experience to Peruvian public-space and mining infrastructure. Source: original framework by the author (Paul Ricardo Prudencio Gálvez, 2026)