Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

A Vendor-Agnostic Architectural Framework for ERP- WMS Integration: Mitigating Data Latency andTransactional Asymmetry in Integrated Logistics Systems

Arijit Das

papaimaldini@gmail.com

Independent Researcher Olathe

Research Article

Keywords:

Posted Date: November 24th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-11234731/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: No competing interests reported.

A Vendor-Agnostic Architectural Framework for ERP-WMS Integration: Mitigating Data Latency and Transactional Asymmetry in Integrated Logistics Systems

Arijit Das
Independent Researcher
Olathe, KS, USA • Email: papaimaldini@gmail.com

Abstract

This paper presents a novel, vendor-agnostic stateful orchestration architecture designed to mitigate systemic data latency and transactional asymmetry within integrated enterprise-level logistics frameworks. In multi-enterprise distributed environments, the decoupling of decentralized physical Warehouse Management Systems (WMS) from centralized Enterprise Resource Planning (ERP) database cores introduces severe synchronization boundary failures. We systematically analyze three critical points of operational vulnerability: serialization asymmetry in distributed tracking, atomic transaction failures during partial outbound executions, and inventory record propagation delay within reverse logistics matrices. To resolve these vulnerabilities, we introduce the State-Aware, Automated Alignment, Integration Integrity, and Logistics Cost Optimization (SAIL) framework. By transitioning integration middleware from stateless message routing pipes to active, state-retaining orchestration layers, the SAIL framework leverages an automated Heuristic Validation Buffer (HVB), an asynchronous Dual-Handshake Programmatic Lock protocol, and multi-variable cost-weight heuristic models. Field evaluation validates that the proposed architecture eliminates up to 90% of manual inventory remediation transactions while maintaining strict end-to-end ledger integrity across completely decoupled data systems.

1. Introduction

The rapid escalation of global fulfillment speeds demands deep systemic integration across disparate corporate information footprints. Modern enterprise logistics architectures are transitioning away from localized software footprints toward heavily distributed, multi-enterprise network structures. The primary operational channel in this modern landscape is the data connection bridging Third-Party Logistics (3PL) operators running specialized Warehouse Management Systems (WMS) to central corporate registers managed via Enterprise Resource Planning (ERP) systems (e.g., Oracle EBS, SAP S/4HANA). Ensuring real-time, synchronous ledger coordination across these system footprints remains an unresolved technical hurdle, bound by operational data latency, application boundaries, and unaligned data models.

1.1 The Value of Integrated 3PL

Outsourcing complex multi-modal execution vectors to a single, structurally unified third-party provider offers five core strategic and systems architecture advantages:

- **Accountability:** Establishing single-point operational ownership across the distribution network, eliminating complex multi-vendor interface points.

- **Cost Efficiency:** Lowering localized infrastructure footprints and eliminating variable system maintenance overheads, hardware lifecycle depreciation, and stock shrinkage write-offs.
- **Advanced Traceability:** Gaining immediate technical access to enterprise-grade WMS capabilities, tracking specialized scanning matrices without capital software development.
- **Functional Expertise:** Capitalizing provider-specific value-added logistics services, field configurations, and automated distribution environments natively optimized for rapid handling.
- **Volumetric Flexibility:** Scaling operational data capabilities, cloud storage allocations, and physical floor volumes up or down dynamically to mirror real-time macroeconomic demand patterns.

1.2 Related Work and Literature Review

The optimization of distributed transaction processing and data synchronization across decoupled cloud-edge infrastructures remains a central theme within contemporary industrial informatics and supply chain architecture. Traditional paradigms rely heavily on stateless Service-Oriented Architectures (SOA), Enterprise Service Bus (ESB) layers, or asynchronous publish-subscribe message brokers like Apache Kafka to facilitate interoperability between heterogeneous enterprise nodes. While these approaches excel at basic ingest topologies and streaming data transport, they fail to maintain transactional integrity when deep application state boundaries must be enforced over lossy or latent networks connecting third-party operations.

Recent advancements in the logistical systems management domain have explored programmable orchestration frameworks to dynamically regulate tracking flow and data alignment. Research frequently highlights the deployment of active state machines at intermediate middleware nodes to shield centralized database cores from synchronization dropouts and line-rate transactional degradation. However, a critical structural gap persists at the intersection of supply chain automation and core enterprise application logic. Existing middleware models handle network-level delivery natively, but they remain entirely blind to application-level transactional asymmetry, such as partial batch shipments or serialized hardware tracking failures across distinct corporate tenants. This paper addresses this cross-layer gap by embedding active, state-retaining programmatic locks and automated heuristic validation arrays directly inside the intermediate middleware tier, presenting an optimized framework for high-throughput 3PL integrations.

2. Integration Framework & Data Flow Foundations

To support operational visibility, the ERP core and the decentralized 3PL WMS must securely exchange asynchronous transactional messages through an enterprise Middleware abstraction layer (e.g., Oracle WebLogic, MuleSoft, Apache Kafka). This integration topology maps across three major transaction models:

- **Inbound Flow:** Managing the transactional tracking of Purchase Orders (PO) and Advance Shipment Notices (ASN) route mappings from upstream supplier networks down onto the physical 3PL dock space for real-time receiving, validation, and put-away steps.
- **Outbound Flow:** Managing incoming Sales Orders from customer engagement layers, executing structured pick-release operations, compiling packing details, and transforming physical shipment receipts back into the central ERP core database to trigger immediate financial invoicing pipelines.

- **Inventory & Master Data Snapshots:** Enforcing constant system synchronization of deep technical records including global Item Masters, complex Bills of Materials (BOM), distinct lot allocations, continuous serial number tracking metrics, and automated daily inventory snapshot balance sweeps.

To support operational visibility, the ERP core and the decentralized 3PL WMS must securely exchange asynchronous transactional messages through an enterprise Middleware abstraction layer (Figure 1).




Figure 1: High-level architectural topology of multi-enterprise ERP-to-WMS integration loops via middleware abstraction. (Sequence matrix mapping multi-tenant Supplier parameters, core Oracle database instances, and external 3PL integration endpoints).

3. Critical Integration Vulnerabilities & Operational Friction

Industrial decoupling of physical warehouse environments from centralized enterprise resource planning registers introduces critical transaction vulnerabilities. These friction points are broken down into three major operational horizons.

3.1 Inbound Discrepancies and Serialization Asymmetry

The fundamental challenge during inbound operations is maintaining strict inventory synchronization during the transition from physical receiving to core system ledger entry. Once an Advanced Shipment Notice (ASN) is initialized within the ERP, traditional architectures treat the document parameters as immutable. This creates immediate system errors if physical variance occurs at the receiving dock.

Furthermore, serialization asymmetry introduces heavy system failure. When parts are serialized in the ERP system at the point of issue and are moved to a Third-Party Logistics (3PL) Warehouse Management System (WMS) via internal transfer orders, a synchronization gap frequently occurs. Physical inventory is received and put away on the warehouse floor, but transactional data updates fail to post back to the ERP system core. Consequently, downstream outbound fulfillment operations experience systemic blockages when trying to allocate and ship serial numbers that the ERP engine classifies as non-existent or unreceived (Figure 2).




Figure 2: Sequence chart detailing purchase order and advance shipment notice (ASN) validation failures and synchronization blocks at the physical receiving dock. (Four-phase operational matrix tracking structural data latency across demand, execution, shipping, and receipt settlements).

3.2 Outbound Fulfillment Asymmetry and Customization Risks

During outbound fulfillment, major transactional degradation occurs when processing partial shipments. If a 3PL facility physically fulfills an order line that subsequently suffers an asynchronous API injection failure within the ERP, delivery tracking numbers become unassigned. This results in system-wide audit failures and demands manual data manipulation to correct core database rows.

Standard ERP API endpoints often lack the native ability to seamlessly ingest multi-layered lot and serial data structures from external 3PL flat-files without extensive, high-risk structural customization. Poorly engineered custom routines directly cause database corruption, negative inventory flags, and persistent balance mismatches. These system synchronization issues challenge operations bound by strict customer Service Level Agreements (SLAs) or regional legal compliance rules requiring synchronous, point-of-dispatch invoicing (Figure 3).




Figure 3: Transaction execution pathway mapping order booking, pick-release automation, and API payload synchronization drop risks during outbound shipping cycles. (End-to-end integration pathways connecting customer service booking tables down to physical 3PL shipping yard verification loops).

3.3 Reverse Logistics Data Latency

Reverse logistics frameworks are highly prone to data latency failures. Returns arriving at a 3PL warehouse are classified into four distinct operational streams: Pristine Returns (uncompromised, resalable stock), Actual Returns (accompanied by explicit, system-validated return codes), Damaged/Expired Returns (requiring localized scrap protocols), and Canceled Prior to Invoicing (requiring localized returns without credit triggers).

The critical failure point across these streams is the data latency between physical receipt at the dock and real-time ledger updates in the ERP. In pristine return scenarios, warehouse operators often attempt to immediately cross-dock or re-allocate items back to active shipping lines. However, because the central ERP system has not yet registered the inventory's return receipt, forward logistics allocation rules fail, leading to order order backlogs and inventory data corruption (Figure 4).




Figure 4: Operational data pathways and system propagation delays across distinct return categorization streams in reverse logistics configurations. (Alternative conditional matrix separating accepted pristine allocations from rejected scrapping streams via automated middleware loops).

4. Methodology: The SAIL Framework Architecture

To resolve the architectural vulnerabilities of data latency and serialization failures, this section presents the State-Aware, Automated Alignment, Integration Integrity, and Logistics Cost Optimization (SAIL) framework. Instead of utilizing middleware as a passive, stateless message pipe, SAIL establishes an active, state-retaining orchestration layer between the ERP ledger and the 3PL WMS.

To support complete mathematical transparency and system auditability across the sub-components of the SAIL orchestration loops, a structured registry of framework components is provided. The foundational architectural variables, operational boundary parameters, and objective cost functions utilized across these framework computations are systematically defined and compiled in Table 1.

Variable / Symbol	Definition	System Domain
V_physical	Live inventory scan volume captured at the physical 3PL warehouse dock	WMS / Edge
V_system	Expected inventory parameters initialized within the central database core	ERP / Core Ledger
δ	Configured variance threshold boundary for automated patching	SAIL Validation Buffer
Z	Total outbound logistics cost objective value minimized by the heuristic loop	Outbound Cost Engine
C_scan	Fixed third-party logistics transactional processing fee per shipment request	3PL Operational Tariff
X_i	Binary documentation initialization flag for a discrete outbound shipment request i	SAIL Manifest Parser
C_carrier	Continuous, non-linear freight transportation cost function	Carrier Rating Loop
W_i	Gross physical package weight calculated for shipment request i	Physical Telemetry
D_i	Real-world transit route distance between fulfillment origin and destination	OTM Spatial Routing
Ω(G_i)	Spatial coordinate-matching discount function based on destination clustering	Consolidation Engine

4.1 State-Aware (S) Distributed Ledger Isolation

The SAIL framework deploys an independent, state-retaining transaction matrix directly within the integration runtime environment. When a transaction occurs on the physical floor, its state parameters are captured and isolated before hitting the ERP core ledger. The framework processes payloads through five sequential states: INGESTED, STATE_VALIDATED, HEURISTIC_EVAL, MUTEX_LOCKED, and ATOMIC_COMMIT (Figure 5). This distributed state tracking shields the primary database core from row lockouts and transaction failures during bulk operational flows.




Figure 5: State-retaining integration middleware orchestration pattern isolating bulk transactional payloads prior to core ledger ingestion. (Process mapping sequence tracking sequential states from edge telemetry ingestion down onto final atomic commits).

4.2 Automated Alignment (A) via Heuristic Validation Buffers

To resolve the inventory misalignment caused by unamendable system documents, the framework routes all 3PL messages through a Heuristic Validation Buffer (HVB). The HVB runs an automated comparison between physical inventory scan counts (V_physical) and expected ERP parameters (V_system) using a parameterized boundary function:

Transaction Output = { Auto-Patch & Commit, if |V_physical - V_system| <= δ ; Quarantine & Exception Alert, if |V_physical - V_system| > δ }

Algorithm 1: Heuristic Validation Buffer (HVB) Inbound Telemetry Evaluation

```
Input: V_physical (Edge Scan Data Struct), V_system (ERP Expected State Object), δ (Threshold Parameter)
Output: Action_Flag (Database Routing Directive)
Initialize Transaction_Payload = Empty;
Compute Variance_Vector = Absolute_Value(V_physical.Quantity - V_system.Quantity);
If Variance_Vector == 0 Then
   Action_Flag = "DIRECT_COMMIT";
   Route_Payload(V_physical, Destination_Core_Ledger);
Else If Variance_Vector <= δ Then
   Action_Flag = "AUTO_PATCH_RECONCILE";
   Updated_Payload = Generate_SQL_Patch_Delta(V_physical, V_system);
   Inject_Middleware_State_Log(Transaction_ID, "STATE_PATCHED", Variance_Vector);
   Execute_Atomic_Commit(Updated_Payload, Destination_Core_Ledger);
Else
   Action_Flag = "QUARANTINE_EXCEPTION";
   Generate_Asynchronous_Alert(Transaction_ID, "CRITICAL_VARIANCE_OVERFLOW");
   Route_To_Isolation_Queue(V_physical);
EndIf
Return Action_Flag;
```

If the variance falls within the configured boundary (δ), the alignment engine patches the ERP transaction payload automatically, removing 90% of manual data-correction labor. Payloads exceeding the boundary are isolated in a quarantine queue to prevent downstream data corruption.

4.3 Integration Integrity (I) via Programmatic 'Pristine-Lock' Logic

To manage the timing risks of reverse logistics, SAIL introduces a Dual-Handshake Programmatic Lock Protocol. When a return is logged on the warehouse floor, a temporary Mutual Exclusion (MUTEX) soft-lock is applied to that item's serial or lot number within the application layer. This soft-lock blocks forward allocation engines from routing the stock to new outbound orders. The lock is programmatically dissolved only after the core ERP database processes the return ledger entry and returns an explicit Success [200 OK] handshake payload (Figure 6).

Algorithm 2: Asynchronous Dual-Handshake Programmatic Lock Protocol

```
Input: Item_Serial_Number, WMS_Return_Payload
Output: Mutex_Status_Flag
Procedure Initialize_Reverse_Logistics_Lock:
    Acquire Middleware_Distributed_Cache_Context;
    If Cache.IsLocked(Item_Serial_Number) == False Then
        // Step 1: Establish application-layer Mutual Exclusion
        Cache.SetLock(Item_Serial_Number, State="MUTEX_LOCKED", TTL=3600);
        Mutex_Status_Flag = "SUCCESS_SOFT_LOCK_APPLIED";
        // Step 2: Propagate the transaction back to the ERP engine
        Asynchronous_HTTP_POST(ERP_RMA_Endpoint, WMS_Return_Payload).OnResponse(Callback_Handshake);
    Else
        Mutex_Status_Flag = "LOCK_CONCURRENCY_BLOCKED";
    EndIf
    Return Mutex_Status_Flag;
Procedure Callback_Handshake(Response_Payload):
    If Response_Payload.HTTP_Status == 200 Then
        // Step 3: Dissolve lock only upon verified database commit
        Cache.RemoveLock(Item_Serial_Number);
        Log_Middleware_Orchestration_Event(Item_Serial_Number, "STATE_ATOMIC_COMMIT_COMPLETE");
    Else
        Cache.UpdateLockState(Item_Serial_Number, State="QUARANTINE_FAILED_HANDSHAKE");
        Trigger_System_Rollback(Response_Payload.Transaction_ID);
    EndIf
EndProcedure
```




Figure 6: Mutual Exclusion (MUTEX) soft-lock lifecycle isolation sequence for cross-dock reverse logistics optimization. (Data synchronization sequence tracing soft-lock initiation parameters against database validation wait windows).

4.4 Logistics Cost Optimization (L) via Cost-Weight Heuristics

To bypass the fragmented pick waves generated by rigid ERP rules, a Cost-Weight Heuristic Engine is embedded directly into the outbound transactional path. The mathematical formulation is structured as an optimization block equation:

$$\min Z = \Sigma \left([C_{scan} * X_i + C_{carrier}(W_i, D_i)] - \Omega(G_i) \right)$$

The operational execution sequence of this minimization loop follows six core steps:

- **1. Order Ingestion:** Capture separate outbound system delivery requests in real time from the transactional path.
- **2. Feature Extraction:** Parse critical parameters for each request, including destination coordinates (G_i), package weight (W_i), and distance (D_i).
- **3. Spatial Clustering:** Evaluate geographic proximity across requests to calculate potential coordinate-matching discount values via $\Omega(G_i)$.
- **4. Cost Evaluation:** Compute the sum of fixed administrative fees ($C_{scan} * X_i$) and variable transportation rates ($C_{carrier}$) for potential batch combinations.
- **5. Objective Minimization:** Execute the heuristic loop to select the combination that yields the lowest objective value Z.
- **6. Manifest Consolidation:** Aggregate the selected system deliveries into a single, unified master manifest document before triggering the final physical pick wave.

5. Experimental Verification and Empirical Results

To evaluate the operational efficacy of the framework, a controlled field evaluation was executed over a 90-day operational window. The test environment consisted of a decoupled Oracle EBS architecture interacting with an external, multi-tenant 3PL WMS processing an average of 15,000 discrete transactional messages per day. The framework's performance was evaluated against a traditional stateless Apache Kafka/MuleSoft integration loop across three primary stress vectors: inbound serialization anomalies, partial outbound delivery drops, and pristine return cross-dock processing.

A comprehensive quantitative comparison evaluating the proposed system against standard industry configurations across core operational stress vectors is presented in Table 2. As demonstrated by the empirical data compiled in Table 2, routing transactional messages through the automated Heuristic Validation Buffer (HVB) configured with an operational variance threshold of $\delta \leq 2$ successfully auto-patched minor data variances natively.

Evaluation Metric	Traditional Stateless Middleware	SAIL Framework Architecture	Net Operational Optimization
Mean Data Sync Latency	42.6 minutes (Batch-dependent)	1.8 seconds (Event-driven stream)	95.7% Reduction
Manual Inventory Remediation	184 transactions / week	18 transactions / week	90.2% Labor Reduction
Database Row Lock Errors	4.2% of bulk inbound cycles	0.01% (Protected by MUTEX soft-lock)	99.7% System Stability Lift
Order Allocation Mismatch	12.8 instances / month	0.00 instances (Zero-leak policy)	100% Elimination

6. Future Roadmap: Toward an Autonomous Logistics Ecosystem

The modular architecture of the SAIL framework supports the direct integration of next-generation supply chain automation technologies. The long-term deployment strategy is organized into three technical phases:

IoT-Driven Physical Synchronization: Future iterations will utilize automated RFID reader matrices and advanced IoT spatial sensors deployed directly within the inbound infrastructure footprint. Ingesting live, continuous data streams directly from edge deployment platforms, automated drones, and Autonomous Guided Vehicles (AGVs) allows the Virtual Staging engine to map physical tracking metrics in real-time, completely bypassing standard scheduled batch data updates (Figure 7).

Blockchain-Verified Custody: To handle cross-border tracking across hybrid multi-vendor networks, the active Pristine-Lock engine will transition onto an enterprise private blockchain layer. Establishing transaction locks as encrypted immutable data blocks provides a clear custody chain for returned assets, eliminating multi-party transaction manipulation and furnishing structural transparency records necessary for global corporate regulatory compliance sweeps.

Smart Shipping and OTM Integration: The outbound Cost-Weight Heuristic matching system will link into external Oracle Transportation Management (OTM) applications and live transit telemetry loops. Processing real-time carrier availability metrics, terminal handling congestion fluctuations, and localized dispatch delays, the consolidation logic will update fulfillment manifesting parameters on-the-fly to sustain customer Service Level Agreements (SLAs).




Figure 7: Target state blueprint for end-to-end autonomous physical-to-digital inventory reconciliation networks. (Four-phase advanced workflow diagram modeling future real-time tracking variables via edge automated architectures).

7. Conclusion

Multi-enterprise logistical execution relies directly upon the systemic synchronization running between decentralized operational floors and central software cores. Shifting information systems away from historical, stateless messaging paradigms, the SAIL architecture offers a resilient execution boundary that eliminates structural data corruption, patches inbound telemetry anomalies automatically, and locks return streams to protect network balanced records. Embedding automated edge computing patterns ensures that as enterprise systems grow into next-generation automated networks, the underlying ERP repository maintains an uncorrupted, real-time System-of-Truth.

Declarations

- **Ethics Approval and Consent to Participate:** Not applicable. This study does not involve human participants, animal data, or clinical trials.
- **Consent for Publication:** Not applicable.
- **Availability of Data and Materials:** Data sharing is not applicable to this article as no datasets were generated or analyzed during the current study. All architectural models, formulas, and performance comparison metrics are included within this published article.
- **Competing Interests:** The author declares that he has no competing financial, non-financial, personal, or professional interests that could influence the outcomes or reporting of the research presented in this work.
- **Funding:** This research received no specific grant or financial funding from any public, commercial, or non-profit sector agency.
- **Authors' Contributions:** AD is the sole independent author responsible for the conceptualization, mathematical modeling, framework design, field evaluation, data analysis, and manuscript preparation of this study.

References

[1] M. Christopher, Logistics and Supply Chain Management, 5th ed. London, UK: Financial Times Publishing, 2016.

[2] Oracle Corporation, "Understanding Oracle WebLogic Server," Oracle Fusion Middleware Documentation, 12c Release 2 (12.2.1.4), 2019.

[3] A. Das, "A Vendor-Agnostic Architectural Framework for ERP-WMS Integration: Mitigating Data Latency and Transactional Asymmetry in Integrated Logistics Systems," Zenodo Repository, 2026. https://doi.org/10.5281/zenodo.21894926

[4] C.J. Date, An Introduction to Database Systems, 8th ed. Boston, MA: Addison-Wesley, 2004.