

QUOTATION**MARCON INTERNATIONAL (USA) INC**

3505 Lake Lynda Drive

Bldg 300, Suite 200

Orlando, FL 32817 U.S.A.

www.marconintl.com

TEL: 1(800)367-9097 FAX: 1(800)367-9153

TO: Department of Energy**TEL: 412-386-4675****EMAIL: stumpf@netl.doe.gov****ATTN: Lora Stumpf**

DATE	August 12, 2020
SOLICITATION#	89243320QFE000196
QUOTE#	0040-20-1322
NO. OF PAGES	2

CLOSING DATE

August 12, 2020

VALIDITY

September 11, 2020

DELIVERY (EXWORKS)

21-23 weeks

PAYMENT TERMS

NET 30 DAYS

ITEM	DESCRIPTION	QTY	UNIT PRICE	EXTENSION
1	Assembly consisting of Type LTR 43-2 (Body with 2 pc. Removable Seat, Disc with 2 pc. Removable Seat); NPS 4; ANSI Class 300; Body Material A351 CF8M ; Body Type: Lugged; Flanges Raised Face (RF) acc ASME B16.5; Blowout Prevention and Flange Sealing Area acc. API 609; Disc Material A351 CF8M; Shaft/Bearing: Nitronic50 (XM-19) /Stellite 6; Seat Ring/Seat: 316L / 316L -Graphite [Lam.]; Packing: Graphite; Seals (Gaskets) Graphite; With 20" (500mm) Extension; Shaft Connection: DR450 F12 SW27; Bracket/Coupling: Standard (for amb. temp. -4°F to 194°F / -20°C to 90°C) L-2-LA04P030-RXE0_SS91AA Mounting Bracket Air Torque double acting pneumatic rotary actuator type PT450; PT450-DA F10/12 DS27 Type 3730 Electropneumatic Positioner Type 3730-3 with LCD and AUTOTUNE, 4 to 20 mA reference variable, HART communication, 2 software limit switches/1 fault alarm contact; Intrinsically safe /non incendive FM/CSA; EXPERTplus diagnostics; Hardware version device index	1 EA	\$10,450.00	\$10,450.00

04; Software version 1.61 Var-ID: 5681596

Adapter M 20 x 1.5 to NPT 1/2, blue with cable grip
1400-7112

Mounting unit for Type 3730

Consisting of:; Mounting parts for attachment to rotary
actuators acc. to VDI/VDE 3845 (09-2010), level 1,
size AA1 to AA4, (1400-9244), heavy-duty version;
Piping completely of stainless steel, standard screw
fittings

Var-ID: 4265164

Type 4708 Supply Pressure Regulator

Type 4708-54 Supply Pressure Regulator, for
mounting to Types 373x/376x/378x Positioners (rotary
actuators);

Connection thread 1/4-18 NPT; Set point range
0.5...6.0 bar,

with pressure gauge (connection nickel-plated brass);

With 2 pressure gauges; Aluminum connecting part;

Filter in black plastic regulator body

Var-ID: 1620715

Mounting unit for Type 4708

For Type 4708-54; Attached to a positioner

Var-ID: 1601440

Type 3710 Reversing Amplifier

Aluminum housing; Connecting thread 1/4-18 NPT

Ready for pressure gauge attachment; Degree of
protection: IP 65, polyamide filter check valve

Var-ID: 2501466

Mounting unit for Type 3710 Reversing Amplifier

Attachment to Type 3730, 3731 Positioners

on all actuators or Type 3766, 3767 to Type 3275

Actuator; One pressure gauge

(1x 1402-1338); Piping completely of stainless steel,
standard screw fittings

Var-ID: 5541238

As per attached specifications.

FED ID# 33-1014848 D & B# 103466558 CAGE CODE# 47UA9 ORCA REGISTERED

MANUFACTURER:
TOTAL WEIGHT; LB

Samson Leusch

TBA

\$10,450.00

APPROVED BY

INCOTERMS

PRICES IN US\$


GUS KHREICH

FOB DESTN

\$10,450.00