Progression of the faecal microbiome in preweaning dairy calves that develop cryptosporidiosis

Harris et al.

Wellcome Sanger Institute Scientific Writing Initiative, on behalf of all authors in the study

Making Sequence Processing and Diversity Data

```
# Load required libraries
library(dada2); packageVersion("dada2")
# Set path to the directory containing the demultiplexed fastq files
path <- "/lustre/scratch124/tol/projects/cryptocalf/analysis/dada2_input"
list.files(path)
# Forward and reverse fastq filenames have format: SAMPLENAME_R1_001.fastq and SAMPLENAME_R2_001.fastq
fnFs <- sort(list.files(path, pattern="_R1_001.fastq", full.names = TRUE))
fnRs <- sort(list.files(path, pattern="_R2_001.fastq", full.names = TRUE))
# Extract sample names, assuming filenames have format: SAMPLENAME_XXX.fastq
sample.names <- sapply(strsplit(basename(fnFs), "_"), `[`, 1)
# Place filtered files in filtered/ subdirectory
filtFs <- file.path(path, "filtered", paste0(sample.names, "_F_filt.fastq.gz"))
filtRs <- file.path(path, "filtered", paste0(sample.names, "_R_filt.fastq.gz"))
names(filtFs) <- sample.names
names(filtRs) <- sample.names
# Quality profiles of forward reads
plotQualityProfile(fnFs[1:2])
# Quality profiles of reverse reads
plotQualityProfile(fnRs[1:2])
# Filter and trim
out <- filterAndTrim(fnFs, filtFs, fnRs, filtRs, truncLen=c(240,160),
              maxN=0, maxEE=c(2,2), truncQ=2, rm.phix=TRUE,
              compress=TRUE, multithread=TRUE)
head(out)
# Learn error rates
errF <- learnErrors(filtFs, multithread=TRUE)
errR <- learnErrors(filtRs, multithread=TRUE)
# Plot error rates
plotErrors(errF, nominalQ=TRUE)
# Dereplicate
derepFs <- derepFastq(filtFs, verbose=TRUE)
derepRs <- derepFastq(filtRs, verbose=TRUE)
# Name the derep-class objects by the sample names
names(derepFs) <- sample.names
names(derepRs) <- sample.names
# Sample inference
dadaFs <- dada(derepFs, err=errF, multithread=TRUE)
dadaRs <- dada(derepRs, err=errR, multithread=TRUE)
# Inspect
dadaFs[[1]]
# Merge paired reads
mergers <- mergePairs(dadaFs, derepFs, dadaRs, derepRs, verbose=TRUE)
# Inspect
head(mergers[[1]])
# Construct sequence table
seqtab <- makeSequenceTable(mergers)
dim(seqtab)
# Inspect distribution of sequence lengths
table(nchar(getSequences(seqtab)))
# Remove chimeras
seqtab.nochim <- removeBimeraDenovo(seqtab, method="consensus", multithread=TRUE, verbose=TRUE)
dim(seqtab.nochim)
sum(seqtab.nochim)/sum(seqtab)
# Track reads through the pipeline
getN <- function(x) sum(getUniques(x))
track <- cbind(out, sapply(dadaFs, getN), sapply(dadaRs, getN), sapply(mergers, getN), rowSums(seqtab.nochim))
# If processing a single sample, remove the sapply calls: e.g. replace sapply(dadaFs, getN) with getN(dadaFs)
colnames(track) <- c("input", "filtered", "denoisedF", "denoisedR", "merged", "nonchim")
rownames(track) <- sample.names
head(track)
# Assign taxonomy
taxa <- assignTaxonomy(seqtab.nochim, "/lustre/scratch124/tol/projects/cryptocalf/analysis/dada2_input/silva_nr99_v138.1_train_set.fa.gz", multithread=TRUE)
taxa.print <- taxa # Removing sequence rownames for display only
rownames(taxa.print) <- NULL
head(taxa.print)
# Write to disk
saveRDS(seqtab.nochim, "/lustre/scratch124/tol/projects/cryptocalf/analysis/dada2_input/seqtab_final.rds")
saveRDS(taxa, "/lustre/scratch124/tol/projects/cryptocalf/analysis/dada2_input/taxa_final.rds")
```

R Alpha and Beta Diversity Figures

```
library(phyloseq)
library(ggplot2)
library(vegan)
library(dplyr)
library(scales)
library(grid)
library(reshape2)
library(patchwork)
library(ggpubr)
library(rstatix)
library(ggrepel)
library(ggforce)
library(ggh4x)
library(ggtext)
library(ggnewscale)
library(ggpattern
```