

		Sample 1		Sample 2		Sample 3	
		M	SD	M	SD	M	SD
Cluster 1	<i>Adjustment Coefficient</i>	-0.78	0.001	-0.81	0.001	-0.78	0.001
	<i>Distance to Attractor</i>	1.88	0.4	2.18	0.4	2.05	0.3
	<i>Valence at Attractor</i>	-0.03	1.0	-0.02	1.0	-0.03	1.0
	Kernel Density at Attractor	-0.62	0	-0.74	0	-0.67	0
	“Perceived Pathology” at Attractor	-0.04	1.0	-0.02	1.0	-0.02	0.9
Cluster 2	<i>Adjustment Coefficient</i>	-0.16	0.4	-0.2	0.4	-0.18	0.4
	<i>Distance to Attractor</i>	-0.1	0.2	-0.42	0.1	-0.42	0.2
	<i>Valence at Attractor</i>	0.16	0.9	0.54	0.5	0.60	0.5
	Kernel Density at Attractor	0.08	1.0	-0.03	0.9	0.02	1.0
	“Perceived Pathology” at Attractor	-0.04	1.0	-0.18	0.9	-0.08	1.0
Cluster 3	<i>Adjustment Coefficient</i>	-0.24	0.5	-0.17	0.5	-0.21	0.4
	<i>Distance to Attractor</i>	-0.07	0.4	-0.42	0.2	-0.41	0.2
	<i>Valence at Attractor</i>	-0.16	1.0	-1.15	0.7	-0.93	0.7
	Kernel Density at Attractor	-0.08	0.9	-0.02	0.8	0.03	1.0
	“Perceived Pathology” at Attractor	0.004	0.9	0.42	1.0	0.02	1.0
Cluster 4	<i>Adjustment Coefficient</i>	2.1	0.5	2.0	0.6	2.1	0.6
	<i>Distance to Attractor</i>	-0.03	0.004	-0.46	0.02	-0.40	0.2
	<i>Valence at Attractor</i>	-0.30	0.9	-0.25	0.9	-0.29	0.9
	Kernel Density at Attractor	0.71	1.0	0.76	1.0	0.70	0.9
	“Perceived Pathology” at Attractor	0.10	0.9	0.11	1.0	0.15	1.0

1 Table 2: Standardized Cluster Values. Following standardization, variables in *italics* were used to conduct
2 unsupervised clustering. Displayed above are the means and standard deviations for each variable and
3 each cluster. Clustering was conducted independently in each sample.