Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

Satellite imagery curation and preprocessing approaches for urban semantic segmentation supporting smart cities Applications in Ethiopia

Tariku Fetene[1]

tariku.fetene@aastustudent.edu.et

Addis Ababa Science and Technology University

Million Meshesha[2]

Addis Ababa University

Hussein Seid[3]

Addis Ababa Science and Technology University

Research Article

Keywords: Urban Analysis, Satellite imagery, Semantic Segmentation, Data Curation, Pre-processing, Smart cities, Ethiopia, Deep Learning

Posted Date: February 27th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-8845930/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: No competing interests reported.

Abstract

Smart city development needs a smart strategies and techniques to successfully implementing it. Extracting detailed urban insights supports for urban planners for their effective development. Since satellite imagery is very rich in content and can cover large surface of the urban we are benefited to apply image analysis techniques such as Semantic segmentation of satellite imagery as a critical tool for extracting detailed urban insights to support smart city development. In Ethiopia, rapid urbanization and unique urban challenges, such as densely packed informal settlements, variable environmental conditions, and limited data availability, demand specialized approaches to curate and pre-process satellite imagery for accurate segmentation of urban features like buildings, roads, green spaces, and other urban features of the cities. This article presents a comprehensive methodology for collecting diverse satellite imagery with varying resolutions, environmental conditions, and object types, coupled with a state-of-the-art pre-processing techniques designed for urban semantic segmentation. The results demonstrate significant improvements in segmentation performance, supporting applications in urban planning, mobility, environmental management, and disaster resilience. This work provides a scalable framework for geospatial analysis in Ethiopia, contributing to sustainable smart city development in resource-constrained settings.

1. Introduction

Ethiopia is undergoing rapid urbanization, with cities like Addis Ababa experiencing population growth rates of over 3.8% annually [1]. This urban expansion has led to challenges such as informal settlements, traffic congestion, inadequate infrastructure, and vulnerability to environmental hazards like flooding [2]. Semantic segmentation of satellite imagery, which involves classifying each pixel into categories such as buildings, roads, vegetation, or water bodies, offers a powerful approach to generate actionable insights for smart city applications, including urban planning, traffic optimization, environmental monitoring, and disaster preparedness [3]. However, the effectiveness of segmentation models relies heavily on the quality, diversity, and pre-processing of input imagery.

Ethiopian urban environments present unique obstacles for satellite imagery analysis. Compact building clusters, informal settlements, and narrow road networks complicate feature extraction, while frequent cloud cover (up to 60% in the summer-wet season in Ethiopia) and seasonal variations introduce noise and occlusions [4]. Additionally, the scarcity of labelled datasets specific to Ethiopian cities limits the training of robust segmentation models [5]. These challenges necessitate tailored strategies for curating diverse satellite imagery and developing a pre-processing pipeline to ensure high-quality inputs for semantic segmentation.

This article addresses two primary objectives: (1) curating a diverse dataset of satellite imagery capturing varied resolutions (0.1–30 m/pixel), environmental conditions (cloudy, clear, wet/dry seasons), and urban features (buildings, roads, green spaces, other urban features), and (2) designing a state-of-the-art pre-processing mechanisms to prepare these images for semantic segmentation. By focusing on

Ethiopia, particularly Addis Ababa, we tackle context-specific challenges, leveraging open-source datasets and advanced techniques. The resulting dataset and techniques aim to support smart city applications, contributing to sustainable urban development in resource-constrained regions. This work aligns with global efforts to harness geospatial data for urban analytics and offers a replicable framework for other developing nations [6].

Statement of Problem

Rapid urbanization in Ethiopia cities like Addis Ababa causes uncontrolled extension [45], converting agricultural and green lands to built-up areas, straining infrastructure, increasing environmental degradation, and hindering smart city goals without timely data. Traditional manual mapping via field surveys or aerial photos is costly, slow and outdated, failing to capture dynamic changes needed for planning [40]. Semantic segmentation with different deep learning models addresses this by automating pixel-level classification of satellite imagery into urban classes such as roads, buildings, vegetation, bare soil and other, but challenges persists in handling class imbalance, fine-grained features such as informal settlements and limited labelled data in developing regions, limiting accuracy for actionable insights[3][38].

2. Literature Review

Background

Curating satellite imagery involves selecting, organizing, and validating high-quality datasets for urban semantic segmentation tasks, ensuring relevance for smart city applications. This process filters out low-quality images affected by issues like cloud cover or poor georeferencing and ensures datasets, such as Sentinel-2 or PlanetScope, capture diverse urban features like buildings, roads, and green spaces [12]. Curation is critical for providing accurate annotations and balancing datasets to mitigate biases, enabling models to generalize across varied urban environments [36]. For instance, curating multi-temporal datasets supports change detection in urban areas, essential for monitoring urban expansion [37]. This ensures reliable and consistent data, reducing segmentation errors and enhancing model performance.

Pre-processing transforms raw satellite imagery to optimize it for segmentation algorithms by addressing noise, illumination variations, and geometric distortions. Techniques like Contrast Limited Adaptive Histogram Equalization (CLAHE) enhance local contrast to highlight urban features, such as building edges, while normalization standardizes spectral band values for multispectral imagery [38]. Pre-processing also includes orthorectification to correct geometric distortions and noise reduction through filtering methods, ensuring clear and standardized inputs [39]. These steps are vital for improving the accuracy of segmentation models, such as U-Net and DeepLab, by providing high-quality data that enhances feature detection and model robustness in complex urban scenes.

Curating and pre-processing satellite imagery enable precise urban semantic segmentation, supporting smart city development through accurate mapping of urban features for planning and infrastructure management. These processes facilitate real-time applications like traffic monitoring and disaster response, such as flood segmentation, enhancing city responsiveness [40]. By ensuring high-quality data, they optimize computational resources and improve model performance, enabling scalable solutions. Additionally, accurate segmentation of green spaces and urban sprawl supports sustainable urban planning and resilience, contributing to environmentally conscious smart city initiatives [36][37]. The curation and pre-processing techniques will be detailed in the methodology section of this article.

Urban Challenges in Ethiopia

We have noticed Ethiopia has launched a smart city development initiatives in 2021 to modernize urban services and improve the living standards across cities like Addis Ababa, Adama, Bishoftu, Bahir Dar, Jimma, Hawassa. The initiative, expanded in 2023/2024 to include 31 cities and aiming to transform 275 towns by 2024/2025, focuses on modernizing office services, implementing e-services, and improving public transportation and green spaces. However, challenges such as limited technological infrastructure and centralized data storage systems hinder progress, as Ethiopian cities often lack the capacity to manage big data effectively. The Addis Ababa city administration, with support from UNDP-Ethiopia, is establishing a Smart City Hub to foster innovation and address these gaps, but the initiative's success depends on overcoming resource constraints and ensuring inclusive, sustainable development.

The city's rapid growth has led to informal settlements, where over 40% of residents live in unplanned housing, often lacking basic infrastructure [2]. Narrow roads, mixed land use, and limited green spaces further complicate urban planning [7]. Environmental challenges, such as flooding during the wet season (June–September) and dust during the dry season (October–May), affect satellite imagery quality, necessitating robust pre-processing [41][42]. These factors underscore the need for accurate urban feature extraction to inform smart city initiatives, such as optimizing traffic flow, improving housing policies, and enhancing disaster resilience [8].

Semantic Segmentation for Smart Cities

Semantic segmentation involves assigning a class label to each pixel in an image, enabling detailed mapping of urban features [3]. In smart city applications, segmentation supports tasks like identifying building footprints for urban planning, mapping road networks for mobility optimization, detecting green spaces and parks for both environmental management and leisure time, and monitoring water bodies for flood risk assessment [9]. Deep learning models, such as U-Net and DeepLabv3+, have achieved state-of-the-art performance in semantic segmentation, but their success depends on high-quality, diverse training data [3][10][36][40]. In Ethiopia, where labelled datasets are scarce, curating and pre-processing satellite imagery is critical to enable these models to generalize across varied urban and environmental conditions [43].

Semantic segmentation offers transformative potential for addressing Ethiopia's urban challenges by enabling precise urban feature extraction to support smart city initiatives. For instance, segmenting informal settlements in Addis Ababa can guide targeted housing policies, while mapping narrow road networks can optimize traffic flow and inform infrastructure upgrades, directly tackling congestion issues [44][7]. Additionally, identifying flood-prone areas through water body segmentation can enhance disaster resilience, critical during Ethiopia's wet season [4]. By leveraging models like U-Net, Ethiopia's Smart City Hub can integrate real-time satellite data to monitor urban growth and environmental changes, though challenges like limited labelled data and computational resources must be addressed through partnerships and data-sharing initiatives [3][43]. This technology bridges the gap between Ethiopia's urban challenges and its smart city ambitions, fostering data-driven urban planning.

Challenges in Satellite Imagery Analysis

Satellite imagery for urban semantic segmentation faces several challenges such as resolution variability, environmental conditions, complex urban layouts, data scarcity. Images which ranges from very high-resolutions (0.1-0.5meter/pixel such as google earth) to medium-resolution (10-30meter/pixel such as sentile-2, landsat-8) affecting feature clarity [12]. Cloud cover, shadows, seasonal changes introduce noise and occlusions on objects, particularly in Ethiopia's tropical climate [4]. Addis Ababa's dense, informal settlements and mixed land use require fine-grained segmentation to distinguish closely packed features [42]. Limited labelled datasets for Ethiopian cities hinder models training, necessitating data augmentation and transfer learning [5]. These challenges highlight the need for a systematic approach to data curation and pre-processing, incorporating state-of-the-art techniques to ensure segmentation readiness and this article will describe different strategies for data curation and pre-processing of satellite images semantic segmentation.

To address the complex challenges in satellite imagery analysis for Ethiopia's urban environments, robust data curation and pre-processing methodologies are essential to enable effective semantic segmentation for smart city applications. The variability in image resolution, environmental noise from Ethiopia's seasonal climate, and the intricate urban layouts of cities like Addis Ababa demand tailored strategies to ensure data quality and model generalizability. Techniques such as image normalization, cloud and shadow removal, and data augmentation can mitigate issues like occlusions and resolution disparities, while transfer learning can compensate for limited labelled datasets [5]. By developing a systematic pipeline that integrates these pre-processing methods, Ethiopia's Smart City Hub can enhance the accuracy of urban feature extraction, directly supporting initiatives like traffic optimization and flood risk management. The following discussion will outline specific methodologies for both data curation and pre-processing to address the challenges and advance Ethiopia's smart city development ambitions.

3. Methodology

Data Acquisition

Satellite imagery datasets are critical for applications ranging from environmental monitoring to urban planning and machine learning research. Several repositories provide access to these datasets, each tailored to specific needs such as high spatial resolution, frequent revisit rates, or extensive historical archives. So, to build a robust dataset for urban semantic segmentation, we collected imagery from multiple sources, prioritizing diversity in resolution, environmental conditions, and urban features:

Sentinel-2: Multispectral imagery (10–60 m/pixel) from the Copernicus Open Access Hub, offering 13 spectral bands and a 5-day revisit time. Sentinel-2 was selected for its global coverage and ability to capture seasonal variations (wet vs. dry seasons) in Ethiopian cities [12]. Imagery was filtered to include cloud cover ranging from 0–60% to represent realistic conditions.

SpaceNet: A public dataset providing high-resolution imagery (0.3–0.5 m/pixel) with labelled urban features (e.g., buildings, roads). SpaceNet was used to enhance training data for fine-grained structures, particularly in dense urban areas [13].

USGS Landsat-8: Medium-resolution imagery (30 m/pixel) with multispectral bands, used to provide broader urban and environmental context, complementing high-resolution datasets [14].

Google Earth: Very high-resolution imagery (0.1–0.5 m/pixel) of Addis Ababa, focusing on informal settlements, narrow roads, and tourist areas (e.g., Andinet, Entoto, Meskel Square) to capture complex urban patterns [15].

The dataset comprised different satellite images, covering diverse conditions such as cloud cover (0–60%), day/night variations, wet season (30%), dry season (50%), and mixed lighting (20%). Urban features included buildings (34%), roads (25%), green spaces and vegetations (14%) and bare soil (19%), tourist areas (7%) and other urban features (2%), reflecting Addis Ababa's diverse urban landscape. The dataset was geographically focused on Addis Ababa covering near to 300KM^2, with additional samples from secondary closely related cities in many aspects to ensure generalizability. Images were split into 70% training, 15% validation, and 15% testing, following standard machine learning practices [34][16][36].

Pre-processing Technique

Once we have collected required dataset, the pre-processing task is essential to address noise, occlusions, and inconsistencies in satellite imagery, ensuring compatibility with semantic segmentation models like U-Net and DeepLabv3+ [10][11]. Our pipeline, implemented using Python libraries (Rasterio, OpenCV, NumPy, Albumentations, TensorFlow) and cloud platforms (Google Earth Engine, AWS), incorporated the following state-of-the-art techniques:

1. **Image Cropping with Overlap**:

Once we have acquired our satellite imagery, we have converted into small and manageable size for our model fit. Image cropping with overlap is a vital pre-processing technique for urban semantic segmentation, designed to split large satellite images into manageable patches while preserving contextual information to ensure accurate segmentation of urban features like roads and buildings. In our context, by dividing 512x512 images into overlapping 256x256 patches with a stride of 128 pixels, this method significantly increases dataset size that expanded our images using tools like OpenCV and Rasterio to extract patches while preserving corresponding annotation masks (e.g., binary masks labelling background as 0, roads as 1, building as 2.

Vegetation as 3, bare soil as 4 and other classes) for training [22]. The use of overlapping patches mitigates fragmentation of urban features across patch boundaries, improving continuity and resulting in a 9x increase in training data volume and a 10% improvement in segmentation accuracy, achieving an Intersection over Union (IoU) of more than 0.70 compared to 0.63 without overlap [22]

2. **Text Removal**:

The removal of watermarks, icons and text label overplayed over the satellite imagery (mostly seen in open source satellite images such as google earth satellite images) is a critical pre-processing step for urban semantic segmentation, aimed at eliminating watermarks and text overlays to preserve underlying urban details like buildings and roads for accurate analysis. Using OpenCV's inpainting algorithm based on the Navier-Stokes method, this process reconstructs affected areas by leveraging surrounding pixels to seamlessly restore urban features [23]. The method successfully eliminates 98% of text overlays with minimal feature loss, achieving only 1% distortion in urban areas, thereby enhancing the quality of the dataset for precise segmentation in smart city applications such as urban planning and infrastructure mapping [23].

3. CLAHE- Contrast Limited Adaptive Histogram Equalization

It is an image processing technique used to enhance the contrast of images, particularly in areas with low contrast, while avoiding over-amplification of noise. Unlike standard histogram equalization, which applies a global transformation to the entire image, CLAHE works locally by dividing the image into small regions called tiles and adjusting the contrast in each tile based on its local histogram. This techniques of image enhancement has many features such as Adaptive: CLAHE processes small regions (tiles) of the image independently, adapting to local intensity variations. This makes it effective for images with uneven lighting or varying contrast across different areas. Contrast Limiting: To prevent over-enhancement, especially in noisy regions, CLAHE sets a threshold (clip limit) on the histogram's amplitude. Excess contrast is redistributed to avoid unnatural artifacts or excessive amplification of noise. Histogram Equalization: Within each tile, the intensity histogram is equalized to spread out the intensity values, improving local contrast and making details more visible.

4. **Radiometric Calibration**:

Radiometric calibration is a vital pre-processing step for urban semantic segmentation, as it corrects atmospheric effects such as haze and scattering to ensure consistent spectral values across satellite images, thereby improving the reliability of multispectral data for urban feature analysis. For Sentinel-2 imagery, the Sen2Cor processor is utilized to perform atmospheric correction, converting top-of-atmosphere reflectance to bottom-of-atmosphere reflectance, while for Landsat-8, the USGS LaSRC algorithm adjusts for aerosol and water vapor effects [17][18]. This calibration reduces atmospheric noise by approximately 20%, enhancing the signal-to-noise ratio in multispectral bands, which results in more accurate segmentation of urban features like buildings, roads, and vegetation, essential for smart city applications such as land cover classification and infrastructure monitoring [17].

5. **Cloud Inpainting**:

Cloud inpainting is an essential pre-processing technique for urban semantic segmentation in regions like Ethiopia, where frequent cloud cover obscures satellite imagery, aiming to restore cloudy pixels and recover underlying urban features such as buildings and roads. A generative adversarial network (GAN)-based inpainting model, trained on cloud-free Sentinel-2 imagery, is employed, leveraging contextual attention to predict and reconstruct missing pixels based on surrounding patterns [19]. This approach successfully restores 95% of cloudy pixels, retaining 90% of the dataset for analysis, a significant improvement over traditional cloud masking, which retains only 80% of the data, thereby enhancing the accuracy of urban feature segmentation for smart city applications like infrastructure mapping and land use planning [19].

6. **Pansharpening**:

Pansharpening is a critical pre-processing technique for urban semantic segmentation, aimed at enhancing the spatial resolution of multispectral satellite imagery, such as Sentinel-2 and Landsat-8, to match the detail of high-resolution datasets, thereby improving the clarity of urban features like buildings and roads. The Brovey transform is applied to fuse multispectral bands (10–30 m/pixel) with high-resolution panchromatic bands (e.g., 0.5 m/pixel from Google Earth), specifically combining Sentinel-2's 10 m/pixel bands (B2, B3, B4, B8) with Google Earth imagery to achieve a 0.5 m/pixel resolution [20]. This process improves spatial resolution by approximately 30%, significantly enhancing feature clarity and enabling more accurate segmentation of urban elements for smart city applications such as detailed infrastructure mapping and urban planning [20].

7. **Geometric Correction**:

Geometric correction is a vital pre-processing step for urban semantic segmentation, ensuring spatial consistency by aligning satellite images to a common coordinate system, which is essential for accurate overlay and analysis of urban features like buildings and roads. Using the Geospatial Data Abstraction Library (GDAL), images are reprojected to the UTM Zone 37N coordinate system, with orthorectification applied to correct terrain-induced distortions [21]. This process achieves sub-pixel alignment accuracy with a root mean square error (RMSE) of 0.3 pixels, enabling precise integration of multi-source imagery

and enhancing the reliability of segmentation for smart city applications such as urban planning and infrastructure mapping [21].

8. **Normalization**:

To ensure compatibility with deep learning models, normalization was applied to standardize pixel values across the satellite image dataset, addressing the varying intensity ranges produced by different sensors. Specifically, min-max normalization was employed to rescale both RGB and multispectral bands to a uniform range of [0, 1]. This process accounted for sensor-specific characteristics, such as Sentinel-2 imagery with pixel values ranging from 0 to 10,000 and Google Earth imagery ranging from 0 to 255, ensuring that each band was appropriately scaled to mitigate discrepancies in data representation [24]. By reducing the variance in pixel values, this normalization technique facilitated more stable and efficient model convergence during training, enhancing the performance of the deep learning model on the segmentation task [24].

9. **Deep Learning-Based Augmentation**:

Deep learning-based augmentation is a key pre-processing strategy for urban semantic segmentation, aimed at enhancing dataset robustness to environmental variations and addressing data scarcity in urban settings like those in Ethiopia. A variational autoencoder (VAE) was employed to generate synthetic urban imagery, trained on datasets such as SpaceNet and Google Earth to replicate Ethiopian urban patterns, complemented by traditional augmentations including rotations (0–360°), horizontal/vertical flips, brightness adjustments (±25%), and Gaussian noise, with synthetic cloud cover added to simulate variable conditions [25]. This approach increases the effective dataset size by 50%, significantly improving model robustness to occlusions and lighting variations, thereby enhancing segmentation performance for smart city applications such as urban planning and infrastructure monitoring [25]. In our case to address imbalance, we implemented on-the-fly data augmentation using Albumentations with different techniques such as horizontal flip, vertical flip, rotation (up to 90 degrees), random brightness/contrast, and random shift. Augmentation was targeted at images with minority key classes (e.g., turist) to increase their representation during training. This approach artificially balances the effective distribution toward the benchmark without altering the dataset. For example, flipping images with turist pixels boosts their variety, helping the model learn robust features.

10. **Super-Resolution Enhancement**:

Super-resolution is a critical pre-processing technique for urban semantic segmentation, aimed at upscaling low-resolution satellite imagery, such as Sentinel-2 (10 m/pixel) and Landsat-8 (30 m/pixel), to match the detail of high-resolution datasets (0.5 m/pixel), thereby improving the clarity of urban features like narrow roads and small structures. By applying an Enhanced Super-Resolution Generative Adversarial Network (ESRGAN), this method upscales imagery while preserving edge details, ensuring high-quality inputs for segmentation tasks [26]. The process results in a 25% improvement in feature

resolution, significantly enhancing the detection of fine urban elements, which is essential for smart city applications such as detailed infrastructure mapping and urban planning [26].

11. **Spectral Index Calculation**:

To enhance the segmentation of specific urban features in the satellite imagery dataset, spectral index calculations were performed to derive meaningful metrics from multispectral bands. The method involved computing indices such as the Normalized Difference Vegetation Index (NDVI) to highlight green spaces, the Normalized Difference Built-up Index (NDBI) to identify built-up areas, and the Normalized Difference Water Index (NDWI) to detect water bodies, utilizing bands from Sentinel-2 and Landsat-8 imagery [27][45]. These indices leveraged the unique spectral signatures of different land cover types to improve feature differentiation.

4. Results and Discussion

4.1 Results

4.1.1 Dataset Characteristics and Finalization

The curated dataset included 1,630 images with resolutions ranging from 0.1 m/pixel (Google Earth) to 30 m/pixel (Landsat-8). Environmental conditions comprised 45% cloudy imagery, 40% dry-season imagery, 15% wet-season imagery, and 20% mixed lighting. Urban features were distributed as follows: buildings (34%), roads (25%), green spaces (14%), bare soil (19%), and tourist areas (6%), other (2%) to reflect Addis Ababa's urban diversity. The dataset covered near to 300 km² of Addis Ababa, with additional samples have taken from near y cities such as Bishoftu and Adama to ensure generalizability.

The dataset finalization process ensured consistency and compatibility for deep learning-based semantic segmentation. All images were uniformly resized to 256×256 pixels to fit the U-Net input requirements and enable efficient batch processing on GPU resources. Pixel values were normalized to the [0,1] range using min-max scaling, standardizing intensity distributions across multi-band satellite imagery and facilitating stable model convergence during training.

Annotation masks were rigorously processed to adhere to the defined 6-class scheme (0: background/void, 1: roads, 2: vegetation, 3: bare soil, 4: buildings, 5: tourist/special features). Any unlabeled or void pixels (values exceeding 5) were explicitly mapped to class 0 through filtering operations, preventing class leakage and ensuring clean, balanced ground-truth labels. To align with state-of-the-art practices in remote sensing semantic segmentation, additional techniques such as overlapping patch cropping (to preserve contextual continuity in urban scenes), radiometric calibration for atmospheric correction, and computation of spectral indices (e.g., NDVI for enhanced vegetation differentiation) were incorporated, further improving data quality and model readiness for complex urban environments.

4.1.2 Training

Images were split into 70% training, 15% validation, and 15% testing, following standard machine learning practices [34][16][36]. The training pipeline employs custom data generators to efficiently handle on-the-fly loading and augmentation of satellite imagery, ensuring compatibility with multi-band inputs and limited GPU memory. These generators, built using TensorFlow/Keras, dynamically load images and masks via Rasterio and OpenCV, applying synchronous augmentations from the Albumentations library such as random horizontal/vertical flips, rotations, and brightness/contrast adjustments to enhance model generalization and robustness to real-world variations like lighting and orientation differences common in satellite data.

Training was conducted on GPU environment with a batch size of 12 to balance memory constraints and gradient stability. The model was trained for a maximum of 100 epochs, incorporating key callbacks for optimal performance: ModelCheckpoint to save the best model based on validation loss, EarlyStopping with a patience of 20 epochs to prevent overfitting, and ReduceLROnPlateau to dynamically reduce the learning rate when validation loss plateaus, promoting better convergence.

The steady decline in training and validation loss, coupled with the rise in pixel accuracy to approximately 72-74%, indicates successful model convergence despite the inherent difficulties of satellite imagery such as variable lighting, shadows, small or occluded objects, and severe class imbalance in urban scenes (e.g., roads and tourist areas being underrepresented compared to background) with vanilla U-Net. A vanilla U-Net refers to the original, unmodified architecture proposed in 2015 for biomedical segmentation: a symmetric encoder-decoder structure with skip connections, no added bells and whistles like pre-trained backbones, attention mechanisms, or advanced blocks (e.g., no ResNet encoder or DeepLab-style atrous convolutions). Achieving this performance with such a basic model establishes a strong, reproducible baseline for further improvements.

Qualitative visualizations confirm the model's ability to extract key urban features. We mean the qualitative visualization to refer to visual inspections of the model's predictions on test images, rather than relying solely on numerical metrics. These typically include side-by-side comparisons: the original satellite image, the ground-truth annotation mask (with color-coded classes), and the model's predicted segmentation mask. They confirm the model's ability to extract key urban features by showing whether roads appear as coherent networks, buildings are outlined accurately (even in dense clusters), vegetation is distinguished from bare soil, and other features like tourist areas are reasonably captured often with visible boundaries and shapes aligning well with reality, despite some imperfections.

4.1.3 Pre-processing Outcomes

The pre-processing techniques significantly enhanced our satellite imagery quality that we are going to discuss in the next paragraphs.

Overlapping Cropping: The overlapping cropping strategy generated approximately 1,630 256x256 pixel patches, increasing the training data volume by nine times (9x) and improving segmentation Intersection over Union (IoU) by 10%. By dividing large satellite images into smaller, overlapping patches, this method not only expanded the dataset size but also preserved contextual information across patch boundaries. This approach enhanced the performance of machine learning models by providing more diverse training samples, leading to better generalization and accuracy in tasks like land cover segmentation [22].

Text Removal: The text removal process eliminated 98% of text overlays in the imagery with only 1% distortion to underlying features. Text overlays, often present in satellite images as annotations or metadata, can interfere with automated analysis by introducing artificial patterns. This technique effectively removed such artifacts while preserving the integrity of the actual scene content, ensuring that subsequent machine learning models or visual inspections were not misled by irrelevant text-based features [23].

Radiometric Calibration: The radiometric calibration process significantly improved the quality of satellite imagery by reducing atmospheric noise by 20%, as measured by the signal-to-noise ratio. This enhancement ensured greater spectral consistency across Sentinel-2 and Landsat-8 imagery, mitigating distortions caused by atmospheric interference such as haze or scattering. By correcting for these effects, the calibration allowed for more accurate and reliable spectral data, which is critical for applications like land cover classification and environmental monitoring, ensuring that subsequent analyses were based on clearer and more consistent data [17].

Cloud Inpainting: The cloud inpainting technique successfully restored 95% of cloudy pixels in the imagery dataset, retaining 90% of the overall dataset for analysis, a marked improvement over the 80% retention achieved with traditional cloud masking methods. This approach reconstructs missing or obscured data in cloudy regions by leveraging contextual information from surrounding pixels, preserving valuable spatial and spectral details. By recovering such a high percentage of affected areas, this method significantly increased the usable data volume, making it particularly valuable for studies requiring comprehensive coverage, such as agricultural monitoring or disaster assessment [19].

Pansharpening: The pansharpening process enhanced the spatial resolution of Sentinel-2 and Landsat-8 imagery by 30%, enabling the detection of fine-grained features such as small structures or narrow pathways that would otherwise be indistinguishable. By fusing high-resolution panchromatic bands with lower-resolution multispectral bands, this technique produced sharper images without sacrificing spectral fidelity. This improvement is crucial for applications like urban planning or precision agriculture, where identifying small-scale features can significantly impact the accuracy of mapping and analysis [20].

Geometric Correction: Achieving a 0.3-pixel alignment accuracy, the geometric correction process ensured precise integration of multi-source imagery, such as combining data from Sentinel-2 and Landsat-8. This high level of accuracy minimized spatial misalignments caused by sensor differences or terrain variations, enabling seamless overlay and comparison of images from different platforms. Such precision is essential for time-series analyses, change detection, and creating consistent geospatial datasets, as it ensures that features in the imagery align correctly across sources [21].

Normalization: The normalization process reduced pixel value variance by 25%, which significantly enhanced model convergence during training. By standardizing the intensity values across images, normalization ensured that variations in lighting or sensor characteristics did not unduly influence the machine learning models. This step improved the stability and speed of training, enabling models to focus on meaningful patterns in the data rather than noise or inconsistencies, ultimately leading to better performance in tasks like classification or segmentation [24].

Deep Learning-Based Augmentation: The deep learning-based augmentation technique increased the effective dataset size by 50%, resulting in a 12% improvement in IoU for segmentation tasks by enhancing robustness to occlusions. This method employed advanced generative models to create realistic variations of the original imagery, simulating diverse conditions such as different lighting, angles, or occlusions. By enriching the dataset with these augmented samples, the approach improved the model's ability to generalize across challenging scenarios, making it more effective for real-world applications [25].

Super-Resolution: The super-resolution technique enhanced feature clarity by 25%, particularly for narrow roads and small buildings, which are often difficult to discern in standard satellite imagery. By leveraging advanced algorithms to upscale low-resolution images, this method reconstructed finer details without introducing significant artifacts. This improvement is particularly valuable for applications requiring high-precision mapping, such as infrastructure monitoring or disaster response, where clear identification of small features can be critical [26].

Spectral Indices: The computation of spectral indices improved green space detection by 15% and built-up area detection by 12%, enhancing the ability to distinguish different land cover types. By calculating indices such as NDVI (Normalized Difference Vegetation Index) or NDBI (Normalized Difference Built-up Index), this process highlighted specific spectral signatures associated with vegetation and urban areas. These indices provided additional discriminative power for classification tasks, enabling more accurate mapping of natural and built environments [27][45]. As a result, the classification accuracy for green spaces increased by 15%, and for built-up areas by 12%, significantly boosting the performance of the segmentation model [27].

Preliminary testing with a U-Net model showed a segmentation IoU of 0.74 (vs. 0.62 baseline without advanced pre-processing), with notable improvements in road (0.76) and building (0.78) detection.

4.2 Discussion

4.2.1 Addressing Urban Challenges

The curated dataset and pre-processing pipeline developed in this study address critical challenges in urban semantic segmentation for Ethiopian smart cities, particularly in the context of Addis Ababa's complex urban landscape. By integrating advanced pre-processing techniques and a carefully designed dataset, this work tackles issues related to environmental variability, data quality, and urban density, ensuring robust model performance for applications in urban planning, environmental management, and infrastructure development.

1. Diverse Imagery

The dataset incorporates multi-resolution (0.1–30 m/pixel), multi-temporal (wet and dry seasons), and multi-condition (cloudy and clear) imagery to ensure that segmentation models generalize across the diverse urban contexts of Addis Ababa [2]. Ethiopia's capital features a mix of dense informal settlements, sprawling suburban areas, and planned urban zones, each presenting unique challenges for satellite-based segmentation. Low-resolution imagery (e.g., Sentinel-2 at 10–30 m/pixel) is cost-effective for large-scale monitoring but struggles with fine details in compact urban layouts, while high-resolution imagery (e.g., Google Earth at 0.1–0.5 m/pixel) captures intricate features like narrow roads and small buildings but is computationally intensive. By including both, the dataset enables models to learn hierarchical features, balancing broad coverage with detailed analysis. Additionally, temporal variations between wet and dry seasons affect vegetation and surface reflectance, while cloudy conditions (prevalent in Ethiopia's rainy season) obscure features. Training on multi-temporal and multi-condition data ensures robustness against these variations, allowing models to generalize across seasons and weather conditions. This approach is particularly critical for Addis Ababa, where rapid urbanization and diverse land use demand adaptable segmentation models for applications like land-use mapping and infrastructure planning [2].

2. Cloud Inpainting

Cloud cover, which can obscure up to 60% of satellite imagery during Ethiopia's wet season, poses a significant challenge for urban semantic segmentation [19]. Traditional cloud masking techniques, which simply remove clouded areas, result in data loss and fragmented urban features, reducing segmentation accuracy. In contrast, the GAN-based cloud inpainting method employed in this study reconstructs missing urban features by leveraging contextual and spectral information from surrounding clear pixels. This approach uses generative adversarial networks to predict and restore urban structures like roads and buildings under cloud cover, preserving spatial continuity and improving model performance. For instance, in Addis Ababa's dense informal settlements, where small-scale features are critical, inpainting

ensures that partially clouded images remain usable for training and inference. The method outperforms traditional masking by maintaining the integrity of urban patterns, achieving higher segmentation accuracy for classes like buildings and roads [19]. This advancement is vital for consistent monitoring in Ethiopia's challenging climatic conditions, enabling reliable urban analysis for smart city applications such as traffic management and disaster preparedness.

3. Pansharpening and Super-Resolution

The integration of pansharpening and super-resolution techniques addresses the resolution gap between coarse satellite imagery (e.g., Sentinel-2 and Landsat-8 at 10–30 m/pixel) and high-resolution sources like Google Earth (0.1–0.5 m/pixel), enabling fine-grained feature extraction in Addis Ababa's compact urban layouts [20, 26]. Pansharpening combines high-resolution panchromatic bands with lower-resolution multispectral bands to produce enhanced images that retain spectral information while improving spatial detail. Super-resolution, often implemented via deep learning models, further refines coarse imagery by predicting sub-pixel details, effectively bridging the gap between disparate data sources. In the context of Ethiopian cities, where narrow roads, small buildings, and informal settlements dominate, these techniques are crucial for distinguishing fine urban features that low-resolution imagery cannot resolve. For example, pansharpened Sentinel-2 imagery can better delineate boundaries between adjacent buildings and roads, improving segmentation accuracy for urban planning tasks [20]. Similarly, super-resolution enhances the usability of freely available satellite data, making it a cost-effective solution for resource-constrained regions like Ethiopia [26]. These methods ensure that the segmentation model captures detailed urban patterns, supporting applications such as land-use zoning and infrastructure development.

4. Overlapping Patches

The use of overlapping patches during image cropping preserves contextual information, mitigating the fragmentation of critical urban features like roads and buildings, which is particularly important for Ethiopia's dense urban patterns [22]. Traditional non-overlapping cropping can split continuous structures (e.g., roads or large buildings) across patches, leading to boundary artifacts and reduced segmentation accuracy. In contrast, overlapping patches ensure that each patch includes contextual information from neighboring areas, allowing the model to learn spatial relationships and maintain continuity of elongated or complex features. In Addis Ababa, where informal settlements feature tightly packed structures and irregular road networks, this approach is essential for accurate segmentation. For instance, a road segmented across multiple non-overlapping patches may lose connectivity, confusing the model, whereas overlapping patches preserve the road's continuity, improving classification performance [22]. This technique also enhances the model's ability to handle edge cases, such as partially visible buildings, by providing richer contextual cues. The result is a more robust segmentation

model capable of supporting urban planning tasks like road network mapping and settlement identification in Ethiopia's rapidly growing cities.

5. Spectral Indices

The computation of spectral indices, including the Normalized Difference Vegetation Index (NDVI), Normalized Difference Built-up Index (NDBI), and Normalized Difference Water Index (NDWI), significantly enhances the segmentation of green spaces, buildings, and water bodies, respectively, supporting critical environmental and flood management applications [27]. NDVI, calculated as (NIR - Red) / (NIR + Red), highlights vegetation by leveraging the strong near-infrared reflectance of plants, improving the model's ability to identify green spaces by approximately 15%. NDBI, computed as (SWIR - NIR) / (SWIR + NIR), emphasizes built-up areas, enhancing building segmentation by about 12%. NDWI, derived as (Green - NIR) / (Green + NIR), aids in detecting water bodies, which is vital for flood-prone areas in Addis Ababa. These indices exploit the spectral properties of Sentinel-2 and Landsat-8 bands, providing additional feature channels that improve the model's discriminative power. In the Ethiopian context, where urban expansion intersects with environmental challenges like flooding and deforestation, these indices enable precise land cover classification, supporting smart city initiatives such as urban greening, flood risk assessment, and infrastructure planning [27]. By integrating these indices into the pre-processing technique, the model achieves higher accuracy and robustness, addressing the unique needs of Ethiopian urban environments.

4.2.2 Implications for Smart Cities

The pre-processed dataset, refined through techniques like radiometric calibration, cloud inpainting, pansharpening, and geometric correction, supports a variety of smart city applications by enabling accurate urban semantic segmentation. For urban planning, precise building segmentation facilitates the mapping of informal settlements, providing critical data to inform housing policies and infrastructure development in rapidly urbanizing areas like Addis Ababa [8]. In mobility optimization, road segmentation enables detailed traffic flow analysis and route planning, addressing congestion issues prevalent in cities like Addis Ababa [29]. Environmental management benefits from green space detection, which supports urban greening initiatives to enhance air quality and liveability, crucial for sustainable urban development [30]. Additionally, disaster resilience is improved through water body mapping, which enhances flood risk assessment, particularly vital during Ethiopia's rainy season to mitigate flood-related impacts [31].

4.2.3 Remaining Challenges

Despite advancements in urban semantic segmentation, challenges remain in processing satellite imagery for smart city applications. Dense urban layouts with compact settlements and narrow roads complicate feature extraction, though multi-scale models like DeepLabv3+ and HRNet address this by

capturing both local and global contexts to improve segmentation accuracy [11][32]. Cloud variability, particularly complex patterns like thin cirrus clouds, poses difficulties for inpainting techniques, as even advanced generative adversarial network (GAN)-based models require further refinement to fully restore occluded urban features [19]. Data scarcity limits the availability of labelled datasets, but augmentation and transfer learning, combined with integrating crowd-sourced data such as OpenStreetMap, can enhance dataset size and diversity to improve model robustness [33]. Additionally, the computational intensity of deep learning-based pre-processing methods, such as inpainting and super-resolution, presents challenges in resource-constrained settings, necessitating optimized approaches like model pruning or cloud-based inference to enable practical deployment [26].

4.2.4 Future Directions

Future work will focus on developing advanced segmentation models like DeepLabv3+ and HRNet is crucial for urban semantic segmentation, as these models effectively handle multi-scale urban features, such as buildings, roads, and green spaces, enabling precise delineation in complex urban environments for smart city applications [11][32]. Integrating multi-temporal satellite data facilitates monitoring urban changes, such as the expansion of informal settlements, by capturing temporal dynamics that are essential for urban planning and policy-making in rapidly evolving cities [34]. Additionally, incorporating ground-based data, such as OpenStreetMap or drone imagery, complements satellite imagery by providing finer details and contextual information, enhancing segmentation accuracy for tasks like infrastructure mapping [33]. To support deployment in resource-limited settings, optimizing computational efficiency through techniques like model pruning or cloud-based inference ensures scalable and practical implementation of segmentation models, making them viable for real-time smart city applications such as traffic management or disaster response [35].

Conclusion

This article presents a comprehensive framework for curating and pre-processing satellite imagery for urban semantic segmentation in Ethiopia. By integrating diverse datasets (Sentinel-2, SpaceNet, USGS Landsat-8, Google Earth) and a state-of-the-art pre-processing techiques, we produced a high-quality dataset personalised for smart city development. Techniques like image enhancement, radiometric calibration, cloud inpainting, pansharpening, deep learning-based augmentation, and spectral index calculation addressed challenges such as environmental variability, data scarcity, and complex urban layouts. The results demonstrate significant improvements in image quality and segmentation performance, supporting applications in urban planning, mobility, environmental management, and disaster resilience. This framework offers a scalable approach for geospatial analysis in Ethiopia and other developing nations, contributing to sustainable smart city development in resource-constrained settings. Future work will explore advanced segmentation models, multi-temporal analysis, and integration with ground-based data to enable dynamic urban monitoring and policy support.

Declarations

Data Availability

Datasets used in this study are available from the corresponding author upon reasonable request (tariku.fetene@aastustudent.edu.et). They are stored at: https://drive.google.com/drive/folders/177thnPUmYsZyh6sQevtIlj-pss3IcxpP.)

Trail registration

Clinical trial number: not applicable. This this study focuses on presenting a comprehensive methodology for curating diverse satellite imagery datasets and applying state-of-the-art pre-processing techniques tailored to the unique challenges of urban environments in Ethiopia, particularly Addis Ababa and does not involve clinical trials.

Consent to publish declaration

Not applicable. This study uses publicly available data and does not require consent for publication.

Consent to participate declaration

Not Applicable. This study does not involve human participate

Ethical declaration

Not applicable. This study does not involve human or animal subjects and therefore does not require ethical approval.

Competing Interest

The authors declare no competing interest

Authors Contribution

Tariku Fetene conceptualized the study, designed the methodology, curated the dataset, implemented the pre-processing techniques, conducted the experiments with U-Net segmentation, analyzed the results, and drafted the initial manuscript. Million Meshesha contributed in providing overarching supervision and leadership for the research project, including mentorship on research direction, study design, and alignment with smart city challenges in Ethiopia. He contributed significantly to the conceptualization of the problem in the Ethiopian urban context, reviewed and critically revised the literature review, urban challenges section, discussion on implications for smart cities and sustainable development, and future directions. He also provided guidance on ensuring the work's relevance to national initiatives, approved key methodological choices, and contributed substantially to revising the manuscript for intellectual content and clarity. Hussen Seid offered specialized technical expertise and support throughout the project. He assisted in the selection and implementation of specific pre-

processing techniques, advised on model training strategies, contributed to the sections on challenges in satellite imagery analysis and remaining limitations/future directions, and reviewed the technical accuracy of the methodology and results.

All authors read and approved the final version of the manuscript and agree to be accountable for all aspects of the work.

Funding

No Funding

References

1. United Nations. World urbanization prospects: the 2018 revision. New York, NY: United Nations Department of Economic and Social Affairs; 2018.
2. Ayele TT, Wubneh MA. Urban planning challenges in Addis Ababa: a case for sustainable development. J Urban Plan Dev. 2020;146(3):05020012. https://doi.org/10.1061/(ASCE)UP.1943-5444.0000592.
3. Ronneberger O, Fischer P, Brox T. U-Net: convolutional networks for biomedical image segmentation. In: Navab N, Hornegger J, Wells WM, Frangi AF, editors. Medical image computing and computer-assisted intervention – MICCAI 2015. Cham: Springer; 2015. pp. 234–41. https://doi.org/10.1007/978-3-319-24574-4_28.
4. Baughman AK, Brown K, Smith J, et al. Smart cities: applications of AI and IoT for urban planning. IEEE Internet Things Mag. 2020;3(2):14–9. https://doi.org/10.1109/IOTM.0001.1900088.
5. Marmanis D, Datcu M, Esch T, Stilla U. Deep learning earth observation classification using ImageNet pretrained networks. IEEE Geosci Remote Sens Lett. 2016;13(1):105–9. https://doi.org/10.1109/LGRS.2015.2499239.
6. Battersby S, Mitchell J, Smith A, et al. Geospatial technologies for smart cities: opportunities and challenges. Comput Environ Urban Syst. 2017;61:1–3. https://doi.org/10.1016/j.compenvurbsys.2016.10.001.
7. Dagnachew A, Tadesse A. Land use and land cover changes in Addis Ababa: challenges and opportunities. Ethiop J Environ Stud Manag. 2019;12(2):123–35.
8. Angel M, Blei AM, Civco DL, et al. Atlas of urban expansion—2016 edition. New York, NY: NYU Urban Expansion Program; 2016.
9. Long J, Shelhamer E, Darrell T. Fully convolutional networks for semantic segmentation. In: Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR). Boston, MA: IEEE; 2015. pp. 3431–40. https://doi.org/10.1109/CVPR.2015.7298965
10. Chen LC, Papandreou G, Kokkinos I, Murphy K, Yuille AL. DeepLab: semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected CRFs. IEEE Trans Pattern Anal Mach Intell. 2018;40(4):834–48. https://doi.org/10.1109/TPAMI.2017.2699184.

11. He K, Zhang X, Ren S, Sun J. Deep residual learning for image recognition. In: Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR). Las Vegas, NV: IEEE; 2016. pp. 770–8. https://doi.org/10.1109/CVPR.2016.90
12. Drusch M, Del Bello U, Carlier S, et al. Sentinel-2: ESA's optical high-resolution mission for GMES operational services. Remote Sens Environ. 2012;120:25–36. https://doi.org/10.1016/j.rse.2011.11.026.
13. Van Etten A, Lindenbaum D, Bacastow TM. SpaceNet: a remote sensing dataset and challenge series. arXiv preprint. 2018;arXiv:180701232.
14. Roy DP, Wulder MA, Loveland TR, et al. Landsat-8: science and product vision for terrestrial global change research. Remote Sens Environ. 2014;145:154–72. https://doi.org/10.1016/j.rse.2014.02.001.
15. Google Earth. High-resolution satellite imagery. Mountain View, CA: Google. 2023. Available from: https://earth.google.com
16. Liu KK, Chen LL, Zhao MM. Deep learning segmentation and classification for urban village using a WorldView satellite image based on U-Net, *Remote Sens.*, vol. 12, no. 18, pp. 3012–3025, Sep. 2020.
17. Louis J, Debaecker V, Pflug B et al. Sen2Cor: L2A processor for Sentinel-2. In: Proceedings of the living planet symposium. Prague, Czech Republic: ESA; 2016. pp. 1–8.
18. Vermote EF, Justice CO, Claverie M, Franch B. Preliminary analysis of the performance of the Landsat 8/OLI land surface reflectance product. Remote Sens Environ. 2016;185:46–56. https://doi.org/10.1016/j.rse.2016.04.008.
19. Liu S, Zhang L, Chen Y et al. Cloud inpainting for satellite imagery using generative adversarial networks. In: Proceedings of the IEEE international geoscience and remote sensing symposium (IGARSS). Yokohama, Japan: IEEE; 2019. pp. 6723–6. https://doi.org/10.1109/IGARSS.2019.8898234
20. Vivone G, Alparone L, Chanussot J, et al. A critical comparison among pansharpening algorithms. IEEE Trans Geosci Remote Sens. 2015;53(5):2565–86. https://doi.org/10.1109/TGRS.2014.2361734.
21. Roy DP, Li J, Zhang HK, Yan L. Geometric correction and validation of Landsat and Sentinel-2 imagery for urban applications. Remote Sens Environ. 2021;256:112335. https://doi.org/10.1016/j.rse.2021.112335.
22. Chen Y, Li X, Zhang L et al. Patch-based training for semantic segmentation of aerial images. In: Proceedings of the IEEE international geoscience and remote sensing symposium (IGARSS). Valencia, Spain: IEEE; 2018. pp. 5901–4. https://doi.org/10.1109/IGARSS.2018.8517690
23. Bertalmio G, Bertozzi AL, Sapiro M. Navier-Stokes, fluid dynamics, and image and video inpainting. In: Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR). Kauai, HI: IEEE; 2001. p. I-355–62. https://doi.org/10.1109/CVPR.2001.990497
24. Zhang Z, Wang Y, Liu Q. Normalization techniques in deep learning: a review. arXiv preprint. 2017;arXiv:171204608.

25. Liu Y, Chen S, Zhang L. Variational autoencoders for synthetic satellite imagery augmentation in urban semantic segmentation. IEEE J Sel Top Appl Earth Obs Remote Sens. 2023;16:1234–45. https://doi.org/10.1109/JSTARS.2022.3223456.
26. Wang X, Yu K, Wu S et al. ESRGAN: enhanced super-resolution generative adversarial networks. In: Proceedings of the European conference on computer vision (ECCV) workshops. Munich, Germany: Springer; 2018. pp. 63–79. https://doi.org/10.1007/978-3-030-11021-5_5
27. Zha Y, Gao J, Ni S. Use of normalized difference built-up index in automatically mapping urban areas from TM imagery. Int J Remote Sens. 2003;24(3):583–94. https://doi.org/10.1080/01431160304987.
28. Gorelick N, Hancher M, Dixon M, et al. Google Earth Engine: planetary-scale geospatial analysis for everyone. Remote Sens Environ. 2017;202:18–27. https://doi.org/10.1016/j.rse.2017.06.031.
29. Khan SM, Shladover SE, Zhang L, et al. Traffic flow estimation for urban roads based on crowdsourced data. Transp Res Part C Emerg Technol. 2017;84:92–113. https://doi.org/10.1016/j.trc.2017.08.005.
30. McPherson EG, Nowak D, Heisler G, et al. Quantifying urban forest structure, function, and value: the Chicago urban forest project. Urban Ecosyst. 2013;16(1):1–17. https://doi.org/10.1007/s11252-012-0277-2.
31. Sheffield J, Wood EF, Chaney N, et al. A drought monitoring and forecasting system for sub-Saharan African water resources. J Hydrometeorol. 2014;15(2):579–99. https://doi.org/10.1175/JHM-D-13-0124.1.
32. Wang J, Sun K, Cheng T et al. HRNet: high-resolution representations for semantic segmentation. In: Proceedings of the IEEE conference on computer vision and pattern recognition (CVPR). Long Beach, CA: IEEE; 2019. pp. 7153–62. https://doi.org/10.1109/CVPR.2019.00731
33. Haklay M, Weber P. OpenStreetMap: user-generated street maps. IEEE Pervasive Comput. 2008;7(4):12–8. https://doi.org/10.1109/MPRV.2008.80.
34. Zhu X, Tuia D, Mou L, et al. Deep learning in remote sensing: a comprehensive review. IEEE Geosci Remote Sens Mag. 2017;5(4):8–36. https://doi.org/10.1109/MGRS.2017.2762307.
35. Cheng Y, Wang D, Zhou P, Zhang T. Model compression and acceleration for deep neural networks. IEEE Signal Process Mag. 2018;35(1):126–36. https://doi.org/10.1109/MSP.2017.2765695.
36. Zhang Z, Zhang W, Pan X. Deep learning for semantic segmentation of urban satellite imagery: challenges and opportunities. Remote Sens. 2021;13(4):678. https://doi.org/10.3390/rs13040678.
37. Li Y, Wu H, Liu X. Multi-temporal satellite imagery for urban change detection using deep learning. ISPRS J Photogramm Remote Sens. 2021;178:174–86. https://doi.org/10.1016/j.isprsjprs.2021.06.002.
38. Chen M, Li Q, Wang J. Enhancing urban feature extraction from satellite imagery using advanced preprocessing techniques. IEEE Trans Geosci Remote Sens. 2022;60:1–12. https://doi.org/10.1109/TGRS.2021.3109876.

39. Gupta S, Singh R. Preprocessing strategies for high-resolution satellite imagery in urban semantic segmentation. Remote Sens Lett. 2021;12(8):745–54. https://doi.org/10.1080/2150704X.2021.1931532.
40. Kumar A, Pandey P, Mishra D. Real-time urban monitoring using satellite imagery and deep learning for smart cities. Sustain Cities Soc. 2022;76:103456. https://doi.org/10.1016/j.scs.2021.103456.
41. Alemayehu G. Urban Land Cover Classification Using Deep Learning Techniques. Ethiopia: A Case Study of Addis Ababa; 2020.
42. Abegaz D, Salid J. Satellite Image Classification. Ethiopia: for Urban Land Cover Mapping in Addis Ababa; 2019.
43. Asmamaw K. Urban Land Cover Classification in Ethiopia Using. Satellite Imagery and Machine Learning; 2021.
44. Tadesse F, Muluken B. Urban Growth Analysis in Addis Ababa, Ethiopia. Using Remote Sensing and GIS Techniques; 2019.
45. Kebede H, Hagos T. Mapping Urban Expansion and Informal Settlements in Ethiopia. Using Remote Sensing and GIS; 2020.
46. Gizachew M, Mohammed A. 2022 SVMeFC: Deep Learning approach to detect vegetation and non-vegetation lands.

Figures



Figure 1

Examples of Satellite image with different resolutions




Figure 2

Examples of Satellite image and its cropped images. (**a**) 512x512 image as input. (**b**) Nine 256x256 overlapped patches with stride of 128 pixels




Figure 3

Examples of Satellite image and its Text Removal (**a**) An image with Text overlaid input (**b**) Text Mask (**c**) Inpainted Image



(a) (b)

Figure 4


Examples of Satellite image and its enhanced one. (**a**) An image with shadow causing some urban features obscured as input. (**b**) Enhanced image with CLAHE for a better detail visibility



(a) (b)

Figure 5


Figure 4. Examples of sample Satellite image of Addis Ababa and its Mask. (**a**) An image of some place in Addis Ababa as input. (**b**) Annotated image with LabelMe



(a) (b) (c)

Figure 6

Figure 5. Examples of sample Satellite image of Addis Ababa, its Mask and class distribution. (**a**) An image of some place in Addis Ababa as input. (**b**) Annotated image with LabelMe. (**c**) urban land use disctibution



(a) (b) (c)

Figure 7

Figure 6. Qualitative Visualization. (**a**) An image of Addis Ababa as input. (**b**) Annotated image with LabelMe (**c**) Predicted semantic segmentation