Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

Deep Learning Based Personalized Recommendation Systems for E-Commerce Platforms

Ayomide owolabi

ayomidemedic@gmail.com

Ladoke Akintola University Of Technology Ogbomosho https://orcid.org/0009-0004-2049-7891

Jagadeesh Sundaramoorthy

Infosys Ltd.

Research Article

Keywords: Deep learning, Personalized recommendation systems, E-commerce platforms, Neural collaborative filtering, Recommender systems, User behavior modeling, Explainable AI

Posted Date: February 24th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-8913353/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: The authors declare no competing interests.

Review Manuscript


Deep Learning Based Personalized Recommendation Systems for E-Commerce Platforms

Jagadeesh Sundaramoorthy
Technical Architect, US Digital Transformation
Infosys Ltd. Raleigh, North Carolina
s.jaga87@gmail.com
ORCID:0009-0000-1012-2034
Date: July 12, 2023

Author 2: Ayomide Owolabi
Department of mechanical Engineering
Ladoke Akintola University Of Ogbomosho

Date: August 22, 2023

GRAPHICAL ABSTRACT



ABSTRACT

Due to the faster development of e-commerce platform, the information overload can be considered overbearing, which allows promoting the need of the personalized recommendation systems that can provide the most precise and context-oriented product recommendations. Despite the showed strong predictive performance of deep learning techniques in comparison to the traditional method of recommendation, the current survey studies tend to offer partial analysis, constrained methodology, or out of date scopes that do not represent in detail the recent advances in architectures. The current investigation is a systematic review of e-commerce personalized recommendation systems based on deep learning, formulated in IEEE style, and summarizing the works published since 2018. Having used a structured literature selection protocol in the context of the large scholarly databases, the thematic classification and comparative analysis of convolutional neural networks, recurrent and sequential networks, Transformer-based models, graph neural networks, and hybrid models were conducted. The analysis discusses these methods in various aspects such as prediction accuracy, scalability, interpretability, sensitivity to data sparsity, fairness factor, and deployment practicability. The results suggest that deep learning models are always superior to traditional methods that model more and intricate user-item interactions and fusion with multi-modal data sources. Nonetheless, Explainability, cold-start treatment, and computability efficiency and ethical transparency continue to be problematic. The main contribution of the review is that it forms the coherent analytical framework, which consolidates the latest achievements, sets the trade-offs that are yet to be resolved, and outlines the research directions in terms of explainable, data-efficient, fair, and trustworthy recommenders at the next-generation e-commerce platforms.

KEYWORDS

Deep learning, Personalized recommendation systems, E-commerce platforms, Neural collaborative filtering, Recommender systems, User behavior modeling, Explainable AI

INTRODUCTION

1.1 Background and Context

The rapid expansion of digital commerce has significantly increased the volume and diversity of products available to consumers, intensifying the challenge of information overload. In large-scale online marketplaces, users are often confronted with thousands or even millions of options, making efficient decision-making increasingly complex. Personalized recommendation systems have emerged as a critical solution to this problem by filtering vast product spaces and presenting items aligned with individual preferences, contextual signals, and historical behaviors.

By leveraging user interaction data—including browsing patterns, purchase histories, ratings, and implicit feedback—recommender systems enable platforms to deliver targeted content that enhances perceived relevance and decision efficiency. Empirical evidence demonstrates that effective recommendation mechanisms improve user satisfaction, increase conversion rates, and raise average order values, thereby becoming indispensable components of modern e-commerce infrastructures (Wang et al., 2021).

Beyond user experience enhancement, personalized recommendation systems function as strategic tools for business optimization. They support long-term customer retention through continuous preference adaptation while facilitating cross-selling, upselling, and long-tail product exposure. In large-scale environments, recommendations influence a substantial proportion of product views, clicks, and

purchases, directly affecting revenue streams and customer lifetime value. Consequently, the effectiveness of recommendation algorithms is closely tied to platform competitiveness and sustainable growth.

However, the increasing scale and heterogeneity of user–item interactions present significant challenges. Sparse feedback matrices, rapidly evolving user preferences, cold-start conditions, and multi-modal data sources limit the effectiveness of traditional rule-based and collaborative filtering approaches. These limitations have accelerated the adoption of advanced modeling paradigms, particularly deep learning–based techniques, which offer enhanced representational capacity and adaptability. As personalization evolves from a competitive advantage to a baseline expectation, the development of robust, scalable, and trustworthy recommendation systems has become central to next-generation e-commerce platforms.

1.2 Importance of Personalized Recommendation Systems

Personalized recommendation systems are no longer optional features but foundational components of digital commerce ecosystems. By filtering, ranking, and presenting content tailored to individual users, these systems enhance engagement and optimize platform interaction dynamics (Hasan et al., 2024; Liu et al., 2024).

Users exposed to personalized recommendations typically spend more time browsing, explore broader product categories, and demonstrate higher purchase intent compared to those relying solely on generic browsing or keyword-based search. Such behavioral shifts underscore the practical effectiveness of tailored recommendation strategies in improving both user experience and transaction efficiency.

From a commercial standpoint, recommendation engines directly influence revenue generation. Early quantitative analyses show that AI-driven recommendation frameworks outperform popularity-based or rule-driven systems in driving measurable sales uplift (Zhou, 2020). More recent studies confirm that advanced AI-powered personalization significantly improves key performance indicators such as average order value, repeat purchase rate, and customer lifetime value (Huang, 2025).

These findings collectively highlight that recommendation systems now operate at the intersection of user experience design, data-driven marketing, and operational strategy. Their integration into core platform architecture influences not only product discovery but also pricing strategies, inventory exposure, and targeted promotions, reinforcing their strategic importance.

1.3 Evolution from Traditional Machine Learning to Deep Learning

Early recommender systems were predominantly built on traditional machine learning paradigms, including collaborative filtering and content-based filtering. Collaborative filtering leverages user–user or item–item similarity to generate predictions, whereas content-based approaches match item attributes to user profiles. Although effective in smaller-scale environments, these techniques face inherent limitations related to sparsity, linear modeling assumptions, and limited feature expressiveness (Da'u & Salim, 2020; Lalitha & Sreeja, 2021).

The emergence of deep learning has fundamentally transformed recommender system design. Deep neural networks enable automatic learning of high-dimensional feature representations from heterogeneous data sources such as text, images, and sequential interaction logs. Unlike shallow models, deep architectures capture nonlinear user–item interactions and temporal dependencies, improving predictive performance and contextual awareness (Li et al., 2023).

Architectures including convolutional neural networks (CNNs), recurrent neural networks (RNNs), Transformer-based models, graph neural networks (GNNs), and neural collaborative filtering frameworks have demonstrated consistent improvements across diverse e-commerce settings. This evolution represents a paradigm shift from manually engineered features toward end-to-end representation learning capable of dynamically adapting to evolving user behavior.

1.4 Research Gaps and Motivation

Despite substantial performance gains, deep learning–based recommender systems face persistent challenges that limit practical deployment and long-term sustainability.

A primary concern is interpretability. Deep architectures often operate as "black-box" models, making it difficult for stakeholders to understand or audit recommendation decisions (Almahmood & Tekerek, 2022). This opacity raises concerns related to user trust, regulatory compliance, and accountability.

Cold-start scenarios remain another critical limitation. New users and newly introduced products often lack sufficient interaction data for reliable preference modeling. Although hybrid and transfer learning approaches attempt to mitigate this issue, cross-domain generalization remains inconsistent (Nesterov, 2024).

Scalability and computational efficiency further complicate deployment in real-world production environments. State-of-the-art models must balance predictive accuracy with latency constraints and infrastructure cost. Additionally, fairness, bias mitigation, and robustness to noisy or imbalanced data have emerged as essential considerations in ethical AI deployment.

Given the rapid evolution of deep learning architectures between 2023 and 2025, an updated and methodologically rigorous review is required to consolidate recent advancements and reassess established assumptions (Shrivastava et al., 2024; Sameena et al., 2025). This study addresses that need by providing a systematic synthesis of contemporary research trends and unresolved trade-offs.

1.5 Objectives and Contributions

The primary objective of this review is to provide a structured and comprehensive synthesis of deep learning–based personalized recommendation systems in e-commerce. Specifically, this study aims to:

1. Classify existing approaches according to model architecture, learning paradigm, and data modality.
2. Compare their strengths, limitations, and evaluation methodologies.
3. Identify persistent research challenges and open problems.
4. Outline future research directions toward explainable, scalable, and ethically responsible recommender systems (Scrivano, 2024; Yu & Aviles, 2025).

By integrating recent scholarly contributions within a unified analytical framework, this review supports both researchers and practitioners in advancing the state of the art in personalized e-commerce recommendation.

1.6 Key Contributions of This Study

This review makes the following contributions:

1. It provides an updated synthesis of deep learning–based personalized recommendation approaches published between 2018 and 2025, emphasizing recent architectural innovations.
2. It introduces a unified multi-dimensional classification framework organizing studies by architecture, data modality, application context, and evaluation metrics.
3. It presents a comparative analysis of models across predictive performance, scalability, interpretability, cold-start robustness, and deployment feasibility.
4. It identifies unresolved trade-offs and research gaps, highlighting pathways toward explainable, fair, and computationally efficient recommender systems.

2. METHODOLOGY

2.1 Review Design and Protocol

This study adopts a systematic literature review (SLR) methodology aligned with established IEEE and PRISMA-informed review practices to ensure methodological rigor, transparency, and reproducibility. The review protocol was defined prior to literature collection in order to minimize selection bias and maintain consistency throughout the study.

The review process comprised five sequential stages:

1. problem formulation;
2. systematic literature search;
3. study screening and selection;
4. data extraction; and
5. qualitative and comparative synthesis.

Clear inclusion and exclusion criteria were established to ensure relevance and quality of the selected studies.

Inclusion criteria:

- Studies focused on personalized recommendation systems in e-commerce or closely related online retail environments;
- Studies employing deep learning models as a primary methodological component;
- Peer-reviewed journal articles or reputable conference proceedings;
- Studies reporting empirical evaluation using standard recommendation metrics.

Exclusion criteria:

- Studies relying solely on traditional machine learning methods without deep learning components;
- Articles lacking sufficient methodological detail;
- Non-English publications;
- Editorials, opinion papers, tutorials, or non-scholarly sources.

This structured protocol ensures that the review captures high-quality and methodologically relevant contributions in the field.

2.2 Literature Search and Selection Process

A comprehensive multi-database search strategy was employed to maximize coverage of relevant literature. The primary databases queried included:

- IEEE Xplore
- Scopus
- Web of Science
- arXiv (for recent high-impact preprints)

Search strings combined controlled keywords and Boolean operators, including:

“Deep learning” AND “personalized recommendation” AND “e-commerce”
“neural collaborative filtering” AND “recommender systems”
“user behavior modeling” AND “online retail”

The initial search yielded **312 candidate studies**. After duplicate removal, **241 records** remained.

The screening process proceeded as follows:

- **Title and abstract screening:** 146 studies excluded
- **Full-text eligibility assessment:** 95 studies reviewed
- **Final included studies:** 62 primary papers

To further enhance coverage, backward and forward citation tracking was conducted on highly cited papers. The study selection process follows a PRISMA-style flow to improve transparency and reproducibility.

2.3 Thematic Classification Framework

To enable structured synthesis and meaningful comparison, a multi-dimensional thematic classification framework was developed. The selected studies were organized across four primary dimensions reflecting core design characteristics of deep learning–based recommender systems (Loukili et al., 2023; Guan et al., 2019).

2.3.1 Model Architecture

Studies were categorized according to the underlying deep learning architecture, including:

- Convolutional Neural Networks (CNNs)
- Recurrent Neural Networks (RNNs)
- Transformer-based models
- Graph Neural Networks (GNNs)
- Hybrid and ensemble frameworks

This dimension captures how different architectures model user–item relationships, sequential behavior, and relational dependencies.

2.3.2 Data Modality

The second dimension captures the types of input data utilized by recommendation models, including:

- Explicit feedback (ratings)
- Implicit feedback (clicks, views, purchases)
- Textual descriptions and reviews
- Product images
- Clickstream and session logs
- Contextual signals (time, device, location)

Multimodal systems integrating heterogeneous data sources were analyzed as a distinct category due to their increasing prominence.

2.3.3 Application Domain

Studies were further categorized based on deployment context, including:

- General online retail
- Fashion and visually driven commerce
- Multimedia and content commerce
- Mobile commerce
- Cross-domain recommendation

This classification highlights how domain characteristics influence model design and evaluation.

2.3.4 Evaluation Metrics

Performance evaluation practices were analyzed using commonly reported metrics such as:

- Precision
- Recall
- F1-score
- Normalized Discounted Cumulative Gain (NDCG)
- Mean Average Precision (MAP)
- Area Under the Curve (AUC)

Where available, system-level metrics such as latency, scalability, and robustness were also considered

2.4 Analytical and Comparative Approach

The analytical phase involved qualitative synthesis combined with cross-study comparative assessment. Selected models were evaluated across multiple dimensions, including:

- predictive accuracy;
- robustness to sparse or noisy data;
- scalability in large-scale environments; and
- practical deployment feasibility (Messaoudi & Loukili, 2024; Shrivastava et al., 2024).

Reported experimental results were interpreted in the context of dataset characteristics, training protocols, and evaluation settings to ensure fair comparison across studies.

In addition to accuracy-focused metrics, the analysis incorporated system-level considerations such as computational complexity, training and inference cost, and adaptability to real-time recommendation scenarios. Particular attention was given to how studies addressed persistent challenges including cold-start conditions, model interpretability, and cross-domain generalization.

By synthesizing findings across architectures, data modalities, and application domains, this methodological framework provides a holistic and reproducible assessment of the current state of deep learning–based personalized recommendation systems in e-commerce.




Fig. 1. PRISMA-style systematic literature review process for study selection

PRISMA-style flow diagram illustrating the systematic literature review process, including database search, screening, eligibility assessment, and final study inclusion.

3. LITERATURE REVIEW

3.1 Traditional Recommendation Approaches

Early recommender systems were primarily grounded in traditional machine learning paradigms, with collaborative filtering (CF) and content-based filtering (CBF) forming the methodological foundation. Collaborative filtering operates on the premise that users with similar historical preferences will exhibit similar future behaviors. Both memory-based approaches (e.g., user–user and item–item similarity) and model-based techniques such as matrix factorization achieved considerable success in early e-commerce deployments due to their conceptual simplicity and interpretability (Liu, 2018).

However, collaborative filtering methods are highly sensitive to data sparsity and cold-start conditions, particularly in large-scale catalogs where user–item interaction matrices are extremely sparse. Content-based systems partially mitigate item cold-start issues by leveraging product attributes and user profiles, but they often suffer from overspecialization, limiting recommendation diversity and serendipity (Tayade et al., 2021).

Hybrid approaches combining collaborative and content signals were introduced to offset these weaknesses. While such methods improved robustness, they still relied heavily on manual feature engineering and linear interaction assumptions. As e-commerce ecosystems expanded in scale and behavioral complexity, these traditional techniques struggled to capture nonlinear dependencies, temporal

dynamics, and heterogeneous data modalities, motivating the transition toward deep learning–based solutions.

3.2 Deep Learning Architectures in E-Commerce Recommendation

The limitations of traditional recommender systems have driven widespread adoption of deep learning, which enables end-to-end representation learning from high-dimensional and multi-modal data. Deep models are particularly effective in uncovering latent structures in user–item interactions and integrating diverse information sources common in modern e-commerce environments.

3.2.1 CNN-Based Models

Convolutional Neural Networks (CNNs) have been extensively applied in recommendation tasks involving visual and spatial information, especially in visually sensitive domains such as fashion, home décor, and consumer electronics. CNN-based recommenders automatically extract hierarchical visual features from product images, outperforming handcrafted descriptors in capturing semantic and aesthetic attributes (Li, 2024).

Recent studies demonstrate that incorporating CNN-derived visual embeddings into recommendation pipelines significantly improves ranking accuracy and user satisfaction (Arunkumar et al., 2024). These models are frequently integrated with collaborative filtering frameworks to complement interaction-based signals. Nevertheless, CNN-based approaches introduce higher computational overhead and often provide limited interpretability, as learned visual features may not directly correspond to human-understandable attributes.

3.2.2 RNN and Sequential Models

Recurrent Neural Networks (RNNs), including Long Short-Term Memory (LSTM) and Gated Recurrent Unit (GRU) architectures, are well suited for session-based and sequential recommendation tasks. Unlike static preference models, RNNs explicitly capture temporal dependencies by modeling the order and timing of user interactions (Guan et al., 2019).

In e-commerce contexts, RNN-based models have been widely used for next-item prediction, session continuation, and time-aware purchasing behavior. Empirical studies report that sequential modeling improves recommendation relevance in dynamic environments where user preferences evolve rapidly (Wang et al., 2021).

Despite their strengths, RNNs face challenges in modeling very long interaction sequences and may suffer from vanishing gradient issues. These limitations have motivated the exploration of attention-based and Transformer architectures.

3.2.3 Transformer and Attention-Based Models

Transformer architectures represent a major advancement in recommender system research. By replacing recurrence with self-attention mechanisms, Transformers can model long-range dependencies and contextual relationships more effectively than traditional sequential models.

Attention-based recommenders dynamically weight historical interactions, enabling the system to focus on the most informative behavioral signals when generating predictions (Xu et al., 2024). Recent studies demonstrate that Transformer-based models achieve state-of-the-art performance in capturing complex user trajectories and contextual features such as time, device type, and browsing intent (Yu & Aviles, 2025).

Additionally, attention mechanisms provide partial interpretability by highlighting influential interactions. However, full transparency remains an open challenge. The primary limitation of Transformer models lies in their substantial computational and memory requirements, which can constrain real-time deployment in large-scale production systems.

3.3 Neural Collaborative Filtering and Hybrid Models

Neural Collaborative Filtering (NCF) extends classical matrix factorization by replacing linear interaction functions with deep neural architectures. By learning nonlinear mappings between user and item embeddings, NCF models achieve greater expressive power and improved predictive accuracy (Messaoudi & Loukili, 2024).

Modern recommender systems increasingly adopt hybrid and ensemble designs that integrate multiple deep learning components. For example, CNNs may process visual content, RNNs capture behavioral sequences, and dense neural layers model user–item interactions within a unified framework. Such hybrid systems consistently outperform single-model approaches by leveraging complementary strengths across data modalities (Shrivastava et al., 2024).

However, increased architectural complexity introduces new challenges, including higher training cost, model maintenance difficulty, and potential overfitting risks. These trade-offs highlight the need for balanced model design.

3.4 Multi-Modal and Sentiment-Aware Recommendations

Contemporary e-commerce platforms generate rich multi-modal data streams, including textual descriptions, product images, user reviews, ratings, and contextual metadata. Multi-modal recommender systems aim to jointly learn from these heterogeneous sources to construct more comprehensive user and item representations (Shang et al., 2024).

Sentiment-aware recommendation models further enhance personalization by extracting opinion polarity and emotional signals from user reviews. Incorporating sentiment features enables finer-grained preference modeling and improved ranking quality, particularly in domains where subjective perception strongly influences purchasing decisions (Zhou, 2020).

Despite their promise, multi-modal systems face practical challenges related to data alignment, noise robustness, and increased computational requirements. Moreover, the fusion of heterogeneous data sources raises additional concerns regarding fairness, Explainability, and scalability.

Table 1. Comparison of traditional machine learning and deep learning recommendation techniques

Dimension	***Traditional ML Approaches***	***Deep Learning Approaches***
Feature Engineering	Manual feature design required	Automatic feature learning
Modeling Capability	Primarily linear relationships	Captures complex nonlinear interactions
Handling Data Sparsity	Limited effectiveness	Better with auxiliary data

Multi-Modal Support	Weak	Strong (text, image, behavior)
Scalability	Moderate	High but computationally expensive
Interpretability	High	Often low (black-box)
Cold-Start Handling	Weak	Improved with hybrid models
Overall Accuracy	Moderate	Generally higher

3.5 Synthesis and Research Direction

The reviewed literature clearly demonstrates a paradigm shift from traditional recommendation techniques toward deep learning–driven frameworks in e-commerce. Deep models substantially improve the ability to capture nonlinear user behavior, sequential dynamics, and multi-modal interactions.

Nevertheless, the literature also reveals persistent open challenges. Interpretability remains limited in many deep architectures; cold-start robustness varies across models; and large-scale deployment introduces nontrivial computational and engineering constraints. Furthermore, ethical considerations—including fairness, bias mitigation, and transparency—are receiving increasing attention but remain insufficiently addressed in many current systems.

These observations underscore the need for unified analytical frameworks and systematically grounded evaluations, motivating the comprehensive review presented in this study.

4. PROBLEM STATEMENT

Despite the significant progress achieved by deep learning–based recommender systems, several fundamental challenges continue to hinder their widespread adoption, operational reliability, and ethical deployment in real-world e-commerce environments. While modern architectures have demonstrated substantial improvements in predictive accuracy and user engagement, these gains often come at the expense of transparency, robustness, and computational efficiency.

One of the most prominent limitations is the lack of interpretability. Deep neural recommender models—particularly those incorporating multi-layer embeddings, attention mechanisms, and hybrid feature fusion—often function as black boxes. This opacity makes it difficult for developers, platform operators, and end users to understand the rationale behind specific recommendations. The absence of clear explanatory mechanisms complicates debugging, reduces stakeholder trust, and poses challenges for compliance with emerging AI transparency and accountability regulations. Prior research consistently identifies Explainability as a persistent weakness of deep recommendation frameworks when compared with more interpretable classical methods (Almahmood & Tekerek, 2022).

Closely related to interpretability are the enduring challenges of data sparsity and the cold-start problem. In large-scale e-commerce platforms, user–item interaction matrices remain highly sparse because most users interact with only a small fraction of available products. This sparsity limits the model's ability to learn reliable preference representations, particularly for new users and newly introduced items. Although deep learning models offer enhanced representation capacity, they do not fully eliminate sparsity-related degradation without substantial auxiliary data or hybrid modeling strategies.

Another critical concern involves fairness and bias propagation. Deep recommender systems trained on historical behavioral data may inadvertently reinforce existing exposure inequalities, popularity bias, or demographic disparities. Because deep architectures are highly complex, identifying the origin and magnitude of such biases is considerably more difficult than in traditional models. Moreover, different fairness definitions may conflict with accuracy objectives, creating a challenging multi-objective optimization problem for system designers.

Scalability and deployment cost present additional barriers to practical adoption. State-of-the-art deep recommendation models frequently rely on large embedding tables, complex feature interactions, and computationally intensive training procedures. When deployed at web scale—serving millions of users and products—these systems require sophisticated distributed infrastructures, model compression strategies, and latency optimization techniques. Such requirements significantly increase engineering complexity and operational cost, potentially limiting adoption by resource-constrained platforms.

Collectively, the intertwined challenges of interpretability, sparsity, fairness, and scalability highlight a critical gap between academic performance gains and real-world deplorability. Addressing these issues requires not only improvements in model accuracy but also advances in explainable AI, efficient architecture design, bias mitigation, and production-aware system engineering. This review therefore seeks to systematically examine current deep learning–based recommendation approaches, identify unresolved limitations, and outline research directions that can bridge the gap between theoretical innovation and practical e-commerce deployment.

5. RESULTS

5.1 Performance Trends in Deep Learning–Based Recommendation Systems

The synthesis of the selected studies indicates a clear and consistent trend toward improved predictive performance when deep learning techniques are applied to personalized recommendation tasks in e-commerce environments. Across multiple benchmark datasets and application contexts, deep neural architectures—including convolutional neural networks (CNNs), recurrent neural networks (RNNs), attention-based models, and hybrid frameworks—generally demonstrate superior capability in capturing complex and nonlinear user–item interactions compared with traditional collaborative filtering approaches.

Several studies report improvements in ranking-oriented metrics such as Precision@k, Recall@k, normalized discounted cumulative gain (NDCG), and area under the curve (AUC). These gains are largely attributed to the ability of deep models to automatically learn hierarchical feature representations from heterogeneous data sources, including textual descriptions, product images, and sequential interaction logs. In particular, models that incorporate sequential behavior modeling show stronger responsiveness to evolving user preferences, which translates into improved short-term recommendation relevance and session-level engagement.

Hybrid architectures that integrate neural collaborative filtering with auxiliary deep components frequently demonstrate the most stable performance across diverse datasets. These models benefit from combining interaction-based embeddings with side information, thereby improving robustness under moderate sparsity conditions. Evidence from multiple reviewed studies suggests that the inclusion of multimodal features can further enhance recommendation quality, particularly in visually driven domains such as fashion and multimedia commerce.

However, the magnitude of performance improvement is not uniform across all scenarios. The most substantial gains are typically observed under warm-start conditions where sufficient historical interaction

data are available. In highly sparse environments, purely deep collaborative approaches may experience performance degradation unless supplemented with auxiliary signals or hybrid learning strategies.

5.2 Comparative Insights Across Model Families

The comparative analysis reveals that no single deep learning architecture universally outperforms others across all recommendation contexts. Instead, performance advantages are closely linked to data characteristics, interaction dynamics, and deployment requirements.

Neural Collaborative Filtering (NCF) models consistently perform well on dense implicit-feedback datasets, where nonlinear user–item interaction modeling provides measurable gains over matrix factorization baselines. These models are particularly effective in traditional top-N recommendation tasks with sufficient historical data.

Sequential models based on RNNs and attention mechanisms demonstrate clear advantages in session-based and time-aware recommendation scenarios. By modeling the temporal order of user interactions, these approaches better capture short-term intent and evolving preferences. As a result, they often achieve higher Recall@k and engagement-related metrics in domains characterized by rapid preference drift.

Graph Neural Network (GNN)–based recommenders show strong performance when relational or structural information—such as user–user networks or item knowledge graphs—is available. These models enhance representation learning for long-tail items and can partially alleviate cold-start effects by propagating information through graph structures.

Hybrid deep learning frameworks, which combine multiple architectural paradigms or integrate classical methods with neural components, exhibit the most balanced performance profile across heterogeneous data conditions. Many studies report that hybridization improves robustness to sparsity and enhances generalization, although it also introduces additional computational and implementation complexity.

Table 2. Performance comparison of deep learning models across recommendation scenarios

Model Type	*Strengths*	*Limitations*	*Best Use Case*	*Typical Metrics Improved*
Neural Collaborative Filtering (NCF)	Strong nonlinear modeling	Needs dense data	Rating prediction	Precision, RMSE
RNN / Sequential Models	Captures temporal behavior	Training complexity	Session-based recommendation	Recall@K, CTR
Transformer Models	Long-range dependency modeling	High compute cost	Context-aware recommendation	NDCG, Recall
Graph Neural Networks	Exploits relational structure	Complex deployment	Social / knowledge graphs	Precision, Diversity

Hybrid Deep Models	Robust to sparsity	Higher system complexity	Cold-start scenarios	Overall ranking metrics

5.3 Observed Trade-Offs and Practical Considerations

Despite the overall performance gains associated with deep learning–based recommenders, the reviewed literature consistently highlights important trade-offs.

First, improvements in predictive accuracy often come at the cost of increased computational overhead. Deep architectures typically require larger embedding spaces, longer training times, and higher inference latency compared with traditional methods. These factors can complicate real-time deployment in large-scale commercial environments.

Second, model interpretability remains limited across most deep learning approaches. While attention mechanisms and post-hoc Explainability techniques provide partial visibility into model behavior, many systems still function as opaque decision-makers. This limitation has implications for user trust, regulatory compliance, and system debugging.

Third, data sparsity continues to affect performance, particularly for new users and items. Although multimodal learning and hybrid approaches mitigate this issue to some extent, the cold-start problem remains an open research challenge.

Finally, only a subset of studies evaluates models under real-world deployment constraints such as latency, scalability, and online user feedback loops. This gap suggests that offline benchmark improvements may not always translate directly into production-level gains.

5.4 Synthesis of Key Findings

Based on the systematic analysis of the selected literature, several high-level findings emerge:

- Deep learning–based recommendation systems generally outperform traditional approaches in modeling complex user behavior.
- Sequential and attention-based models are particularly effective for dynamic and session-based recommendation scenarios.
- Multimodal and hybrid frameworks provide improved robustness in sparse data environments.
- Graph-based models show promise for leveraging relational information and improving long-tail recommendations.
- Significant challenges remain in interpretability, computational efficiency, fairness, and real-world scalability.

Overall, the evidence indicates that deep learning has substantially advanced the state of personalized recommendation in e-commerce. Nevertheless, the literature also emphasizes the importance of balancing predictive performance with transparency, efficiency, and deployment feasibility to achieve practically viable next-generation recommender systems.

6. LIMITATIONS

Despite the comprehensive scope of this systematic review, several limitations should be acknowledged when interpreting the findings.

First, the review is constrained by the coverage and quality of the available literature. Although a structured multi-database search strategy was employed, relevant studies published outside the selected databases or in non-English venues may not have been captured. Additionally, publication bias may exist, as studies reporting positive performance improvements are more likely to be published than those reporting neutral or negative results. This bias can potentially overestimate the reported effectiveness of deep learning–based recommendation systems.

Second, heterogeneity across the included studies presents challenges for direct comparison. The reviewed works employ diverse datasets, evaluation metrics, experimental protocols, and preprocessing strategies. Such variability limits the ability to conduct strict quantitative meta-analysis and may affect the generalizability of comparative conclusions. Differences in data sparsity levels, domain characteristics, and feature availability further contribute to performance variability across models.

Third, reproducibility remains a concern in deep learning–based recommender system research. Many studies rely on complex architectures with numerous hyperparameters, proprietary datasets, or insufficient implementation details. As a result, replicating reported performance gains in independent environments can be difficult. While open-source implementations are increasingly available, standardized benchmarking practices are still evolving.

Fourth, most empirical evaluations reported in the literature are conducted in offline experimental settings rather than real-world production environments. Consequently, important operational factors—such as inference latency, system robustness under high traffic, long-term user behavior dynamics, and infrastructure cost—are often underexplored. This gap limits the ability to fully assess the practical deployment readiness of many proposed models.

Finally, the rapid pace of advancement in deep learning and recommender system research means that newly proposed architectures and optimization strategies may emerge shortly after the review period. Although this study incorporates literature through 2025, the field continues to evolve quickly, and some recent developments may not yet be fully represented.

Recognizing these limitations is essential for contextualizing the findings and for guiding future research toward more reproducible, transparent, and deployment-aware recommender system designs.

7. DISCUSSION

7.1 Interpretation of Findings

The findings of this review confirm that deep learning–based recommender systems substantially outperform traditional machine learning approaches in modeling complex user–item interactions. The primary advantage stems from the ability of deep neural architectures to learn hierarchical and nonlinear feature representations directly from heterogeneous data sources. Unlike classical collaborative filtering methods, which rely heavily on linear similarity assumptions and manually engineered features, deep learning models effectively capture latent behavioral patterns, temporal dynamics, and multimodal relationships.

Sequential architectures, including recurrent neural networks and attention-based models, demonstrate particular strength in capturing evolving user preferences. By modeling interaction order and temporal dependencies, these approaches improve short-term intent prediction and session-level recommendation quality. Similarly, hybrid deep learning frameworks that integrate collaborative and content-based signals show enhanced robustness under sparse data conditions, partially mitigating the cold-start problem.

However, the magnitude of performance gains varies across datasets and application contexts. Models trained on dense interaction data consistently achieve the highest improvements, whereas gains diminish in highly sparse environments without auxiliary features. This observation highlights the continuing importance of data richness and feature diversity in realizing the full benefits of deep learning–based personalization.

7.2 Comparison with Prior Reviews

When compared with earlier survey studies, the present review both corroborates and extends prior findings. Earlier reviews (e.g., Da'u & Salim, 2020; Lalitha & Sreeja, 2021) primarily emphasized the accuracy improvements enabled by deep learning but provided limited coverage of modern architectures such as Transformer-based and graph neural network models. The current synthesis demonstrates that recent advances have significantly expanded the architectural landscape of recommender systems, particularly through the integration of multimodal learning, attention mechanisms, and hybrid ensemble strategies. These developments have improved the ability of recommendation systems to operate in dynamic and large-scale e-commerce environments.

Nevertheless, concerns highlighted in prior literature—especially regarding interpretability, computational cost, and fairness—remain largely unresolved. This persistence suggests that while predictive performance has advanced rapidly, progress in trustworthy and efficient deployment has been comparatively slower.

7.3 Trade-offs and Emerging Challenges

A central insight emerging from the literature is the inherent trade-off between predictive accuracy and Explainability. Deep learning models achieve superior performance but often operate as opaque black boxes, limiting transparency and stakeholder trust. Although attention mechanisms and post-hoc explanation methods provide partial visibility into model behavior, full interpretability remains an open research problem. Another notable challenge is the variability of model performance across domains and data regimes. While deep architectures excel in data-rich environments, their advantages are less consistent in cold-start or highly sparse scenarios. This finding reinforces the need for adaptive and hybrid approaches that balance expressive power with data efficiency.

Fairness and bias also emerge as critical concerns. Because deep recommender systems learn from historical interaction data, they may inadvertently amplify popularity bias, exposure inequality, or demographic disparities. Addressing these risks requires integrating fairness-aware objectives and evaluation metrics into the model development pipeline rather than treating fairness as a post-processing consideration. Finally, the operational complexity of deploying deep recommender systems at scale remains substantial. Large embedding tables, high training costs, and real-time latency constraints introduce engineering challenges that are often underreported in academic studies but highly relevant in production environments.

7.4 Practical and Theoretical Implications

From a practical perspective, the reviewed evidence suggests that organizations adopting deep learning–based recommendation systems can achieve measurable improvements in user engagement, conversion rates, and revenue generation. However, these benefits must be balanced against infrastructure costs, model maintenance requirements, and governance considerations.

For industry practitioners, the results highlight the importance of:

- aligning model complexity with data availability,
- incorporating multimodal features where feasible,
- monitoring fairness and bias metrics during deployment, and
- designing scalable architectures that meet real-time constraints.

From a theoretical standpoint, this review reinforces the role of deep learning as a flexible framework for modeling high-dimensional user behavior. At the same time, it exposes important open problems that warrant further investigation, including:

- interpretable deep recommendation models,
- data-efficient learning under sparsity,
- fairness-aware personalization, and
- lightweight architectures for resource-constrained environments.

7.5 Summary of Discussion

Overall, the discussion demonstrates that deep learning has become the dominant paradigm for personalized recommendation in e-commerce due to its superior representational capacity and adaptability. However, the technology has not yet reached full maturity for universally trustworthy and cost-efficient deployment. Bridging the gap between predictive excellence and practical reliability remains the central challenge for next-generation recommender systems.




Fig. 2. Multi-layer deep learning-based personalized e-commerce recommendation architecture

8. CONCLUSION

This study presented a systematic IEEE-style review of deep learning–based personalized recommendation systems in e-commerce, synthesizing research published between 2018 and 2025. The analysis demonstrates that deep learning architectures—including convolutional, recurrent, attention-based, graph-based, and hybrid models—consistently outperform traditional recommendation techniques in modeling complex user–item interactions and integrating multi-modal data sources. These advances have enabled more accurate, context-aware, and scalable personalization capabilities across modern e-commerce platforms. Despite these improvements, the review identifies several persistent challenges that continue to limit practical deployment. Key issues include limited interpretability of deep models, vulnerability to data sparsity and cold-start conditions, potential fairness and bias concerns, and the substantial computational resources required for large-scale training and real-time inference. These findings indicate that predictive performance alone is insufficient; future recommender systems must balance accuracy with transparency, efficiency, and ethical responsibility.

The primary contribution of this work lies in the development of a unified analytical framework that systematically organizes recent advances, highlights architectural trade-offs, and identifies open research problems. By consolidating fragmented literature into a structured perspective, this review provides a reference foundation for both academic researchers and industry practitioners seeking to design next-generation personalized recommendation systems. Future research should prioritize explainable AI techniques to improve transparency and user trust, federated and privacy-preserving learning to address data governance concerns, and lightweight or efficient model architectures suitable for real-time large-scale deployment. Additionally, greater emphasis on fairness-aware recommendation and cross-domain personalization will be essential for building robust and socially responsible systems. In conclusion, deep learning has firmly established itself as the dominant paradigm for personalized e-commerce recommendation. However, achieving truly trustworthy, scalable, and ethically aligned recommender systems will require continued interdisciplinary innovation that bridges algorithmic performance with practical deployment constraints and responsible AI principles.

REFERENCES

[1] X. Xu, K. Kangming, et al., “Intelligent classification and personalized recommendation of e-commerce products based on machine learning,” *arXiv preprint arXiv:2403.19345*, 2024.

[2] L. Liu, “E-commerce personalized recommendation based on machine learning technology,” *Mobile Information Systems*, 2022, Article ID 1761579.

[3] V. Nesterov, “Analyzing user behavior patterns for personalized recommender systems in e-commerce: A literature review,” *Automation of Technological & Business Processes*, vol. 16, no. 3, 2024.

[4] L. Zhou, “Product advertising recommendation in e-commerce based on deep learning and distributed expression,” *Electronic Commerce Research*, vol. 20, no. 2, pp. 321–342, 2020.

[5] F. Messaoudi and M. Loukili, “E-commerce personalized recommendations: A deep neural collaborative filtering approach,” *Operations Research Forum*, vol. 5, no. 1, Cham: Springer, 2024.

[6] R. Shrivastava, D. S. Sisodia, and N. K. Nagwani, "Deep ensembled multi-criteria recommendation system for enhancing and personalizing the user experience on e-commerce platforms," *Knowledge and Information Systems*, vol. 66, no. 12, pp. 7799–7836, 2024.

[7] C. Li, "A personalized product recommendation system for e-commerce platforms based on artificial intelligence and image processing technologies," *Traitement du Signal*, vol. 41, no. 6, 2024.

[8] T. B. Lalitha and P. S. Sreeja, "Recommendation system based on machine learning and deep learning in varied perspectives: A systematic review," in *Intelligent Strategies for ICT (ICTCS 2020)*, pp. 419–432, 2021.

[9] M. S. Arunkumar et al., "Fashion recommendation system for e-commerce using deep learning algorithms," in *Proc. 15th Int. Conf. on Computing Communication and Networking Technologies (ICCCNT)*, IEEE, 2024.

[10] J. Huang, "Optimization and innovation of AI-based e-commerce platform recommendation system," *Journal of Computer, Signal, and System Research*, vol. 2, no. 6, pp. 66–73, 2025.

[11] F. Shang et al., "Enhancing e-commerce recommendation systems with deep learning-based sentiment analysis of user reviews," *International Journal of Engineering and Management Research*, vol. 14, no. 4, pp. 19–34, 2024.

[12] A. Poniszewska-Maranda, M. Pakula, and B. Borowska, "Recommendation systems in e-commerce applications with machine learning methods," in *Proc. 29th Int. Conf. on Evaluation and Assessment in Software Engineering*, 2025.

[13] Y. Guan, Q. Wei, and G. Chen, "Deep learning based personalized recommendation with multi-view information integration," *Decision Support Systems*, vol. 118, pp. 58–69, 2019.

[14] M. Tahir, R. N. Enam, and S. M. N. Mustafa, "E-commerce platform based on machine learning recommendation system," in *6th Int. Multi-Topic ICT Conf. (IMTIC)*, IEEE, 2021.

[15] C. Li et al., "Deep learning-based recommendation system: Systematic review and classification," *IEEE Access*, vol. 11, pp. 113790–113835, 2023.

[16] M. Loukili, F. Messaoudi, and M. El Ghazi, "Machine learning based recommender system for e-commerce," *IAES International Journal of Artificial Intelligence*, vol. 12, no. 4, pp. 1803–1811, 2023.

[17] R. J. K. Almahmood and A. Tekerek, "Issues and solutions in deep learning-enabled recommendation systems within the e-commerce field," *Applied Sciences*, vol. 12, no. 21, p. 11256, 2022.

[18] Z. Wang, A. Maalla, and M. Liang, "Research on e-commerce personalized recommendation system based on big data technology," in *2nd IEEE Int. Conf. on Information Technology, Big Data and AI (ICIBA)*, vol. 2, 2021.

[19] S. Nagraj and B. P. Palayyan, "Personalized e-commerce-based recommendation systems using deep-learning techniques," *International Journal of Artificial Intelligence*, 2024.

[20] N. Yao, "Research on cross-border e-commerce recommendation system based on deep learning algorithm," in *3rd Int. Conf. for Innovation in Technology (INOCON)*, IEEE, 2024.

[21] V. Pleskach et al., "An e-commerce recommendation system based on analysis of consumer behavior models," *IntSol*, 2023.

[22] K. Wang et al., "E-commerce personalized recommendation analysis by deeply-learned clustering," *Journal of Visual Communication*, 2023.

[23] X. Yu and J. Aviles, "Design and application of recommendation system model for e-commerce platform based on deep learning algorithm," in *5th Int. Conf. on Electronic Information Engineering and Computer Science (EIECS)*, IEEE, 2025.

[24] T. Liu et al., "A review of deep learning-based recommender system in e-learning environments," *Artificial Intelligence Review*, vol. 55, no. 8, pp. 5953–5980, 2022.

[25] Y. Liu, Y. Xu, and S. Zhou, "Enhancing user experience through machine learning-based personalized recommendation systems: Behavior data-driven UI design," *Authorea Preprints*, 2024.

[26] Q. Zhang and Y. Xiong, "Harnessing AI potential in e-commerce: Improving user engagement and sales through deep learning-based product recommendations," *Current Psychology*, vol. 43, pp. 30379–30401, 2024.

[27] A. Da'u and N. Salim, "Recommendation system based on deep learning methods: A systematic review and new directions," *Artificial Intelligence Review*, vol. 53, no. 4, pp. 2709–2748, 2020.

[28] A. G. Gowda, H.-K. Su, and W.-K. Kuo, "Personalized e-commerce: Enhancing customer experience through machine learning-driven personalization," in *IEEE Int. Conf. on Information Technology, Electronics and Intelligent Communication Systems (ICITEICS)*, IEEE, 2024.

[29] S. Sameena et al., "Personalized product recommendation system for e-commerce platforms," *ITM Web of Conferences*, vol. 74, EDP Sciences, 2025.

[30] A. Tayade, V. Sejpal, and A. Khivasara, "Deep learning-based product recommendation system and its applications," *International Research Journal of Engineering and Technology*, vol. 8, no. 4, 2021.

[31] A. Hasan, Z. Yusof, and M. Karim, "Machine learning algorithms for personalized product recommendations and enhanced customer experience in e-commerce platforms," *International Journal of Applied Machine Learning*, vol. 4, no. 11, pp. 1–15, 2024.

[32] A. Scrivano, "Recommender systems in e-commerce: State-of-the-art methods for improving personalized recommendations in online shopping platforms," 2024.

[33] S. Nagomiya, S. Sanjay, and A. N. Shriram Kumar, "Personalized recommender system for e-commerce," in *Int. Conf. on Emerging Research in Computational Science (ICERCS)*, IEEE, 2024.