Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

Multimodal Fusion of EEG and Physiological Signals for Robust Emotion Recognition via Machine Learning

Shital R.Shegokar

shital1703@gmail.com

Poornima University https://orcid.org/0009-0003-9284-9334

Research Article

Keywords: Multimodal Fusion, EEG, Emotion Recognition, Machine Learning, Affective Computing, Bio signal Processing.

Posted Date: February 26th, 2026

DOI: https://doi.org/10.21203/rs.3.rs-8966083/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: The authors declare no competing interests.

Multimodal Fusion of EEG and Physiological Signals for Robust Emotion Recognition via Machine Learning

Shital R. Shegokar [1, a], Devendra Kumar Somwanshi[2, b]

[1]Research Scholar, Department of Electrical & Electronics Engineering, Poornima University, Jaipur, India

[2]Department of Electrical & Electronics Engineering, Poornima University, Jaipur, India

[a]Shital1703@gmail.com

[b]imdev.som@gmail.com

Abstract

Emotion recognition based on physiological activity has become a vital component of affective computing and human–machine interaction. Electroencephalography (EEG) offers direct neural insight into emotional processing but suffers from noise sensitivity, motion artifacts, and high inter-subject variability. Peripheral physiological signals such as electrocardiography (ECG), galvanic skin response (GSR), photoplethysmography (PPG), and respiration provide stable indicators of autonomic changes but lack the specificity necessary for distinguishing subtle emotional states. Multimodal fusion has emerged as a promising solution by integrating complementary bio signals to build more reliable and generalizable affect-recognition models. This study presents a comprehensive review of multimodal EEG–physiology fusion systems, examining fusion strategies, representation-learning approaches, robustness challenges, and cross-subject generalization. Evidence from recent literature shows that unimodal EEG systems typically achieve 60–72% accuracy, while multimodal fusion methods reach 82–90%, and advanced hybrid deep-fusion architectures exceed 92% in subject-independent evaluations. Key limitations persist, including heterogeneous feature spaces, misaligned modalities, sensor noise, and dataset inconsistencies. The synthesis identifies hybrid deep-learning fusion as the most resilient and effective strategy, establishing multimodal physiological learning as a foundational pathway toward future real-time, noise-robust, and generalizable emotion-recognition technologies.

Keywords

Multimodal Fusion; EEG; Emotion Recognition; Machine Learning; Affective Computing; Bio signal Processing.

1. Introduction

Automatic detection of the human emotional conditions is one of the key conditions of the next generation of intelligent systems especially in health care monitoring, adaptive learning systems and human computer interaction (HSI). Although classical models of emotion recognition have mainly focused on behavioural signals (e.g. facial expressions and speech patterns) visible to the eyes, these modes of expression are inherently constrained as they can be subject to voluntary

suppression and social masking. There has therefore been a shift in the direction of the field where physiological signal analysis is offered as an objective, continuous measure of an affective condition based on internal biological activities. Compared to external expressions of emotion, physiological expressions are controlled by both the central and autonomic nervous systems, giving it a good ground truth, which cannot be consciously controlled by a subject, which makes it more valid in high-stakes applications such as mental health assessment and fatigue in driving [1].

Electroencephalography (EEG) is a key portal into the central nervous system (CNS), which records sustained neural activity of high frequencies related to cognitive functioning and the process of emotional regulation. It is temporally highly resolved and can process fast affective variations that are not detected by slower physiological sources. Nevertheless, there exist several constraints to practical EEG-based emotion recognition that lie in the fact that EEG signals are highly non-stationary, prone to muscle artifacts, eye movement, and environmental noise, and the large inter-subject variability, which inhibits the performance of traditional classifiers on unknown subjects and blocks cross-subject generalization [2]. Simultaneously, peripheral autonomic monitors like electrocardiography (ECG), galvanic skin response (GSR), and respiration are more stable measures of stress and arousal but fail to differentiate between arousal similar but valence different emotions, like anger and excitement [3]. To overcome such drawbacks, multimodal fusion methods have become popular, which unites the high-temporization of EEG with the complementary, strong information of peripheral signals to comprehensively represent the emotional states. Other more recent developments that include hybrid fusion models, attention, and transformer models, also increase the classification accuracy and robustness even in the case of sensor failure or a partial signal loss [4].

Over the past decade, multimodal emotion recognition has advanced considerably, particularly through the integration of EEG with peripheral physiological signals. Combining neural and autonomic information consistently improves performance compared to unimodal approaches. For example, Li et al. achieved high dimensional accuracy on the DEAP dataset (95.89% arousal, 94.99% valence) by modeling cross-modal correlations and heterogeneity within deep networks [5]. Deep learning strategies, including EEG signal reconstruction and extraction of time-, frequency and time-frequency features from EEG, ECG, and PPG, have further enhanced classification, achieving up to 96.12% binary and 94.25% multiclass accuracy in naturalistic emotion tasks. Parallel fusion models employing graph convolution and recurrent architectures effectively integrate EEG functional connectivity with ECG temporal dynamics, outperforming baseline methods on DREAMER [6]. Attention-based hybrid models, such as Att-1DCNN-GRU, demonstrate improved generalization, with valence estimation reaching 95.95% on DREAMER and comparable results on DEAP [7]. Classical machine-learning approaches, including SVM, decision trees, and KNN, also show enhanced fusion performance over single modalities [8]. Recent trends favor learned cross-modal representations over handcrafted features, with transformer and attention-based models capturing complex interdependencies between EEG and peripheral signals [9]. Concurrently, the development of multimodal datasets incorporating EEG, GSR, PPG, facial video, and subjective ratings facilitates evaluation and generalization. Overall, integrating EEG specificity with peripheral robustness through multimodal fusion offers enhanced emotion classification, stability, and practical applicability [10, 11].

However, not all of these methodology improvements resolve several issues, such as the coordination of asynchronous streams of data, the explainability of complex deep fusions, and the lack of frameworks that can theoretically work with missing information in real-time. The current paper analyzes how fusion strategies have changed, their usefulness in rejecting noise and inter-subject variability. This study combines the results of large datasets like the DEAP [12] and SEED [13] and points to the major trends in architectural design and builds a roadmap to support the creation of more adaptive, noise-tolerant, and interpretable affective computing systems [5].

2. METHODOLOGY

This article introduces a multimodal theory of emotion recognition that combines electroencephalographic, with peripheral physiological data by the use of machine learning strategies of fusion. The new methodology will have the complementary nature of neural and autonomic responses to harness and increase the accuracy of emotion classification, resistance to noise, and cross-subjects generalization. The general pipeline is formed by the data acquisition, pre-processing, feature extraction, multimodal fusion, and classification and performance evaluation. As shown in figure 1




Figure 1 Methodological flowchart illustrating the complete multimodal emotion-recognition pipeline from signal acquisition to model evaluation.

Dataset and Feature Extraction

A. DEAP dataset and Data Pre-processing.

The experiment was conducted on the DEAP dataset [12], designed by a group of researchers at Queen Mary University of London, a large open source dataset of physical cues and emotional judgments. In its induced EEG, ECG, EMG, data collection experiment and other bioelectrical signals were noted and recorded as 32 participants were viewing 40 music videos and various emotional inclinations, some half an hour or so each video. The subjects rated the videos after that on a scale of 1-9 in relation to Arousal, Valence, Liking, Dominance and Familiarity. The rating score between small and large indicated that the indices were negative through positive, respectively. Weak to strong, respectively. The 40 videos of stimuli were used. There were 20 high valence/arousal and 20 low valence/arousal stimuli. The first 32-channel EEG was used in this paper. Signals in DEAP dataset that had been pre-processed by down-sampling to 128 Hz, band-pass 4-45Hz, withdrawing the common average and eliminating ocular artifacts by blind source separation algorithms. The duration of the EEG signals processed by the denoising algorithm take 63-s, 60-s each trail. One of the totals has a watching before watch and 3-s video watching of 8,064 readings for each channel.

B. Feature Extraction

Extraction of features is a central step in multimodal emotion recognition systems since it allows the transformation of the raw physiological data to a small and discrimination representation. The frequency-domain analysis is largely used in EEG-based emotion recognition because it has a high neurophysiological interpretation, and it is more or less robust to signal non-stationary. Power Spectral Density (PSD) estimation is the most popular frequency-domain estimate used to describe emotion related neural oscillations.

Given a discrete EEG signal x (n) of length N, the PSD at frequency f is commonly estimated using the Discrete Fourier Transform (DFT) as:

$$PSD\ (f) = \frac{1}{N}\left\lfloor \sum_{n=1}^{N} x(n) e^{-j2\pi f n/N} \right\rfloor^2 \quad (1)$$

In this formulation, the EEG signal is turned off the time domain into the frequency domain and the power of the signal of each frequency part is measured. PSD values are in most cases averaged over canonical EEG frequency bands, that is, delta (0.5 to 4 Hz), theta (4 to 8 Hz), alpha (8 to 13 Hz), beta (13 to 30 Hz), and gamma (>30 Hz) which are known to carry emotional arousal, valence, attention processes and cognitive load. Subsequently, band-limited PSD characteristics are a stable and physiologically relevant representation of EEG-based emotion recognition.

Besides EEG, peripheral physiological cues are also often used in modelling autonomic nervous system processes that are complementary to central neural activity. Heart rate variability (HRV) features based on electrocardiogram (ECG) are widely used because they are sensitive to

emotional and stress responses. One HRV measure based on time is the Root Mean Square of Successive Differences (RMSSD) which is defined as:

$$HRV_{RMSSD} = \sqrt{\frac{1}{M-1}\sum_{i=1}^{M-1}(RR_{i+1} - RR_i)^2} \quad (2)$$

Where, RR_i indicates the period between consecutive R-peaks and M is the number of the RR intervals. RMSSD records short term beat-beat variation and is the main expression of the actions of the parasympathetic nervous system. Therefore, HRV-related features offer additional emotional data to EEG-derived frequency-domain features. The combination of PSD-derived EEG characteristics and HRV-derived peripheral characteristics form the system staple signal-processing underpinnings, of which numerous publications on multimodal emotion recognition contain.

C. **Fusion Strategy Evaluation**

To synthesize heterogeneous physiological properties, an array of multimodal fusion measures has been explored, and may be broadly divided into the early fusion, late fusion and hybrid fusion approaches. These plans vary in the point where information across several modalities would be integrated.

In early fusion, feature vectors that are specific to a given modality are combined together on the input level:

$$F_{early} = [F_{EEG} \;||\; F_{periph}] \quad (3)$$

Although this method allows for the collaborative learning of features across modalities, it may be adversely affected by high dimensionality and susceptibility to noisy or missing channels.

Late fusion, conversely, combines the prediction made at the decision level based on modality-specific predictions by summing up the posterior probabilities.

$$P_{late}(y \mid x) = \alpha P_{EEG}(y \mid x) + (1-\alpha)P_{periph}(y \mid x) \quad (4)$$

This formulation corresponds to a **late (decision-level) fusion strategy**, in which posterior probabilities obtained from modality-specific classifiers are combined through a weighted linear aggregation. Here, $P_{EEG}(y \mid x)$ and $P_{periph}(y \mid x)$denote the class posterior probabilities predicted from EEG and peripheral physiological signals, respectively, while $\alpha \in [0, 1]$ controls their relative contribution. Late fusion enables independent optimization of each modality and provides increased robustness to noisy or missing sensor data, as cross-modal integration is performed at the decision stage rather than at the feature level.

Hybrid fusion approaches combine the advantages of early and late fusion by integrating both low-level features and high-level learned representations:

$$F_{hybrid} = \phi(W_1[F_{EEG} \;||\; F_{periph}] \;+\; W_2[h_{EEG} \;||\; h_{periph}]) \quad (5)$$

This formulation represents a **hybrid fusion strategy**, in which both low-level handcrafted features and F_{EEG} and F_{periph} high-level learned representations from multiple physiological modalities are jointly

integrated. Here, denote modality-specific feature vectors extracted from EEG and peripheral signals, respectively, while h_{EEG} and h_{periph} correspond to latent representations learned by modality-specific models. The concatenated representations are projected into a shared feature space through learnable weight matrices W1 and W2, and subsequently transformed by a nonlinear activation function $\phi(.)$ By simultaneously exploiting feature-level and representation-level information, hybrid fusion enables more expressive cross-modal interaction modelling and has been shown to provide improved performance compared to early or late fusion strategies.

Model Training and Evaluation: The supervised process of the proposed model is to be trained with the help of the categorical cross-entropy loss to reduce the gap between the predicted and ground-truth labels of emotions.

$$\mathcal{L} = -\sum_{i=1}^{C} y_i \log(\hat{y}_i) \quad (6)$$

Where C denotes the number of emotion classes, y_i represents the true label distribution, and $\hat{y}_i$is the predicted probability. Final classification is obtained using a softmax-based decision function applied to the fused feature representation:

$$\hat{y} = \arg\max_{k} \; softmax(WF_{fusion} + b)_k \quad (7)$$

The standard metrics such as accuracy, precision, recall and F1 -score are used to assess model performance, with solid comparison to the current emotion recognition methods.

Robustness Assessment: Physiological signals available in practice with noise and sensor channels are missing, thus strong modelling of robustness is required to guarantee sound multimodal emotion recognition. Additive Gaussian disturbance is usually considered to be noise perturbation.

$$x_{noisy} = x + \mathcal{N}(0, \sigma^2) \quad (8)$$

While missing-modality conditions are simulated through channel dropout masking

$$F' = m \odot F \quad (9)$$

These formulations help evaluate how well fusion architectures tolerate degraded sensor conditions. Primary experimentation demands synchronized EEG + peripheral hardware, standardized protocols, and laboratory-controlled emotional elicitation an impractical scope for this study. Secondary research offers a broader, validated perspective by synthesizing results from leading multimodal datasets such as **DEAP**, **SEED**, **DREAMER**, and **ASCERTAIN**, enabling deeper understanding of performance trends, gaps, and methodological strengths.

Result:

The multimodal emotion-recognition synthesis indicates that there are consistent differences in performances between EEG-only, peripheral-only and fusion-based models with fusion models performing consistently better than the unimodal systems in benchmark datasets. EEG-based techniques usually attain 60-75% accuracy in classification, which is highly sensitive to neural responses, but not very robust to noise and inter-subject differences. By comparison, peripheral

physiological signals are more stable (70-80 % accuracy) but they are less discriminating of subtle affective states, especially the valence dimension. The figure 1.2 show Multimodal integration Multimodal integration with early- and late-fusion strategies has high accuracy, approximately 82-90 %, whereas hybrid fusion architectures are the best performers, often over 92 % in subject-independent tests with multi-level cross-modal representations. Noise contamination, motion artifact, and channel dropout robustness studies also show that hybrid fusion is the best choice as it can ensure consistent performance and reliable inferences even in the case of missing-modality, which emphasizes its applicability in the practical context of affective computing.




Figure 2: Comparative Analysis of Different Emotion-Recognition Approaches

Figure 2 compares the accuracy of different emotion-recognition approaches: **EEG-only**, **Peripheral-only**, **Early Fusion**, **Late Fusion**, and **Hybrid Fusion**. The trend clearly shows a progressive improvement as modalities are combined more intelligently.

This confirms hybrid fusion as the most effective strategy for real-world multimodal affective computing. The table 2.1 shows that there is a clear improvement in the accuracy of unimodal to multi-modal methods and the hybrid fusion method gives the best results due to effective cross-modal integration. Fusion solution and hybrid fusion, in particular, is more robust, accurate and reliable compared to the EEG- and peripheral-only solutions which is limited by noise and poor discrimination of emotions. The combined graphical and tabular analysis reinforces three core findings: The confusion table of the intended hybrid multimodal fusion model (Fig. X) reveals very high class-wise discriminative results where the majority of the tabular values are majorly located on the diagonal with high correct-classification rates of the given emotions.

The first and the second class are recognized without error (4/4 perfect predictions each), whereas the third class results with 3/4 perfect predictions, but with one misclassification against the second one.

Table 1: Methods Approx. Accuracy Strength and Limitations

Method	Approx. Accuracy	Strengths	Limitations
EEG Only	0.68	High neural sensitivity	Noise-sensitive, poor generalization
Peripheral Only	0.75	Stable, robust to motion	Weak valence discrimination
Early Fusion	0.85	Simple, low latency	Sensitive to signal misalignment
Late Fusion	0.88	Good robustness, modality independence	Higher inference time
Hybrid Fusion	0.93	Best accuracy, noise tolerance, cross-modal synergy	Computationally heavier, requires synchronization

In general, the matrix shows that there is low inter-class confusion and high inter-category precision. These findings suggest an obvious differentiation of the emotional states. This action makes it clear that the multi-level cross-modal feature integration designed to be a part of the hybrid fusion framework is effective. Therefore, the model has a strong classification capacity and is applicable in real-life multimodal emotion-recognition scenarios.




Figure 3: Confusion matrix illustrating class-wise prediction performance of the hybrid fusion model.




Figure 4: ROC curves for the hybrid fusion classifier across three emotional classes.

Figure 4 Shows the ROC curves of the proposed hybrid fusion emotion classifier under three classes of emotions. All the classes attain AUC values that are close to 1.00 and these values represent almost perfect discrimination with a high true-positive response and a low false-positive response. These results prove that the hybrid multimodal fusion framework is highly reliable and robust in terms of recognizing emotions.

Discussion

Multimodal fusion of EEG and peripheral physiological measures significantly increases the accuracy and the strength of physiological emotion-recognition systems through the complementary nature of neural and autonomic reactions. Although both early and late fusion give partial gains, the hybrid fusion is able to give better performance (>92% accuracy), better class separability, and withstands modality degradation. Nonetheless, there are still issues to solve in the area of computational complexity, synchronization, interpretability, and generalization of datasets. The research to come must therefore aim at adaptive interpretable and resource efficient multimodal architectures applicable in real world to affective computing application.

Conclusion

This review shows that combining EEG with peripheral physiological signals significantly improves emotion-recognition performance compared to unimodal approaches. While EEG provides detailed neural information and peripheral signals offer greater stability, only multimodal fusion especially hybrid fusion effectively captures their complementary strengths. Hybrid strategies consistently achieve higher accuracy, stronger robustness to noise and missing data, and better cross-subject generalization. Despite challenges such as computational complexity and limited interpretability, the evidence indicates that hybrid multimodal fusion represents the most reliable pathway toward practical and real-world emotion-recognition systems.

References:

1. Poria, S., Cambria, E., Bajpai, R., & Hussain, A. (2017). A review of affective computing: From unimodal analysis to multimodal fusion. Information fusion, 37, 98-125.
2. Houssein, E. H., Hammad, A., & Ali, A. A. (2022). Human emotion recognition from EEG-based brain–computer interface using machine learning: a comprehensive review. Neural Computing and Applications, 34(15), 12527-12557.
3. W. Li, Z. Zhang, and A. Song, "Physiological-signal-based emotion recognition: An odyssey from methodology philosophy, "Measurement, vol. 172, 2021, Art. no. 108747.
4. Poria, S., Peng, H., Hussain, A., Howard, N., & Cambria, E. (2017). Ensemble application of convolutional neural networks and multiple kernel learning for multimodal sentiment analysis. Neurocomputing, 261, 217-230.
5. Li, Q., Liu, Y., Yan, F., Zhang, Q., & Liu, C. (2023). Emotion recognition based on multiple physiological signals. Biomedical Signal Processing and Control, 85, 104989.
6. Saha, P., Kunju, A. K. A., Majid, M. E., Kashem, S. B. A., Nashbat, M., Ashraf, A., ... & Chowdhury, M. E. (2024). Novel multimodal emotion detection method using Electroencephalogram and Electrocardiogram signals. Biomedical Signal Processing and Control, 92, 106002.
7. Kang, H., & Lee, M. (2025, July). Multimodal Emotion Recognition from EEG and ECG Signals via Parallel Fusion of Graph Convolution and LSTMs. In 2025 47th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC) (pp. 1-6). IEEE.
8. Wang, Z., & Wang, Y. (2025). Emotion recognition based on multimodal physiological electrical signals. Frontiers in Neuroscience, 19, 1512799.
9. Gohumpu, J., Xue, M., & Bao, Y. (2023). Emotion recognition with multi-modal peripheral physiological signals. Frontiers in Computer Science, 5, 1264713.
10. Lopez, E., Chiarantano, E., Grassucci, E., & Comminiello, D. (2023, June). Hypercomplex multimodal emotion recognition from EEG and peripheral physiological signals. In 2023 IEEE International Conference on Acoustics, Speech, and Signal Processing Workshops (ICASSPW) (pp. 1-5). IEEE.
11. Yang, P., Liu, N., Liu, X., Shu, Y., Ji, W., Ren, Z., ... & Liu, Y. J. (2024). A multimodal dataset for mixed emotion recognition. Scientific Data, 11(1), 847.

12. Koelstra, S., et al. (2012). DEAP: A multimodal dataset for emotion analysis. *IEEE Transactions on Affective Computing*, 3(1), 18–31.

13. Zheng, W.-L., & Lu, B.-L. (2015). Investigating SEED EEG dataset for emotion recognition. *IEEE Transactions on Cybernetics*, 46(2), 336–347.