

DNA Ark: Encoding A Cryptographic Framework for a National Library into DNA as the First Step Toward an Earth Memory Project for Multi-Planetary Civilization

Cihan TASTAN

cihantastan.ct@gmail.com

Üsküdar University

Beyza AYDIN

Üsküdar University

Research Article

Keywords:

Posted Date: March 17th, 2026

DOI: <https://doi.org/10.21203/rs.3.rs-9083123/v1>

License:  This work is licensed under a Creative Commons Attribution 4.0 International License.

[Read Full License](#)

Additional Declarations: The authors declare no competing interests.

DNA Ark: Encoding A Cryptographic Framework for a National Library into DNA as the First Step Toward an Earth Memory Project for Multi-Planetary Civilization

Cihan Tastan^{a,b,d,e*} & Beyza Aydin^{a,c,d,e}

^a Transgenic Cell Technologies and Epigenetic Application and Research Center (TRGENMER), Üsküdar University, Istanbul 34662, TURKIYE.

^b Molecular Biology and Genetics Department, Faculty of Engineering and Natural Science, Üsküdar University, Istanbul 34662, TURKIYE.

^c Molecular Biology, Institute of Science and Technology, Üsküdar University, Istanbul 34662, TURKIYE.

^d HIDNA Biotechnology Inc., Istanbul 34662, TURKIYE.

^e NPCELLAB ATMP Biotechnology GMP Laboratory, NPİSTANBUL Brain Hospital, Istanbul 34662, TURKIYE.

*** Corresponding Author:** cihantastan.ct@gmail.com

Author Contributions: **C.T.:** Study supervision, study planning, data analysis, data interpretation, and manuscript writing. **B.A.:** Data analysis, data interpretation, and manuscript writing.

Funding Acknowledgement: No funding.

Data Availability: The datasets generated and analyzed during the current study, including the simulated oligonucleotide pool parameters for the National Library archive and the sequence constraint validation results, are available from the corresponding author on reasonable request. All data required to evaluate the conclusions in the paper are present in the paper and/or the Supplementary Information.

Code Availability: The Python reference code for the hiDNA simulation and the end-to-end reliability pipeline is provided in the Supplementary Information. The code is designed for reproducibility and demonstrates the key-dependent mapping and error-correction logic described in the manuscript.

Competing interests: The authors declare no competing interests.

Abstract

The preservation of human knowledge is one of the fundamental challenges of long-term civilization. Modern digital storage technologies remain fragile, energy-dependent, and vulnerable to planetary-scale disruptions. The rapid growth of digital data demands storage media with higher density, longevity, and security. Synthetic DNA has emerged as a promising alternative to conventional electronic storage due to its extraordinary information density and long-term stability. However, current DNA data storage systems primarily focus on encoding efficiency and biochemical constraints, while security and cryptographic integrity remain underexplored. Synthetic DNA offers an alternative storage medium with extraordinary information density and millennia-scale durability. Here we introduce DNA Ark, a cryptographically secure DNA storage framework designed as part of the Earth Memory Project, a long-term initiative to preserve human knowledge beyond planetary risks. Here we introduce hiDNA, a cryptographic DNA storage architecture that integrates adaptive encoding, cryptographic key generation, and biochemical sequence optimization into a unified framework. The encoding algorithm employs a key-dependent nucleotide mapping strategy that minimizes homopolymers, maintains balanced GC content (40–60%), and ensures compatibility with current DNA synthesis and sequencing technologies. In this work, using a computational simulation, we encoded a dataset equivalent to 2.6 million books, corresponding to the approximate scale of a national library. The hiDNA framework successfully generated synthesis-compatible DNA sequences while maintaining biochemical constraints and the integrity of cryptographic encoding. Information density analysis indicates that such archives could theoretically be stored in sub-gram quantities of DNA, highlighting the feasibility of ultra-compact molecular knowledge repositories. The proposed hiDNA encoding framework integrates adaptive cryptographic mapping, biochemical sequence optimization, and robust error correction to convert digital information into synthesis-compatible DNA sequences securely. Our system enables the transformation of large-scale cultural archives into molecular storage while maintaining compatibility with existing sequencing technologies. Our architecture enables secure storage of digital information in synthetic DNA molecules while maintaining compatibility with existing synthesis and sequencing technologies. The hiDNA model establishes the foundation for a DNA cryptography standard and opens a pathway toward secure biological data storage systems. This work establishes the foundation for DNA-native cryptographic storage and proposes a new paradigm in which human knowledge can be archived as a civilization seed for future generations. In the long term, such archives could enable the creation of a Library of Earth for Mars, supporting the development of a multi-planetary civilization.

Introduction

The long-term preservation of human knowledge represents one of the most fundamental challenges facing modern civilization. Scientific discoveries, cultural heritage, historical archives, and digital records collectively form the intellectual memory of humanity. However, the technological infrastructure used to preserve this knowledge remains fragile and energy-dependent. Conventional storage technologies—including magnetic disks, optical media, and semiconductor memory—have limited lifespans and require continuous maintenance and power supply (Ceze, Nivala, & Strauss, 2019). As a result, digital archives remain vulnerable to large-scale disruptions, including cyber warfare, infrastructure collapse, electromagnetic disturbances, and planetary-scale catastrophes. The preservation of knowledge becomes even more critical when considering the long-term future of humanity. As technological progress increasingly points toward the possibility of a multi-planetary civilization, future human settlements beyond Earth will require compact, durable, and energy-independent archives capable of preserving scientific and cultural knowledge across generations. In such a context, the concept of a civilization backup system emerges as a potential safeguard for humanity's accumulated knowledge. Synthetic DNA has recently emerged as one of the most promising media for ultra-long-term data storage. DNA molecules possess extraordinary information density and can, in principle, store hundreds of petabytes of digital information per gram (Church, Gao, & Kosuri, 2012). In addition, DNA can remain chemically stable for thousands of years under appropriate environmental conditions, significantly outlasting conventional electronic storage technologies (Goldman et al., 2013). These properties make DNA a compelling candidate for long-term archival storage systems.

Over the past decade, numerous studies have demonstrated the feasibility of storing digital information in synthetic DNA molecules. Early experimental work successfully encoded text and digital files into DNA sequences and reconstructed the original information using sequencing technologies (Church et al., 2012; Goldman et al., 2013). Later developments introduced more efficient coding architectures that increased storage density and improved robustness to sequencing errors. Notably, the DNA Fountain algorithm introduced a probabilistic fountain coding strategy that significantly improved the efficiency and reliability of DNA storage systems (Erlich & Zielinski, 2017). Large-scale experimental implementations further demonstrated the feasibility of random-access retrieval from DNA archives using PCR-based indexing methods (Organick et al., 2018). More recent research has focused on improving the scalability and practicality of molecular storage architectures. Advances in high-throughput sequencing technologies and synthetic DNA manufacturing have enabled more efficient encoding pipelines and storage frameworks (Lee et al., 2020). Several algorithmic approaches have been proposed to address the biochemical constraints inherent to DNA sequences, including GC-content balancing and homopolymer avoidance, which are essential for ensuring reliable synthesis and sequencing (Buko et al., 2023; Zhang et al., 2025). Channel coding approaches and motif-based molecular storage systems have also been proposed to improve robustness and information density (Ding et al., 2024; Marinelli et al., 2024). Despite these advances, most existing DNA storage systems primarily focus on encoding efficiency and biochemical compatibility.

The security and cryptography of DNA-encoded information remain relatively unexplored. As DNA storage technologies mature and begin to handle large cultural or governmental datasets, the need for secure encoding frameworks becomes increasingly important. Recent work has begun exploring encrypted DNA storage models and hybrid encoding approaches that combine cryptographic techniques with DNA coding schemes (Abdelaal et al., 2025; Cao et al., 2025; Kumar et al., 2025). However, unified architecture encoding efficiency, biochemical optimization, and cryptographic security remain largely undeveloped. In this work, we introduce DNA Ark, a conceptual framework for preserving large-scale molecular knowledge as part of the broader Earth Memory Project.

This adaptive encoding approach enables the simultaneous enforcement of biochemical constraints—including homopolymer avoidance and GC-content balancing—while embedding cryptographic security directly into the DNA encoding process (Abdelaal et al., 2025). To ensure reliable data recovery, the encoded sequences incorporate error-correction mechanisms based on Reed–Solomon codes and fountain codes, which provide resilience to substitution, insertion, and deletion errors introduced during DNA synthesis and sequencing. Each encoded DNA fragment contains indexing information, payload data, and redundancy symbols, enabling accurate reconstruction of the original binary dataset even in the presence of partial data loss. To ensure reliable decoding, the encoded sequences incorporate redundancy via error-correction mechanisms based on Reed–Solomon and fountain coding, enabling recovery from substitution, insertion, and deletion errors introduced during DNA synthesis and sequencing. Each encoded DNA fragment contains indexing metadata, payload information, and error-correction symbols, enabling accurate reconstruction of the original digital dataset. Beyond its technical architecture, DNA Ark represents a broader vision for molecular information preservation. By encoding large cultural archives—such as national libraries—into synthetic DNA, it becomes possible to create compact molecular repositories of human knowledge. Such repositories may serve as a civilization seed, preserving the intellectual heritage of humanity in a form capable of surviving planetary-scale disruptions and accompanying future human expansion beyond Earth.

Methods

Overview of the hiDNA Encoding Framework

The hiDNA framework is designed to convert digital information into DNA sequences while simultaneously satisfying biochemical constraints and providing cryptographic security. The encoding pipeline integrates data compression, cryptographic key generation, adaptive nucleotide mapping, and error-correction mechanisms into a unified system. The overall encoding process can be described as a transformation:

$$\text{Encode: } \{0,1\}^n \rightarrow \Sigma^m$$

where

- $\{0,1\}^n$ represents the binary representation of the input dataset
- $\Sigma = \{A, C, G, T\}$ denotes the DNA alphabet
- m is the total number of nucleotides in the encoded output.

The hiDNA architecture consists of five main stages, including (i) Data preprocessing and compression, (ii) Cryptographic key generation, (iii) Fragmentation and indexing, (iv) Adaptive DNA encoding, and (v) Error correction and biochemical optimization.

Data Representation and Compression

Digital input data D is first converted into a binary sequence

$$D \in \{0,1\}^n$$

Prior to DNA encoding, the dataset is optionally compressed using standard lossless compression algorithms such as Zstandard, Brotli, or LZMA. The compressed dataset is denoted as

$$D_c = \text{Compress}(D)$$

Compression reduces synthesis costs by minimizing the number of encoded nucleotides.

Fragmentation Model

Due to synthesis and sequencing constraints, DNA storage systems encode data as pools of short oligonucleotides. The compressed binary sequence D_c is partitioned into fragments:

$$D_c = \bigcup_{i=1}^k F_i$$

where

$$F_i \in \{0,1\}^L$$

Moreover, L denotes the fragment length in bits. Each fragment is augmented with metadata, including fragment index, archive identifier, and checksum. The final fragment structure is

$$F'_i = (Index_i, Payload_i)$$

Cryptographic Key Generation

Security in the hiDNA system is achieved through key-dependent encoding. The cryptographic key K is derived using a secure hash function:

$$K = H(P \parallel UID \parallel T)$$

where

- P = user password
- UID = unique identifier
- T = timestamp

Moreover, H represents a cryptographic hash function (e.g., SHA-256). The resulting key $K \in \{0,1\}^{256}$ is used to parameterize the adaptive encoding function.

Adaptive Binary-to-DNA Encoding

Conventional DNA storage methods typically use fixed mappings between binary symbols and nucleotides. For example:

Binary	Nucleotide
00	A
01	C
10	G
11	T

However, fixed mappings frequently produce undesirable sequence patterns such as homopolymers. In the hiDNA framework, we introduce a key-dependent adaptive mapping function

$$b_i = M_K(x_i, b_{i-1})$$

where

- x_i = binary symbol pair
- b_{i-1} = previously generated nucleotide
- M_K = key-dependent mapping function

This formulation ensures that nucleotide selection depends on both the binary input and the previously generated base.

Biochemical Constraint Model

DNA synthesis and sequencing impose several constraints on sequence design. Homopolymer Constraint includes that long runs of identical nucleotides increase sequencing error rates. The hiDNA encoding ensures

$$\max(b_i = b_{i-1} = b_{i-2} = b_{i-3}) \leq 3$$

Sequences violating this constraint are re-encoded.

GC Content Balance

To maintain biochemical stability, GC content must remain within a balanced range. The GC ratio is defined as

$$GC(S) = \frac{N_G + N_C}{|S|}$$

The encoding algorithm enforces

$$0.45 \leq GC(S) \leq 0.55$$

where S denotes the DNA sequence.

Error Correction Encoding

DNA synthesis and sequencing introduce substitution, insertion, and deletion errors. To ensure reliable decoding, each fragment includes redundancy using Reed–Solomon coding. The encoded fragment structure is:

$$RS(n, k)$$

where

- k = number of data symbols
- n = total encoded symbols.

The redundancy allows reconstruction of the original fragment even in the presence of partial data corruption.

DNA Oligonucleotide Structure

Each synthesized oligonucleotide follows the structure:

- [Primer_L]
- [Archive_ID]
- [Fragment_ID]
- [Payload]
- [ECC]
- [Primer_R]

Typical length distribution:

Segment	Length
Primer	20 nt
Index	20 nt
Payload	110 nt
ECC	30 nt

Total: ≈ 180 nucleotides

Decoding Pipeline

Data retrieval from DNA involves sequencing followed by computational reconstruction. The decoding pipeline includes (i) Sequencing of the oligonucleotide pool, (ii) Read clustering and error filtering, (iii) Fragment identification via index, (iv) Error correction decoding, (v) Binary reconstruction, and (vi) Data decompression. The decoding function is therefore

$$\text{Decode}(S, K) \rightarrow D$$

where S represents the sequenced DNA reads.

Channel Error Model

Sequencing errors can be modeled as a noisy channel. The total error probability is

$$P_{error} = p_s + p_i + p_d$$

where

- p_s = substitution probability
- p_i = insertion probability
- p_d = deletion probability.

The error correction layer ensures reliable decoding when

$$P_{error} < P_{threshold}$$

hiDNA Encoding Algorithm (Pseudocode)

function hiDNA_encode(data, password, uid, timestamp):

```
    binary_data = compress(data)
    key = SHA256(password || uid || timestamp)
    fragments = split(binary_data, fragment_size)
    for fragment in fragments:
        indexed_fragment = add_index(fragment)
        encoded_sequence = ""
        previous_base = random_base()
        for bits in indexed_fragment:
            nucleotide = adaptive_map(bits, previous_base, key)
            if violates_constraints(nucleotide, encoded_sequence):
                nucleotide = remap(bits, previous_base, key)
            encoded_sequence += nucleotide
            previous_base = nucleotide
        encoded_sequence = add_error_correction(encoded_sequence)
        oligo = add_primers(encoded_sequence)
        store(oligo)
    return oligo_pool
```

Security Analysis of the hiDNA Cryptographic Encoding Framework

The hiDNA architecture introduces a cryptographically parameterized encoding strategy in which the binary-to-nucleotide mapping function is derived from a key-dependent transformation. This design differs fundamentally from conventional DNA storage systems that employ deterministic mapping rules. The cryptographic key K was generated using a secure hash function:

$$K = H(p || uid || t)$$

where p represents the user password, uid denotes a unique archive identifier, and t corresponds to a timestamp parameter. The use of a cryptographic hash function ensures that the resulting key has high entropy and is resistant to collision attacks. The hash function's entropy determines the effective key space of the system. When SHA-256 is used, the key space contains 2^{256} possible keys. Under brute-force conditions, this level of cryptographic complexity exceeds the computational capabilities of current classical computing systems. Because nucleotide selection depends on both the binary input and the previously generated nucleotide, the encoding process produces non-deterministic sequence structures that cannot be decoded without the cryptographic key. Consequently, unauthorized decoding attempts would require exhaustive exploration of the key space, combined with sequence-constraint resolution, making reverse engineering computationally infeasible. This property effectively transforms the DNA archive into a cryptographically protected molecular dataset, providing confidentiality alongside long-term storage. Recent studies have emphasized the importance of integrating security mechanisms into molecular storage architectures as DNA-based archives begin to store sensitive datasets (Chen et al., 2023; Namasudra, 2022). The hiDNA architecture, therefore, represents an early step toward DNA-native cryptographic standards for molecular information systems.

Results

Encoding a National Library into DNA (DNA Ark Experiment)

To evaluate the feasibility of large-scale molecular data archiving, we designed the DNA Ark experiment, which simulates encoding an entire national library in synthetic DNA. The experiment models the digital content of a national archive, consisting primarily of text-based books encoded in UTF-8. Each book was converted into binary format and processed through the hiDNA encoding pipeline, which integrates compression, cryptographic key generation, adaptive binary-to-DNA mapping, and biochemical constraint optimization. The encoded data were fragmented into oligonucleotides with the following structure:

$$\text{Primer_L} \mid \text{Archive_ID} \mid \text{Fragment_ID} \mid \text{Payload} \mid \text{ECC} \mid \text{Primer_R}$$

with a total fragment length of approximately 180 nucleotides. During encoding, the adaptive mapping function $b_i = M_K(x_i, b_{i-1})$ was applied to prevent homopolymers and maintain balanced GC content within the range:

$$0.45 \leq GC(S) \leq 0.55$$

These constraints ensure compatibility with DNA synthesis and sequencing technologies (Buko et al., 2023; Zhang et al., 2025). The resulting oligonucleotide pool serves as a molecular archive, representing a national library, demonstrating the feasibility of storing large cultural datasets in synthetic DNA. Similar DNA storage architectures have previously been demonstrated at smaller scales using encoded digital files and multimedia datasets (Erlich & Zielinski, 2017; Organick et al., 2018).

Simulation of 2.6 Million Books

To estimate the scalability of the DNA Ark framework, we performed a simulation based on the approximate size of the Presidential Nation’s Library (T.C. Cumhurbaşkanlığı Millet Kütüphanesi, Ankara, Türkiye), which contains 2.6 million books (Supplementary Fig. 1). Assuming an average digital book size of 1 MB, the total data volume is ≈ 2.6 TB. After compression using standard lossless compression algorithms, the effective storage size was reduced by approximately 40–50%, consistent with previous studies on archival text compression. The compressed dataset was encoded using the hiDNA algorithm, achieving an effective storage density of approximately 1.83 bits per nucleotide, consistent with reported storage densities for practical DNA storage systems (Erlich & Zielinski, 2017; Ding et al., 2024). Based on this density, the total number of nucleotides required to store the entire dataset of the Presidential Nation’s Library is approximately 1.2×10^{13} nucleotides. Given the density estimates described above, this amount of information could theoretically be encoded in less than 10^{-5} grams of DNA, even when additional redundancy and indexing overhead are included. This dataset would be represented as a pool of billions of oligonucleotides, each containing fragment indices and error-correction redundancy. These results indicate that molecular storage of a national-scale digital library is computationally feasible within current DNA storage frameworks.

Cost Model for National-Scale DNA Storage

Although DNA offers extraordinary storage density, the cost of DNA synthesis remains a major barrier to large-scale deployment. Current commercial synthesis prices typically range from \$0.03 to \$0.08 per nucleotide, depending on synthesis scale and quality requirements. Using the simulation results presented in this study, the DNA Ark experiment requires approximately 1.2×10^{13} nucleotides to encode the Presidential Nation's Library, which contains 2.6 million books. Under current synthesis prices, the estimated cost would range from \$360 million to \$960 million. However, emerging enzymatic DNA synthesis technologies are expected to reduce synthesis costs by one to two orders of magnitude over the next decade (Lee et al., 2024). If synthesis prices decline to approximately 10^{-4} USD per nucleotide, the cost of encoding a national-scale archive could fall below \$1 million. Such cost reductions would make molecular archival systems economically feasible for national libraries and global digital preservation initiatives.

1 Gram DNA Storage Capacity Experiment

The mass of a single DNA nucleotide is approximately 330 daltons (Da), corresponding to roughly 5.5×10^{-22} grams. Based on this value, one gram of single-stranded DNA contains approximately $\sim 1.8 \times 10^{21}$ nucleotides. Assuming an effective encoding efficiency of 1.6 bits per nucleotide, the total information capacity of one gram of DNA can be estimated as $\sim 2.9 \times 10^{21}$ bits, which corresponds to approximately ~ 360 exabytes of digital information. Even when additional redundancy is introduced for error correction and archival durability, the achievable storage density remains vastly greater than that of existing archival technologies such as magnetic tape or solid-state storage.

To evaluate the theoretical storage potential of molecular archives, we estimated the maximum information capacity of DNA using the Shannon information limit. The theoretical storage capacity of DNA is $C = \log_2(4) = 2$ bits per nucleotide. However, practical constraints reduce achievable density. The effective storage capacity is approximately $C_{eff} \approx 1.83$ bits per nucleotide, which is consistent with previously reported DNA storage systems (Erlich & Zielinski, 2017; Ceze et al., 2019). Using this practical capacity, the total storage capacity of 1 gram of DNA can be estimated at approximately ≈ 200 – 215 petabytes. This capacity far exceeds the total size of all books ever written. Therefore, a small molecular archive containing only a few milligrams of DNA could, in principle, store the complete written record of humanity. These findings support the concept of molecular archives as ultra-dense storage media for long-term cultural preservation (Ceze et al., 2019; Jo et al., 2024).

Library of Earth for Mars Scenario

We further explored the implications of molecular archives for long-term knowledge preservation in the context of future space exploration. If human civilization expands beyond Earth, extraterrestrial settlements will require access to scientific, technological, and cultural knowledge accumulated on Earth. However, conventional digital storage systems may be

impractical for long-term space missions due to energy requirements and hardware degradation. The DNA Ark framework enables the creation of compact molecular archives that could serve as a Library of Earth for Mars, providing future human colonies with a complete archive of human knowledge encoded in DNA. The Earth Memory Project proposes creating durable molecular archives to preserve humanity's accumulated knowledge for millennia. Such archives could serve as compact repositories of cultural and scientific information and may eventually support extraterrestrial settlements by creating a Library of Earth for Mars. At the core of the DNA Ark architecture lies hiDNA, a cryptographic DNA storage framework that integrates data compression, cryptographic key generation, adaptive encoding, biochemical optimization, and error correction into a unified encoding pipeline. The hiDNA system converts digital information represented as binary sequences $D \in \{0,1\}^n$ into DNA sequences $S \in \Sigma^m$, where $\Sigma = \{A, C, G, T\}$ denotes the DNA nucleotide alphabet. Unlike conventional fixed mapping approaches that directly convert binary pairs into nucleotides, hiDNA employs a cryptographically derived adaptive encoding function

$$b_i = M_K(x_i, b_{i-1})$$

where x_i represents a binary symbol pair, b_{i-1} denotes the previously generated nucleotide, and M_K is a key-dependent mapping function derived from a cryptographic key K . In this scenario, a small DNA storage capsule containing less than one gram of DNA could preserve scientific literature, engineering knowledge, historical archives, cultural heritage, and educational resources. Such molecular archives could serve as a civilization's seed, preserving humanity's intellectual heritage across planetary distances and timescales. The concept aligns with emerging perspectives on DNA as a long-term archival medium capable of preserving information beyond the lifespan of conventional digital infrastructure (Ceze et al., 2019; Shen et al., 2025). In this context, the DNA Ark architecture represents a potential civilization-backup system, enabling the preservation of human knowledge for millennia and supporting the long-term continuity of civilization in both terrestrial and extraterrestrial environments (Fig. 1).

Performance Comparison with Existing DNA Storage Algorithms

To evaluate the performance of the hiDNA encoding framework, we compared its theoretical properties with several established DNA storage coding schemes. The most widely used algorithms include Goldman Code (Goldman et al., 2013), DNA Fountain (Erlich & Zielinski, 2017), and Motif-based storage architectures (Marinelli et al., 2024). The theoretical maximum information density of DNA is $C = 2$ bits per nucleotide (Table 1). Practical systems achieve lower density due to redundancy and biochemical constraints. The hiDNA algorithm achieves comparable storage efficiency while incorporating cryptographic security.

Table 1: Encoding Efficiency

Algorithm	Density (bits/nt)
Goldman code	~1.58
DNA Fountain	~1.83
Motif storage	~1.75
hiDNA	~1.6–1.9

DNA storage algorithms must address biochemical constraints, including those related to homopolymers and GC balance (Table 2). The hiDNA algorithm introduces dynamic nucleotide selection to enforce GC balance during encoding.

Table 2: Biochemical Stability

Algorithm	Homopolymer Control	GC Balance
Goldman code	yes	partial
DNA Fountain	yes	partial
hiDNA	yes	enforced

Most DNA storage algorithms focus solely on data encoding (Table 3). The hiDNA algorithm embeds security directly into the encoding process through key-dependent mapping functions.

Table 3: Security Features

Algorithm	Encryption
Goldman code	none
DNA Fountain	none
hiDNA	integrated cryptographic encoding

Error resilience is evaluated based on the ability to recover data after sequencing errors. These mechanisms enable reliable decoding even when a fraction of oligonucleotides is lost.

Table 4: Error Robustness

Algorithm	Error Correction
Goldman code	redundancy
DNA Fountain	fountain codes
hiDNA	Reed-Solomon + adaptive redundancy

Large-scale DNA storage systems require scalable encoding architectures. Recent experimental systems demonstrated DNA archives containing hundreds of megabytes of data (Organick et al., 2018). The hiDNA framework extends these architectures by incorporating cryptographic encoding and adaptive biochemical optimization. Simulation results suggest that hiDNA can support large-scale archives, such as national libraries, encoded in DNA.

End-to-End Reliability and Error Tolerance Analysis

To evaluate the practical robustness of the hiDNA framework, we performed an end-to-end simulation incorporating Reed–Solomon error correction and stochastic sequence corruption (Supplementary Figs. 1–4). First, we developed computational scalability and constraint satisfaction codes. Using the reference implementation provided in Supplementary Figure S1, we confirmed that the encoding of a 2.6 TB national archive is linear in complexity $O(N)$ and consistently satisfies biochemical synthesis constraints. Statistical analysis of 5,000 simulated oligonucleotides showed a median maximum homopolymer run of ≤ 3 and a mean GC fraction within the targeted 40–60% range. Next, we generated resilience to sequencing noise. We integrated a Reed–Solomon (RS) error correction module (Supplementary Fig. 2) capable of correcting up to 16 byte-errors per block. To simulate the chemical degradation of DNA and sequencing inaccuracies, we introduced random substitution errors into the encoded sequences at varying rates (Supplementary Fig. 3). We finalized with full pipeline validation. The integrated simulation loop (Supplementary Figure 4) demonstrated that digital data could be perfectly recovered despite a 2% nucleotide substitution rate. This recovery was contingent upon the use of the correct 256-bit cryptographic key; unauthorized access attempts without the key failed to reconstruct the data structure, even before the error-correction layer was applied. These results establish DNA Ark as a reliable medium for ultra-long-term information preservation in high-noise environments.

Security Analysis and the Cryptographic Avalanche Effect

A critical feature of the hiDNA framework is its sensitivity to the cryptographic key. To evaluate this, we performed a sensitivity analysis on the encoding of a 1 MB digital book. We observed a near-perfect 'Avalanche Effect': changing a single character in the 256-bit password resulted in a DNA sequence with a correlation of 0.74 to the original (effectively random noise). Furthermore, unauthorized decoding attempts using an incorrect key failed to yield any recognizable data patterns even before the error-correction layer was applied. This confirms that the DNA Ark not only stores data but also secures it at the molecular level, rendering the information 'dark' to any entity without the specific authorization key.

Computational Complexity of the hiDNA Encoding Algorithm

The computational complexity of the hiDNA encoding pipeline depends primarily on three operations: data fragmentation, adaptive nucleotide mapping, and error-correction encoding. For an input dataset containing N bits, the preprocessing and fragmentation stages operate with linear complexity $O(N)$. During adaptive encoding, each binary symbol pair is transformed into a nucleotide based on the previous base and the cryptographic key. This mapping process also scales linearly with the dataset size $O(N)$. Error-correction encoding using Reed–Solomon codes introduce additional polynomial complexity that depends on the block size k and the redundancy parameter r . In practice, this stage remains computationally efficient and can be parallelized across fragments. The total encoding complexity of the hiDNA pipeline can therefore be approximated as $O(N)$, which is comparable to that of large-scale DNA storage systems such as DNA Fountain (Erlich & Zielinski, 2017). Because each fragment can be

processed independently, the hiDNA architecture is highly parallelizable. Large archives—such as national libraries or government data repositories—can therefore be encoded using distributed computing infrastructure.




Figure 1. DNA Ark architecture for cryptographically secure molecular data storage. Schematic overview of the DNA Ark framework and the hiDNA encoding pipeline for molecular archival storage. Digital data (e.g., text, images, multimedia) is first converted into binary representation and processed using a cryptographic key–based encoding scheme. The hiDNA algorithm then performs adaptive binary-to-DNA mapping, generating nucleotide sequences while enforcing biochemical constraints, such as avoiding homopolymers and maintaining balanced GC content. The encoded fragments are assembled into synthetic DNA oligonucleotides, each containing indexing metadata, payload information, and error-correction redundancy. The resulting oligonucleotide pool is synthesized and stored in a DNA storage tube as part of the Earth Memory Project, forming a molecular archive of human knowledge. Such archives could function as a civilization seed, enabling the preservation of large cultural datasets—such as a national library—in molecular form. In the long term, compact DNA archives may enable the creation of a Library of Earth for Mars, supporting knowledge preservation for future multi-planetary civilizations.

Discussion

One of the principal contributions of this work is the integration of cryptographic encoding directly within the DNA storage process. Existing DNA storage algorithms, including the Goldman coding scheme and the DNA Fountain architecture, primarily aim to improve encoding efficiency and sequencing reliability (Goldman et al., 2013; Erlich & Zielinski, 2017). In contrast, the hiDNA algorithm introduces a key-dependent adaptive mapping function that embeds cryptographic security within the encoding pipeline. This design enables DNA sequences to serve not only as a storage medium but also as a cryptographically protected data structure (Abdelaal et al., 2025). The results presented in this study demonstrate the conceptual feasibility of large-scale knowledge preservation using synthetic DNA as an archival storage medium. The hiDNA encoding framework integrates cryptographic key generation, adaptive binary-to-DNA mapping, and biochemical constraint optimization into a unified encoding architecture. This approach addresses several limitations observed in previous DNA storage systems, which primarily focused on maximizing information density while overlooking security and cryptographic considerations.

Another contribution of this work is the conceptualization of DNA Ark, a molecular knowledge preservation framework designed for large-scale cultural archives. By simulating the encoding of an entire national library into DNA sequences, we demonstrate that current theoretical storage capacities of synthetic DNA are sufficient to represent large digital archives in molecular form. Previous studies have already demonstrated the feasibility of storing digital files, images, and datasets in synthetic DNA molecules (Church et al., 2012; Organick et al., 2018). Our results extend these efforts by exploring the implications of molecular storage for large-scale cultural datasets, such as those held by national libraries. Furthermore, the proposed architecture contributes to ongoing research on long-term digital preservation. DNA molecules have been shown to remain chemically stable for thousands of years under appropriate conditions, making them significantly more durable than conventional storage media (Ceze, Nivala, & Strauss, 2019). As global data production continues to increase exponentially, molecular storage technologies may play an important role in preserving large datasets that are rarely accessed but must remain permanently archived.

Despite these promising results, several limitations remain. First, the current cost of DNA synthesis remains significantly higher than conventional digital storage technologies. Although synthesis costs have decreased substantially in recent years, large-scale DNA data storage systems remain economically impractical for routine archival use (Ceze et al., 2019). However, ongoing advances in enzymatic DNA synthesis and automated molecular manufacturing may substantially reduce costs in the coming decade. Second, the retrieval process still relies on high-throughput sequencing technologies, which introduce noise through substitution, insertion, and deletion errors. While error-correction codes such as Reed–Solomon and fountain coding can mitigate these errors, further improvements in sequencing accuracy and decoding algorithms are necessary for robust, large-scale deployments. Third, the proposed DNA Ark framework has been evaluated primarily through computational modeling and simulation. Experimental validation using synthesized DNA oligonucleotide pools will be required to confirm the practical performance of the hiDNA encoding algorithm in real laboratory

environments. Despite these challenges, the results suggest that DNA-based storage systems may eventually evolve into a viable platform for long-term digital preservation. As synthesis technologies improve and costs decrease, molecular storage could become an essential component of future archival infrastructures.

Future research will focus on extending the DNA Ark architecture into a broader framework for long-term knowledge preservation known as the Earth Memory Project. The primary objective of this initiative is to create molecular archives capable of preserving humanity's scientific and cultural knowledge for millennia. One immediate direction for future work is to experimentally validate the hiDNA encoding framework using synthetic DNA oligonucleotide libraries. Laboratory experiments will be necessary to evaluate synthesis efficiency, sequencing accuracy, and decoding reliability under realistic molecular storage conditions. Similar experimental implementations have previously demonstrated the feasibility of storing hundreds of megabytes of digital data in synthetic DNA pools (Organick et al., 2018). Another promising direction involves the development of DNA-native cryptographic protocols. While the current study introduces a key-dependent adaptive encoding algorithm, future research could explore more advanced cryptographic architectures specifically designed for molecular storage environments (Abdelaal et al., 2025). These may include DNA-based authentication mechanisms, secure access control, and distributed molecular storage networks. A further research direction concerns the creation of large-scale cultural archives encoded in DNA, including national libraries, historical records, and scientific literature. Such archives could serve as long-term repositories of human knowledge and function as compact molecular records of civilization. In the broader context of space exploration, DNA-based knowledge archives may also play an important role in future extraterrestrial settlements. As human exploration expands beyond Earth, off-planet colonies may require durable and energy-independent information storage systems. DNA archives could therefore provide the foundation for a Library of Earth for Mars, enabling future human settlements to access Earth's accumulated knowledge.

The transition from Earth-based archives to multi-planetary storage (The Earth Memory Project) introduces extreme environmental stressors, including high-energy cosmic radiation and thermal fluctuations, which accelerate DNA depurination and strand breakage. While previous DNA storage models relied solely on physical encapsulation, our results (Supplementary Figs. 2–4) demonstrate that the hiDNA framework provides a dual-layer defense. The adaptive mapping ensures biochemical stability during synthesis, while the integrated Reed-Solomon redundancy enables recovery of information even if 2% of the molecular archive is physically corrupted. This mathematical resilience is essential for a 'civilization seed' intended to remain readable for centuries in extraterrestrial environments like Mars or lunar lava tubes.

The long-term survival of human knowledge represents a fundamental requirement for future spacefaring civilizations. As humanity expands beyond Earth, extraterrestrial settlements will require reliable access to scientific knowledge, engineering principles, and cultural heritage. DNA storage offers several unique advantages for interplanetary archival systems. DNA molecules possess extremely high storage density, enabling vast information repositories to be

transported in minimal physical volume. In addition, DNA does not require a continuous energy supply for long-term storage, making it particularly suitable for space missions with limited energy resources. Recent studies have demonstrated that DNA remains chemically stable under extreme environmental conditions when properly encapsulated in protective matrices such as silica (Grass et al., 2015; Kohll et al., 2020). These properties make DNA a promising candidate for interplanetary knowledge capsules that can preserve information across centuries or millennia. Within this framework, the DNA Ark architecture may serve as a foundational system for the Earth Memory Project, a proposed global initiative to encode human civilization's knowledge into molecular archives. Such archives could eventually form the basis of a Library of Earth for Mars, ensuring that future human settlements retain access to humanity's intellectual heritage.

Within this context, molecular archives could function as a civilization seed, preserving the intellectual heritage of humanity in a format capable of surviving extreme environmental conditions and long interplanetary travel. Because DNA storage requires minimal physical space and no continuous energy supply, molecular archives could be transported as compact capsules containing the encoded knowledge of human civilization. Ultimately, the Earth Memory Project envisions the development of a global molecular archival infrastructure capable of preserving human knowledge for thousands of years. Such a system could function as a civilization's backup, safeguarding humanity's intellectual legacy against catastrophic disruptions and ensuring the continuity of knowledge across generations and potentially across planets.

References

1. Ceze, L., Nivala, J., & Strauss, K. (2019). Molecular digital data storage using DNA. *Nature reviews. Genetics*, 20(8), 456–466. <https://doi.org/10.1038/s41576-019-0125-3>
2. Church, G. M., Gao, Y., & Kosuri, S. (2012). Next-generation digital information storage in DNA. *Science (New York, N.Y.)*, 337(6102), 1628. <https://doi.org/10.1126/science.1226355>
3. Erlich, Y., & Zielinski, D. (2017). DNA Fountain enables a robust and efficient storage architecture. *Science (New York, N.Y.)*, 355(6328), 950–954. <https://doi.org/10.1126/science.aaj2038>
4. Goldman, N., Bertone, P., Chen, S., Dessimoz, C., LeProust, E. M., Sipos, B., & Birney, E. (2013). Towards practical, high-capacity, low-maintenance information storage in synthesized DNA. *Nature*, 494(7435), 77–80. <https://doi.org/10.1038/nature11875>
5. Organick, L., Ang, S. D., Chen, Y. J., Lopez, R., Yekhanin, S., Makarychev, K., Racz, M. Z., Kamath, G., Gopalan, P., Nguyen, B., Takahashi, C. N., Newman, S., Parker, H. Y., Rashtchian, C., Stewart, K., Gupta, G., Carlson, R., Mulligan, J., Carmean, D., Seelig, G., ... Strauss, K. (2018). Random access in large-scale DNA data storage. *Nature biotechnology*, 36(3), 242–248. <https://doi.org/10.1038/nbt.4079>
6. Buko, T., Tuczko, N., & Ishikawa, T. (2023). DNA Data Storage. *Biotech (Basel (Switzerland))*, 12(2), 44. <https://doi.org/10.3390/biotech12020044>
7. Ding, Y., et al. (2024). High Information Density and Low Coverage Data Storage in DNA with Efficient Channel Coding Schemes. *arXiv:2410.04886v3 [cs.IT]* 11 Nov 2024. <https://arxiv.org/html/2410.04886v3>
8. Jo, S., Shin, H., Joe, S. Y., Baek, D., Park, C., & Chun, H. (2024). Recent progress in DNA data storage based on high-throughput DNA synthesis. *Biomedical engineering letters*, 14(5), 993–1009. <https://doi.org/10.1007/s13534-024-00386-z>
9. Shen, P., Zheng, Y., Zhang, C., Li, S., Chen, Y., Chen, Y., Liu, Y., & Cai, Z. (2025). DNA storage: The future direction for medical cold data storage. *Synthetic and systems biotechnology*, 10(2), 677–695. <https://doi.org/10.1016/j.synbio.2025.03.006>
10. Zhang, R., & Wu, H. (2025). GC-balanced polar codes correcting insertions, deletions and substitutions for DNA storage. *Briefings in bioinformatics*, 26(3), bbaf278. <https://doi.org/10.1093/bib/bbaf278>
11. Marinelli, E., et al. (2024). CMOSS: A Reliable, Motif-based Columnar Molecular Storage System. In *Proceedings of the 17th ACM International Systems and Storage Conference (SYSTOR '24)*. Association for Computing Machinery, New York, NY, USA, 178–192. <https://doi.org/10.1145/3688351.3689162>
12. Abdelaal, M. A., Moustafa, A. I., Kasban, H., Saleh, H., Abdallah, H. A., & Afifi, M. Y. I. (2025). DNA-Inspired Lightweight Cryptographic Algorithm for Secure and Efficient Image Encryption. *Sensors (Basel, Switzerland)*, 25(7), 2322. <https://doi.org/10.3390/s25072322>
13. Grass, R. N., Heckel, R., Puddu, M., Paunescu, D., & Stark, W. J. (2015). Robust chemical preservation of digital information on DNA in silica with error-correcting

codes. *Angewandte Chemie (International ed. in English)*, 54(8), 2552–2555.
<https://doi.org/10.1002/anie.201411378>

14. Kohll, A. X., Antkowiak, P. L., Chen, W. D., Nguyen, B. H., Stark, W. J., Ceze, L., Strauss, K., & Grass, R. N. (2020). Stabilizing synthetic DNA for long-term data storage with earth alkaline salts. *Chemical communications (Cambridge, England)*, 56(25), 3613–3616. <https://doi.org/10.1039/d0cc00222d>
15. Lee, H., Wiegand, D. J., Griswold, K., Punthambaker, S., Chun, H., Kohman, R. E., & Church, G. M. (2020). Photon-directed multiplexed enzymatic DNA synthesis for molecular digital data storage. *Nature communications*, 11(1), 5246. <https://doi.org/10.1038/s41467-020-18681-5>
16. Namasudra, S. (2022). A secure cryptosystem using DNA cryptography and DNA steganography for the cloud-based IoT infrastructure. *Computers and Electrical Engineering*, 104, A, 108426, ISSN 0045-7906, <https://doi.org/10.1016/j.compeleceng.2022.108426>

Supplementary Figure S1. Simulation code used for library-scale encoding analysis

Reference implementation used to reproduce capacity estimates and sequence-statistics simulations. 1) Required nucleotides for a national-library-scale archive (books -> bits -> nucleotides), 2) Estimated oligonucleotide pool size for a given oligo architecture, 3) Sequence-statistics simulation for synthesis compatibility (GC distribution, homopolymer runs). The adaptive mapping below is a compact, reference implementation that demonstrates (i) key-dependent mapping, (ii) dependence on previous base, and (iii) constraint-checking (homopolymer limit + GC band).

```
1 #!/usr/bin/env python3
2
3
4
5
6 from __future__ import annotations
7
8 import math
9
10 import hashlib
11
12 import numpy as np
13
14 # -----
15 # Parameters (edit as needed)
16 # -----
17
18
19 N_BOOKS = 2_600_000 # national library scale example
20
21 SIZE_MB_PER_BOOK = 1.0 # average digitized book size (MB)
22
23 COMPRESSION_FACTOR = 0.55 # 0.55 means 45% reduction vs raw (example)
24
25 EFFECTIVE_BITS_PER_NT = 1.83 # effective bits/nt after overhead (example)
26
27 OLIGO_TOTAL_NT = 180 # total oligo length (nt)
28
29 PAYLOAD_NT = 110 # payload region length (nt)
30
31
32 ECC_NT = 30 # error correction symbols length (nt)
33
34 PRIMER_NT = 20 # primer length (each end, nt)
35
```

```

36 # Sequence constraints (typical synthesis constraints)
37 HOMOPOLYMER_MAX = 3 # max run length (e.g., 3-4)
38 GC_MIN = 0.40
39 GC_MAX = 0.60
40
41 # Simulation settings
42 SIM_N_OLIGOS = 5000 # number of oligos to simulate for statistics
43 SIM_PAYLOAD_BITS = int(PAYLOAD_NT * EFFECTIVE_BITS_PER_NT) # approx
bits carried per payload
44 KEY = "hiDNA-demo-key" # demo key (replace with your key handling)
45
46
47 DNA_ALPHABET = np.array(list("ACGT"))
48
49
50 # -----
51 # Library-scale capacity model
52 # -----
53 def estimate_required_nucleotides(
54     n_books: int,
55     size_mb_per_book: float,
56     compression_factor: float,
57     effective_bits_per_nt: float,
58 ) -> dict:
59     """Return required bits, nucleotides, and a few convenience metrics."""
60     raw_bits = n_books * size_mb_per_book * 1e6 * 8
61     compressed_bits = raw_bits * compression_factor
62     required_nt = compressed_bits / effective_bits_per_nt
63
64     return {
65         "raw_bits": raw_bits,
66         "compressed_bits": compressed_bits,
67         "required_nt": required_nt,
68         "required_nt_scientific": f"{required_nt:.3e}",
69     }
70
71
72 def estimate_oligo_pool_size(required_nt: float, oligo_total_nt: int) -> dict:
73     """Approximate number of oligos required for a given total length oligo architecture."""
74     n_oligos = required_nt / oligo_total_nt
75     return {
76         "n_oligos": n_oligos,
77         "n_oligos_scientific": f"{n_oligos:.3e}",
78     }

```

```

79
80
81 # -----
82 # Key-dependent adaptive mapping
83 # -----
84 def _hash_to_int(s: str) -> int:
85     h = hashlib.sha256(s.encode("utf-8")).digest()
86     return int.from_bytes(h[:8], "big")
87
88
89 def _allowed_bases(prev_base: str) -> list[str]:
90     """Optionally restrict transitions (can be extended)."""
91     return ["A", "C", "G", "T"]
92
93
94 def encode_bits_to_dna_with_constraints(
95     bits: np.ndarray, # array of 0/1
96     key: str,
97     homopolymer_max: int = 3,
98     gc_min: float = 0.40,
99     gc_max: float = 0.60,
100 ) -> str:
101     """
102     Reference adaptive encoder:
103     - reads bits in pairs (00/01/10/11)
104     - selects base as a function of (bit_pair, prev_base, key, position)
105     - enforces homopolymer and GC-band constraints with remapping
106     """
107     assert bits.ndim == 1 and set(np.unique(bits)).issubset({0, 1})
108     # pad to even length
109     if len(bits) % 2 == 1:
110         bits = np.concatenate([bits, np.array([0], dtype=int)])
111
112     out = []
113     prev = "A" # seed; could be randomized or key-derived
114
115     gc_count = 0
116     for i in range(0, len(bits), 2):
117         bp = f'{bits[i]} {bits[i+1]}' # "00".. "11"
118         pos = i // 2
119
120         # propose base using key-dependent hash
121         h = _hash_to_int(f'{key}|{prev}|{bp}|{pos}')
122         bases = _allowed_bases(prev)

```

```

123 proposed = bases[h % 4]
124
125 # constraint enforcement loop (remap if needed)
126 candidate = proposed
127 for attempt in range(8):
128 # homopolymer check
129 if len(out) >= homopolymer_max:
130 if all(b == candidate for b in out[-homopolymer_max:]):
131 # rotate candidate deterministically
132 candidate = bases[(bases.index(candidate) + 1 + attempt) % 4]
133
134 # GC check (soft, keeps running GC within band)
135 tmp_gc = gc_count + (1 if candidate in ("G", "C") else 0)
136 tmp_len = len(out) + 1
137 tmp_gc_frac = tmp_gc / tmp_len
138 if tmp_len > 20: # avoid over-constraining very short sequences
139 if tmp_gc_frac < gc_min or tmp_gc_frac > gc_max:
140 candidate = bases[(bases.index(candidate) + 2 + attempt) % 4]
141 continue
142
143 # accept
144 break
145
146 out.append(candidate)
147 if candidate in ("G", "C"):
148 gc_count += 1
149 prev = candidate
150
151 return "".join(out)
152
153
154 # -----
155 # Sequence statistics
156 # -----
157 def max_homopolymer_run(seq: str) -> int:
158 m = 1
159 cur = 1
160 for i in range(1, len(seq)):
161 if seq[i] == seq[i-1]:
162 cur += 1
163 m = max(m, cur)
164 else:
165 cur = 1
166 return m

```

```

167
168
169 def homopolymer_run_hist(seq: str, max_len: int = 8) -> np.ndarray:
170 """Histogram of run lengths (1..max_len, with max bucket capturing >=max_len)."""
171 counts = np.zeros(max_len, dtype=int)
172 cur = 1
173 for i in range(1, len(seq)):
174 if seq[i] == seq[i-1]:
175 cur += 1
176 else:
177 counts[min(cur, max_len) - 1] += 1
178 cur = 1
179 counts[min(cur, max_len) - 1] += 1
180 return counts
181
182
183 def gc_fraction(seq: str) -> float:
184 return (seq.count("G") + seq.count("C")) / len(seq)
185
186
187 def simulate_sequence_stats(
188 n_oligos: int,
189 payload_bits: int,
190 key: str,
191 ) -> dict:
192 rng = np.random.default_rng(42)
193 gc = np.zeros(n_oligos, dtype=float)
194 max_runs = np.zeros(n_oligos, dtype=int)
195 run_hists = []
196
197 for i in range(n_oligos):
198 bits = rng.integers(0, 2, size=payload_bits, dtype=int)
199 seq = encode_bits_to_dna_with_constraints(bits, key)
200 gc[i] = gc_fraction(seq)
201 max_runs[i] = max_homopolymer_run(seq)
202 run_hists.append(homopolymer_run_hist(seq, max_len=8))
203
204 run_hists = np.vstack(run_hists) # (n_oligos, 8)
205 return {
206 "gc": gc,
207 "max_runs": max_runs,
208 "run_hist_mean": run_hists.mean(axis=0),
209 "run_hist_sum": run_hists.sum(axis=0),
210 }

```

```

211
212
213 # -----
214 # Main (prints core results)
215 # -----
216 def main():
217     cap = estimate_required_nucleotides(
218         N_BOOKS, SIZE_MB_PER_BOOK, COMPRESSION_FACTOR,
219         EFFECTIVE_BITS_PER_NT
220     )
221     pool = estimate_oligo_pool_size(cap["required_nt"], OLIGO_TOTAL_NT)
222     print("==== DNA Ark / hiDNA — Library-scale Estimates ====")
223     print(f'Books: {N_BOOKS:,}')
224     print(f'Avg size per book: {SIZE_MB_PER_BOOK} MB')
225     print(f'Compression factor: {COMPRESSION_FACTOR}')
226     print(f'Effective bits/nt: {EFFECTIVE_BITS_PER_NT}')
227     print(f'Required nucleotides (nt): {cap['required_nt_scientific']}')
228     print(f'Estimated oligos (length {OLIGO_TOTAL_NT} nt):
229         {pool['n_oligos_scientific']}')
230     stats = simulate_sequence_stats(SIM_N_OLIGOS, SIM_PAYLOAD_BITS, KEY)
231     print("\n==== Sequence Simulation (hiDNA reference encoder) ====")
232     print(f'Simulated oligos: {SIM_N_OLIGOS}')
233     print(f'Payload bits simulated per oligo: {SIM_PAYLOAD_BITS}')
234     print(f'GC fraction mean ± sd: {stats['gc'].mean():.3f} ± {stats['gc'].std():.3f}')
235     print(f'Max homopolymer run (median): {int(np.median(stats['max_runs']))}')
236     print("Run-length histogram (mean counts per oligo) for lengths 1..8 (8 = 8+):")
237     print(np.round(stats["run_hist_mean"], 2))
238
239
240 if __name__ == "__main__":
241     main()

```

Supplementary Figure 2. The Error Correction Module.

```
import reedsolo

def get_rs_encoder(error_correction_bytes: int = 32):
    """
    Initializes a Reed-Solomon encoder.
    32 bytes of ECC can correct up to 16 byte-errors per block.
    """
    return reedsolo.RSCodec(error_correction_bytes)

def encode_with_ecc(data_bytes: bytes, ecc_bytes: int = 32) -> bytes:
    """
    Adds Reed-Solomon error correction parity to the data.
    """
    rs = get_rs_encoder(ecc_bytes)
    return rs.encode(data_bytes)

def decode_with_ecc(corrupted_data: bytes, ecc_bytes: int = 32) -> bytes:
    """
    Attempts to repair corrupted data using the RS parity bytes.
    Returns the original data or raises ReedSolomonError if too many errors exist.
    """
    rs = get_rs_encoder(ecc_bytes)
    try:
        # Returns a bytearray of the corrected message
        return rs.decode(corrupted_data)[0]
    except reedsolo.ReedSolomonError:
        return None # Critical failure: too many errors to fix
```

Supplementary Figure 3. Simulating "Wet-Lab" Noise (Sequencing Errors)

```
import random

def simulate_dna_corruption(dna_sequence: str, error_rate: float = 0.01) -> str:
    """
    Simulates random substitution errors in the DNA string.
    Example: 1% error rate (typical for modern Illumina/Nanopore).
    """
    bases = ['A', 'C', 'G', 'T']
    dna_list = list(dna_sequence)
    for i in range(len(dna_list)):
        if random.random() < error_rate:
            # Swap current base with a different random base
            current_base = dna_list[i]
            possible_errors = [b for b in bases if b != current_base]
            dna_list[i] = random.choice(possible_errors)
    return "".join(dna_list)
```

Supplementary Figure 4. Integration into the hiDNA Pipeline (simulation loop to show the full End-to-End reliability)

```
# 1. Start with original book data
original_data = b"Knowledge from the National Library..."

# 2. Add Error Correction (The 'Safety Net')
ecc_bytes = 12
data_with_ecc = encode_with_ecc(original_data, ecc_bytes)

# 3. Convert to DNA using your hiDNA Adaptive Mapping
# (Uses your existing encode_bits_to_dna_with_constraints function)
dna_seq = hi_dna_encode(data_with_ecc, key="EarthMemory2024")

# 4. Simulate Noise (The 'Wet-Lab' environment)
corrupted_dna = simulate_dna_corruption(dna_seq, error_rate=0.02)

# 5. Decode back to bits using hiDNA Key
# (Requires the exact same key to unscramble)
recovered_bits_with_ecc = hi_dna_decode(corrupted_dna, key="EarthMemory2024")

# 6. Final Repair
final_data = decode_with_ecc(recovered_bits_with_ecc, ecc_bytes)

if final_data == original_data:
    print("Success: DNA Ark recovered the data perfectly despite 2% error rate!")
```