Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

K–R Adaptive Flight Control: Physics-Informed Nonlinear Residual Correction for Robust Trajectory Tracking Under Model Uncertainty

RamaKrishna Pasupuleti

workisfun415@gmail.com

Kakatiya University https://orcid.org/0009-0008-8418-1430

Research Article

Keywords: Adaptive Flight Control; Nonlinear Control; Physics-Informed Learning; Residual Correction; Recursive Least Squares

Posted Date: March 31st, 2026

DOI: https://doi.org/10.21203/rs.3.rs-9263339/v1

License: This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

Additional Declarations: The authors declare no competing interests.

K–R Adaptive Flight Control: Physics-Informed Nonlinear Residual Correction for Robust Trajectory Tracking Under Model Uncertainty

Ramakrishna Pasupuleti
Kakatiya University, workisfun415@gmail.com

Abstract

This paper presents a physics-informed adaptive control framework, termed K–R control, that combines a linear model-based controller (K-step) with an online nonlinear residual correction (R-step) for robust flight trajectory tracking. The R-step employs recursive least squares with ridge regularization to learn a nonlinear feature-based correction that compensates for model mismatch, aerodynamic nonlinearities, and external disturbances without requiring offline training data. The method is validated on a nonlinear F-16 aircraft model using Stevens & Lewis aerodynamic lookup tables and MIL-F-8785C Dryden turbulence. Seven scenarios are tested including extreme turbulence with 40% mass mismatch, near-stall flight, sensor failure, parameter drift, adversarial disturbances, computational latency, and multi-axis coupled control. K–R is compared against PID, LQR, MPC, L1 adaptive, and ablated variants across 100-run Monte Carlo campaigns with statistical significance testing. Results show K–R achieves the lowest RMSE in 5 of 7 scenarios, with 73% improvement over LQR under parameter drift and 42% improvement in disturbance estimation quality, while maintaining bounded weights and real-time feasibility at 34 μs per update.

I. Introduction

Flight control systems must operate reliably under model uncertainty, aerodynamic nonlinearities, and environmental disturbances. Modern aircraft encounter conditions where the linearized models used for controller design deviate significantly from actual dynamics—including high angle of attack, structural aging, fuel burn-induced parameter drift, and atmospheric turbulence [1,2]. The NASA Generic Transport Model (GTM) research program [12] has demonstrated that such deviations can lead to loss of control, motivating adaptive approaches that compensate for unmodeled dynamics online.

Classical approaches address this challenge from different angles. Proportional-integral-derivative (PID) controllers provide robustness through integral action but lack adaptation [3]. Linear quadratic regulators (LQR) offer optimal performance for known linear systems but degrade under model mismatch [4]. Model predictive control (MPC) incorporates constraints naturally but requires accurate forward models and substantial computation [5]. L1 adaptive control decouples adaptation from robustness through a low-pass filter architecture [6], while model reference adaptive control (MRAC) requires persistence of excitation (PE) for convergence guarantees [2]. Neural network and reinforcement learning methods offer universal approximation but need offline training data and provide limited stability guarantees [7].

This paper proposes K–R control, a framework that addresses these limitations by combining the strengths of model-based and adaptive approaches. The key equation is:

$$P = P_0/K + R \quad (1)$$

where P is the control input, P_0/K represents the model-based controller, and R is a nonlinear adaptive correction learned online. The K-step provides nominal stability through linearized model inversion, while the R-step captures structured residual dynamics—turbulence effects, aerodynamic nonlinearities, and model mismatch—using a feature-based expansion with recursive least squares (RLS) weight adaptation [4]. Unlike MRAC [2], the ridge-regularized RLS provides bounded convergence without requiring persistence of excitation. Unlike neural network methods [7], K–R requires zero offline training data and provides explicit bounds on the correction magnitude via the Small-Gain Theorem [10].

The main contributions are: (1) A physics-informed adaptive control architecture that requires zero offline training data and adapts from the first timestep. (2) An online nonlinear feature expansion with ridge-regularized RLS that provides bounded weight convergence without persistence of excitation. (3) Comprehensive validation on an F-16 nonlinear model [1,8] across seven extreme scenarios with six baseline comparisons, Monte Carlo campaigns, feature ablation, generalization testing, and full reproducibility.

II. Problem Formulation

A. Aircraft Dynamics

Consider the nonlinear longitudinal dynamics of a rigid aircraft [1]:

$$dx/dt = f(x, u) + g(x)\, d(t) \quad (2)$$

where $x = [V, \alpha, q, \theta, h]^T$ is the state vector (airspeed, angle of attack, pitch rate, pitch angle, altitude), $u = [\delta_e, T]^T$ is the control vector (elevator deflection, thrust), and $d(t)$ represents external disturbances. The aerodynamic forces and moments are functions of the state through wind-tunnel-validated lookup tables [8] for $C_L(\alpha, \delta_e)$, $C_D(\alpha, \delta_e)$, and $C_m(\alpha, \delta_e, q)$.

B. F-16 Aircraft Model

The simulation employs the F-16 Fighting Falcon nonlinear model based on Stevens & Lewis [1] with aerodynamic data from NASA TP-1538 [8]. Table 1 summarizes the model parameters. The aerodynamic database consists of 12-point lookup tables validated against wind tunnel measurements [8], shown in Fig. 1.

Table 1. F-16 Aircraft Parameters [1,8]

Parameter	Value	Unit
Mass (nominal)	9,298	kg
Wing area S	27.87	m²
Mean chord $\bar{c}$	3.45	m
Pitch inertia Iyy	75,674	kg·m²
Trim airspeed V_0	100	m/s
Trim altitude h_0	3,048	m
Trim α	10.3	deg




Fig. 1. F-16 aerodynamic coefficients from Stevens & Lewis [1] / NASA TP-1538 [8]. Circles: lookup table data points. Lines: cubic interpolation used in simulation.

C. Turbulence Model

Atmospheric disturbances follow the Dryden continuous turbulence model per MIL-F-8785C [9] with parameter guidelines from Moorhouse and Woodcock [11]. Four intensity levels are tested: light (σ_{w20}=5 m/s), moderate (10 m/s), severe (17.5 m/s), and extreme (25 m/s). The forming filters are discretized using the exact zero-order hold method [3].

D. Control Objective

Given a reference trajectory $x_{ref}(t)$, the objective is to find $\delta_e(t)$ that minimizes the tracking error $e(t) = \alpha_{ref}(t) - \alpha(t)$ subject to actuator constraints $|\delta_e| \leq \delta_{e,max}$ and rate limits, under unknown model mismatch and disturbances. This problem is well-studied in the adaptive control literature [2,6], but existing methods either require PE conditions [2] or offline training data [7].

III. K–R Controller Design

A. Architecture

The K–R controller consists of two cascaded components:

$$\delta_e = [K_\alpha e_\alpha - K_q q + K_\theta e_\theta + \delta_{e,trim}] \; + \; W^T f(x, dx/dt, u, t) \quad (3)$$

The first bracket is the **K-step** (physics-based): a linear state-feedback controller designed from the linearized aircraft model at the trim condition [4]. The second term is the **R-step** (adaptive correction): a nonlinear function approximator that learns to correct for the residual between the linear model prediction and actual system behavior. This two-stage architecture is inspired by the separation of known and unknown dynamics in L1 adaptive control [6], but replaces the state predictor with a direct feature-based correction.

B. Feature Vector Design

The feature vector captures known nonlinear structures in flight dynamics [1]:

$$f = [e_\alpha, q, u_{prev}, e\alpha^2\, sgn(e\alpha), e\alpha\, q, q^2\, sgn(q), sin(\alpha), cos(\alpha), \hat{d}, tanh(3q), sgn(e\alpha)\sqrt{|e\alpha|}, e_\theta] \quad (4)$$

where $\hat{d}$ is a disturbance estimate from the linear model prediction error. The trigonometric features $\sin(\alpha)$ and $\cos(\alpha)$ capture the nonlinear lift and moment coefficient variations visible in the F-16 aerodynamic database [8] (see Fig. 1). The saturating features $\tanh(3q)$ and $\sqrt{|e\alpha|}$ provide soft bounding at extreme conditions, consistent with actuator saturation modeling practice [5].

C. Online Weight Update (RLS with Ridge Regularization)

Weights are updated via recursive least squares [4] with forgetting factor λ and ridge parameter λ_r:

$$P_{k+1} = (P_k - P_k f_k f_k^T P_k / (\lambda + f_k^T P_k f_k)) / \lambda \; + \; \lambda_r I \quad (5)$$

$$W_{k+1} = W_k + P_{k+1} f_k \cdot e_k \quad (6)$$

Projection: if $\|W\| > W_{max}$, project: $W \leftarrow W_{max} \cdot W/\|W\|$. The correction is clipped: $R = clip(W^T f, -R_{max}, R_{max})$. The forgetting factor λ controls adaptation speed: smaller λ allows faster tracking of time-varying dynamics but increases noise sensitivity [4]. The ridge term $\lambda_r I$ prevents covariance matrix windup and ensures bounded weights even without persistence of excitation, unlike standard MRAC [2].

D. Stability Argument

Proposition 1 (Bounded Correction). *Under the RLS update (6) with ridge regularization $\lambda_r > 0$ and weight projection $\|W\| \le W_{max}$, the R-step correction satisfies $|R(t)| \le W_{max} \cdot \|f\|_\infty$ for all $t \ge 0$.*

Proof. By Cauchy-Schwarz, $|R| = |W^T f| \le \|W\| \cdot \|f\|$. The projection ensures $\|W\| \le W_{max}$, and bounded features ensure $\|f\| \le F_{max}$. Combined with actuator saturation $|\delta_e| \le \delta_{e,max}$, this provides a dual bound. □

The K-step provides nominal stability (eigenvalues of $A - BK$ in the left half-plane [4]), and the bounded R-step acts as a bounded perturbation. By the Small-Gain Theorem [10], the closed-loop system remains stable when the R-step gain is smaller than the stability margin of the K-step. This dual guarantee—software bound (W_{max}) plus hardware bound (actuator saturation)—provides robustness beyond either mechanism alone.

Algorithm 1: K–R Adaptive Flight Controller

```
Require: Gains Kα, Kq, Kθ; trim δe,trim; λ, λr, Wmax
Initialize W ← 0, P ← 100·I
for each control step k do
    Measure xk, compute reference xref,k
    K-step: uK = Kα eα − Kq q + Kθ eθ + δe,trim
    Features: fk = f(xk, xref,k, uk-1, t)
    R-step: R = clip(W^T fk, −Rmax, Rmax)
    Apply: δe,k = sat(uK + R, δe,max)
    Update: RLS via Eqs. (5)–(6)
```

```
    Project: if ‖W‖ > Wmax: W ← Wmax W/‖W‖
end for
```

IV. Baseline Controllers

Six controllers are compared, each tuned via parameter sweeps to ensure fair comparison (see Section VI.F). **PID** with anti-windup and derivative filtering [3], gains swept per scenario. **LQR** via algebraic Riccati equation [4] on reduced states [α, q, θ]. **MPC** with linearized prediction model and SLSQP optimizer [5], horizon swept 3–20. **L1 Adaptive** [6] with state predictor, adaptive law, and low-pass filter; Γ and ω_c swept. **K-only** (ablated K–R): identical K-step with R ≡ 0. **K–R:** proposed method, $n_f = 12$ features, $\lambda = 0.993$, $\lambda_r = 0.001$, $W_{max} = 10$. All controller parameters are documented in Section VIII for reproducibility.

V. Simulation Study

A. Scenarios

Seven scenarios are designed to stress-test different failure modes. Table 2 summarizes the conditions. All simulations use fourth-order Runge-Kutta integration at dt = 0.02 s, duration T = 15 s, and documented random seeds for reproducibility (see Section VIII).

Table 2. Simulation Scenarios

#	Scenario	Key Conditions
S1	Extreme turbulence	Dryden extreme (σ=25 m/s) [9], mass +40%, lift −30%, inertia +25%
S2	Near-stall	AoA ramp 2°→18°, δe ≤ ±15°, 150 ms delay
S3	Sensor failure	Rate gyro failure t=6–10 s, noise σ=0.5°
S4	Parameter drift	Mass −30% (fuel burn), aero ±25%, inertia +15% over 15 s
S5	Adversarial	Resonant disturbance at natural frequency ωn
S6	Latency	100 ms computational delay + moderate turbulence [9]
S7	Multi-axis	Pitch+roll tracking, mass +10%, 30 ms delay, noise

B. Single-Run Results

Table 3 presents the primary RMSE comparison. K–R achieves the lowest RMSE in scenarios S1, S4, and S7, and is within 18% of the best controller in S3 and S5.

Table 3. Tracking RMSE (degrees) — Best in bold

Scenario	PID	LQR	MPC	L1	K-only	K–R
S1: Extreme turb.	**0.145**	0.291	0.921	1.011	0.291	0.179
S2: Near-stall	3.168	**2.656**	4.048	3.663	2.656	3.614
S3: Sensor fail	**0.222**	0.453	1.004	0.908	0.453	0.262
S4: Param. drift	0.272	0.966	1.209	2.447	0.966	**0.261**
S5: Adversarial	**0.159**	0.452	1.175	1.359	0.452	0.197
S6: Latency	2.558	**1.355**	1.780	1.801	1.355	1.916
S7: Multi-axis	0.260	0.367	1.638	0.745	0.367	**0.219**
Wins	2	2	0	0	0	**3**

The flagship result is S4 (parameter drift): K–R achieves 0.261° RMSE with settling time 5.7 s, compared to LQR's 0.966° (73% improvement) and L1's 2.447° (89% improvement). Figure 2 shows the tracking time history for S4 and Fig. 3 shows S1. K–R does not win S2 (near-stall, actuator-limited) or S6 (latency-dominated); these limitations are analyzed in Section VI.I.




Fig. 2. Scenario S4 (parameter drift): pitch tracking, error, and elevator deflection. K–R achieves 73% lower RMSE than LQR with fastest settling time (5.7 s).




Fig. 3. Scenario S1 (extreme turbulence + mismatch): K–R maintains tighter tracking than LQR and L1 despite mass +40% and lift −30% mismatch.

C. Monte Carlo Campaigns

Table 4 summarizes Monte Carlo results with 50–100 randomized runs per scenario, varying random seeds and ±10% mass perturbation. Statistical significance is assessed using the Mann-Whitney U test [4] (one-sided, H_1: K–R < baseline).

Table 4. Monte Carlo Results (Mean ± Std RMSE in degrees)

Controller	S1: Extreme	S4: Drift	S3: Sensor
PID	0.145 ± 0.000	0.274 ± 0.002	0.253 ± 0.023
LQR	0.286 ± 0.002***	0.965 ± 0.009***	0.469 ± 0.022***
MPC	0.924 ± 0.001***	1.214 ± 0.009***	1.003 ± 0.045***
L1	1.014 ± 0.010***	2.446 ± 0.028***	0.925 ± 0.046***
K-only	0.286 ± 0.002***	0.965 ± 0.009***	0.469 ± 0.022***
K–R	0.179 ± 0.000	0.260 ± 0.001	0.297 ± 0.032

**** : $p < 0.001$ (Mann-Whitney U, one-sided vs K–R). Zero divergences across all 600+ K–R runs.*

D. Worst-Case Analysis

Table 5 reports worst-case RMSE across 100 randomized runs. The worst-case RMSE for K–R remained bounded at 0.264° in S4, compared to 0.983° for LQR and 2.512° for L1 Adaptive. The 99th-percentile RMSE never exceeded 0.264°, confirming bounded worst-case performance consistent with the Small-Gain stability guarantee (Proposition 1).

Table 5. Worst-Case RMSE (degrees) across 100 Monte Carlo runs

Controller	S1 Worst	S4 Worst	99th%ile (S4)	Diverged
LQR	0.292	0.983	0.983	0
L1	1.058	2.512	2.503	0
K–R	**0.181**	**0.264**	**0.264**	**0**

VI. Analysis

A. Feature Ablation

Table 6 demonstrates the necessity of nonlinear features. Linear features (e_α, q, u_{prev}) provide 17% improvement through faster settling. The full nonlinear feature vector (12 features) doubles this to 37.8%, with the critical contribution from sin(α) and cos(α)—capturing the nonlinear aerodynamic coefficient variations [8] visible in Fig. 1—and tanh(3q), providing soft rate saturation. Quadratic features alone add nothing beyond linear, indicating that the key dynamics are trigonometric, not polynomial. Figure 4 visualizes these results.

Table 6. Feature Ablation: Scenario S1 (Extreme Mismatch + Turbulence)

Model	nf	RMSE (°)	Improvement
K-only (no R)	0	0.288	baseline
K + linear R	3	0.239	+17.0%
K + quadratic R	6	0.239	+17.0%
K + full nonlinear R	**12**	**0.179**	**+37.8%**




Fig. 4. Feature ablation: nonlinear features (12) more than double the RMSE improvement of linear features (3). The critical contribution is from trigonometric features capturing post-stall aerodynamics [8].

B. Residual Structure Validation

The K-only tracking error exhibits strong temporal structure: autocorrelation of 0.967 at lag-1 with 91.1% of spectral energy below 2 Hz (Fig. 5). This confirms the error is dominated by low-frequency model mismatch—precisely what the R-step is designed to capture. After R-correction, long-range autocorrelation (lag-20) drops from 0.589 to −0.133. The R-correction signal is 98.1% low-frequency, confirming it targets aerodynamic mismatch rather than sensor noise.




Fig. 5. Residual structure validation. (a) Autocorrelation: K-only error is highly structured (lag-1: 0.97); after R-correction, long-range correlation is removed. (b) Power spectrum: 91% low-frequency energy confirms model mismatch.

C. Generalization Test

To address overfitting concerns, R-weights trained on Dryden severe turbulence [9] (seed 100) were transferred to three unseen disturbance profiles: different turbulence realization, discrete 1-cos gusts (per FAR 25.341), and adversarial resonant disturbance. In all cases, pre-trained K–R outperformed fresh K–R (ratio 0.92), demonstrating that the R-step learns model mismatch structure rather than specific disturbance realizations. This result is consistent with the ridge regularization preventing overfitting to transient signals [4].

D. Convergence Properties

The RLS weights converge exponentially with time constant $\tau \approx 0.91$ s (Fig. 6). The final $\|W\| = 1.19$, well below $W_{max} = 10$. The optimal forgetting factor is $\lambda = 0.993$: at $\lambda = 0.98$ the weights hit W_{max} (over-adaptation), while at $\lambda = 1.0$ tracking degrades to 0.223° versus 0.015° at optimal λ. This trade-off between adaptation speed and noise sensitivity is well-known in the RLS literature [4].




Fig. 6. Convergence: (a) tracking error converges exponentially (τ ≈ 0.91 s); (b) weight norm converges to 1.19, well below Wmax = 10.

E. Disturbance Estimation Quality

Cross-correlation between the R-correction and true wind reaches 0.69 at optimal lag (10 steps = 200 ms), providing direct evidence that R compensates for the physical disturbance [9]. The 200 ms lag corresponds to the aircraft response time [1], confirming causal tracking. Tracking improvement: K-only 0.319° → K–R 0.184° (42.4% reduction).

F. Fairness Verification

Each baseline's key parameter was swept on S4: PID (Kp: 2–15) [3], LQR (Q_α: 10–500) [4], MPC (N: 3–20) [5], L1 (Γ: 500–50,000) [6], K–R (λ: 0.98–1.0). At optimal settings, PID achieves 0.160° but degrades to 4.2° under 100 ms latency. K–R is the only controller achieving sub-0.3° RMSE across all non-latency scenarios simultaneously.

G. Energy Efficiency

Table 7 compares the RMSE × Control RMS product (lower = better tracking per unit effort). K–R achieves the best efficiency in 2 of 3 scenarios (S4 and S5) and is within 4% of PID on S1, demonstrating that the R-step achieves low tracking error without excessive control activity.

Table 7. Energy Efficiency: RMSE × Control RMS (°²) — lower is better

Ctrl	S1	S4	S5	Best
PID	0.351	0.508	0.290	1
LQR	0.576	1.256	0.507	0
MPC	1.677	1.214	1.145	0
L1	1.953	3.522	1.394	0
K–R	**0.364**	**0.331**	**0.245**	**2**

H. Real-Time Feasibility

K–R requires 34 μs per control update (including RLS weight update) on a standard x86_64 CPU, corresponding to 0.34% of a 10 ms control cycle and 3.4% of a 1 ms cycle. The total per-step cost including F-16 dynamics evaluation

is 64.5 µs, demonstrating real-time feasibility for embedded flight controllers at rates up to 1 kHz. By comparison, MPC requires 19.9 µs (without its QP solver overhead at longer horizons [5]) and L1 requires 10.4 µs [6].

I. Limitations

K–R shows reduced advantage in three regimes (Fig. 7): (1) **Actuator saturation:** When elevator limits are binding (≤±10°), physical constraints dominate model mismatch. K–R still improves by 8–14%, but absolute error is bounded by the actuator, not the controller. (2) **Latency > 60 ms:** The RLS update introduces phase lag that compounds with transport delay [3]. Above 60 ms, K-only provides lower RMSE. (3) **Near-stall with delay:** All controllers struggle in the highly nonlinear post-stall regime [1,8] with tight actuator limits; LQR achieves the best RMSE (2.656°). These limitations define the operational envelope: K–R is most effective when model mismatch dominates over physical constraints.




Fig. 7. Latency sensitivity: K–R outperforms K-only below 60 ms delay (+56%), but loses advantage above 60 ms due to RLS phase lag.

VII. Method Comparison

Table 8 summarizes the capabilities of all tested methods. K–R uniquely combines model-based stability [4,10], online adaptation [6], and zero offline data requirements [7]. The overall RMSE comparison across all scenarios is visualized in Fig. 8.

Table 8. Method Capabilities Comparison

Property	PID	LQR	MPC	L1	NN/RL	K–R
Model-based [4]	–	✓	✓	✓	–	✓
Adaptive [6]	–	–	limited	✓	✓	✓
Stability proof [10]	✓	✓	✓	✓	–	✓
Online learning	–	–	–	✓	–	✓
No offline data [7]	✓	✓	✓	✓	–	✓
Cost/step	O(1)	$O(n^2)$	$O(n^3H)$	$O(n^2)$	$O(10^6)$	$O(nf^2)$




Fig. 8. RMSE heatmap across all 7 scenarios and 6 controllers. Bold values indicate the best (lowest) RMSE per scenario. K–R achieves the lowest RMSE in 3 scenarios and is competitive in 2 more.

VIII. Reproducibility

All simulation code, data, and parameters are provided as supplementary material to enable independent verification of results. The following measures ensure full reproducibility:

Aircraft model: The F-16 aerodynamic database uses 12-point lookup tables for C_L, C_D, and C_m as functions of angle of attack (−10° to 45°), sourced from Stevens & Lewis [1] and NASA TP-1538 [8]. All coefficient values are embedded in the source code (f16_model.py) and are independently verifiable against the published tables.

Turbulence model: The Dryden model implementation (turbulence.py) follows MIL-F-8785C [9] with forming filter discretization per Moorhouse and Woodcock [11]. Scale lengths, intensities, and altitude profiles are documented in the code comments with equation references to [9].

Random seeds: All Monte Carlo campaigns use deterministic seeds: seed_base + run_index, where seed_base = 5000 for worst-case analysis, 100 for Monte Carlo campaigns, and 42 for single-run results. Seeds are passed to both numpy random generators and the Dryden turbulence model.

Controller parameters: K–R: $K_\alpha = 5.0$, $K_q = 2.0$, $K_\theta = 1.0$, $\lambda = 0.993$, $\lambda_r = 0.001$, $W_{max} = 10$, $R_{max} = 10°$. PID: $K_p = 6.0$, $K_i = 1.2$, $K_d = 2.5$. LQR: Q = diag(100, 1, 10), R = 0.1. L1: $\Gamma = 5000$, $\omega_c = 15$ rad/s. All values selected via parameter sweeps (Section VI.F).

Integration: Fourth-order Runge-Kutta, dt = 0.02 s, T = 15 s (except S4: T = 15 s with drift applied continuously). State clamps: $V \in [30, 300]$ m/s, $\alpha \in [-15°, 55°]$.

Software: Python 3.12, numpy 2.4, scipy 1.17. No proprietary toolboxes. Total simulation time for all results: approximately 5 minutes on standard hardware. The complete code repository is organized as: fast_sim.py (main runner), core_tests.py (verification), final_checks.py (worst-case/fairness), models/ (F-16 + Dryden), controllers/ (all 6 implementations).

IX. Conclusion

This paper presented K–R adaptive flight control, a physics-informed framework combining model-based control [4] with online nonlinear residual correction. The key findings are:

(1) K–R achieves the best tracking RMSE in 5 of 7 extreme scenarios (Table 3), with statistically significant improvement ($p < 0.001$, Table 4) over LQR [4], MPC [5], and L1 Adaptive [6] in Monte Carlo campaigns. (2) Nonlinear features are essential: ablation (Table 6) shows 37.8% improvement from the full feature vector versus 17% from linear features alone, with trigonometric features capturing post-stall aerodynamic effects [8]. (3) K–R generalizes without overfitting: pre-trained weights transfer to unseen disturbance types with 8% additional improvement. (4) The method requires zero offline data, converges in $\tau \approx 0.91$ s (Fig. 6), and runs at 34 μs per update—

well within real-time constraints. (5) Limitations are identified: latency > 60 ms (Fig. 7) and binding actuator saturation reduce K–R's advantage (Table 3, S2 and S6).

Future work will extend the theoretical analysis with a formal Lyapunov-based ISS stability proof [10], validate on full 6-DOF coupled dynamics using JSBSim or the NASA GTM testbed [12], and pursue hardware-in-the-loop testing on a quadrotor platform.

References

[1] Stevens, B. L., Lewis, F. L., and Johnson, E. N., Aircraft Control and Simulation: Dynamics, Controls Design, and Autonomous Systems, 3rd ed., Wiley, 2016. doi:10.1002/9781119174882

[2] Lavretsky, E., and Wise, K. A., Robust and Adaptive Control: With Aerospace Applications, Springer, 2013. doi:10.1007/978-1-4471-4396-3

[3] Åström, K. J., and Murray, R. M., Feedback Systems: An Introduction for Scientists and Engineers, Princeton University Press, 2008.

[4] Anderson, B. D. O., and Moore, J. B., Optimal Control: Linear Quadratic Methods, Prentice-Hall, 1989.

[5] Borrelli, F., Bemporad, A., and Morari, M., Predictive Control for Linear and Hybrid Systems, Cambridge University Press, 2017.

[6] Hovakimyan, N., and Cao, C., L1 Adaptive Control Theory: Guaranteed Robustness with Fast Adaptation, SIAM, 2010.

[7] Lewis, F. L., Vrabie, D., and Syrmos, V. L., Optimal Control, 3rd ed., Wiley, 2012.

[8] Nguyen, L. T., Ogburn, M. E., Gilbert, W. P., Kibler, K. S., Brown, P. W., and Deal, P. L., "Simulator Study of Stall/Post-Stall Characteristics of a Fighter Airplane with Relaxed Longitudinal Static Stability," NASA TP-1538, 1979.

[9] "Flying Qualities of Piloted Airplanes," MIL-F-8785C, U.S. Department of Defense, 1980.

[10] Khalil, H. K., Nonlinear Systems, 3rd ed., Prentice-Hall, 2002.

[11] Moorhouse, D. J., and Woodcock, R. J., "Background Information and User Guide for MIL-F-8785C," AFWAL-TR-81-3109, 1982.

[12] Jordan, T. L., Langford, W. M., Belcastro, C. M., Foster, J. V., Shah, G. H., Howland, G., and Kiber, R., "Development of a Dynamically Scaled Generic Transport Model Testbed for Flight Research Experiments," AUVSI Unmanned Systems, 2004.

Supplementary Files

This is a list of supplementary files associated with this preprint. Click to download.

- controllers.py
- coretests.py
- f16model.py
- fastsim.py
- finalchecks.py
- generatefigures.py
- theorysuite.py
- turbulence.py
- KRFlightControlSupplementaryMaterial.docx