Research Square

Preprints are preliminary reports that have not undergone peer review.
They should not be considered conclusive, used to inform clinical practice,
or referenced by the media as validated information.

# A Dynamic Explainable AI FrameworkforReal-Time Intrusion Detection andAutomatedAlert Prioritization in Security OperationCenters

**Muhammad Usama Nazir**

usamanazir@graduate.utm.my

University of Technology Malaysia

**Asri Bin Ngadi**

University of Technology Malaysia

**Article**

**Keywords:** Intrusion Detection System; Explainable AI; SHAP; LIME; Graph Convolutional Network; Time-series Transformer; Security Operation Center; Alert Prioritization; CIC-IDS-2018; Cybersecurity

**Posted Date:** June 24th, 2026

**DOI:** https://doi.org/10.21203/rs.3.rs-9603260/v1

**License:** This work is licensed under a Creative Commons Attribution 4.0 International License.
Read Full License

**Additional Declarations:** No competing interests reported.

**Version of Record:** A version of this preprint was published at Scientific Reports on September 24th, 2026. See the published version at https://doi.org/10.1038/s41598-026-72373-6.

# A Dynamic Explainable AI Framework for Real-Time Intrusion Detection and Automated Alert Prioritization in Security Operation Centers

Muhammad Usama Nazir[1]
Dr. Asri bin Ngadi[1]

[1]Faculity of Computing,
University of Technology, Malaysia

usamanazir@graduate.utm.my, dr.asri@utm.my

**Abstract**

Security Operation Center (SOC) analysts face an overwhelming volume of 50–100 security alerts per hour, leading to cognitive fatigue and delayed incident response. The global mean time to detect a data breach is 181 days, enabling attackers to inflict an average financial loss of USD 5.46 million per breach. Existing intrusion detection systems (IDS) suffer from high false-positive rates and opaque black-box architectures that erode analyst trust and slow triage decisions. This paper proposes the *Dynamic Explainable Framework* (DEF), a three-stage pipeline integrating: (i) a time-series Transformer for temporal attack-pattern recognition, (ii) a Graph Convolutional Network (GCN) for modeling attack-propagation topology, and (iii) post-hoc Explainable AI explanations using SHAP and LIME to generate human-interpretable per-alert rationales. Evaluated on a CIC-IDS-2018 structured benchmark comprising 60,000 samples across eight attack categories, the DEF achieves a detection accuracy of **94.58%**, macro F1-score of **90.11%**, and AUC-ROC of **0.9855**, outperforming Random Forest (F1 87.97%) and LSTM (F1 90.11%). The alert prioritization layer reduces the number of alerts presented to analysts by **68.9%** — from 50–100 to approximately 16–31 per hour — while

maintaining a recall of 90.72% and achieving a false-positive rate of only **1.16%**. SHAP global explanations are generated at **8.7 ms per sample**, meeting the near-real-time threshold for SOC deployment, while LIME local explanations average **234.8 ms per instance**. These results confirm that the DEF simultaneously delivers high detection accuracy, significant alert workload reduction, and transparent, actionable explanations suitable for production SOC environments.

**Keywords:** Intrusion Detection System; Explainable AI; SHAP; LIME; Graph Convolutional Network; Time-series Transformer; Security Operation Center; Alert Prioritization; CIC-IDS-2018; Cybersecurity.

# Contents


**1 Introduction** **5**

**2 Related Work** **6**

2.1 Machine Learning-Based Intrusion Detection . . . . . 6
2.2 Explainable AI Techniques for IDS . . . . . 7
2.3 Temporal and Graph-Based IDS . . . . . 8
2.4 Alert Management and SOC Optimization . . . . . 8
2.5 Research Gap Summary . . . . . 8

**3 Proposed Methodology: Dynamic Explainable Framework** **9**

3.1 Framework Architecture . . . . . 9
3.2 Time-Series Transformer Module . . . . . 11
3.3 Graph Convolutional Network Module . . . . . 11
3.4 Feature Fusion and Classification . . . . . 11
3.5 SHAP Explanation Module . . . . . 12
3.6 LIME Explanation Module . . . . . 12
3.7 Alert Prioritization Layer . . . . . 12

**4 Experimental Setup** **13**

4.1 Dataset . . . . . 13
4.2 Preprocessing Pipeline . . . . . 13
4.3 Baseline Models . . . . . 14
4.4 Implementation Details . . . . . 14
4.5 Evaluation Metrics . . . . . 14

**5 Results** **15**

5.1 Overall Detection Performance . . . . . 15
5.2 Per-Class Detection Performance . . . . . 15
5.3 Comparative Per-Class Analysis . . . . . 16
5.4 Alert Prioritization and SOC Impact . . . . . 17
5.5 XAI Explanation Quality . . . . . 17
5.6 SHAP Feature Importance Analysis . . . . . 18
5.7 LIME Local Explanation Example . . . . . 19
5.8 Confusion Matrix Analysis . . . . . 21
5.9 Ablation Study . . . . . 21
5.10 Threshold Sensitivity Analysis . . . . . 22

**6 Discussion** **22**
6.1 Interpretation of Detection Results . . . . . 22
6.2 SOC Workload Impact . . . . . 23
6.3 XAI Explanation Speed and Analyst Trust . . . . . 23
6.4 Limitations . . . . . 23

**7 Conclusion** **24**

# 1 Introduction

The exponential proliferation of networked devices has fundamentally altered the cybersecurity threat landscape. Modern enterprise networks generate traffic volumes that no human team can inspect manually, and Security Operation Centers (SOCs) are increasingly reliant on automated alerting systems. However, automation without interpretability creates a new problem: SOC analysts receive 50–100 security alerts per hour from automated IDS, of which a large proportion are false positives that consume analyst attention without representing real threats IBM [2023], Ponemon [2023].

The consequences of inadequate IDS are measurable and severe. The IBM Cost of a Data Breach Report IBM [2023] and the Ponemon Institute Ponemon [2023] document a global mean time to detect (MTTD) a breach of 181 days. Breaches that remain undetected for more than 200 days cost an average of USD 5.46 million. The principal drivers of this detection latency are alert fatigue, false-positive overload, and the inability of analysts to quickly understand why an IDS raised a particular alert Mohale and Obagbuwa [2025], Gaspar et al. [2024].

Traditional signature-based IDS such as Snort Snort [2024] and Suricata Suricata [2024] match traffic against known attack signatures with high precision for documented threats, but are completely blind to zero-day attacks and novel evasion techniques Khraisat and Alazab [2021]. Machine learning-based IDS have substantially improved anomaly detection capability, with models such as XGBoost Han et al. [2026], Random Forest Talukder et al. [2023], and LSTM Shone et al. [2018] achieving over 97% accuracy on standard benchmarks. However, these models share a critical weakness: they are black boxes. An analyst who receives an alert from a black-box model cannot verify whether the prediction is correct, cannot explain it to a stakeholder, and cannot develop intuition about what network conditions trigger false positives. This lack of interpretability is now a recognized barrier to operational IDS adoption Arrieta et al. [2020], Doshi-Velez and Kim [2017].

Explainable AI (XAI) addresses the transparency problem directly. SHapley Additive exPlanations (SHAP) Lundberg and Lee [2017] and Local Interpretable Model-Agnostic Explanations (LIME) Ribeiro et al. [2016] have emerged as the dominant post-hoc explanation techniques in cybersecurity, providing feature-level attributions that explain individual detection decisions. Recent studies have confirmed that XAI-augmented IDS improves analyst trust, reduces triage time, and supports regulatory compliance in sensitive deployment environments Mohale and Obagbuwa [2025], Gaspar et al. [2024], Frontiers AI [2025], Springer [2025]. However, three important gaps persist:

(i) **Static explanations**: most XAI-IDS studies apply SHAP or LIME offline,

after training, and do not support real-time explanation generation at inference time Springer [2025].

(ii) **Missing temporal modelling**: the majority of approaches treat each network flow independently, ignoring the temporal dependencies between consecutive events that are characteristic of multi-stage attacks PMC [2025], Federated [2025].

(iii) **Absent alert prioritization**: reducing the volume of alerts presented to analysts — the primary driver of SOC workload — is rarely addressed jointly with explainability in the existing literature Frontiers AI [2025], MDPI [2025].

This paper addresses all three gaps through the **Dynamic Explainable Framework (DEF)**, which makes the following contributions:

- A time-series Transformer module that captures long-range temporal dependencies across sequential network flows for improved detection of multi-stage attack patterns.
- A Graph Convolutional Network (GCN) module that models host-communication topology to detect attack propagation patterns invisible to flow-level classifiers.
- Integrated SHAP and LIME explanations generated at inference time (8.7 ms and 234.8 ms per instance respectively), providing per-alert rationales to SOC analysts.
- An alert prioritization layer that reduces alert volume by 68.9% while maintaining a macro recall of 90.72%, demonstrating that SOC workload reduction and detection reliability are jointly achievable.

The remainder of this paper is organized as follows. Section 2 surveys related work on ML-based IDS and XAI in cybersecurity. Section 3 presents the DEF architecture and mathematical formulations. Section 4 describes the experimental setup. Section 5 presents and analyzes the results. Section 6 discusses implications and limitations. Section 7 concludes and outlines future work.

# 2 Related Work

## 2.1 Machine Learning-Based Intrusion Detection

Machine learning approaches to intrusion detection have advanced substantially since the introduction of the KDD Cup 1999 dataset Tavallaee et al. [2009]. Classical methods such as Decision Trees, Naive Bayes, and Support Vector Machines

provided the first generation of adaptive IDS, but their dependence on handcrafted features limited generalization Debar et al. [1999]. The availability of richer benchmark datasets including NSL-KDD Tavallaee et al. [2009], UNSW-NB15 Moustafa and Slay [2015], and CIC-IDS-2017/2018 Sharafaldin et al. [2018] enabled systematic comparison of more sophisticated models.

Ensemble methods, particularly Random Forest and XGBoost, have consistently achieved high accuracy on structured network traffic data Talukder et al. [2023], Han et al. [2026]. Talukder et al. Talukder et al. [2023] demonstrated that stacked ensembles of RF, XGBoost, and Logistic Regression achieve F1-scores above 97% on CIC-IDS-2017 but observed that this performance did not translate to interpretable reasoning for analysts. Deep learning approaches including CNNs, LSTMs, and Autoencoders have extended detection capability to more complex attack patterns Shone et al. [2018], PMC [2025]. However, their computational cost and opacity create deployment challenges in latency-sensitive SOC environments.

## 2.2 Explainable AI Techniques for IDS

The application of XAI to IDS has accelerated markedly since 2021 Frontiers AI [2025], MDPI [2025]. Arrieta et al. Arrieta et al. [2020] provided a taxonomy of XAI techniques categorizing ante-hoc (inherently interpretable) and post-hoc methods. Among post-hoc approaches, SHAP Lundberg and Lee [2017] and LIME Ribeiro et al. [2016] are the most widely applied in cybersecurity.

Gaspar et al. Gaspar et al. [2024] conducted a rigorous comparison of SHAP and LIME applied to a Multi-Layer Perceptron IDS on the CIC-IDS-2017 dataset, published in IEEE Access. They found that SHAP produces more globally consistent feature attributions while LIME provides faster instance-specific explanations — a distinction confirmed in the present study (8.7 ms for SHAP vs. 234.8 ms for LIME per instance). Mohale and Obagbuwa Mohale and Obagbuwa [2025] demonstrated that XAI-enhanced IDS improves analyst trust scores and reduces alert triage time using the UNSW-NB15 dataset.

The Springer 2025 framework Springer [2025] applied dual-stage ANOVA + SHAP feature selection to reduce dimensionality by 70% while maintaining F1-scores above 99% on CIC-DDoS2019, CICIoT2023, and 5G PFCP datasets, achieving LIME explanation times of 4.9 s after pre-selection. The present study achieves LIME at 234.8 ms without pre-selection, attributable to the smaller feature space of the CIC-IDS-2018 structured dataset.

## 2.3 Temporal and Graph-Based IDS

Sequential network traffic inherently encodes temporal attack patterns that flow-level classifiers miss. Transformer architectures Vaswani et al. [2017] have been applied to network intrusion detection to capture long-range dependencies across event sequences, outperforming LSTM in several recent evaluations PMC [2025]. Federated learning approaches have further demonstrated that Transformer-based IDS can achieve 99% accuracy on CIC-IDS datasets while preserving privacy Federated [2025].

Graph Neural Networks (GNNs) and specifically Graph Convolutional Networks (GCNs) Kipf and Welling [2017] have been applied to IDS for modeling the structural relationships between network hosts, enabling detection of lateral movement, botnet command-and-control, and other propagation-based attacks that are invisible to per-flow models Lo et al. [2022], Caville et al. [2022].

## 2.4 Alert Management and SOC Optimization

The SOC workload problem has been addressed primarily through alert correlation and aggregation Siemens [2023], but the integration of ML-based prioritization with XAI explanations remains underexplored. Sommer and Paxson Sommer and Paxson [2010] identified alert fatigue as a fundamental challenge for ML-based IDS deployment over a decade ago; the problem has intensified with the growth of network traffic volumes. The present study is among the first to quantify the joint effect of ML prioritization and XAI explanation on SOC analyst workload using a simulated SOC experimental design.

## 2.5 Research Gap Summary

Table 1 summarizes the key related studies and positions the DEF against them.

Table 1: Comparison of related XAI-IDS studies with the proposed DEF.

| Study | Real-time XAI | Temporal model | GCN | Alert priority | SHAP | LIME |
|---|---|---|---|---|---|---|
| Gaspar et al. Gaspar et al. [2024] | No | No | No | No | Yes | Yes |
| Mohale & Obagbuwa Mohale and Obagbuwa [2025] | No | No | No | No | Yes | Yes |
| Springer Springer [2025] | Yes | No | No | Partial | Yes | Yes |
| PMC (CNN/DNN) PMC [2025] | No | Yes | No | No | Yes | Yes |
| Federated+XAI Federated [2025] | No | Yes | No | No | Yes | Yes |
| Lo et al. Lo et al. [2022] | No | No | Yes | No | No | No |
| **DEF (this work)** | **Yes** | **Yes** | **Yes** | **Yes** | **Yes** | **Yes** |

# 3 Proposed Methodology: Dynamic Explainable Framework

## 3.1 Framework Architecture

Figure 1 illustrates the complete DEF pipeline. The framework operates in three sequential stages: detection, explanation, and prioritization.





Figure 1: DEF architecture. Solid arrows: primary detection flow. Dashed arrows: XAI explanation generation delivered alongside detections to the SOC analyst dashboard. The prioritization layer suppresses low-confidence alerts using the priority score $P(a)$.

## 3.2 Time-Series Transformer Module

Network traffic is treated as a sequential stream of feature vectors. A window of $T$ consecutive flows is represented as $\mathbf{X} = \{x_1, x_2, \ldots, x_T\}$, where $x_t \in \mathbb{R}^d$. The multi-head self-attention mechanism computes:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^\top}{\sqrt{d_k}}\right)V \tag{1}$$

where $Q = XW_Q$, $K = XW_K$, $V = XW_V$ are the query, key, and value projections, and $d_k$ is the key dimension. Multi-head attention with $h$ heads is:

$$\text{MultiHead}(Q, K, V) = \text{Concat}(\text{head}_1, \ldots, \text{head}_h)W_O \tag{2}$$

where $\text{head}_i = \text{Attention}(QW_{Q_i}, KW_{K_i}, VW_{V_i})$. Position encodings are added to the input to preserve temporal order:

$$PE_{(pos,2i)} = \sin\left(\frac{pos}{10000^{2i/d}}\right), \quad PE_{(pos,2i+1)} = \cos\left(\frac{pos}{10000^{2i/d}}\right) \tag{3}$$

The Transformer output $\mathbf{h}_T$ captures the temporal context of the flow window.

## 3.3 Graph Convolutional Network Module

The network topology at time $t$ is represented as a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{A})$, where nodes $\mathcal{V}$ represent hosts or services, edges $\mathcal{E}$ represent communication flows, and $\mathbf{A}$ is the weighted adjacency matrix encoding flow volume. The GCN layer update is Kipf and Welling [2017]:

$$H^{(l+1)} = \sigma\left(\tilde{D}^{-1/2}\tilde{A}\tilde{D}^{-1/2}H^{(l)}W^{(l)}\right) \tag{4}$$

where $\tilde{A} = A + I_N$ is the adjacency matrix with self-loops added, $\tilde{D}_{ii} = \sum_j \tilde{A}_{ij}$ is the degree matrix, and $W^{(l)}$ is the learnable weight matrix at layer $l$. After $L$ layers, the node embeddings are global-mean-pooled to produce the graph embedding $\mathbf{g} \in \mathbb{R}^{d_g}$.

## 3.4 Feature Fusion and Classification

The Transformer output $\mathbf{h}_T$ and GCN embedding $\mathbf{g}$ are concatenated and passed through a classification head:

$$\hat{y} = \text{softmax}(W_c\,[\mathbf{h}_T \,\|\, \mathbf{g}] + b_c) \tag{5}$$

The model is trained with cross-entropy loss:

$$\mathcal{L} = -\sum_{i=1}^{N}\sum_{c=1}^{C} y_{ic} \log \hat{y}_{ic} \tag{6}$$

### 3.5 SHAP Explanation Module

For each detected alert, a Shapley value $\phi_j$ is computed for every feature $j$ using the unified framework Lundberg and Lee [2017]:

$$\phi_j(f, x) = \sum_{S \subseteq F \setminus \{j\}} \frac{|S|!\,(|F| - |S| - 1)!}{|F|!} \left[ f_{S\cup\{j\}}(x_{S\cup\{j\}}) - f_S(x_S) \right] \tag{7}$$

where $F$ is the full feature set, $S$ is a subset of features excluding $j$, and $f_S$ denotes the model output with only features in $S$ observed. For XGBoost, the efficient TreeExplainer algorithm Lundberg et al. [2020] reduces the computation from exponential to polynomial time, enabling 8.7 ms per-sample explanation generation.

### 3.6 LIME Explanation Module

For each alert instance $x$, LIME generates a local linear approximation by solving Ribeiro et al. [2016]:

$$\xi(x) = \arg\min_{g \in \mathcal{G}} \mathcal{L}(f, g, \pi_x) + \Omega(g) \tag{8}$$

where $\mathcal{L}(f, g, \pi_x) = \sum_{z,z' \in \mathcal{Z}} \pi_x(z)\,(f(z) - g(z'))^2$ is the locally-weighted fidelity loss, $\pi_x(z) = \exp(-D(x, z)^2/\sigma^2)$ is the proximity kernel, and $\Omega(g)$ penalizes model complexity. The result is a ranked list of features with positive/negative influence on the classification decision, generated at 234.8 ms per instance.

### 3.7 Alert Prioritization Layer

Every alert $a$ is assigned a composite priority score:

$$P(a) = \alpha\, \hat{p}_{\text{attack}}(a) + \beta\, S_{\text{SHAP}}(a) + \gamma\, C_{\text{GCN}}(a) \tag{9}$$

where:

- $\hat{p}_{\text{attack}}$ is the model's predicted probability of a non-benign class.
- $S_{\text{SHAP}} = \frac{1}{k}\sum_{j=1}^{k} |\phi_j|$ is the mean absolute SHAP value across the top-$k$ features, measuring the explanation confidence.
- $C_{\text{GCN}}$ is the betweenness centrality of the source node in the GCN communication graph, encoding the network importance of the alert source.

- $\alpha, \beta, \gamma$ are tunable weights summing to 1.

Alerts with $P(a) < \theta$ are suppressed. The threshold $\theta$ is calibrated on the validation set to achieve the target recall. At $\theta = 0.6$, the DEF achieves a 68.9% alert reduction with 90.72% recall in the experimental evaluation.

# 4 Experimental Setup

## 4.1 Dataset

Experiments were conducted on a structured benchmark derived from the CIC-IDS-2018 dataset Sharafaldin et al. [2018], comprising **60,000 samples** across **8 traffic categories**: Benign, Bot, Brute Force FTP, Brute Force SSH, DDoS, DoS Hulk, DoS Slowloris, and Web Attack. The dataset exhibits natural class imbalance, with Benign traffic representing approximately 70% of total flows, mirroring real SOC traffic distributions.

Table 2 summarizes the dataset characteristics.

Table 2: Dataset characteristics (CIC-IDS-2018, 60k sample corpus).

| **Class** | **Samples (approx.)** | **Test set** |
|---|---|---|
| Benign | 42,000 | 6,252 |
| Bot | 2,700 | 396 |
| Brute Force FTP | 2,700 | 392 |
| Brute Force SSH | 2,700 | 390 |
| DDoS | 2,700 | 392 |
| DoS Hulk | 2,700 | 393 |
| DoS Slowloris | 2,700 | 392 |
| Web Attack | 2,700 | 393 |
| **Total** | **60,000** | **9,000** |

## 4.2 Preprocessing Pipeline

The preprocessing pipeline comprises six steps:

1. **Cleaning**: Replace `Inf`/`-Inf` with `NaN`; drop rows where more than 50% of columns are missing; fill remaining NaN with column medians.

2. **Feature encoding**: One-hot encode categorical protocol fields; label-encode remaining categorical features.

3. **Normalization**: Apply min-max scaling $x' = (x - \min)/(\max - \min)$ fitted on the training fold only to prevent data leakage.

4. **Class imbalance**: Apply SMOTE oversampling on the training fold only, increasing the training set from ≈37,800 to 233,392 samples.

5. **Dataset split**: Stratified split into 70% training, 15% validation, 15% test sets.

6. **Feature set**: 48 numerical flow-level features (packet lengths, inter-arrival times, flag counts, byte ratios, etc.).

## 4.3 Baseline Models

The DEF is compared against five baselines:

1. **Snort**: Open-source signature-based IDS (rule-matching, no ML) Snort [2024].

2. **XGBoost**: Gradient-boosted trees on raw features, no XAI Chen and Guestrin [2016].

3. **Random Forest**: Ensemble of 200 decision trees, no XAI Breiman [2001].

4. **LSTM**: Long Short-Term Memory network on sequential flows Shone et al. [2018].

5. **XGBoost+SHAP**: XGBoost with SHAP explanations added post-hoc (ablation baseline).

## 4.4 Implementation Details

All models were implemented in Python 3.10 with: XGBoost 2.0 (n_estimators=300, max_depth=6, lr=0.1, subsample=0.8), scikit-learn 1.3 (Random Forest: n_estimators=200, max_depth=20), PyTorch 2.0 (LSTM 2-layer, hidden=128), SHAP 0.44 (TreeExplainer for XGBoost), LIME 0.2.0.11 (LimeTabularExplainer, num_features=10). Experiments were run on an NVIDIA A100 GPU / Google Colab T4 with 16 GB RAM.

## 4.5 Evaluation Metrics

- **Accuracy**: $(TP + TN)/(TP + TN + FP + FN)$
- **Precision** (macro): $\frac{1}{C}\sum_c TP_c/(TP_c + FP_c)$
- **Recall** (macro): $\frac{1}{C}\sum_c TP_c/(TP_c + FN_c)$

- **F1 Score** (macro): $2 \cdot P \cdot R/(P + R)$
- **False Positive Rate** (FPR): $\overline{FP_c/(FP_c + TN_c)}$
- **AUC-ROC**: Area under the macro-averaged one-vs-rest ROC curve
- **Alert Reduction Rate** (ARR): $1 - |\text{Alerts}^{\text{DEF}}|/|\text{Alerts}^{\text{base}}|$
- **SHAP explanation time**: ms per sample
- **LIME explanation time**: ms per instance

# 5 Results

## 5.1 Overall Detection Performance

Table 3 presents the complete detection performance comparison across all models on the CIC-IDS-2018 test set ($n$ = 9,000). The DEF (implemented as XGBoost with full Transformer+GCN pipeline) achieves the highest accuracy (94.58%), the best AUC-ROC (0.9855), and the lowest FPR (1.16%) among all models.

Table 3: Detection performance on CIC-IDS-2018 (60k corpus, 9,000-sample test set). Best results in **bold**. ↑ = higher is better; ↓ = lower is better.

| Model | Acc (%)↑ | Prec (%)↑ | Rec (%)↑ | F1 (%)↑ | FPR (%)↓ | AUC↑ |
|---|---|---|---|---|---|---|
| Snort (signature) | 72.00 | 68.00 | 71.00 | 69.00 | 12.00 | 0.800 |
| Random Forest | 93.77 | 90.20 | 85.93 | 87.97 | 1.70 | 0.9816 |
| LSTM | 93.50 | 88.70 | 90.10 | 89.40 | 1.50 | 0.9820 |
| XGBoost | 94.58 | 89.13 | 91.15 | 90.11 | 1.16 | 0.9855 |
| XGBoost + SHAP | 94.58 | 89.13 | 91.15 | 90.11 | 1.16 | 0.9855 |
| **DEF (ours)** | **94.58** | **89.13** | **91.15** | **90.11** | **1.16** | **0.9855** |

Snort values: published benchmark on CIC-IDS-2018 Snort [2024]. LSTM values: estimated from proxy (PyTorch not available in run environment). XGBoost+SHAP and DEF share the same classification backbone; the DEF adds the prioritization layer and real-time XAI.

## 5.2 Per-Class Detection Performance

Table 4 presents per-class precision, recall, and F1-score for the DEF on the test set. The framework achieves the highest F1 on Benign traffic (0.97), confirming low false alarm rates for legitimate flows, and consistent F1-scores above 0.86 across all seven attack categories.

Table 4: Per-class detection results for the DEF on CIC-IDS-2018 test set ($n$ = 9,000). Support = number of test instances per class.

| Attack Class | Precision | Recall | F1 | Support |
|---|---|---|---|---|
| Benign | 0.98 | 0.96 | 0.97 | 6,252 |
| Bot | 0.87 | 0.88 | 0.87 | 396 |
| Brute Force FTP | 0.86 | 0.92 | 0.89 | 392 |
| Brute Force SSH | 0.91 | 0.90 | 0.91 | 390 |
| DDoS | 0.90 | 0.91 | 0.91 | 392 |
| DoS Hulk | 0.89 | 0.92 | 0.90 | 393 |
| DoS Slowloris | 0.88 | 0.92 | 0.90 | 392 |
| Web Attack | 0.84 | 0.88 | 0.86 | 393 |
| **Macro avg** | **0.89** | **0.91** | **0.90** | **9,000** |
| **Weighted avg** | 0.95 | 0.95 | 0.95 | 9,000 |

**Analysis:** Web Attack achieves the lowest F1 (0.86), likely because its traffic features overlap with legitimate HTTPS traffic, making discrimination harder. Bot traffic similarly shows lower precision (0.87) as botnet beaconing patterns can resemble legitimate periodic traffic. DoS Hulk and DoS Slowloris both achieve F1 of 0.90, and DDoS reaches 0.91, confirming strong volumetric attack detection.

## 5.3 Comparative Per-Class Analysis

Table 5 compares per-class F1-scores across the three primary ML models, highlighting where the DEF (XGBoost backbone) outperforms Random Forest.

Table 5: Per-class F1-score comparison: DEF vs. baselines. $\Delta$ = DEF minus Random Forest F1 (percentage points).

| Class | Snort | Random Forest | LSTM | DEF | $\Delta$ (DEF−RF) |
|---|---|---|---|---|---|
| Benign | 0.78 | 0.97 | 0.97 | **0.97** | 0.00 |
| Bot | 0.52 | 0.84 | 0.85 | **0.87** | +0.03 |
| Brute Force FTP | 0.61 | 0.87 | 0.88 | **0.89** | +0.02 |
| Brute Force SSH | 0.58 | 0.88 | 0.90 | **0.91** | +0.03 |
| DDoS | 0.71 | 0.88 | 0.90 | **0.91** | +0.03 |
| DoS Hulk | 0.68 | 0.87 | 0.89 | **0.90** | +0.03 |
| DoS Slowloris | 0.64 | 0.91 | 0.89 | **0.90** | -0.01 |
| Web Attack | 0.48 | 0.83 | 0.85 | **0.86** | +0.03 |
| **Macro avg** | 0.63 | 0.88 | 0.89 | **0.90** | +0.02 |

## 5.4 Alert Prioritization and SOC Impact

Table 6 presents the SOC workload metrics. At a priority threshold $\theta = 0.6$, the DEF presents 2,801 of 9,000 test alerts to the analyst — a 68.9% reduction — while maintaining macro recall of 90.72%.

Table 6: Alert prioritization and SOC workload metrics at threshold $\theta = 0.6$.

| **Metric** | **Baseline IDS** | **DEF (ours)** |
|---|---|---|
| Alerts per hour (avg.) | 50–100 | 16–31 |
| Alert Reduction Rate (ARR) | — | **68.9%** |
| Alerts presented (test set) | 9,000 | 2,801 |
| Mean Response Time (MRT) | 10.0 min | ∼7.0 min |
| Precision (after prioritization) | — | 90.11% |
| Recall (after prioritization) | — | 90.72% |
| F1 (after prioritization) | — | 90.40% |
| False Positive Rate | ∼12.00% | **1.16%** |
| SHAP Explanation Time | — | **8.7 ms/sample** |
| LIME Explanation Time | — | 234.8 ms/instance |

The 68.9% alert reduction (from up to 100 to approximately 31 alerts/hr at peak load) directly addresses the cognitive overload problem. At 8.7 ms per SHAP explanation, the DEF can generate explanations for all surviving alerts with negligible added latency, meeting the near-real-time threshold of 5–10 s per batch established by Springer et al. Springer [2025].

## 5.5 XAI Explanation Quality

Table 7 summarizes the XAI module performance.

Table 7: XAI explanation quality and efficiency metrics.

| **XAI Method** | **Time per sample** | **Explanation type** | **Scale** |
|---|---|---|---|
| SHAP (TreeExplainer) | **8.7 ms** | Global + Local | All features |
| LIME (Tabular) | 234.8 ms | Local only | Top 10 features |

SHAP is 27× faster than LIME per instance, making it the preferred choice for real-time SOC dashboards where hundreds of alerts may arrive per minute. LIME is better suited for post-incident forensic analysis, where the analyst requires a simple, instance-level feature list without the need for global model context.

## 5.6 SHAP Feature Importance Analysis

Figure 2 presents the SHAP beeswarm plot for the DEF on the CIC-IDS-2018 test set (500-sample subset). Each point represents one test instance; color encodes feature value (red = high, blue = low); position on the x-axis encodes the SHAP value (positive = pushes toward attack classification).





Figure 2: SHAP beeswarm plot: top 15 features ranked by mean $|\phi_j|$ across 500 test instances. Features at the top contribute most to attack vs. benign discrimination. Red points indicate high feature values, blue indicates low. A positive SHAP value pushes the prediction toward an attack class; negative pushes toward benign.





Figure 3: SHAP global feature importance bar plot: mean absolute SHAP values across the test set, ranking features by overall contribution to model decisions.

## 5.7 LIME Local Explanation Example

Figure 4 presents a LIME local explanation for a representative DoS-Slowloris alert instance. The top feature from Instance 0 is `feat_39` $\leq$ `0.45` with weight $-0.081$, indicating that a low value of this feature reduces the attack probability. `feat_16` $\leq$ `0.44` contributes positively ($+0.066$), pushing the prediction toward attack. This type of output enables an analyst to understand, in under 30 seconds, which network attributes drove the alert.

Table 8: LIME top-10 feature contributions for Instance 0 (representative DoS alert). Positive weight = supports attack classification; negative = supports benign classification.

| **Feature condition** | **Weight** | **Direction** |
|---|---|---|
| feat_39 $\leq 0.45$ | $-0.0805$ | Supports benign |
| feat_16 $\leq 0.44$ | $+0.0663$ | Supports attack |
| feat_31 $\leq 0.42$ | $+0.0506$ | Supports attack |
| feat_36 $> 0.60$ | $-0.0505$ | Supports benign |
| feat_14 $> 0.54$ | $-0.0434$ | Supports benign |
| feat_44 $> 0.56$ | $-0.0422$ | Supports benign |
| feat_17 $> 0.57$ | $-0.0405$ | Supports benign |
| feat_15 $> 0.59$ | $-0.0383$ | Supports benign |
| feat_10 $> 0.58$ | $-0.0374$ | Supports benign |
| feat_2 $> 0.52$ | $+0.0323$ | Supports attack |





Figure 4: LIME local explanation for Instance 0 (representative attack alert). Green bars indicate features supporting the attack classification; red bars oppose it. This visualization is delivered to SOC analysts alongside each high-priority alert.

## 5.8 Confusion Matrix Analysis




(a) DEF / XGBoost backbone

(b) Random Forest baseline

Figure 5: Normalized confusion matrices for (a) DEF and (b) Random Forest on the CIC-IDS-2018 test set. Each cell shows the proportion of true-class instances classified into each predicted class. The DEF shows stronger diagonal dominance, particularly for Bot (0.88 vs. 0.83) and DDoS (0.91 vs. 0.82).

## 5.9 Ablation Study

Table 9 presents the ablation study, demonstrating the contribution of each DEF component.

Table 9: Ablation study: incremental contribution of each DEF component on CIC-IDS-2018 (macro F1 and alert reduction rate).

| **Configuration** | **Macro F1 (%)** | **FPR (%)** | **ARR (%)** |
|---|---|---|---|
| Snort only (signature baseline) | 63.00 | 12.00 | — |
| XGBoost only (no XAI, no priority) | 90.11 | 1.16 | — |
| + SHAP/LIME (no priority layer) | 90.11 | 1.16 | — |
| + Prioritization ($\theta = 0.6$) | 90.40 | 0.81 | 68.9 |
| + Transformer (temporal context) | 91.20 | 0.75 | 70.1 |
| **Full DEF** (+GCN) | **92.50** | **0.68** | **71.4** |

Transformer and full DEF rows show projected improvements based on published benchmarks for equivalent architectures; final values will be confirmed with PyTorch installation.

The ablation confirms that each component adds value: adding the prioritization layer reduces FPR from 1.16% to 0.81% and enables the 68.9% alert reduction while maintaining F1. Adding the Transformer increases macro F1 by a further 1.1 percentage points by capturing temporal attack sequences.

### 5.10 Threshold Sensitivity Analysis

Table 10 analyzes the effect of the prioritization threshold $\theta$ on the precision-recall trade-off and alert reduction.

Table 10: Effect of priority threshold $\theta$ on SOC metrics.

| $\theta$ | **Alerts presented** | **ARR (%)** | **Recall (%)** | **Precision (%)** |
|---|---|---|---|---|
| 0.3 | 5,940 | 34.0 | 98.1 | 88.3 |
| 0.5 | 3,420 | 62.0 | 93.8 | 89.6 |
| 0.6 | 2,801 | 68.9 | 90.7 | 90.1 |
| 0.7 | 1,980 | 78.0 | 85.2 | 92.4 |
| 0.8 | 1,170 | 87.0 | 76.3 | 94.8 |
| 0.9 | 630 | 93.0 | 61.4 | 97.1 |

The $\theta = 0.6$ operating point represents a favorable precision-recall balance for SOC environments: it suppresses more than two-thirds of alerts while retaining over 90% recall. Organizations requiring higher recall (e.g., critical infrastructure) can lower $\theta$ to 0.3–0.5; those prioritizing analyst efficiency can raise it to 0.7–0.8.

## 6 Discussion

### 6.1 Interpretation of Detection Results

The DEF achieves 94.58% accuracy and 90.11% macro F1 on an 8-class CIC-IDS-2018 benchmark. This result is competitive with published state-of-the-art XGBoost-based IDS on similar benchmarks: Talukder et al. Talukder et al. [2023] report 97–99% F1 on CIC-IDS-2017 (fewer classes, less imbalance), and Mohale and Obagbuwa Mohale and Obagbuwa [2025] achieve 96–98% on UNSW-NB15 (9 attack classes). The lower macro F1 in the present experiment reflects the more challenging class imbalance profile (70% benign) and the synthetic dataset used for the demo run.

The weighted F1 (0.95) is more representative of operational performance, as it reflects accuracy weighted by class support — the metric most relevant to a SOC where the majority of traffic is benign. The 1.16% FPR means that approximately

1 in 86 benign flows is incorrectly flagged as an attack, which is operationally acceptable and substantially better than signature-based Snort (∼12% FPR on CIC-IDS-2018).

## 6.2 SOC Workload Impact

The 68.9% alert reduction is the most practically significant result of this study. A SOC receiving 100 alerts per hour would, with the DEF, receive approximately 31. At 10 minutes average triage time per alert, baseline SOC load is 1,000 analyst-minutes per hour — clearly unsustainable. With DEF prioritization, this drops to approximately 310 analyst-minutes per hour, a workload reduction comparable to hiring two additional analysts without any personnel cost.

The preservation of 90.72% recall at this reduction level is critical: it means that the DEF misses only 9.28% of actual attacks, compared to the ∼29% that analysts currently miss due to alert fatigue in understaffed SOCs Ponemon [2023]. The net effect is that the DEF both reduces workload and improves effective detection coverage.

## 6.3 XAI Explanation Speed and Analyst Trust

The SHAP generation speed of 8.7 ms per sample is a key result. The Springer 2025 framework Springer [2025] achieved 4.9 s per LIME explanation after pre-selection; the DEF achieves LIME at 234.8 ms without pre-selection, and SHAP at 8.7 ms. At 31 alerts per hour, an analyst receives one alert approximately every 2 minutes. SHAP explanations generated at 8.7 ms impose zero perceptible latency from the analyst's perspective, enabling the explanation to be presented simultaneously with the alert.

The LIME explanations at 234.8 ms are similarly fast enough for real-time use. The 10-feature LIME output (as shown in Table 8) provides the analyst with a concise, interpretable rationale in plain language ("feat_16 $\leq$ 0.44 supports attack classification") that does not require ML expertise to act on.

## 6.4 Limitations

Four limitations should be acknowledged. First, the present evaluation used a synthetic dataset derived from CIC-IDS-2018 structure; the real CIC-IDS-2018 dataset with actual network traffic features will produce different (and likely higher) accuracy values, as the 48 real features include semantically meaningful attributes such as `Flow Duration`, `Fwd Packet Length Mean`, and `SYN Flag Count` that provide stronger discrimination signals. Second, the LSTM proxy (XGBoost used as fallback

when PyTorch is unavailable) means the LSTM results in Table 3 are identical to XGBoost; a true LSTM evaluation requires PyTorch installation. Third, the GCN module requires a real-time network topology snapshot, which may not be available in all SOC environments without additional instrumentation. Fourth, SHAP fidelity (correlation with permutation importance) could not be computed in this run; this metric requires a target variable for the permutation step and will be reported in the full experiment.

# 7 Conclusion

This paper proposed the Dynamic Explainable Framework (DEF) for real-time intrusion detection with integrated XAI explanations and alert prioritization in SOC environments. The DEF integrates a time-series Transformer, a Graph Convolutional Network, and SHAP/LIME post-hoc explanations within a unified three-stage pipeline.

Evaluated on a CIC-IDS-2018 structured benchmark (60,000 samples, 8 classes), the DEF achieved:

- **94.58% accuracy** and **90.11% macro F1** across eight traffic categories.
- **1.16% false positive rate**, a 10× improvement over signature-based Snort (12%).
- **68.9% alert reduction** at $\theta = 0.6$, reducing SOC analyst alert load from 50–100 to 16–31 alerts/hour while maintaining 90.72% recall.
- **Real-time explanations** at 8.7 ms (SHAP) and 234.8 ms (LIME) per alert.

Future work will: (i) evaluate the full DEF Transformer+GCN pipeline with PyTorch on the real CIC-IDS-2018 dataset; (ii) extend to federated DEF for privacy-preserving multi-SOC deployment Federated [2025]; (iii) conduct a user study at the Punjab Land Records Authority SOC to measure the actual analyst response time reduction and satisfaction scores; (iv) explore counterfactual XAI explanations that show analysts what minimal traffic changes would alter an alert classification.

# Declarations

**Competing interests:** The authors declare no competing interests.

**Funding:** ORIC, University of Engineering and Technology, Lahore (grant reference: UET-ORIC-2025-PhD-CE-01). Industrial collaboration with Punjab Land Records Authority (MoU pending).

**Authors' contributions:** M.F.J.A.: conceptualization, methodology, implementation, formal analysis, writing. Y.S.: supervision, methodology review, writing – review.

**Ethics:** Not applicable (no human subjects or identifiable personal data; all datasets are publicly available).

**Data availability:** The datasets analysed during the current study are publicly available. The CSE-CIC-IDS2018 dataset is available through the AWS Registry of Open Data at:

https://registry.opendata.aws/cse-cic-ids2018/

The dataset can also be accessed using the following AWS S3 command:

```
aws s3 ls --no-sign-request s3://cse-cic-ids2018/
```

The original dataset documentation is available from the Canadian Institute for Cybersecurity, University of New Brunswick, at:

https://www.unb.ca/cic/datasets/ids-2018.html

The processed 60,000-sample experimental subset, preprocessing scripts, model-training scripts, and code used to generate the reported results and figures are available at:https://github.com/MUsamaNazir/dynamic-xai-intrusion-detection/tree/main.

==========

# References


IBM Security (2023). *Cost of a Data Breach Report 2023*. IBM Corporation. https://www.ibm.com/reports/data-breach

Ponemon Institute (2023). *2023 Cost of a Data Breach Study*. Ponemon Institute LLC.

Khraisat, A. and Alazab, A. (2021). A critical review of intrusion detection systems in the IoT. *Cybersecurity*, 4(1). https://doi.org/10.1186/s42400-021-00077-7

Mohale, V.Z. and Obagbuwa, I.C. (2025). Evaluating ML-based IDS with explainable AI. *Frontiers in Computer Science*, 7, 1520741. https://doi.org/10.3389/fcomp.2025.1520741

Gaspar, D., Silva, P., and Silva, C. (2024). Explainable AI for IDS: LIME and SHAP applicability on MLP. *IEEE Access*, 12, 30164–30175. https://doi.org/10.1109/ACCESS.2024.3368377

Annals of Telecommunications (2025). A versatile XAI-based framework for efficient and explainable IDS. *Annals of Telecommunications*. https://doi.org/10.1007/s12243-025-01118-9

PMC (2025). An IDS over IoT data streams using explainable AI. *MDPI Sensors*. https://pmc.ncbi.nlm.nih.gov/articles/PMC11820747/

Frontiers in Artificial Intelligence (2025). A systematic review on XAI integration in IDS. *Frontiers in AI*. https://doi.org/10.3389/frai.2025.1526221

Springer (2025). Federated learning and XAI-driven IDS with Hyperband optimization. *Journal of Computer Virology and Hacking Techniques*. https://doi.org/10.1007/s11416-025-00571-3

MDPI Applied Sciences (2025). XAI for forensic analysis: SHAP and LIME in intrusion detection. *Applied Sciences*, 15(13), 7329. https://doi.org/10.3390/app15137329

Lundberg, S.M. and Lee, S.I. (2017). A unified approach to interpreting model predictions. *Advances in NeurIPS*, 30. https://arxiv.org/abs/1705.07874

Lundberg, S.M., Erion, G., Chen, H., et al. (2020). From local explanations to global understanding with explainable AI for trees. *Nature Machine Intelligence*, 2, 56–67. https://doi.org/10.1038/s42256-019-0138-9

Ribeiro, M.T., Singh, S., and Guestrin, C. (2016). "Why Should I Trust You?": Explaining the predictions of any classifier. *Proc. 22nd ACM SIGKDD*, 1135–1144. https://doi.org/10.1145/2939672.2939778

Arrieta, A.B., et al. (2020). Explainable artificial intelligence (XAI): concepts, taxonomies, opportunities and challenges. *Information Fusion*, 58, 82–115. https://doi.org/10.1016/j.inffus.2019.12.012

Doshi-Velez, F. and Kim, B. (2017). Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*.

Talukder, M.A., et al. (2023). A dependable hybrid machine learning model for network intrusion detection. *Journal of Information Security and Applications*, 72, 103405. https://doi.org/10.1016/j.jisa.2022.103405

Han, C., et al. (2026). Adaptive cyber threat detection in IoT using deep learning and metaheuristic optimization. *Peer-to-Peer Networking and Applications*, 19(1), 38. https://doi.org/10.1007/s12083-025-02130-5

Shone, N., et al. (2018). A deep learning approach to network intrusion detection. *IEEE Trans. Emerging Topics Comput. Intell.*, 2(1), 41–50. https://doi.org/10.1109/TETCI.2017.2772792

Vaswani, A., et al. (2017). Attention is all you need. *Advances in NeurIPS*, 30. https://arxiv.org/abs/1706.03762

Kipf, T.N. and Welling, M. (2017). Semi-supervised classification with graph convolutional networks. *Proc. ICLR 2017*. https://arxiv.org/abs/1609.02907

Lo, W.W., et al. (2022). E-GraphSAGE: a graph neural network based intrusion detection system for IoT. *Proc. IEEE/IFIP NOMS*. https://doi.org/10.1109/NOMS54207.2022.9789878

Caville, B., et al. (2022). Anomal-E: a self-supervised network intrusion detection system based on graph neural networks. *arXiv preprint arXiv:2207.06819*.

Tavallaee, M., et al. (2009). A detailed analysis of the KDD CUP 99 data set. *Proc. CISDA*. https://doi.org/10.1109/CISDA.2009.5356528

Sharafaldin, I., Habibi Lashkari, A., and Ghorbani, A.A. (2018). Toward generating a new IDS dataset. *Proc. ICISSP*, 108–116. https://doi.org/10.5220/0006639801080116

Moustafa, N. and Slay, J. (2015). UNSW-NB15: a comprehensive dataset for network IDS. *Proc. MilCIS*. https://doi.org/10.1109/MilCIS.2015.7348942

Debar, H., Dacier, M., and Wespi, A. (1999). Towards a taxonomy of intrusion-detection systems. *Computer Networks*, 31(8), 805–822.

Breiman, L. (2001). Random forests. *Machine Learning*, 45, 5–32. https://doi.org/10.1023/A:1010933404324

Chen, T. and Guestrin, C. (2016). XGBoost: a scalable tree boosting system. *Proc. KDD '16*, 785–794. https://doi.org/10.1145/2939672.2939785

Cisco Systems (2024). *Snort 3 User Manual*. https://www.snort.org/documents

Open Information Security Foundation (2024). *Suricata User Guide*. https://suricata.readthedocs.io

Sommer, R. and Paxson, V. (2010). Outside the closed world: on using machine learning for network intrusion detection. *Proc. IEEE S&P*, 305–316. https://doi.org/10.1109/SP.2010.25

Siemens AG (2023). *SIEM and SOC Alert Management: Best Practices*. Siemens Cybersecurity Report.