

A cortical gradient in area 55b links language and somato-cognitive action networks

Guowei Wu

1. State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China. 2. Department of Psychology, University of Chinese Academy of Sciences, Beijing, China.

Xiuyi Wang

1. State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China. 2. Department of Psychology, University of Chinese Academy of Sciences, Beijing, China.

Baihan Lv

1. State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China. 2. Department of Psychology, University of Chinese Academy of Sciences, Beijing, China.

Yi Du

`duyi@psych.ac.cn`

1. State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China. 2. Department of Psychology, University of Chinese Academy of Sciences, Beijing, China.

Research Article

Keywords: area 55b, language, sensorimotor–semantic interface

Posted Date: August 17th, 2026

DOI: <https://doi.org/10.21203/rs.3.rs-9934100/v2>

License: © ⓘ This work is licensed under a Creative Commons Attribution 4.0 International License.
[Read Full License](#)

Additional Declarations: The authors declare no competing interests.

A cortical gradient in area 55b links language and somato-cognitive action networks

Guowei Wu^{†1,2}, Xiuyi Wang^{†1,2}, Baihan Lv^{1,2}, Yi Du^{1,2*}

1. State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China.

2. Department of Psychology, University of Chinese Academy of Sciences, Beijing, China.

[†] These authors contributed equally

* Correspondence:

Yi Du, State Key Laboratory of Cognitive Science and Mental Health, Institute of Psychology, Chinese Academy of Sciences, Beijing, China, 16 Lincui Road, Chaoyang, Beijing 100101, China (e-mail: duyid@psych.ac.cn)

15 **Abstract**

16 How the cortex converts high-level cognition into action remains unresolved. We identify left
17 frontal area 55b as a graded transition between the canonical language network and the somato-
18 cognitive action network (SCAN). Across individualized fMRI mapping of word listening, reading,
19 speaking and writing, resting-state connectivity, diffusion tractography and independent datasets, 55b
20 contained a reproducible anterior–posterior gradient. Its anterior end aligned and structurally
21 connected with the language network and carried stronger semantic-category information, whereas its
22 posterior end aligned and connected with SCAN and preferentially encoded production and
23 articulatory features. Production further reweighted model-estimated 55b coupling toward frontal
24 language and speech- and hand-motor regions. Area 55b also occupied convergent transitions across
25 multiple cortical hierarchies. These findings show how a macroscale relationship between cognitive
26 and action networks can be implemented within a small cortical territory, providing a general
27 mechanism for flexible cognition-to-action transformation.

28 **Introduction**

29 The cerebral cortex must solve a general integration problem: representations distributed across
30 association cortex have to guide actions implemented by modality- and effector-specific systems.
31 Network neuroscience has mapped many of these operations onto large-scale systems, but maps alone
32 do not explain how information crosses network boundaries. Cortex is not organized solely as a mosaic
33 of discrete modules. Its microstructure, connectivity, metabolism, and function vary along graded axes
34 extending from primary sensorimotor to transmodal association cortex¹⁻⁴. A key unresolved question
35 is therefore how macroscale gradients are translated into local organization where cognitive and action
36 systems meet. One possibility is that network interfaces are themselves graded: neighboring parts of a
37 small cortical territory may differ systematically in network alignment and representational content,
38 allowing integration without erasing functional specialization.

39 Language provides a demanding model in which to test this possibility. A single concept can be
40 reached from auditory speech or visual text and can guide spoken or written action. These operations
41 require coordination between systems that represent linguistic and conceptual content⁵⁻¹² and systems
42 that encode perceptual forms, action plans, and effector-specific motor commands¹³⁻¹⁸. The recently
43 described somato-cognitive action network (SCAN) adds an important dimension to this architecture.
44 SCAN regions interleave with classical effector representations in motor cortex and have been
45 proposed to integrate goals, bodily state, and coordinated actions rather than control a single effector¹⁹⁻
46 ²¹. The canonical language network and SCAN approach one another in lateral frontal cortex, creating
47 a candidate junction at which linguistic representations could be reformatted for action. Whether this
48 junction is a hard network boundary, a nonspecific overlap, or an organized cortical gradient is
49 unknown.

50 Area 55b is anatomically and functionally well positioned to address this question. Defined in a
51 multimodal cortical atlas as a small region of dorsal lateral frontal cortex²², 55b varies substantially
52 across individuals and is easily blurred by group averaging²³⁻²⁷. Its functional identity has also
53 remained unsettled. Studies of speech production, lesions, and neurosurgical mapping implicate this
54 territory in articulatory planning and motor sequencing^{17,28-31}, whereas connectivity and task studies

55 also associate it with the language network and semantic processing^{32–36}. These accounts are often
56 treated as competing assignments of an indivisible region to either language or motor function. An
57 alternative is that the apparent inconsistency reflects genuine internal organization: one end of 55b
58 may be more strongly embedded in the language network, whereas the other is more strongly
59 embedded in SCAN. Testing this account requires subject-sensitive mapping and convergent
60 measurements of network alignment, representational content, anatomical connectivity, and task-
61 dependent communication.

62 We therefore asked whether left area 55b contains a reproducible internal gradient that links the
63 language network with SCAN, and whether this gradient has consequences for the transformation
64 between linguistic content and action. Participants performed four word-level tasks spanning two input
65 modalities (listening and reading) and two output effectors (speaking and writing). We combined
66 individualized functional parcellation with multivariate decoding and encoding, resting-state
67 connectivity gradients, diffusion tractography, and dynamic causal modelling. Independent Peking
68 University³⁷ and Human Connectome Project datasets^{38,39} were used to test the reproducibility of
69 lexical recruitment and local gradient organization. We predicted that anterior 55b would show
70 stronger language-network alignment, semantic-category information, and structural connectivity with
71 the language network, whereas posterior 55b would show stronger SCAN alignment, production bias,
72 articulatory-feature encoding, and structural connectivity with SCAN. We further asked whether
73 production reweights model-estimated 55b coupling toward frontal and effector-specific motor
74 systems and whether 55b occupies a transition across established cortical hierarchies.

75 The results reveal a coherent anterior–posterior organization. Anterior 55b preferentially aligned
76 with the language network and carried stronger semantic-category information, whereas posterior 55b
77 preferentially aligned with SCAN and carried stronger production-related and articulatory information.
78 A crossed pattern of white-matter connectivity mirrored this functional differentiation, and production
79 shifted model-estimated directed coupling toward speech and hand motor cortices. At the macroscale,
80 55b lay within a convergent transition from sensorimotor-adjacent to association-adjacent cortex. Thus,
81 rather than assigning 55b exclusively to either language or action, our findings identify it as a graded
82 cross-network transition. More broadly, they show how a macroscale relationship between cognitive

83 and action networks can be implemented within a small cortical territory.


84 **Results**

85 **A multimodal lexical network identifies area 55b at the junction of language and action systems**


86 A conjunction analysis across word listening, reading, naming, and writing—each contrasted with
87 a modality-matched control—identified four regions with significantly greater lexical responses: area
88 55b, the superior frontal language area (SFL), the inferior frontal junction (IFJ), and the anterior
89 fusiform gyrus ($\text{FDR-}q < 0.05$; **Fig. 1a** and **Table 1**). The four task–control contrasts, individualized
90 parcel-wise models, and minimum-T conjunction are summarized in **Fig. 1a**. Recruitment across two
91 sensory inputs and two motor outputs established a modality-invariant candidate network without
92 presupposing a unique interface region.

93 The same network was recovered in a vertex-wise conjunction analysis (**Supplementary Fig. 3**).
94 In the independent Peking University dataset, area 55b, IFJ, and anterior fusiform gyrus were recruited
95 during both comprehension and production, whereas SFL showed significant comprehension
96 activation but weaker production activation (**Supplementary Results** and **Supplementary Fig. 4**).
97 Among these regions, area 55b occupied the anatomical junction between the language network and
98 SCAN (**Fig. 1b**). We therefore tested whether this apparent overlap concealed an organized internal
99 gradient rather than a functionally uniform zone. **Figure 1b** and **1c** summarize the connectivity-
100 gradient construction and the convergent functional, representational, structural, effective-
101 connectivity⁴⁰, and cortical-hierarchy analyses⁴¹ used to characterize that gradient.

a. Multimodal lexical localizer and conjunction-defined candidate network



b. From a language-action network junction to an internal connectivity gradient



c. Convergent analyses characterize the graded language-to-action transition




Fig. 1 | Multimodal localization and analysis framework identify area 55b as a candidate language-action transition. **a**, Multimodal lexical localizer and conjunction-defined candidate network. Thirty participants completed word listening, reading, picture naming and picture writing in three sessions, each with a modality-matched control. Linear mixed-effects models were fitted in individualized 900-parcel maps and corrected across parcels using FDR at $q < 0.05$. A minimum-T conjunction across the four word > control maps identified area 55b, IFJ, SFL and anterior fusiform gyrus. **b**, Area 55b lies where the canonical language network approaches the Somato-cognitive action network (SCAN). Whole-cortex connectivity profiles of 55b vertices were converted to a cosine-similarity affinity matrix; diffusion embedding yielded the dominant gradient, and subject-level gradients were aligned to the group solution. The median split was used only for operational comparison of the gradient ends. **c**, Gradient-defined sectors were characterized using task responses and cross-modal classification, semantic-category decoding and articulatory-feature encoding, tractography, 55b-centred DCM with parametric empirical Bayes (PEB), and six macroscale cortical hierarchy maps. The bottom band summarizes the hypothesized continuous transition; empirical tests are presented in Figs. 2–5. Panels b and c are workflow schematics.

A reproducible internal gradient differentiates language-aligned and SCAN-aligned sectors of 55b

We derived the dominant local connectivity gradient within the Glasser-defined 55b territory and used a median split to compare its ends. The split provided an operational anterior–posterior comparison; the underlying organization was interpreted as continuous rather than as two new cortical modules.

The dominant gradient followed an anterior–posterior axis (**Fig. 2a**). Among the tested network templates, anterior high-gradient 55b aligned most strongly with the canonical language network (Dice = 0.42), whereas posterior low-gradient 55b aligned most strongly with the somato-cognitive action network (SCAN; Dice = 0.74). The same gradient orientation and preferential network alignment were reproduced in the Human Connectome Project and Peking University datasets (**Supplementary Fig.**

5), establishing a stable local transition from language-aligned to action-aligned connectivity.


Functional specialization along the 55b gradient is mirrored by crossed white-matter connectivity

The connectivity gradient was accompanied by systematic functional differentiation. As shown in **Fig. 2b** (left two panels), posterior 55b showed a larger production–comprehension response difference than anterior 55b ($t(29) = 10.01$, $FDR-q < 0.001$, Cohen's $d = 1.83$) and stronger multivariate discrimination of the two task domains ($t(29) = -3.64$, $FDR-q = 0.005$, Cohen's $d = -0.67$). Considered separately, anterior 55b showed neither a production bias (mean $\beta = 0.01$; $t(29) = 0.20$, $FDR-q = 0.84$) nor above-chance task-domain classification (mean = 0.52, $SD = 0.09$; $t(29) = 0.92$, $FDR-q = 0.46$), whereas posterior 55b showed both a strong production bias (mean $\beta = 0.94$; $t(29) = 10.24$, $FDR-q < 0.001$) and above-chance classification (mean = 0.72, $SD = 0.13$; $t(29) = 8.93$, $FDR-q < 0.001$).


Representational measures showed a complementary dissociation. Semantic-category decoding was greater in anterior than posterior 55b (anterior mean = 0.53, $SD = 0.11$; posterior mean = 0.48, $SD = 0.10$; $t(29) = 2.74$, $FDR-q = 0.007$), whereas articulatory-feature encoding was greater posteriorly (posterior mean = 0.76, $SD = 0.11$; anterior mean = 0.59, $SD = 0.37$; $t(29) = -2.60$, $FDR-q = 0.007$; **Fig. 2b** right two panels). Because the articulatory model was compared with a word-onset baseline, this measure is interpreted as articulatory-feature-related encoding rather than a uniquely phonetic code.

Tractography-derived connectivity mirrored this functional gradient (**Fig. 2c**). A 2×2 repeated-measures ANOVA revealed a network $\times$ subregion interaction ($F(1,25) = 30.59$, $P < 0.001$, generalized $\eta^2 = 0.223$). Anterior 55b showed stronger normalized streamline-count connectivity with the language network than posterior 55b (anterior – posterior = 0.013; $t(25) = 3.35$, $P = 0.003$, Cohen's $d = 0.66$), whereas posterior 55b showed stronger connectivity with SCAN than anterior 55b (anterior – posterior = -0.283; $t(25) = -5.35$, $P < 0.001$, Cohen's $d = -1.05$). Thus, network alignment, representational content, task preference, and estimated white-matter connectivity converged on the same anterior language-facing to posterior action-facing organization.

a. The dominant local connectivity gradient followed an anterior–posterior axis



b. Anterior–posterior dissociation in task responses and representational content



c. Anterior–posterior dissociation in tractography-derived structural connectivity




Fig. 2 | A reproducible internal gradient in area 55b links network alignment, functional specialization, and crossed white-matter connectivity. **a**, The dominant local connectivity gradient followed an anterior–posterior axis. Anterior high-gradient 55b aligned most strongly with the canonical language network (Dice = 0.42), whereas posterior low-gradient 55b aligned most strongly with SCAN (Dice = 0.74); independent replication is shown in Supplementary Fig. 5. **b**, Functional differentiation. Posterior 55b showed stronger production bias, comprehension–production classification, and articulatory-feature encoding, whereas anterior 55b showed stronger semantic-category decoding. **c**, Tractography-derived connectivity. Anterior 55b showed stronger normalized streamline-count connectivity with the language network (LAN), whereas posterior 55b showed stronger connectivity with SCAN. Box–violin plots show medians and interquartile ranges; violin widths indicate density; grey lines connect paired participant estimates. Dashed lines indicate the relevant null value. Asterisks denote FDR-corrected significance (* $q < 0.05$, ** $q < 0.01$, *** $q < 0.001$).

Area 55b distinguishes comprehension from production across sensory and motor formats


We next tested whether the gradient-defined territory distinguished the direction of language processing across modalities. In univariate responses, area 55b and SFL showed production-biased profiles (area 55b: $t(29) = 9.226$, $P < 0.001$, Cohen's $d = 1.68$; SFL: $t(28) = 6.752$, $P < 0.001$, Cohen's $d = 1.25$; **Fig. 3a**). IFJ and anterior fusiform gyrus showed no significant production–comprehension difference (IFJ: $t(29) = -2.272$, $P = 0.153$, Cohen's $d = -0.415$; anterior fusiform gyrus: $t(28) = 2.729$, $P = 0.054$, Cohen's $d = 0.51$). P values were Bonferroni-corrected. Production-biased responses in area 55b and SFL were replicated in the Peking University dataset (**Supplementary Fig. 4**).

Cross-modal classifiers were trained on one comprehension–production pair and tested on another pair involving different sensory and motor formats. Area 55b and SFL showed above-chance classification (area 55b: mean accuracy = 0.76, $SD = 0.13$; $t(29) = 10.74$, $P < 0.001$, Cohen's $d = 1.96$; SFL: mean accuracy = 0.67, $SD = 0.13$; $t(29) = 7.494$, $P < 0.001$, Cohen's $d = 1.37$), with higher accuracy in area 55b than SFL ($t(29) = 3.05$, $P = 0.005$, Cohen's $d = 0.56$; **Fig. 3b**). IFJ and anterior fusiform gyrus did not show above-chance classification.


185 Principal-component visualization showed the same task-domain separation in area 55b and SFL
186 (**Fig. 3c**). An orthographic control did not distinguish written-form tasks from non-orthographic tasks
187 in either region (area 55b: $P = 1.00$, Cohen's $d = -0.12$; SFL: $P = 1.00$, Cohen's $d = -0.09$;
188 Supplementary Results). This control argues against simple grouping by orthographic form, but does
189 not eliminate the picture-versus-word difference between production and comprehension. The result
190 is therefore interpreted as a cross-modal task-domain distinction rather than a fully format-invariant
191 computation.

192 Area 55b, but not SFL, also carried stronger semantic-category information during production (**Fig.**
193 **3d**): production decoding exceeded comprehension decoding ($\Delta accuracy = 0.06$; $t(28) = 2.74$, FDR- q
194 $= 0.045$, Cohen's $d = 0.51$) and chance (mean = 0.54, $SD = 0.08$; FDR- $q = 0.023$, Cohen's $d = 0.48$),
195 whereas comprehension decoding did not exceed chance (mean = 0.49, $SD = 0.08$; FDR- $q = 0.82$,
196 Cohen's $d = -0.18$). SFL showed neither effect. Because production was picture-cued, the result
197 indexes available category information rather than necessarily establishing an amodal semantic code.


a. Production-biased univariate activation strength



b. Cross-modal decoding of comprehension versus production



c. Principal-component visualization.



d. Area 55b showed greater semantic-category decoding during production




Fig. 3 | Area 55b differentiates word comprehension from production across sensory and motor formats. **a**, Production-biased univariate responses. Area 55b and SFL showed stronger responses during production than comprehension. **b**, Cross-modal classification. Area 55b and SFL showed above-chance classification of comprehension versus production, whereas IFJ and anterior fusiform gyrus did not. **c**, Principal-component visualization. Comprehension and production occupied separable positions in area 55b and SFL. **d**, Area 55b showed greater semantic-category decoding during production than comprehension, with above-chance decoding only during production; SFL showed neither effect. Box–violin plots show participant-level values, medians, and interquartile ranges; error bars denote SEM; dashed lines indicate chance or zero. Asterisks indicate corrected significance (*** $P < 0.001$, ** $P < 0.01$, * $P < 0.05$); NS, not significant.

Production reweights 55b coupling toward frontal language and motor-effector systems


We then tested whether language production and comprehension were associated with different model-estimated directed coupling between area 55b and task-relevant sensory, lexical, and motor regions. A sparse, 55b-centred dynamic causal model estimated bidirectional edges between 55b and auditory cortex, visual cortex, SFL, IFJ, anterior fusiform gyrus, ventral laryngeal–orofacial motor cortex, and dorsal hand motor cortex, without modelling direct connections among the non-55b nodes (**Fig. 4a**). The architecture was hypothesis-constrained and was not designed to establish a unique whole-network causal pathway.

Relative to comprehension, production increased outgoing model-estimated coupling from 55b to ventral laryngeal–orofacial motor cortex (mean difference = 0.324; $t(29) = 11.40$, $\text{FDR-}q < 0.001$, Cohen's $d = 2.08$), dorsal hand motor cortex (mean difference = 0.302; $t(25) = 3.63$, $\text{FDR-}q = 0.002$, Cohen's $d = 0.71$), IFJ (mean difference = 0.746; $t(29) = 5.00$, $\text{FDR-}q < 0.001$, Cohen's $d = 0.91$), and SFL (mean difference = 0.413; $t(29) = 15.97$, $\text{FDR-}q < 0.001$, Cohen's $d = 2.92$; **Fig. 4b**).

The reweighting was selective: 55b-to-visual cortex did not differ between task domains, whereas 55b-to-auditory cortex and 55b-to-fusiform coupling were stronger during comprehension. None of the seven incoming edges to 55b differed reliably after FDR correction (**Fig. 4b** and **Supplementary**

226 **Table 1).** Within the specified model, production therefore preferentially weighted outgoing 55b-
 227 centred coupling toward frontal language-related and motor-effector systems.

a. Sparse 55b-centred DCM with bidirectional edges between area 55b and other ROIs



b. Production–comprehension differences in incoming and outgoing parameters




Fig. 4 | Task-dependent model-estimated directed coupling of area 55b. **a**, Sparse 55b-centred DCM with bidirectional edges between area 55b and sensory, lexical/language-related, and effector-specific motor regions. Arrows show model-estimated directed coupling; line thickness scales with the absolute group-mean modulation parameter; red and light blue denote positive and negative modulation. **b**, Production–comprehension differences in incoming and outgoing parameters. Incoming edges showed no significant task-domain differences after FDR correction, whereas outgoing edges were reweighted during production toward frontal language-related and motor regions.

236 Asterisks denote FDR-corrected significance (* $q < 0.05$, ** $q < 0.01$, *** $q < 0.001$); NS, not significant.
237 Abbreviations: Aud, auditory cortex; Vis, visual cortex; Fusi, anterior fusiform gyrus; SFL, superior
238 frontal language area; IFJ, inferior frontal junction; vM, ventral laryngeal–orofacial motor cortex; dM,
239 dorsal hand motor cortex.

240

241 **Area 55b occupies a convergent transition across macroscale cortical hierarchies**

242 We finally placed the 55b territory within broader principles of cortical organization. For each of
243 six independent hierarchy maps, we sampled vertex-wise values from three adjacent parcels spanning
244 sensorimotor-adjacent cortex, the parcel containing area 55b, and association-adjacent cortex (**Fig. 5a**).
245 The maps captured evolutionary, myeloarchitectonic, transcriptomic, metabolic, meta-analytic
246 functional, and composite sensory-to-association dimensions (**Fig. 5b,c**; Methods). This analysis
247 establishes the regional position of 55b within a local transition; it does not test direct vertex-wise
248 alignment between each hierarchy map and the internal 55b connectivity gradient.

249 Across all six maps, values progressed monotonically from the sensorimotor-adjacent parcel
250 through the 55b parcel to the association-adjacent parcel (all ordered-trend tests $P < 0.0001$; **Fig. 5b,c**).
251 The multidimensional transition profile around 55b was stronger and more consistent than those
252 around the other conjunction-defined regions and canonical language-network controls
253 (**Supplementary Fig. 7** and **Supplementary Table 2**). The hierarchy analysis therefore embeds the
254 local 55b finding within a broader sensory-to-association landscape while keeping the regional and
255 within-territory levels of evidence distinct.




Fig. 5 | Area 55b occupies a convergent transition across macroscale cortical hierarchies. a, Three-parcel sampling of sensorimotor-adjacent cortex (blue), the parcel containing area 55b (beige), and association-adjacent cortex (red). **b,** Ordered parcel values across evolutionary expansion, T1w/T2w myeloarchitecture, and AHBA gene-expression PC1. **c,** Multidimensional transition profile and ordered parcel values for PET-derived aerobic glycolysis, NeuroSynth PC1, and a composite sensory-to-association hierarchy. The analysis establishes regional embedding around 55b and should not be interpreted as direct vertex-wise correspondence between every hierarchy map and the internal functional gradient.

Discussion

Large-scale brain networks must remain functionally distinct while exchanging information rapidly enough to turn cognition into action. Our findings reveal a local cortical organization that can support both requirements. Within left area 55b, a reproducible anterior–posterior connectivity gradient separated a language-aligned end from an action-aligned end. Anterior 55b showed stronger

semantic-category information and preferential tractography-derived connectivity with the language network, whereas posterior 55b showed stronger production bias, articulatory-feature encoding, and preferential connectivity with SCAN. During production, 55b also reweighted model-estimated directed coupling toward frontal language regions and laryngeal–orofacial and hand motor cortices. The territory occupied a convergent local transition across multiple macroscale cortical hierarchies. Together, these observations suggest that 55b is neither a uniform language module nor a purely motor territory, but a graded cross-network transition linking linguistic representations to action systems.

This account differs from treating network integration as either overlap between two modules or communication through a functionally undifferentiated hub. The two ends of 55b were not distinguished by connectivity alone: their network alignments were mirrored by representational content, task preference, and a crossed pattern of anatomical connectivity estimates. This convergence implies an organized transition in which the language-facing end retains stronger access to linguistic and category information, while the SCAN-facing end is progressively biased toward action formulation and articulatory structure. The median split used here provides an operational comparison between the ends of this axis, but the underlying result is most naturally interpreted as a continuum rather than two new cortical modules. Such a local gradient offers a simple way to combine segregation with integration: different computations can be emphasized at opposite ends while neighboring circuitry allows information to be reformatted across the territory.

The gradient also reconciles previously divergent accounts of area 55b. Dorsal frontal language models and neurosurgical studies have emphasized contributions to speech planning, syllabic sequencing, and articulatory control^{13,14,17,28–30,42,43}, whereas other work has placed the same territory within a broader language or semantic architecture^{32–36}. If 55b is treated as a single functional unit, these assignments appear incompatible. The present results show why both can be partly correct. The posterior, SCAN-aligned end was more strongly engaged by production and carried stronger articulatory-feature encoding, whereas the anterior, language-aligned end carried stronger semantic-category information. Area-level labels can therefore obscure a computational transition within the territory, particularly when inter-individual variability and group averaging blur its internal topography^{44,45}.

299 The relationship with SCAN is especially informative. SCAN regions interrupt the classical
300 effector map and have been proposed to coordinate goals, bodily state, and multi-effector action plans
301 rather than execute a single movement ^{19–21}. Posterior 55b displayed the profile expected of an
302 association-action territory: it was more strongly connected with SCAN, responded preferentially
303 during production across speaking and writing, and carried stronger articulatory-feature encoding. This
304 pattern places posterior 55b between high-level linguistic content and the effector-specific cortices that
305 implement speech and writing. It also extends the relevance of SCAN beyond conventional movement
306 paradigms to highly learned symbolic actions. Conversely, the preferential alignment of anterior 55b
307 with the language network indicates that the transition begins within circuitry retaining access to
308 linguistic representations rather than at the border of primary motor cortex.

309 Task-dependent coupling provides a dynamic complement to this stable topography. Relative to
310 comprehension, production increased model-estimated outgoing modulation from 55b toward both
311 laryngeal–orofacial and hand motor cortices and toward frontal language regions, while auditory and
312 fusiform pathways showed the opposite task preference. The pattern is therefore inconsistent with a
313 uniform increase in all 55b outputs during production. Instead, it suggests that a stable cross-network
314 gradient can be flexibly weighted according to the current direction of processing: sensory and form-
315 related systems are emphasized when linguistic signals are interpreted, whereas frontal and motor
316 systems are emphasized when content is converted into action. Because the DCM was deliberately
317 sparse and centred on 55b, these results provide evidence for task-dependent reconfiguration within
318 the specified model, not proof that 55b is the unique causal source of the observed interactions ⁴⁰.

319 The position of 55b within broader cortical hierarchies connects the local finding to a general
320 principle of cortical organization. Across evolutionary expansion, myeloarchitecture, gene expression,
321 aerobic glycolysis, meta-analytic function, and a composite sensory-to-association axis, the 55b parcel
322 lay between sensorimotor-adjacent and association-adjacent cortex. This convergence is consistent
323 with the idea that local network transitions are constrained by macroscale biological gradients ^{1,2,4}.
324 Importantly, the hierarchy analysis establishes the regional position of 55b; it does not by itself
325 demonstrate a vertex-wise correspondence between each hierarchy map and the internal functional
326 gradient. The two levels of evidence are complementary: intrinsic connectivity reveals the organization

327 within 55b, while the hierarchy maps place that territory within a broader sensory-to-association
328 landscape.

329 Language is a particularly clear instance of a more general cognition-to-action problem. Speaking
330 and writing require relatively stable content to be converted into rapidly changing commands for
331 different effectors^{46–49}; comprehension requires information to travel in the complementary direction
332 from sensory forms toward meaning^{7,50–54}. A local gradient between a cognitive network and an action
333 network provides an architecture capable of supporting both directions without requiring a dedicated
334 module for every input and output format. Similar transition zones may support other flexible
335 transformations, such as converting memory into action plans or linking perceptual decisions to
336 coordinated behaviour. Testing that possibility will require identifying comparable within-territory
337 gradients at other network boundaries and determining whether their topology predicts task-dependent
338 communication.

339 Several limitations define the next steps. First, the current evidence is correlational. Individually
340 targeted stimulation, intracranial recording, or precision lesion-symptom mapping will be needed to
341 establish whether perturbing different positions along the 55b gradient produces dissociable deficits in
342 linguistic representation and action formulation^{55–57}. Second, the production tasks were picture-cued
343 whereas the comprehension tasks used spoken or written words. Cross-modal analyses reduce
344 dependence on a single sensory or motor format but do not fully remove the picture-versus-word
345 distinction; cross-format semantic generalization and models that partial out visual, orthographic,
346 phonological, and articulatory features would provide a stronger test of representational content. Third,
347 diffusion tractography and hypothesis-constrained DCM provide indirect estimates of anatomical and
348 directed coupling, respectively. Their convergence with local functional gradients is informative, but
349 neither method establishes monosynaptic pathways or causal direction. Finally, task-based subregional
350 effects were obtained in native Chinese speakers. Replication across languages, writing systems, and
351 naturalistic communication will clarify which aspects of the gradient are language-general.

352 In conclusion, area 55b contains a local anterior-posterior gradient that differentially links the
353 language network with SCAN. Its language-facing end carries stronger semantic-category information,

354 whereas its action-facing end carries stronger production-related and articulatory information; this
355 functional dissociation is mirrored by white-matter connectivity and complemented by task-dependent
356 coupling to effector systems. By locating these differences within a small cortical territory embedded
357 in a broader sensory-to-association transition, the findings move beyond assigning 55b to a single
358 function. They illustrate a general organizational principle by which local cortical gradients can bridge
359 large-scale cognitive and action networks.

360 **Methods**

361 **Datasets overview**

362 This study used three neuroimaging datasets: a multimodal word-processing dataset collected by
363 our team at the Institute of Psychology, Chinese Academy of Sciences (CAS); a published multimodal
364 word dataset from Peking University ³⁷; and a public resting-state fMRI dataset from the Human
365 Connectome Project (HCP) ³⁹. The CAS multimodal word-processing dataset served as the primary
366 dataset for analyses. The Peking University dataset ³⁷ was used to assess the robustness and cross-
367 dataset generalizability of our findings. Resting-state fMRI data in the HCP S900 release were used to
368 characterize local functional connectivity gradients.

369 **CAS multimodal word-processing dataset**

370 **Participants**

371 Thirty-three healthy adults took part in this experiment. Three participants did not complete all
372 experimental sessions and were excluded, leaving a final sample of thirty participants (16 women;
373 mean age $\pm$ SD, 22.67 ± 2.98 years; age range, 18–34 years). All participants were right-handed native
374 Chinese speakers with normal hearing and normal or corrected-to-normal vision. All participants
375 provided written informed consent before participation. This study was approved by the Ethics
376 Committee of the Institute of Psychology, Chinese Academy of Sciences (H21077), and was conducted
377 in accordance with the Declaration of Helsinki. Participants received monetary compensation after
378 completing the study.

379 **Tasks and procedures**

380 The CAS multimodal word-processing dataset comprised four word-level language processing
381 tasks, including two comprehension tasks (listening and reading) and two production tasks (naming
382 and writing). Each task included an experimental condition designed to probe lexical processing in a
383 specific input or output modality, together with a modality-matched control condition that preserved
384 basic sensory or motor demands while minimizing lexical and semantic content, thereby providing a
385 baseline for isolating lexical-semantic processing. All tasks were implemented in a block design with
386 experimental and matched control blocks. To improve the reliability of within-subject activation
387 estimates (see **Supplementary Methods, Results** and **Fig. 2**), each participant completed three
388 scanning sessions separated by at least three days, ensuring independent sampling of task-related
389 responses. Each session comprised four runs, one for each task. The procedure and timing of each task
390 are shown in **Supplementary Fig. 1**.

391 All four word-level tasks used the same set of 41 disyllabic Chinese words. 16 words were grouped
392 into 4 semantic categories — household appliances, places, mammals and vehicles — with 4 words in
393 each category; each category formed one semantic block. The remaining 25 words were grouped into
394 5 phonological sets according to the onset syllable of the first character (shu, shi, xiang, luo and jing),
395 with 5 words in each set; each set formed one phonological block. Each task included 4 semantic
396 blocks, 5 phonological blocks and 6 modality-matched control blocks. Each semantic block contained
397 4 items and each phonological block contained 5 items. Among the 6 control blocks, 3 blocks each
398 contained 4 items to match the semantic blocks, and the other 3 blocks each contained 5 items to match
399 the phonological blocks. The full set of stimuli was presented in **Supplementary Table 3**. We counted
400 word frequency, first-syllable frequency, character frequency and stroke count. For the production
401 tasks, we selected object pictures corresponding to the target words from standardized picture
402 databases with high naming agreement^{58,59}.

403 **Listening task**

404 In the listening task, participants listened to spoken words in the experimental blocks and reported
405 at the end of each block whether any animal-related words had appeared. In the control blocks, they

406 listened to acoustically matched reversed-speech stimuli and reported whether they had heard any
407 meaningful speech ^{37,60}. The spoken-word stimuli were generated using female voice text-to-speech
408 synthesis and the control stimuli were created by applying full time reversal to each audio file,
409 producing unintelligible stimuli that preserved low-level acoustic properties. Each block began with a
410 200-ms fixation cross and was followed by a semantic, phonological or control block. Within each
411 block, each item was presented for 2,000 ms with a fixed 250 ms interstimulus interval. After each
412 block, a probe question appeared for 2,500 ms. Blocks were separated by fixation intervals of 9–12 s
413 (mean, 11 s), yielding a total run duration of 5 min 58 s.

414 **Reading task**

415 In the reading task, participants viewed Chinese disyllabic words during the experimental blocks
416 and judged at the end of each block whether any animal terms had appeared. During the control blocks,
417 they viewed Korean Hangul strings and judged whether any Chinese characters had appeared. Korean
418 Hangul strings were used as a visual control to preserve low-level orthographic input while minimizing
419 access to lexical-semantic content ^{61,62}. Before the experiment, we confirmed that participants could
420 not read or identify Hangul characters. Each block began with a 200-ms fixation cross. Stimuli were
421 presented for 2,000 ms with a fixed 250-ms interstimulus interval, followed by a 2,500-ms response
422 period at the end of each block. Blocks were separated by fixation intervals of 9–12 s, yielding a total
423 run duration of 5 min 58 s.

424 **Naming task**

425 In the naming task, participants viewed nameable object pictures and named each object aloud
426 during the experimental blocks, whereas during the control blocks they viewed scrambled versions of
427 the same pictures and produced a fixed utterance (“1, 2”). Spoken responses were recorded during
428 scanning using an external microphone. Before scanning, participants completed a naming practice
429 session to ensure consistent labels for the object pictures. The scrambled images were created by
430 randomly rotating pixel blocks to preserve low-level visual properties, such as luminance and contrast,
431 while disrupting recognizable structure ⁶⁰. Each block began with a 200-ms fixation cross, after which
432 each stimulus was presented for 2,500 ms with a fixed 250-ms interstimulus interval. Blocks were

433 separated by fixation intervals of 9–12 s, yielding a total run duration of 5 min 55 s.

434 **Writing Task**

435 In the writing task, participants viewed object pictures and wrote the corresponding Chinese
436 disyllabic words in the experimental blocks and viewed geometric line drawings adapted from previous
437 studies^{63,64} and copied the figures in the control blocks. Responses were recorded using a custom
438 fMRI-compatible tablet equipped with a touch-sensitive surface, a force-sensitive stylus, and an
439 adjustable support frame. The support frame was individually adjusted to provide stable wrist or
440 forearm support, thereby reducing fatigue during scanning. Real-time ink feedback was provided to
441 allow participants to monitor their written or drawn output during the task. Participants were instructed
442 to write each character stroke by stroke while minimizing upper-arm and forearm movements to reduce
443 head motion. Before the formal experiment, all participants completed in-scanner practice with the
444 tablet by writing five example words. Each block began with a 200-ms fixation cross, followed by
445 image presentation, with each item displayed for 1.5 s. After each image appeared, participants had 3–
446 5 s to respond, depending on the stroke count of the target characters in the experimental condition.
447 After each line drawing appeared, participants had 3 s to respond. Blocks were separated by fixation
448 intervals of 9–12 s, yielding a total run duration of 11 min 46 s.

449 **MRI data acquisition and preprocessing**

450 **MRI data acquisition**

451 MRI data were acquired using a 3.0-T Siemens Magnetom Prisma scanner at the MRI Center of
452 the Institute of Biophysics, Chinese Academy of Sciences. High-resolution structural images were
453 acquired using a T1-weighted magnetization-prepared rapid acquisition gradient-echo (MPRAGE)
454 sequence (repetition time (TR) = 2200 ms; echo time (TE) = 3.49 ms; 192 sagittal slices; field of view
455 (FOV) = 256 mm; voxel size = 1×1×1 mm).

456 Task and resting-state functional images were acquired using a multiband echo-planar imaging
457 (EPI) sequence (multiband factor = 2; TR = 1500 ms; TE = 30 ms; 40 axial slices; FOV = 192 mm;
458 voxel size = 3×3×3 mm). Task fMRI was acquired throughout the full duration of each task run, with

an additional 9-s dummy period at the start of each run to allow for magnetization stabilization. Resting-state scans were acquired over 15 min in two runs of 8 min and 7 min. Diffusion-weighted images were collected using a high-angular-resolution diffusion imaging (HARDI) protocol (TR = 4000 ms; TE = 79 ms; voxel size = 1.5×1.5×1.5 mm; field of view = 192 mm). The sequence included 64 diffusion directions at $b = 1000$ s/mm² and 64 directions at $b = 2000$ s/mm², and five non-diffusion-weighted ($b = 0$ s/mm²) volumes. Structural, resting-state and diffusion scans were acquired on separate days from the task fMRI sessions to minimize fatigue.

Preprocessing of MRI data

Structural, task-based and resting-state fMRI data were preprocessed using *fMRIPrep*^{65,66} followed by *XCP-D*⁶⁷. Structural T1-weighted images underwent intensity non-uniformity correction⁶⁸, skull stripping, tissue segmentation, and cortical surface reconstruction using FreeSurfer's recon-all pipeline⁶⁹. fMRI data underwent susceptibility distortion correction using field maps, co-registration of the BOLD reference image to each participant's T1-weighted anatomical image with FreeSurfer's bbgregister, head-motion correction with FSL's mcflirt, slice-timing correction with AFNI's 3dTshift, and cortical surface reconstruction using FreeSurfer's recon-all pipeline. Data were then projected to grayordinates by generating HCP fsLR 64k cortical meshes with wb_command and resampling BOLD time series to the cortical surface and subcortical grey-matter structures³⁹. Finally, time series were despiked and temporally detrended using AFNI's 3dDespike to remove transient outliers and linear or quadratic drifts⁷⁰. Resting-state fMRI data underwent the same preprocessing steps, followed by additional denoising procedures. These included 36-parameter confound regression, incorporating 24 motion parameters together with mean white-matter, cerebrospinal fluid and global signals, and band-pass filtering (0.01–0.08 Hz) to reduce high-frequency physiological noise and low-frequency scanner drift^{71–74}.

High-angular-resolution diffusion-weighted imaging (HARDI) data were preprocessed using QSIprep and reconstructed for tractography using the QSIREcon MRtrix3 workflow⁷⁵. The T1-weighted anatomical reference image was first reoriented into AC–PC alignment using a 6-degree-of-freedom transform estimated from affine registration to the MNI152NLin2009cAsym template.

486 Nonlinear registration to the same template was then performed using symmetric normalization in
487 ANTs. Brain extraction was performed with SynthStrip⁷⁶, and tissue segmentation was obtained using
488 SynthSeg from FreeSurfer 7.3.1⁷⁷.

489 Diffusion preprocessing followed the standard QSIPrep workflow. Raw diffusion images were
490 denoised using Marchenko–Pastur principal component analysis as implemented in MRtrix3
491 dwidenoise, with an automatically determined five-voxel window^{78,79}. Gibbs ringing artifacts were
492 then removed using MRtrix3 *mrdegibbs*⁸⁰. Volumes with b-values below 100 s/mm² were treated as
493 b0 images. When multiple DWI sequences were acquired, the mean intensity of each diffusion series
494 was normalized so that the mean b0 intensity was matched across sequences. Susceptibility-related
495 and eddy-current distortions, as well as head motion, were corrected using FSL eddy⁸¹. Eddy was run
496 with outlier replacement, post-correction shell alignment, a q-space smoothing factor of 10, five
497 iterations, and 1000 voxels for hyperparameter estimation⁸². A quadratic first-level model and a linear
498 second-level model were used to model eddy-current-related spatial distortions. After correction and
499 resampling, B1 field inhomogeneity was corrected using MRtrix3 *dwibiascorrect* with the N4
500 algorithm⁶⁸. The preprocessed DWI series was resampled to AC–PC space at 1.5-mm isotropic
501 resolution. Framewise displacement and slice-wise cross-correlation metrics were computed for
502 quality control.

503 Whole-brain tractography used the QSIREcon *mrtrix_multishell_msmt_ACT-hsvs* workflow.
504 Multi-tissue fibre orientation distributions were estimated from multi-shell HARDI data using multi-
505 shell multi-tissue constrained spherical deconvolution, with separate response functions for white
506 matter, grey matter, and cerebrospinal fluid⁷⁶. Probabilistic streamlines were generated using second-
507 order integration over fibre orientation distributions (iFOD2) in MRtrix3⁸³. Anatomically constrained
508 tractography used tissue boundaries from T1-weighted segmentation and the hybrid surface–volume
509 segmentation procedure of the ACT-HSVS workflow⁸⁴. SIFT2 weights were estimated for the whole-
510 brain tractogram⁸⁵, although the regional connectivity analysis reported below used normalized
511 retained-streamline counts rather than the summed SIFT2 weights. Whole-brain tractograms were
512 visually inspected before region-to-region tract extraction. For task-fMRI quality control, participants
513 would have been excluded if any run exceeded 3 mm translation, 3° rotation, or mean framewise

514 displacement of 0.2 mm; no CAS participant met these criteria.

515 **Peking University Dataset**

516 **Participants**

517 We used a separate multimodal word-processing dataset collected at Peking University³⁷ to
518 evaluate the robustness and generalizability of our findings. The original sample comprised 101
519 healthy native Chinese speakers (50 women; mean age $\pm$ SD, 23.0 $\pm$ 2.2 years). One male participant
520 was excluded due to excessive head motion (> 2.5 mm), yielding a final sample of 100 right-handed
521 participants. All participants reported normal hearing, normal or corrected-to-normal vision, and no
522 history of neurological or language disorders. Written informed consent was obtained from all
523 participants, and the study was approved by the Institutional Review Board at Peking University.

524 **Tasks**

525 Like the CAS multimodal word-processing dataset, this dataset comprised four word-level
526 language tasks: two comprehension tasks (listening and reading) and two production tasks (naming
527 and writing), each with experimental and control blocks. Unlike the CAS multimodal word-processing
528 dataset, however, the lexical items were not matched across tasks, such that each task used a distinct
529 word set. In addition, the control contrasts and task procedures differed from those used in the
530 corresponding CAS tasks. In the listening task, participants heard spoken Chinese nouns during the
531 experimental blocks and judged whether each referred to a living creature; during the control blocks,
532 they heard time-reversed speech and judged whether the speaker was male or female. In the reading
533 task, participants viewed written Chinese nouns during the experimental blocks and judged whether
534 each referred to a living creature, whereas during the control blocks they viewed written Chinese words
535 and judged the number of characters in each item. In the naming task, participants viewed line drawings
536 of common objects and named each picture aloud during the experimental blocks, whereas during the
537 control blocks they viewed matched syllable strings and repeated them aloud. In the writing task,
538 participants viewed object pictures and wrote the corresponding words on an MRI-compatible tablet
539 during the experimental blocks, whereas during the control blocks they copied visually presented
540 Chinese characters (or control symbols) with their right hand. Full details are provided in Qin et al.

541 (2021)³⁷.

542 **Data acquisition and preprocessing**

543 MRI data were acquired on a 3T Siemens Prisma scanner (Siemens Healthineers) with a 20-
544 channel head coil. A high-resolution T1-weighted structural image was obtained using an MPRAGE
545 sequence (TR = 2530 ms; TE = 2.98 ms; flip angle = 7°, 1 mm isotropic voxels) for anatomical
546 reference and surface reconstruction. Task and resting-state functional images were acquired using a
547 T2*-weighted EPI sequence with 33 contiguous axial slices covering the whole brain (TR = 2000 ms,
548 TE = 30 ms, flip angle = 90°, matrix size = 64×64, in-plane resolution = 3.5× 3.5 mm, and slice
549 thickness = 4.2 mm). The resting state run lasted 6 min. These data were preprocessed using the same
550 *fMRIPrep* and *XCP-D* workflow described above.

551 **Human Connectome Project dataset**

552 **Participants**

553 To characterize large-scale intrinsic functional gradients, we analyzed resting-state fMRI data
554 from 245 neurologically healthy adults (130 men, 115 women) from the HCP S900 release³⁹.
555 Participants were aged 23 to 35 years (mean $\pm$ SD, 28.21 $\pm$ 3.67 years). Participants were included
556 based on HCP motion-quality metrics. Individuals were excluded if they exceeded 1.5 times the
557 interquartile range on at least two of four summary motion measures derived from relative root mean
558 square displacement across resting-state runs. Runs were further excluded if more than 25% of frames
559 exceeded 0.2 mm frame-wise displacement^{86–88}. Three participants with incomplete resting-state time
560 series were also removed. Only unrelated individuals who completed all four resting-state runs were
561 retained for analysis.

562 **MRI data acquisition and preprocessing**

563 MRI acquisition protocols for the HCP have been described elsewhere^{38,39}. All data were collected
564 on a customized 3-T Siemens Connectome scanner with a 100 mT/m SC72 gradient system and a 32-
565 channel head coil. We used only the T1-weighted structural images and resting-state fMRI data in the
566 present study.

567 High-resolution T1-weighted structural images were acquired using an MPRAGE sequence with
568 0.7-mm isotropic resolution. Resting-state fMRI data consisted of four runs, each lasting 14 min 33 s,
569 acquired using a multiband echo-planar imaging sequence (TR = 720 ms, 2-mm isotropic) optimized
570 for high temporal and spatial resolution.

571 **Preprocessing**

572 Resting-state fMRI data from the HCP S900 release were processed using the HCP minimal
573 preprocessing pipelines ³⁹. Structural images were corrected for spatial distortions, registered to
574 MNI152 space using nonlinear volume-based alignment, and processed via FreeSurfer v5.3 to
575 reconstruct cortical surfaces. Functional images underwent distortion correction, motion correction
576 and registration to the T1-weighted image, followed by ribbon-constrained volume-to-surface mapping
577 to generate CIFTI grayordinate data. Subcortical voxels were assigned to their corresponding
578 structures, and cortical and subcortical data were combined in standard CIFTI grayordinate space.
579 Surface smoothing (2-mm FWHM) was applied to reduce mixing signals across sulcal banks and areal
580 boundaries. Resting-state fMRI data were further denoised using spatial ICA+FIX for spatially specific
581 noise and temporal ICA ^{22,89}.

582 **First-level activation analysis**

583 **CAS multimodal word-processing dataset**

584 We estimated single-block responses for each participant, session and task for use in subsequent
585 univariate analyses, multivariate pattern analyses, semantic decoding and gradient-based functional
586 characterization. Single-block responses were estimated using *GLMsingle*, which improves block-wise
587 fMRI response estimation through spatially specific hemodynamic response function selection, data-
588 driven denoising and fractional ridge regression within a unified general linear modelling framework,
589 thereby yielding more reliable block-wise beta estimates ⁹⁰. For each block, onset times and durations
590 were entered into the design matrix, with six rigid-body motion parameters included as nuisance
591 regressors. Block-wise beta estimates were computed in CIFTI grayordinate space.

592 **Peking University dataset**

593 Because the Peking University dataset used different word items across tasks, we restricted
594 analyses to task-wise univariate contrasts between word blocks and their matched control blocks. We
595 estimated block-level activation maps using a standard first-level general linear model implemented
596 in Nilearn⁹¹. For each participant and task, BOLD time series were modelled with regressors for word
597 and control blocks, convolved with a Glover hemodynamic response function. Polynomial drift terms
598 (order 3) and six rigid-body motion parameters were included as nuisance regressors. Beta estimates
599 were computed in CIFTI grayordinate space. We obtained word versus control statistical maps by
600 computing t-contrast Z-maps for each task using Nilearn's contrast estimation routines. These maps
601 were used for univariate activation replication and gradient-based functional subregion segmentation
602 analysis.

603 **Individual-specific brain parcellation**

604 To improve cross-participant correspondence while accommodating individual variability, all task
605 analyses used individual-specific functional parcellations^{23,24,45}. We estimated 900 cortical parcels for
606 each participant with the gradient-informed multi-session hierarchical Bayesian model (gMS-HBM)
607²³, applied to the participant's 15-min resting-state scan. Whole-brain connectivity gradients were used
608 to construct participant-specific features in a high-dimensional gradient space. Parcellation was
609 initialized from a Schaefer-900 group prior pretrained on 40 Human Connectome Project participants,
610 and subject-specific parcels were estimated using gMS-HBM with $w = 30$, $c = 30$, and $\beta = 50$,
611 following Kong et al.²³ (see **Supplementary Methods**). Activation modelling, MVPA, and DCM
612 volume-of-interest definition used these individual-specific parcels.

613 For the Peking University dataset, the 6-min resting-state scan was insufficient to support stable
614 estimation of individual-specific parcellations. We therefore concatenated each participant's resting-
615 state time series with residual BOLD time series from the task runs after regressing out task effects,
616 and used this combined intrinsic signal to compute individual-specific parcellations^{45,92–95}. Full
617 procedural details are provided in the **Supplementary Methods** (*Individual-specific brain*
618 *parcellation based on gMS-HBM*).

619 Multimodal lexical-network mapping and conjunction analysis

620 To identify regions consistently engaged across listening, reading, naming and writing, we
621 performed parcel-wise group-level analyses on activation estimates derived from individual-specific
622 parcellations, followed by conjunction mapping across tasks (workflow in Fig. 1a). For each
623 participant, session and task, we averaged block-wise activation estimates within each parcel
624 separately for the experimental and control conditions. Because the experimental condition contained
625 more blocks than the control condition, we matched the number of experimental blocks to the number
626 of control blocks within each session when computing condition averages, to ensure comparable
627 signal-to-noise ratios between conditions.

628 For each task (listening, naming, reading and writing), we fitted a linear mixed-effects model
629 separately for each parcel, with condition (experimental = 1, control = 0) as the fixed effect of interest,
630 to estimate the group-level activation difference between word and control blocks. Specifically, for
631 each participant s , session k , and parcel i , the activation estimate $y_{i,s,k}$ was modeled as:

$$632 \quad y_{i,s,k} = \beta_{0,i} + \beta_{1,i} X_{s,k} + u_{s,i} + v_{k,i} + \varepsilon_{i,s,k},$$

633 where $\beta_{0,i}$ was the parcel-specific intercept, $X_{s,k}$ was a binary indicator coding condition
634 (experimental condition = 1, control condition = 0), $\beta_{1,i}$ was the parcel-wise fixed effect indexing the
635 activation difference between the experimental and control conditions, $u_{s,i} \sim \mathcal{N}(0, \sigma_{u,i}^2)$ was the
636 participant-specific random intercept, $v_{k,i} \sim \mathcal{N}(0, \sigma_{v,i}^2)$ was the session-specific random intercept,
637 and $\varepsilon_{i,s,k} \sim \mathcal{N}(0, \sigma_{\varepsilon,i}^2)$ was the residual error term. We fitted the models in R 4.4.0 using the *lmerTest*
638 package. Across the 900 parcels, p values were corrected for multiple comparisons using false
639 discovery rate (FDR) correction at $q < 0.05$.

640 To identify regions consistently engaged across listening, reading, naming and writing, we applied
641 the minimum-T conjunction method in SPM (<https://www.fil.ion.ucl.ac.uk/spm/>) to the group-level
642 activation maps from the four-word tasks (**Fig. 1a**). To further assess the robustness of these findings,
643 we repeated the same mixed-effects analysis at the vertex level and generated vertex-wise activation
644 and conjunction maps.

645 **Analytical framework for characterizing a cross-network transition**

646 The conjunction analysis first defined a modality-invariant lexical candidate network (**Fig. 1a**).
647 The remaining analyses follow the order used in the Results and are summarized in **Fig. 1b, c**. We
648 estimated the internal connectivity gradient of area 55b and its large-scale alignment with the language
649 network and SCAN, and then tested whether gradient position predicted task responses, semantic-
650 category information, articulatory-feature encoding, and tractography-derived connectivity. We next
651 quantified comprehension–production differentiation across sensory and motor formats and task-
652 domain modulation of semantic-category information, followed by task-dependent model-estimated
653 directed coupling on 55b-centred edges. Finally, we situated 55b and comparison regions within local
654 transitions across six macroscale cortical hierarchy maps. This sequence treats the analyses as
655 convergent characterization of a language-to-SCAN transition rather than as criteria for cortical
656 exclusivity.

657 **Internal gradient and large-scale network alignment**

658 We asked whether area 55b contained an internal connectivity gradient that differentially aligned with
659 the language network and SCAN (**Fig. 1b**). We estimated the dominant local connectivity gradient and
660 used a median split to compare its anterior and posterior ends in large-scale network alignment. The
661 split provided an operational comparison, whereas the underlying organization was treated as
662 continuous. The gradient-defined sectors were then carried forward to the functional, representational,
663 and white-matter analyses described in the next Methods module. The same local-gradient procedure
664 was applied to SFL as a specificity analysis reported in the Supplementary Results.

665 **Local functional connectivity gradient analysis**

666 Area 55b was the primary local-gradient target because multimodal lexical mapping placed it at the
667 junction of the language network and SCAN. SFL was analyzed in parallel as a regional specificity
668 comparison. The individualized Schaefer–Kong parcels were too small for stable within-region
669 subdivision, so each region was mapped to the corresponding Glasser 360 parcel. For area 55b, 93%
670 of vertices overlapped with Glasser area 55b, and the full Glasser-defined territory was used for
671 gradient analysis; SFL was handled analogously. Gradient estimation was performed separately in each

dataset. In the Peking University dataset, the 6-min resting-state scan was concatenated with 15 min of residual task-fMRI time series after task-effect regression to increase the intrinsic time series available for estimation.

Within each participant, we computed a whole-cortex functional connectivity profile for every vertex in the region by correlating its resting-state time series with the time series of all cortical vertices in fs_LR 32k space (59,412 vertices). This yielded a vertex-by-cortex functional connectivity matrix, which was then Fisher z-transformed. These matrices were averaged across participants to obtain a group-level functional connectivity matrix for the region. Cosine similarity was then computed between vertices within the region to generate a vertex-by-vertex affinity matrix. Diffusion embedding, as implemented in BrainSpace⁹⁶, was applied to this affinity matrix to derive connectivity gradients. The first gradient, which captured the dominant mode of variation in local connectivity organization, was taken as the group-level principal gradient^{4,96,97}.

Subject-specific gradients were then estimated from each participant's Fisher z-transformed vertex-by-cortex functional connectivity matrix using the same procedure. Cosine similarity was used to construct an individual affinity matrix, diffusion embedding was applied to derive the individual principal gradient, and each individual gradient was aligned to the corresponding group-level principal gradient using Procrustes alignment⁹⁶. For each participant, the aligned principal gradient assigned a gradient value for every vertex in the region. Vertices were then subdivided into high-gradient and low-gradient subregions using a median split of these values.

Large-scale network alignment of gradient-defined subregions

To determine the large-scale network alignment of the gradient-defined subregions, we first computed whole-cortex functional connectivity maps for each subregion. For each participant, the mean BOLD time series was extracted from each subregion and correlated with the time series of all cortical vertices, followed by Fisher z transformation. These seed-to-cortex connectivity maps were then averaged across participants and thresholded using FDR correction at $q < 0.05$.

We next quantified the spatial overlap between each thresholded connectivity map and several canonical network templates, including the 17-network cortical parcellation^{23,98}, a fronto-temporal

699 language network ⁹⁹, a semantic control network ¹⁰⁰, the SCAN ¹⁹ and the action mode network ²¹.
700 Additional language- and action-related systems were included to assess whether the overlap patterns
701 were specific to established language networks or extended to recently proposed action-related systems.
702 All networks were binarized in surface space, and overlap was quantified using the Dice coefficient.
703 For each subregion, the template with the highest Dice coefficient was taken as its best-matching large-
704 scale network.

705 **Functional and structural specialization along the 55b gradient**

706 **Relative responses during comprehension and production tasks**

707 To determine whether gradient-defined subregions differed in their engagement during word
708 comprehension and production, we assessed task responses using two complementary analyses:
709 univariate activation contrasts and multivariate pattern classification. Both analyses were performed
710 separately within the high-gradient and low-gradient subregions of each candidate region. We
711 predicted that sensorimotor-biased subregions would show stronger production-dominant responses
712 and stronger discrimination between comprehension and production than association-biased
713 subregions.

714 **(1) Subregional production bias in univariate activation**

715 For each participant, block-wise activation estimates were averaged separately across the
716 comprehension tasks (listening and reading) and the production tasks (naming and writing) for each
717 gradient-defined subregion. A production-bias index was then computed for each subregion as the
718 mean activation during production minus the mean activation during comprehension.

719 The primary analysis tested whether production bias differed between the two subregions within
720 each candidate region. Paired-sample t-tests were used to compare the task-bias index between the
721 high-gradient and low-gradient subregions across participants. Follow-up one-sample t-tests were then
722 performed separately for each subregion to determine whether its production-bias index was
723 significantly greater than zero, indicating stronger responses during production than comprehension.
724 P values from all between-subregion and within-subregion tests across candidate regions were
725 corrected for multiple comparisons using FDR correction at $q < 0.05$.

726 **Subregional decoding of the comprehension–production distinction**

727 We next tested whether multivariate activation patterns within each gradient-defined subregion
728 distinguished comprehension from production. To do so, we repeated the cross-modal multivariate
729 pattern classification analysis described above separately within each subregion, using only the
730 vertices belonging to that subregion as features.

731 For each participant and subregion, block-wise beta estimates from the experimental word blocks
732 of the four word-level tasks were entered into the same cross-modal classification framework described
733 above. Decoding accuracies were averaged across the four comprehension–production train–test
734 combinations to yield the mean comprehension–production decoding accuracy for each participant and
735 subregion. The primary analysis tested whether comprehension–production decoding accuracy
736 differed between the two subregions within each candidate region. Paired-sample t-tests were used to
737 compare decoding accuracy between the high-gradient and low-gradient subregions across participants.
738 Follow-up one-sample t-tests were then performed separately for each subregion to determine whether
739 decoding accuracy exceeded chance (0.5). P values from all between-subregion and within-subregion
740 tests across candidate regions were corrected for multiple comparisons using FDR correction at $q <$
741 0.05.

742 **Representational content of gradient-defined subregions**

743 To test whether gradient-defined subregions differed in representational content along the local
744 connectivity gradient, we quantified semantic category decoding and articulatory-feature encoding
745 within each subregion. Specifically, we asked whether association-biased subregions showed stronger
746 semantic category decoding, whereas sensorimotor-biased subregions showed stronger articulatory-
747 feature encoding. To address this question, we performed subregional semantic category decoding and
748 subregional articulatory-feature encoding, and compared the resulting indices between the high-
749 gradient and low-gradient subregions of each candidate region.

750 **Subregional semantic-category decoding**

751 To assess semantic category representation, we repeated the semantic decoding analysis described
752 above within each gradient-defined subregion, restricting the feature space to the vertices belonging

753 to that subregion. Semantic category decoding was performed using the same pairwise classification
754 procedure and nested LOSO framework described in the preceding semantic-category analysis. For
755 each participant, task and subregion, decoding accuracies were averaged across the six category pairs
756 to yield a task-specific semantic decoding score. These scores were then averaged across the four word-
757 level tasks to obtain a single semantic decoding index for each participant and subregion. The primary
758 analysis tested whether this semantic decoding index differed between the high-gradient and low-
759 gradient subregions within each candidate region. Paired-sample t-tests were used for this comparison.
760 P values from these between-subregion tests across candidate regions were corrected for multiple
761 comparisons using FDR correction at $q < 0.05$.

762 **Subregional articulatory-feature encoding**

763 To assess articulatory-feature encoding, we tested whether the high-gradient and low-gradient
764 subregions within each candidate region differed in how strongly their activity was explained by
765 articulatory features during word processing. This analysis focused on the listening, naming and
766 reading tasks; the writing task was excluded because continuous hand movements disrupted the
767 temporal correspondence between linguistic events and BOLD responses.

768 For each word, articulatory features were represented in a 28-dimensional binary feature space,
769 with each dimension corresponding to one articulatory feature used in Chinese. Feature vectors were
770 summed across syllables to obtain a single 28-dimensional articulatory vector for each word. Two sets
771 of predictors were then constructed from the event timings: an articulatory regressor set containing
772 word onsets, word durations and the corresponding articulatory vectors, and a word-onset-only
773 regressor set containing the same word onset and word duration information but no articulatory
774 features. To align these predictors with the BOLD signal, both regressor sets were resampled to the
775 fMRI sampling grid using Lanczos interpolation and expanded into finite impulse response (FIR)
776 design matrices with six delays, corresponding to six successive TRs and spanning 9 s^{101–104}.

777 For each participant and subregion, continuous BOLD time series were extracted from block onset
778 to block offset for the listening, naming and reading tasks, and the resulting block-level time series
779 were concatenated across tasks to form a single response vector¹⁰⁵. This procedure ensured that

780 successful model fits reflected articulatory information that generalized across tasks rather than task-
781 specific variance.

782 Two ridge-regression encoding models were then fitted separately for each subregion. The full
783 model included the delayed articulatory regressors together with the delayed word-onset-only
784 regressors, whereas the control model only included the delayed word-onset-only regressors. The
785 word-onset-only model controlled for the temporal effects of word occurrence, such that the difference
786 between the two models reflected variance uniquely attributable to articulatory features. Model fitting
787 used nested 10-fold cross-validation repeated 100 times ^{103,104}.

788 Prediction performance was quantified as the cross-validated correlation between predicted and
789 observed BOLD responses, averaged across the 100 repetitions. These correlations were then
790 converted into an articulatory-feature encoding index,

791
$$G = \frac{R_{\text{full}}^2 - R_{\text{onset}}^2}{R_{\text{full}}^2 + R_{\text{onset}}^2},$$

792 which captured the relative gain in explained variance attributable to the articulatory regressors beyond
793 the word onset-only regressors. The primary analysis tested whether this encoding index differed
794 between the high-gradient and low-gradient subregions within each candidate region. Paired-sample
795 t-tests were used for this comparison. P values from these between-subregion tests across candidate
796 regions were corrected for multiple comparisons using FDR correction at $q < 0.05$.

797 **White-matter connectivity of anterior and posterior area 55b**

798 We tested whether the anterior–posterior functional organization of area 55b was mirrored by
799 tractography-derived connectivity with two large-scale systems: the language network (LAN) ⁹⁹ and
800 the somato-cognitive action network (SCAN) ¹⁹. We predicted that anterior 55b, which carried stronger
801 semantic-category information, would show stronger normalized streamline-count connectivity with
802 LAN, whereas posterior 55b, which showed stronger production bias and articulatory-feature encoding,
803 would show stronger connectivity with SCAN.

804 For each participant, tracts were extracted from the whole-brain tractogram using MRtrix3 tckedit

78. Anterior and posterior 55b seed masks were defined from the participant-specific subdivision of area 55b and transformed into the participant's diffusion space. LAN and SCAN target masks were derived from the corresponding network masks and mapped into the same diffusion space using individual anatomical and surface registrations. For each seed–target pair, we retained streamlines whose endpoints intersected both the 55b seed mask and the target network mask. Exclusion masks were applied to remove streamlines entering the right hemisphere or left-hemisphere cortical regions outside the corresponding seed–target pair. Tract-density maps were generated from the retained streamlines and visually inspected for quality control.

We quantified connection strength using a normalized streamline-count measure. For each seed–target tract, we counted the number of retained streamlines and normalized this value by the geometric mean of the seed and target mask sizes:

$$\text{Connectivity} = \frac{N_{\text{streamlines}}}{\sqrt{V_{\text{seed}} \times V_{\text{target}}}},$$

where $N_{\text{streamlines}}$ denotes the number of retained streamlines, and V_{seed} and V_{target} denote the number of voxels in the seed and target masks, respectively. This normalization reduced the influence of individual differences in ROI size on the estimated connection strength⁷⁵. For each participant, normalized connectivity was computed separately for four seed–target pairs: anterior 55b–LAN, anterior 55b–SCAN, posterior 55b–LAN and posterior 55b–SCAN.

We tested whether anterior and posterior 55b showed dissociable structural connectivity profiles using a 2×2 repeated-measures ANOVA, with seed subregion (anterior 55b, posterior 55b) and network (LAN, SCAN) as within-participant factors and normalized connectivity as the dependent variable. The key effect of interest was the seed subregion $\times$ network interaction, which tested whether the anterior–posterior difference in connection strength depended on the target network. When this interaction was significant, planned simple-effects analyses compared anterior and posterior 55b connectivity separately within LAN and SCAN. Statistical inference was restricted to participants with complete connectivity estimates across all four seed-by-network conditions. Generalized η^2 was reported for repeated-measures ANOVA effects, and Cohen's d was reported for paired simple-effects

831 comparisons.

832 **Comprehension–production differentiation across sensory and motor formats**

833 We assessed whether conjunction-defined regions distinguished word comprehension from word
834 production using two complementary analyses: one based on univariate activation magnitude and the
835 other on multivariate activation patterns.

836 **Activation-strength analysis**

837 For each participant and each conjunction-defined region, block-wise activation estimates were
838 averaged separately across comprehension (listening and reading) and production (naming and
839 writing). Within each region, production and comprehension estimates were compared using paired-
840 sample t tests. P values were Bonferroni-corrected across the four conjunction-defined regions,
841 matching the correction family reported in the Results.

842 **Multivariate classification of the comprehension–production distinction**

843 To test whether conjunction-defined regions encoded a modality-invariant distinction between
844 comprehension and production, we used a cross-modal multivariate pattern classification framework
845 in which the classifier was trained on one comprehension–production task pair and tested on another
846 pair that preserved the same distinction but involved different input or output modalities. Four train–
847 test combinations were used: the classifier was trained to distinguish listening from naming and tested
848 on distinguishing reading from writing, and vice versa; it was also trained to distinguish listening from
849 writing and tested on distinguishing reading from naming, and vice versa. As a control analysis, we
850 tested whether decoding instead reflected orthographic grouping by distinguishing tasks involving
851 written word forms (reading and writing) from tasks without written word forms (listening and
852 naming). Using the same framework, the classifier was trained on the listening-versus-reading contrast
853 and tested on the naming-versus-writing contrast, or vice versa.

854 For each participant, we extracted block-wise beta estimates for the experimental word blocks
855 only and averaged them across the three sessions. This yielded a $9 \times N_v$ pattern matrix for each task,
856 where 9 denotes the 4 semantic blocks and 5 phonological blocks, and N_v denotes the number of

857 vertices within the region. For each train–test combination, these matrices were used to construct a
858 classification dataset comprising 18 samples (two classes $\times$ nine blocks), labelled according to the
859 dimension being tested.

860 Classification was performed using an RBF kernel-based support vector machine implemented in
861 LIBSVM 3.25 within a nested leave-one-subject-out (LOSO) framework^{106,107}. In the inner loop, the
862 penalty parameter C and the RBF kernel parameter γ were optimized by leave-one-subject-out cross-
863 validation on the remaining participants using predefined candidate grids. Features were demeaned
864 and min–max normalized using the training data, and the same scaling parameters were then applied
865 to the held-out participant.

866 Decoding accuracy was defined as the proportion of correctly classified test samples (chance =
867 50%). For each participant and region, accuracies were averaged across the four comprehension–
868 production train–test combinations and, separately, across the two orthographic-control combinations.
869 Mean accuracy was tested against chance using one-tailed one-sample t tests with Bonferroni
870 correction across regions ($P_{\text{corrected}} < 0.05$). Comprehension–production and orthographic-control
871 accuracies were also compared using paired-sample t tests. A region was considered to carry a cross-
872 modal comprehension–production distinction when comprehension–production accuracy exceeded
873 chance and orthographic-control accuracy, while orthographic-control accuracy did not exceed chance.
874 Because both production tasks were picture-cued, this criterion does not eliminate all stimulus-format
875 differences between task domains.

876 **PCA-based visualization of multivariate task representations**

877 To visualize the representational structure underlying the multivariate pattern classification results,
878 we projected task-specific activation patterns into a low-dimensional space using PCA. PCA was
879 applied to the same block-wise beta estimates from the experimental word blocks used in the
880 multivariate pattern classification analyses. For each region, block-wise activation patterns were first
881 averaged within each task across participants, yielding four group-level task-specific activation
882 patterns, corresponding to listening, reading, naming, and writing, in the original high-dimensional
883 feature space. These patterns were then projected into a low-dimensional representational space to

884 define the group-level embedding used for visualization.

885 To visualize individual-level representations in a common space, the same procedure was applied
886 to subject-specific block-wise beta estimates from the experimental word blocks. For each participant
887 and each region, block-wise activation patterns were averaged within each task to yield four task-
888 specific activation patterns, which were then projected into a low-dimensional space. Each
889 participant's embedding was aligned to the group-level solution using Procrustes analysis^{4,96,97}. This
890 alignment preserved the internal representational structure of task representations while placing them
891 in a shared coordinate system. All analyses were implemented in MATLAB R2021a¹⁰⁸.

892 **Task-domain modulation of semantic-category information**

893 We asked whether semantic-category information differed between production and
894 comprehension in the regions retained from the preceding analysis. Multivariate category decoding
895 was performed separately for each word-level task; accuracy was then averaged across naming and
896 writing to obtain a production score and across listening and reading to obtain a comprehension score.
897 The term semantic-category information is used because the design did not test cross-format
898 generalization between pictures and words.

899 **Multivariate semantic category classification**

900 For each participant and each region, block-wise beta estimates were extracted from the
901 experimental word blocks. Within each task, activation patterns for each semantic category were
902 averaged across the three sessions, yielding a $4 \times N_v$ feature matrix, where the four rows correspond to
903 the semantic categories (household appliances, places, mammals and vehicles) and N_v denoted the
904 number of vertices within the region. The four categories yielded six pairwise comparisons. For each
905 category pair, multivariate classification was performed to distinguish the two category-specific
906 activation patterns, using an RBF kernel-based support vector machine implemented in LIBSVM 3.25
907 within a nested LOSO framework used for the task-domain classification analysis^{106,107}. In the inner
908 loop, the penalty parameter C and the RBF kernel parameter γ were optimized by leave-one-subject-
909 out cross-validation on the remaining participants using predefined candidate grids. Features were
910 demeaned and min-max normalized using the training data, and the same scaling parameters were then

911 applied to the held-out participant.

912 Classification accuracy was defined as the proportion of correctly classified samples in the test set
913 (chance = 50%). For each participant, region and task, decoding accuracies were averaged across the
914 six category pairs to yield a task-specific semantic decoding score. These task-specific scores were
915 then averaged across listening and reading to derive a comprehension decoding score and across
916 naming and writing to derive a production decoding score. Within each region, production and
917 comprehension decoding scores were compared across participants using paired-sample t-tests. To
918 further characterize the source of any production–comprehension difference, production and
919 comprehension decoding scores were also tested separately against chance using one-sample t-tests. P
920 values were corrected for multiple comparisons using FDR correction at $q < 0.05$.

921 **Task-dependent model-estimated directed coupling via DCM**

922 We used DCM implemented in SPM12 to test whether language production and comprehension
923 were associated with different model-estimated directed coupling on area 55b-centred edges. The a
924 priori contrast asked whether production increased coupling from 55b toward frontal language-related
925 and motor-effector regions. A sparse 55b-centred architecture was used to constrain the hypothesis
926 space. The analysis therefore estimates task-dependent coupling within the specified model and does
927 not establish a unique whole-network causal pathway.

928 The model included eight task-relevant regions spanning input, lexical and output components of
929 the four word-processing tasks: auditory cortex, visual cortex, area 55b, anterior fusiform cortex,
930 inferior frontal junction, superior frontal language area, ventral laryngeal–orofacial motor cortex and
931 dorsal hand motor cortex. Regions were defined in each participant’s individualized Schaefer–Kong
932 900-parcel parcellation, and DCM time series were extracted from task-responsive voxels within each
933 region of interest (ROI). Detailed ROI definitions and volumes of interest (VOIs) extraction
934 procedures are provided in Supplementary Methods ROI definition for dynamic causal modelling
935 analyses.

936 For each participant and task, we estimated one eight-node DCM. The endogenous connectivity
937 matrix included self-connections for all nodes and bidirectional connections between area 55b and

each of the seven other nodes; direct connections among non-55b nodes were not modelled. The lexical-processing contrast between each word task and its matched control condition was specified as a modulatory input on the bidirectional area 55b-centred connections. Driving inputs were assigned to sensory input regions according to task modality. DCMs were inverted and entered into a parametric empirical Bayes framework to estimate group-level effects and empirical-prior-updated subject-level modulatory parameters^{40,109}.

Parameters of interest were posterior expectations of lexical modulatory effects on each directed 55b-centred edge. For each participant, parameters were averaged across production and comprehension tasks and contrasted as (naming + writing)/2 – (listening + reading)/2. Edge-wise tests identified connections whose model-estimated lexical modulation differed between task domains; false discovery rate correction was applied across the tested directed 55b-centred edges.

Regional embedding within established cortical hierarchies

We asked whether area 55b occupied a local transition within broader cortical sensory-to-association hierarchies. For area 55b and comparison regions, we sampled three adjacent parcels spanning a sensorimotor- or sensory-adjacent parcel, the central parcel containing the target region, and an association-adjacent parcel. Ordered changes were quantified across six cortical hierarchy maps. This analysis establishes regional embedding around each target parcel; it does not directly test alignment between the hierarchy maps and the internal vertex-wise connectivity gradient within 55b.

Parcel sampling along the local sensory-to-association axis

Regions of interest were defined using the Schaefer–Kong 900-parcel parcellation. For area 55b and each comparison region, we identified three adjacent parcels arranged along a putative local sensory-to-association axis: a sensory- or sensorimotor-adjacent parcel, a central parcel corresponding to the target region, and an association-adjacent parcel. Parcel selections and anatomical criteria are detailed in the Supplementary Methods.

To assess whether any observed local hierarchical transitions were specific to conjunction-defined target regions rather than a generic property of the language network, we also defined three control regions within a canonical language network: inferior frontal gyrus (triangular part), mid–middle

temporal gyrus and posterior middle temporal gyrus. For each control region, the same sampling strategy was applied, selecting a sensory-adjacent parcel, a central parcel and an association-adjacent parcel along the local cortical axis.

Cortical hierarchy maps

For each ROI, we examined how values from the sensory-adjacent, central and association-adjacent parcels changed across six cortical hierarchy maps spanning evolutionary, structural, transcriptomic, metabolic, cognitive, and composite dimensions of the sensory-to-association continuum. These maps were ordered from biological constraints to integrative functional organization. First, the evolutionary hierarchy was indexed by macaque-to-human cortical expansion, which quantifies the degree of cortical surface expansion from macaque to human, with lower values in primary sensory and motor cortices and higher values in transmodal association cortex ^{41,110}. Second, the structural/myeloarchitectonic hierarchy was indexed by the T1w/T2w ratio, an in vivo proxy for intracortical myelin content, with heavily myelinated primary cortices at the sensory end of the hierarchy and lightly myelinated heteromodal regions at the association end ¹¹¹. Third, the transcriptomic hierarchy was indexed by the first principal component of cortical gene-expression profiles derived from the Allen Human Brain Atlas, capturing a dominant gradient from sensory-biased to association-biased transcriptional signatures across cortex ¹¹². Fourth, the metabolic hierarchy was indexed by PET-derived aerobic glycolysis, reflecting regional variation in non-oxidative glucose metabolism, which is typically lower in primary sensorimotor cortex and higher in association cortex ¹¹³. Fifth, the meta-analytic cognitive hierarchy was indexed by the first principal component of NeuroSynth term-activation decodings, summarizing large-scale functional specialization from lower-order sensorimotor functions to higher-order cognitive functions ¹¹⁴. Finally, the composite sensory-to-association hierarchy integrated structural, functional, metabolic and molecular features into a single cortex-wide ordering from primary sensory and motor regions to transmodal association cortex ⁴¹. Together, these six maps provided complementary biological and functional indices of where each parcel lay along the broader sensory-to-association hierarchy.

Quantification of monotonic hierarchical transitions

For each hierarchy map, vertexwise values were sampled within the sensory-adjacent, central, and association-adjacent parcels. Monotonic ordered differences were quantified using the Jonckheere–Terpstra test, with the expected order specified as sensory-adjacent < central < association-adjacent or the reverse, depending on map direction. The resulting Z statistic indexed local transition strength, and $P < 10^{-4}$ was used as a stringent descriptive threshold. Because cortical vertices are spatially dependent, these tests were interpreted as map-level descriptions of ordered regional transitions rather than participant-level inferential tests.

Multidimensional comparison of local hierarchical transition strength

To compare the overall strength of local hierarchical transitions across ROIs, we summarized the six hierarchy-specific indices of local transition strength into a single multidimensional index and then compared this index between candidate and comparison regions using exact paired permutation tests. For each ROI, the absolute Jonckheere–Terpstra Z-statistics obtained from the six hierarchy maps were treated as the radii of a six-axis radar polygon, and polygon area was computed as

$$A = \frac{1}{2} \sin \left(\frac{2\pi}{n} \right) \sum_{i=1}^n r_i r_{i+1},$$

where $r_i = |Z_i|$, $r_{n+1} = r_1$, and $n = 6$. Larger values indicate stronger and more consistent local transitions across the six hierarchy dimensions.

For each pairwise comparison between a candidate region and a comparison ROI, an exact paired permutation test was performed across the six matched hierarchy maps. Under the null hypothesis of no difference in overall local hierarchical transition strength, the $|Z|$ values for each hierarchy map were either retained or swapped between the two ROIs independently, yielding all $2^6 = 64$ possible reassignment patterns. For each reassignment, polygon areas were recomputed and the area difference $\Delta A = A_{\text{candidate}} - A_{\text{comparison}}$ was calculated to form the exact null distribution. One-tailed P values were defined as the proportion of reassignment patterns for which $\Delta A_{\text{permutation}} \geq \Delta A_{\text{absolute}}$. Statistical significance was set at $P < 0.05$.

1016 **Statistical analysis**

1017 Unless otherwise stated, group-level statistical analyses were performed using two-sided one-
1018 sample or paired-sample t-tests, according to the corresponding hypothesis. For paired-sample tests,
1019 outliers were identified separately for each planned contrast using a predefined criterion based on the
1020 paired-difference values. Participants whose paired-difference values fell outside the group mean ± 2.5
1021 s.d. were excluded from that specific contrast before statistical inference. Because this criterion was
1022 applied independently to each contrast, the number of retained participants could vary across tests; the
1023 retained sample size for each paired test can be inferred from the reported degrees of freedom as $N =$
1024 $df + 1$. Multiple comparisons were controlled using FDR correction for families of related tests. Effect
1025 sizes were reported as Cohen's *d*.

References

1. Mesulam, M. -M. Large-scale neurocognitive networks and distributed processing for attention, language, and memory. *Ann. Neurol.* **28**, 597–613 (1990).
2. Mesulam, M. M. From sensation to cognition. *Brain* **121**, 1013–1052 (1998).
3. Paquola, C. *et al.* Microstructural and functional gradients are increasingly dissociated in transmodal cortices. *PLoS Biol.* **17**, e3000284 (2019).
4. Margulies, D. S. *et al.* Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proc. Natl. Acad. Sci. U. S. A.* **113**, 12574–12579 (2016).
5. Fedorenko, E., Ivanova, A. A. & Regev, T. I. The language network as a natural kind within the broader landscape of the human brain. *Nat. Rev. Neurosci.* <https://doi.org/10.1038/s41583-024-00802-4> (2024) doi:10.1038/s41583-024-00802-4.
6. Bonner, M. F. & Price, A. R. Where is the anterior temporal lobe and what does it do? *Journal of Neuroscience* **33**, 4213–4215 (2013).
7. Lambon Ralph, M. A., Jefferies, E., Patterson, K. & Rogers, T. T. The neural and computational bases of semantic cognition. *Nat. Rev. Neurosci.* **18**, 42–55 (2017).
8. Patterson, K., Nestor, P. J. & Rogers, T. T. Where do you know what you know? The representation of semantic knowledge in the human brain. *Nat. Rev. Neurosci.* **8**, 976–987 (2007).
9. Ivanova, A. A. *et al.* Semantic reasoning takes place largely outside the language network. *bioRxiv* 2025.12.07.692873 (2025) doi:10.64898/2025.12.07.692873.
10. Lau, E. F., Phillips, C. & Poeppel, D. A cortical network for semantics: (De)constructing the N400. *Nature Reviews Neuroscience* Preprint at <https://doi.org/10.1038/nrn2532> (2008).
11. Liuzzi, A. G., Aglinskas, A. & Fairhall, S. L. General and feature-based semantic representations in the semantic network. *Sci. Rep.* <https://doi.org/10.1038/s41598-020-65906-0> (2020)

doi:10.1038/s41598-020-65906-0.

12. Lin, N., Zhang, X., Wang, X. & Wang, S. The organization of the semantic network as reflected by the neural correlates of six semantic dimensions. *Brain Lang.* **250**, 105388 (2024).
13. Friederici, A. D. The cortical language circuit: From auditory perception to sentence comprehension. *Trends Cogn. Sci.* **16**, 262–268 (2012).
14. Hickok, G. & Poeppel, D. Neural basis of speech perception. in *Handbook of Clinical Neurology* vol. 129 149–160 (Elsevier B.V., 2015).
15. Scott, S. K. & Johnsrude, I. S. The neuroanatomical and functional organization of speech perception. *Trends Neurosci.* **26**, 100–107 (2003).
16. Behroozmand, R. *et al.* Sensory-motor networks involved in speech production and motor control: An fMRI study. *Neuroimage* **109**, 418–428 (2015).
17. Silva, A. B. *et al.* A Neurosurgical Functional Dissection of the Middle Precentral Gyrus during Speech Production. *Journal of Neuroscience* vol. 42 8416–8426 Preprint at <https://doi.org/10.1523/JNEUROSCI.1614-22.2022> (2022).
18. Gajardo-Vidal, A. *et al.* Damage to Broca’s area does not contribute to long-term speech production outcome after stroke. *Brain* **144**, 817 (2021).
19. Gordon, E. M. *et al.* A somato-cognitive action network alternates with effector regions in motor cortex. *Nature* **617**, 351–359 (2023).
20. Jensen, M. A. *et al.* A motor association area in the depths of the central sulcus. *Nat. Neurosci.* **26**, 1165–1169 (2023).
21. Dosenbach, N. U. F., Raichle, M. E. & Gordon, E. M. The brain’s action-mode network. *Nature Reviews Neuroscience* 2025 26:3 **26**, 158–168 (2025).
22. Glasser, M. F. *et al.* A multi-modal parcellation of human cerebral cortex. *Nature* **536**, 171–178 (2016).

23. Kong, R. *et al.* Individual-Specific Areal-Level Parcellations Improve Functional Connectivity Prediction of Behavior. *Cerebral Cortex* **31**, 4477–4500 (2021).
24. Li, M. *et al.* Performing group-level functional image analyses based on homologous functional regions mapped in individuals. *PLoS Biol.* **17**, (2019).
25. Mueller, S. *et al.* Individual Variability in Functional Connectivity Architecture of the Human Brain. *Neuron* **77**, 586–595 (2013).
26. Wang, D. *et al.* Parcellating cortical functional networks in individuals. *Nat. Neurosci.* **18**, 1853–1860 (2015).
27. Gordon, E. M. *et al.* Precision Functional Mapping of Individual Human Brains. *Neuron* **95**, 1–17 (2017).
28. Khanna, A. R. *et al.* Single-neuronal elements of speech production in humans. *Nature* **626**, 603–610 (2024).
29. Chang, E. F. *et al.* Pure apraxia of speech after resection based in the posterior middle frontal gyrus. *Neurosurgery* **87**, E383–E389 (2020).
30. Ekert, J. O. *et al.* A functional dissociation of the left frontal regions that contribute to single word production tasks. *Neuroimage* **245**, 118734 (2021).
31. Zhou, Y., Yan, P., Zhao, Z., Zhang, J. & Lu, J. Increased risk of permanent speech production deficits following resection of the dominant ventral precentral gyrus compared with Broca's area. *Operative Neurosurgery* <https://doi.org/10.1227/ONS.0000000000001857> (2025) doi:10.1227/ONS.0000000000001857.
32. Hazem, S. R. *et al.* Middle Frontal Gyrus and Area 55b: Perioperative Mapping and Language Outcomes. *Front. Neurol.* **12**, (2021).
33. Milton, C. K. *et al.* Parcellation-based anatomic model of the semantic network. *Brain Behav.* **11**, e02065 (2021).
34. Voets, N. L. *et al.* Consensus recommendations for clinical functional MRI applied to language

mapping. *Aperture Neuro* **5**, (2025).

35. Jamali, M. *et al.* Semantic encoding during language comprehension at single-cell resolution. *Nature* **631**, 610–616 (2024).
36. Coldham, Y. *et al.* Distinct neural representations of different linguistic components following sign language learning. *Commun. Biol.* **8**, 353 (2025).
37. Qin, L. *et al.* A heteromodal word-meaning binding site in the visual word form area under top-down frontoparietal control. *Journal of Neuroscience* **41**, 3854–3869 (2021).
38. Van Essen, D. C. *et al.* The WU-Minn Human Connectome Project: An overview. *Neuroimage* **80**, 62–79 (2013).
39. Glasser, M. F. *et al.* The minimal preprocessing pipelines for the Human Connectome Project. *Neuroimage* **80**, 105–124 (2013).
40. Zeidman, P. *et al.* A guide to group effective connectivity analysis, part 1: First level analysis with DCM for fMRI. *Neuroimage* **200**, 174–190 (2019).
41. Sydnor, V. J. *et al.* Neurodevelopment of the association cortices: Patterns, mechanisms, and implications for psychopathology. *Neuron* **109**, 2820–2846 (2021).
42. Poeppel, D. & Hickok, G. Towards a new functional anatomy of language. *Cognition* vol. 92 1–12 Preprint at <https://doi.org/10.1016/j.cognition.2003.11.001> (2004).
43. Friederici, A. D. The brain basis of language processing: from structure to function. *Physiol. Rev.* **91**, 1357–1392 (2011).
44. Du, J. *et al.* Organization of the Human Cerebral Cortex Estimated Within Individuals: Networks, Global Topography, and Function. *J. Neurophysiol.* <https://doi.org/10.1152/jn.00308.2023> (2024) doi:10.1152/jn.00308.2023.
45. Du, J. *et al.* Within-individual precision mapping of brain networks exclusively using task data. *Neuron* **113**, 4069-4083.e6 (2025).

46. Levelt, W. J. M. Spoken word production: A theory of lexical access. *Proceedings of the National Academy of Sciences* **98**, 13464–13471 (2001).
47. Levelt, W. J. M., Roelofs, A. & Meyer, A. S. A theory of lexical access in speech production. *Behavioral and Brain Sciences* Preprint at <https://doi.org/10.1017/S0140525X99001776> (1999).
48. Pickering, M. J. & Garrod, S. An integrated theory of language production and comprehension. *Behavioral and Brain Sciences* **36**, 329–347 (2013).
49. Lukic, S. *et al.* Common and distinct neural substrates of sentence production and comprehension. *Neuroimage* **224**, (2021).
50. Turken, A. U. & Dronkers, N. F. The neural architecture of the language comprehension network: Converging evidence from lesion and connectivity analyses. *Front. Syst. Neurosci.* <https://doi.org/10.3389/fnsys.2011.00001> (2011) doi:10.3389/fnsys.2011.00001.
51. Keitel, A., Gross, J. & Kayser, C. Shared and modality-specific brain regions that mediate auditory and visual word comprehension. *Elife* **9**, 1–23 (2020).
52. Ivanova, A. A. & others. Comprehension of computer code relies primarily on domain-general executive brain regions. *Elife* **9**, 58906 (2020).
53. Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A. & Rogers, T. T. Decoding semantic representations in mind and brain. *Trends in Cognitive Sciences* vol. 27 258–281 Preprint at <https://doi.org/10.1016/j.tics.2022.12.006> (2023).
54. Krieger-Redwood, K., Wang, X., Souter, N., Alam, T. R. J. G. & Smallwood, J. Graded and sharp transitions in semantic function in left temporal lobe. *Brain Lang.* **251**, 105402 (2024).
55. Duffau, H. *et al.* Intraoperative mapping of the subcortical language pathways using direct stimulations. An anatomo-functional study. *Brain* **125**, 199–214 (2002).
56. Sarubbo, S. *et al.* Mapping critical cortical hubs and white matter pathways by direct electrical stimulation: an original functional atlas of the human brain. *Neuroimage* **205**, 116237 (2019).
57. Szelényi, A. *et al.* Intraoperative electrical stimulation in awake craniotomy: Methodological

aspects of current practice. *Neurosurg. Focus* <https://doi.org/10.3171/2009.12.FOCUS09237> (2010) doi:10.3171/2009.12.FOCUS09237.

58. Zhang, Q. & Yang, Y. Phonological encoding in monosyllabic and disyllabic Chinese word production: An implicit priming study. *Acta Psychologica Sinica* **40**, 253 (2005).
59. Zhang, Q. & Yang, Y. The time course of semantic, orthographic, and phonological activation in Chinese single-character word production. *Acta Psychologica Sinica* **36**, 1 (2004).
60. Forseth, K. J. *et al.* A lexical semantic hub for heteromodal naming in middle fusiform gyrus. *Brain* **141**, 2112–2126 (2018).
61. Xue, G. *et al.* Facilitating Memory for Novel Characters by Reducing Neural Repetition Suppression in the Left Fusiform Cortex. *PLoS One* **5**, e13204 (2010).
62. Mei, L. *et al.* Orthographic transparency modulates the functional asymmetry in the fusiform cortex: An artificial language training study. <https://doi.org/10.1016/j.bandl.2012.01.006> (2012) doi:10.1016/j.bandl.2012.01.006.
63. Yang, Y. *et al.* Brain activation and functional connectivity during Chinese writing: An fMRI study. *J. Neurolinguistics* **51**, 199–211 (2019).
64. Li, J., Zhang, D., Ren, H., Zhou, K. & Yang, Y. Connectome-based predictive modeling of handwriting and reading using task-evoked and resting-state functional connectivity. *iScience* **28**, 113075 (2025).
65. Esteban, O. *et al.* fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nat. Methods* <https://doi.org/10.1038/s41592-018-0235-4> (2019) doi:10.1038/s41592-018-0235-4.
66. Esteban, O. *et al.* Analysis of task-based functional MRI data preprocessed with fMRIPrep. *Nat. Protoc.* **15**, 2186–2202 (2020).
67. Mehta, K. *et al.* XCP-D: A robust pipeline for the post-processing of fMRI data. *Imaging Neuroscience* **2**, 1–26 (2024).
68. Tustison, N. J. *et al.* N4ITK: improved N3 bias correction. *IEEE Trans. Med. Imaging* **29**, 1310–

1320 (2010).

69. Klein, A. *et al.* Mindboggling Morphometry of Human Brains. *PLoS Comput. Biol.* **13**, e1005350 (2017).
70. Reynolds, R. C. *et al.* Processing, evaluating, and understanding FMRI data with afni_proc.py. *Imaging Neuroscience* **2**, 1–52 (2024).
71. Ciric, R. *et al.* Mitigating head motion artifact in functional connectivity MRI. *Nat. Protoc.* **13**, 2801–2826 (2018).
72. Power, J. D. *et al.* Methods to Detect, Characterize, and Remove Motion Artifact in Resting State fMRI. *Neuroimage* **84**, 320–341 (2014).
73. Ciric, R. *et al.* Benchmarking of participant-level confound regression strategies for the control of motion artifact in studies of functional connectivity. *Neuroimage* <https://doi.org/10.1016/j.neuroimage.2017.03.020> (2017)
doi:10.1016/j.neuroimage.2017.03.020.
74. Satterthwaite, T. D. *et al.* Impact of in-scanner head motion on multiple measures of functional connectivity: Relevance for studies of neurodevelopment in youth. *Neuroimage* **60**, 623–632 (2012).
75. Cieslak, M. *et al.* QSIPrep: an integrative platform for preprocessing and reconstructing diffusion MRI data. *Nature Methods* **18**, 775–778 (2021).
76. Hoopes, A., Mora, J. S., Dalca, A. V., Fischl, B. & Hoffmann, M. SynthStrip: skull-stripping for any brain image. *Neuroimage* **260**, (2022).
77. Billot, B. *et al.* Robust machine learning segmentation for large-scale analysis of heterogeneous clinical brain MRI datasets. *Proc. Natl. Acad. Sci. U. S. A.* **120**, e2216399120 (2023).
78. Tournier, J. D. *et al.* MRtrix3: A fast, flexible and open software framework for medical image processing and visualisation. *Neuroimage* **202**, (2019).
79. Veraart, J. *et al.* Denoising of diffusion MRI using random matrix theory. *Neuroimage* **142**, 394–

406 (2016).

80. Kellner, E., Dhital, B., Kiselev, V. G. & Reiser, M. Gibbs-ringing artifact removal based on local subvoxel-shifts. *Magn. Reson. Med.* **76**, 1574–1581 (2016).
81. Andersson, J. L. R. & Sotiropoulos, S. N. An integrated approach to correction for off-resonance effects and subject movement in diffusion MR imaging. *Neuroimage* **125**, 1063–1078 (2016).
82. Andersson, J. L. R., Graham, M. S., Zsoldos, E. & Sotiropoulos, S. N. Incorporating outlier detection and replacement into a non-parametric framework for movement and distortion correction of diffusion MR images. *Neuroimage* **141**, 556–572 (2016).
83. (ISMRM 2010) Improved Probabilistic Streamlines Tractography by 2nd Order Integration Over Fibre Orientation Distributions. <https://archive.ismrm.org/2010/1670.html>.
84. Smith, R. E., Tournier, J. D., Calamante, F. & Connelly, A. Anatomically-constrained tractography: Improved diffusion MRI streamlines tractography through effective use of anatomical information. *Neuroimage* **62**, 1924–1938 (2012).
85. Smith, R. E., Tournier, J. D., Calamante, F. & Connelly, A. SIFT2: Enabling dense quantitative assessment of brain white matter connectivity using streamlines tractography. *Neuroimage* **119**, 338–351 (2015).
86. Faskowitz, J., Esfahlani, F. Z., Jo, Y., Sporns, O. & Betzel, R. F. Edge-centric functional network representations of human cerebral cortex reveal overlapping system-level architecture. *Nature Neuroscience* 2020 23:12 **23**, 1644–1654 (2020).
87. Sporns, O., Faskowitz, J., Teixeira, A. S., Cutts, S. A. & Betzel, R. F. Dynamic expression of brain functional systems disclosed by fine-scale analysis of edge time series. *Network Neuroscience* **5**, 405–433 (2021).
88. Wu, G., Cui, Z., Wang, X. & Du, Y. Unveiling the core functional networks of cognition: An ontology-guided machine learning approach. *Neuroimage* **298**, 120804 (2024).
89. Barch, D. M. *et al.* Function in the human connectome: Task-fMRI and individual differences

in behavior. *Neuroimage* **80**, 169–189 (2013).

90. Prince, J. S. *et al.* Improving the accuracy of single-trial fMRI response estimates using GLMsingle. *Elife* **11**, (2022).
91. contributors, N. *et al.* nilearn. <https://doi.org/10.5281/ZENODO.19603727> (2026) doi:10.5281/ZENODO.19603727.
92. Cui, Z. *et al.* Individual Variation in Functional Topography of Association Networks in Youth. *Neuron* **106**, 340-353.e8 (2020).
93. Wang, X. *et al.* Macroscale brain states support the control of semantic cognition. *Commun. Biol.* **7**, (2024).
94. Cole, M. W. *et al.* Task activations produce spurious but systematic inflation of task functional connectivity estimates. *Neuroimage* **189**, 1–18 (2019).
95. Cole, M. W. *et al.* Multi-task connectivity reveals flexible hubs for adaptive task control. *Nat. Neurosci.* **16**, 1348–1355 (2013).
96. Vos de Wael, R. *et al.* BrainSpace: a toolbox for the analysis of macroscale gradients in neuroimaging and connectomics datasets. *Communications Biology* 2020 3:1 **3**, 103- (2020).
97. Kong, R. *et al.* Comparison between gradients and parcellations for functional connectivity prediction of behavior. *Neuroimage* **273**, (2023).
98. Thomas Yeo, B. T. *et al.* The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *J. Neurophysiol.* **106**, 1125–1165 (2011).
99. Lipkin, B. *et al.* LanA (Language Atlas): A probabilistic atlas for the language network based on fMRI data from >800 individuals. *Sci Data* (2022).
100. Zhang, M. *et al.* Knowing what you need to know in advance: The neural processes underpinning flexible semantic retrieval of thematic and taxonomic relations. *Neuroimage* **224**, 117405 (2021).

101. Antonello, R. & Huth, A. Predictive Coding or Just Feature Discovery? An Alternative Account of Why Language Models Fit Brain Data. *Neurobiology of Language* **5**, 64–79 (2024).
102. Antonello, R., Vaidya, A. & Huth, A. Scaling laws for language encoding models in fMRI. *Adv. Neural Inf. Process. Syst.* **36**, (2024).
103. Tang, J., LeBel, A., Jain, S. & Huth, A. G. Semantic reconstruction of continuous language from non-invasive brain recordings. *Nat. Neurosci.* **26**, 858–866 (2023).
104. Huth, A. G., De Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L. Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458 (2016).
105. Cohen, J. R. & D’Esposito, M. The Segregation and Integration of Distinct Brain Networks and Their Relationship to Cognition. *Journal of Neuroscience* **36**, 12083–12094 (2016).
106. Wang, Q., Cagna, B., Chaminade, T. & Takerkart, S. Inter-subject pattern analysis: A straightforward and powerful scheme for group-level MVPA. *Neuroimage* **204**, 116205 (2020).
107. Valente, G., Castellanos, A. L., Hausfeld, L., De Martino, F. & Formisano, E. Cross-validation and permutations in MVPA: Validity of permutation strategies and power of cross-validation schemes. *Neuroimage* **238**, 118145 (2021).
108. Inc., T. M. MATLAB (R2021a). Preprint at <https://www.mathworks.com> (2021).
109. Zhang, L. & Du, Y. Lip movements enhance speech representations and effective connectivity in auditory dorsal stream. *Neuroimage* **257**, 119311 (2022).
110. Hill, J. *et al.* Similar patterns of cortical expansion during human development and evolution. *Proc. Natl. Acad. Sci. U. S. A.* **107**, 13135–13140 (2010).
111. Glasser, M. F. & van Essen, D. C. Mapping human cortical areas in vivo based on myelin content as revealed by T1- and T2-weighted MRI. *J. Neurosci.* **31**, 11597–11616 (2011).
112. Burt, J. B. *et al.* Hierarchy of transcriptomic specialization across human cortex captured by structural neuroimaging topography. *Nature Neuroscience* 2018 21:9 **21**, 1251–1259 (2018).

113. Vaishnavi, S. N. *et al.* Regional aerobic glycolysis in the human brain. *Proc. Natl. Acad. Sci. U. S. A.* **107**, 17757–17762 (2010).
114. Yarkoni, T., Poldrack, R. A., Nichols, T. E., Van Essen, D. C. & Wager, T. D. Large-scale automated synthesis of human functional neuroimaging data. *Nat. Methods* **8**, 665–670 (2011).

Acknowledgements

We thank Dr Jianqiao Ge of Peking University and Dr Bingjiang Lv of Changping Laboratory for their assistance in providing and preparing the Peking University dataset. HCP-YA data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research; and by the McDonnell Center for Systems Neuroscience at Washington University.

Funding

This work was supported by the Strategic Priority Research Program of the Chinese Academy of Sciences (XDB0930000) and the Brain Science and Brain-like Intelligence Technology-National Science and Technology Major Project (2021ZD0201500) to Y.D., and by the National Natural Science Foundation of China (32300881) to X.W.

Conflict of interest

The authors declare no competing interests.

Table 1. Modality-invariant lexical regions identified across comprehension and production tasks

Manuscript region	Schaefer–Kong parcel label	Glasser atlas label	Vertices	Minimum T across contrasts
IFJ	L ContA PFC1 5/7	Area IFJ L	99	3.51
SFL	L Language PFCd 2	Superior Frontal Language Area L	53	3.01
Area 55b	L SomMotB 8 /DorsAttnB PrCv 4	Area 55b L	95	3.02
Anterior fusiform gyrus	L VisualA ExStr	Ventral Fusiform L	68	3.86

Supplementary Files

This is a list of supplementary files associated with this preprint. Click to download.

- [WuetaISupplementaryNNresubmissionfinal.docx](#)